

ANUNȚ DE PARTICIPARE

privind achiziționarea Echipamentelor de producție video: pedestal și multicam recorder prin procedura de achiziție licitație deschisă

1. **Denumirea autorității contractante:** *IP Compania „Teleradio – Moldova”.*
2. **IDNO:** *1004600050558.*
3. **Adresa:** *str. Miorița 1, mun. Chișinău, MD-2028.*
4. **Numărul de telefon/fax:** *068482641.*
5. **Adresa de e-mail și pagina web oficială ale autorității contractante:** *trm@trm.md, www.trm.md.*
6. **Adresa de e-mail sau pagina web oficială de la care se va putea obține accesul la documentația de atribuire:** *documentația de atribuire este anexată în cadrul procedurii în SIA RSAP.*
7. **Tipul autorității contractante și obiectul principal de activitate (dacă este cazul, mențiunea că autoritatea contractantă este o autoritate centrală de achiziție sau că achiziția implică o altă formă de achiziție comună):** *Instituție Publică Compania „Teleradio – Moldova” este radiodifuzor public național, care oferă produse audiovizuale și multimedia de diverse genuri pentru diferite categorii de public*
Planul de achiziții pentru anul 2026 <https://trm.md/ro/achizitii/planul-de-achizitii-pentru-anul-2026-modificat-18-05-2026>
8. **Cumpărătorul invită operatorii economici interesați, care îi pot satisface necesitățile, să participe la procedura de achiziție privind livrarea bunuri:**

| Cod CPV | Denumirea bunurilor | Unit. măs. | Can. | Descrierea bunurilor și specificarea tehnică | Valoarea estimată fără TVA (pentru fiecare lot în parte) |
|--|---|------------|------|---|--|
| Echipamente de producție video: pedestal și multicam recorder | | | | | |
| 32320000-2 | Lotul nr. 1 Compact camera (set) | buc | 1 | Camera <i>Imaging</i> - Lens E Mount or equivalent; Image Sensor - 35.6 x 23.8 mm (Full-Frame) CMOS Effective Sensor Resolution - min. 10.2 Megapixel Image Stabilization - Sensor-Shift, 5-Axis <i>Exposure Control</i> - Shutter Type - Mechanical Focal Plane Shutter and Electronic Rolling Shutter Shutter Speed - 1/4 to 1/8000 Second; Advertised Dynamic Range - 15 Stops ISO/Gain Sensitivity - Native: 80 to 102,400 White Balance - Range: 2500 to 9900K, Presets: Auto, Cloudy, Daylight, Flash, Fluorescent, Incandescent, Shade, Underwater <i>Video Capture</i> - Internal Recording - Professional video codec with minimum 4:2:2 10bit recording, minimum bitrate 200 Mbps; Built-In Microphone - Stereo Audio Recording - 4-Channel. <i>Interface</i> - Media/Memory Card Slot - Dual Slot: CFexpress Type A or SDXC Video I/O - min. 1x HDMI Output Audio I/O - min. 1x 1/8" / 3.5 mm TRS Stereo Microphone Input, min. 1x 1/8" / 3.5 mm TRS Stereo; Power I/O - USB-C Input; Wireless - Wi-Fi / Bluetooth | 233 333,33 |

Monitor - Display Type - Primary Monitor: Touchscreen LCD

Include: XLR Handle Unit, Accessory Shoe Cap, Accessory Shoe Kit, Battery Charger, Body Cap, Handle Shoe Cap, Power Cord, Rechargeable Lithium-Ion Battery, USB Type-A to Type-C.

*** Dual Battery Charger+2 pcs. Rechargeable Lithium-Ion Battery(compatible with camera)**

*** Mirrorless Lens with Filter Kit (2 pcs)**

Lens E Mount or equivalent; Focal Length - 16 to 35mm;

Aperture - Maximum: f/4, Minimum: f/22

Lens Format Coverage - Full-Frame; Angle of View - 107° to 63°

Aperture/Iris Blades - 7, Rounded

Minimum Focus Distance - 24 cm; Focus Type - Autofocus;

Filter Size - 72 mm (Front)

Include: 72 mm UV filter and a kit for cleaning and maintaining optical equipment

*** Mirrorless Lens with Filter Kit (1 pcs.)**

Lens E Mount or equivalent; Focal Length - 28 to 135mm;

Maximum Aperture - f/4; Minimum Aperture - f/22

Lens Format Coverage - Full-Frame; Angle of View - Full Frame Horizontal: 75 to 18°

Aperture/Iris Blades - 9; Filter Thread - 95 mm; Zoom Ratio - min. 4,5x

Minimum Focus Distance - From Camera Sensor: 40 cm (Wide) to 95 cm (Tele)

Lens Mounting - 1x 1/4"-20 (via Included Support Foot)

Include: Pro 95mm 98-UVATS UV Filter, Optics Care and Cleaning Kit

*** Memory card:** 256GB CFexpress Type A or SDXC (4 pcs)

*** CFexpress Type A and UHS-II SD Card Reader** (1 pcs)

*** Aluminum Tripod Kit + Video Head Camera Attachment**

Camera Mounting Screw - 1x 1/4"-20 Male, 1x 3/8"-16 Male

Camera Plate - Quick Release: 504PLONG; Head Type - Fluid

Head; Base Mount - Flat Base with 3/8"-16 Female; Counter Balance - Fixed (4 kg)

Head Dimensions - Base Diameter: 2.95" / 7.49 cm, Height: 5.12" / 13.00 cm

Vertical Tilt - +90° to -80°; Load Capacity -10 kg

Accessory Mounting - 1x 3/8"-16 Female Thread, 2x Pan Handle Fitting

Bubble Level; Weight - 1.69 kg

***Gimbal Combo Kit with AI Tracking Module & Briefcase Handle**

Gimbal - Load Capacity - 3 kg; Number of Axes - Three: Pitch (Tilt) / Roll / Yaw (Pan)

Rotation Range - Mechanical Range Yaw (Pan): 360°; Follow Speed - Pan/Tilt/Roll: 360°/s

Gimbal Design - Single Handgrip (Slanted), Dual Handgrip (Slanted)

Camera Mounting Screw - 1x 1/4"-20 Male

Inputs/Outputs - 1x USB-C (Power); Wireless - 2.4 GHz

Radio/RF / Bluetooth 5.1

Battery Type - Built-In;

Materials - Aluminum Alloy; Display Type - Fixed Touchscreen OLED

Accessory Mounting - 1 x 1/4"-20 Female, 2 x NATO Rail

Transmitter I/O-2 x NATO, 2xUSB-C (Power/Camera

| | | | | |
|------------|---|-----|--|-------------------|
| | | | <p>Control/Video Transmission/Focus Motor) Transmission System - Bluetooth 5.1, 2.4 GHz <i>Include:</i> Gimbal, Electronic Briefcase Handle, Tracking Module, Upper Quick Release Plate, Lower Quick Release Plate, Battery Grip, Quick-Open Tripod, Lens Support, Screw Kit, USB-C Multicamera Control Cable * Video Recorder/Monitor 3G-SDI/HDMI 5" (1 pcs) <u>Display:</u> Display Size - 5.0"; Native Resolution - min. 1920 x 1080; Aspect Ratio - 16:9; Viewing Angle - Horizontal: min. 135°; Brightness - 250-350 nits / cd/m2; Color Gamut - 100% Rec. 709 Image Controls - Anamorphic De-Squeeze, Blue Only, False Color, Focus Peaking, Histogram, Image Flip, Picture-in-Picture, RGB Parade, Screen Markers, Vectorscope, Waveform, Zebra <u>Inputs / Outputs min.-</u> Video I/O - 1x HDMI Input, 1x Micro BNC (3G-SDI) Input, 1x HDMI Output, 1x Micro BNC (3G-SDI) Output, 1x USB-C Output; Embedded Audio - HDMI: 8-Channel, SDI: 16-Channel; Audio I/O - 1x 1/8" / 3.5 mm Headphone Output Power I/O - 1x Barrel (12 VDC) Input; Other I/O - 1x USB-C Media/Memory Card Slot - Single Slot: SD/SDHC/SDXC (UHS-II) Include: (1pcs) L-Series Lithium-Ion Battery Pack (4400mAh). * Backpack for professional camera kit (mirrorless + lenses) (equivalent Shootout 14L Slim) (1 pcs) Backpack designed to carry 1-2 mirrorless or compact DSLR cameras and 3-5 lenses (up to 70-200mm f/2.8). Features secure rear camera access positioned against the user's back to prevent front or side access during travel; allows the bag to be rotated to the front for gear exchange without removing it from the body. Shoulder straps automatically adjust to different shoulder and body shapes for a custom fit. Body contact points are covered with ventilated, moisture-wicking 3D air mesh for all-day comfort. Constructed from high-quality, water-repellent nylon with durable zippers and clips, and heavily reinforced stitching for enhanced durability and weather resistance. Warranty: 3 years.</p> | |
| 32320000-2 | Lotul nr. 2 Compact camera (set) | buc | <p>Camera <u>Imaging</u> - Lens E Mount or equivalent; Image Sensor - 35.6 x 23.8 mm (Full-Frame) CMOS Effective Sensor Resolution - min. 10.2 Megapixel Image Stabilization - Sensor-Shift, 5-Axis <u>Exposure Control</u> - Shutter Type - Mechanical Focal Plane Shutter and Electronic Rolling Shutter Shutter Speed - 1/4 to 1/8000 Second; Advertised Dynamic Range - 15 Stops ISO/Gain Sensitivity - Native: 80 to 102,400 White Balance - Range: 2500 to 9900K, Presets: Auto, Cloudy, Daylight, Flash, Fluorescent, Incandescent, Shade, Underwater <u>Video Capture</u>- Internal Recording - Professional video codec with minimum 4:2:2 10bit recording, minimum bitrate 200 Mbps; Built-In Microphone - Stereo Audio Recording - 4-Channel.</p> | 125 000,00 |

Interface - Media/Memory Card Slot - Dual Slot: CFexpress Type A or SDXC
Video I/O - min. 1x HDMI Output
Audio I/O - min. 1x 1/8" / 3.5 mm TRS Stereo Microphone Input, min. 1x 1/8" / 3.5 mm TRS Stereo;
Power I/O - USB-C Input;
Wireless - Wi-Fi / Bluetooth

Monitor - Display Type - Primary Monitor: Touchscreen LCD

Include: XLR Handle Unit, Accessory Shoe Cap, Accessory Shoe Kit, Battery Charger, Body Cap, Handle Shoe Cap, Power Cord, Rechargeable Lithium-Ion Battery, USB Type-A to Type-C.

*** Dual Battery Charger+2 pcs. Rechargeable Lithium-Ion Battery (compatible with camera)**

*** Mirrorless Lens (1 pcs.)**
Lens E Mount or equivalent; Focal Length - 24 to 50mm;
Aperture - Maximum: f/2.8, Minimum: f/22
Full-Frame - Angle of View 84° to 47°; Minimum Focus Distance - 18 cm
Magnification - 1:3 Macro Reproduction Ratio, 0.33x Magnification
Aperture/Iris Blades - 11; Focus Type - Autofocus



*** Macro lens**
Lens E Mount or equivalent; Focal Length - 90mm; Aperture - Maximum: f/2.8, Minimum: f/22
Lens Format - Full-Frame; Angle of View - 27°; Minimum Focus Distance - 20.5 cm
Magnification - 2:1 Macro Reproduction Ratio, 2x Magnification; Manual Focus.

*** Led ring light system**
Type: LED ring light; Number of LEDs: min. 72; Color temperature: 5600K ±200K; CRI: ≥ 96; TLCI: ≥ 97
Brightness control: 10% - 100% (stepless); Lighting control: dual (independent left/right)
Power supply: 4× AA batteries (Alkaline/NiMH)
Mounting: front lens thread
Included adapters: 49, 52, 55, 58, 62, 67, 72, 77 mm

***Compact system external flash**
Type: compact external flash; Interface: digital hot shoe interface (direct camera communication, no cables)
Control: via camera menu (flash settings); Exposure control: face detection synchronization
White balance: automatic transfer to camera; Guide number: 28 (50 mm / ISO 100)
Flash head tilt: 0°, 20°, 40°, 60°, 80°, 120°; Sync: High-Speed Sync (HSS) supported
Metering: TTL-compatible; Wireless: integrated 2.4 GHz transceiver (master/slave)

***Professional carbon fiber system**
Type: carbon fiber tripod system; Leg sections: 6; Leg design: reverse folding (180°);
Center column: lateral (90°), 360° rotation; Center column diameter: 20 mm
Maximum height (with column): 130.8 cm; Maximum height (without column): 107.4 cm
Minimum height: 19 cm; Maximum load capacity: 5.9 kg; Total weight (with head): ≤ 1.1 kg

| | | | | | |
|------------|----------------------------------|-----|---|--|-------------------|
| | | | | <p>Leg locks: twist-lock; Leg angle positions: 23°, 55°, 80°; Head type: ball head; Level: integrated bubble level Mounting thread (head): 3/8"-16; Mounting screw (plate): 1/4"-20; Stabilization: counterweight hook Included accessories: carrying case, metal spikes, hex keys * Camera backpack Type: camera backpack (modular, 3-in-1); Volume: 32 L Configuration: backpack + removable camera compartment + divider system External dimensions (max): 36.0 × 23.0 × 52.0 cm Camera compartment dimensions: 36.0 × 15.0 × 22.0 cm Camera insert: removable, standalone use (shoulder/waist carry) Access: roll-top closure + side access panel Side pocket: expandable (tripod / bottle) Material/finish: water-resistant, matte finish Warranty: 3 years.</p> | |
| 32320000-2 | Lotul nr. 3 Tripod System | buc | 5 | <p>Legs compatible with Ace XL head Head Mount Type - 75 mm Bowl; Primary Material - Aluminum <i>General</i> - Load Capacity - min. 20 kg Maximum Working Height -158 cm; Minimum Working Height - 43 cm; Closed Length - 71 cm Spreader Support - Ground/Mid-Level; Weight - 2.2 kg Include: Aluminum Tripod, Mid-Level Spreader, Rubber Feet (Set of 3)</p> | 83 333,33 |
| 32320000-2 | Lotul nr. 4 Videohub | buc | 2 | <p><i>Processing</i> Switching Type - Pushbutton, Software; Processing Resolution Color Processing - 8-Bit 4:2:2, 10-Bit 4:2:2, 12-Bit 4:4:4; Audio Processing - 48 kHz / 24-Bit <i>Input</i> - Video Inputs - min. 40x BNC (12G-SDI) Input Video Format - SDI (10/12-Bit 4:4:4 RGB, YUV), SDI (10-Bit 4:2:2 RGB, YUV) Embedded Audio Input - SDI <i>Output</i> - Video Outputs - min. 40x BNC (12G-SDI) Output Video Format - SDI (10/12-Bit 4:4:4 RGB, YUV), SDI (10-Bit 4:2:2 RGB, YUV) Embedded Audio Output - SDI <i>Connectivity</i> - Other I/O - 1x RJ45 LAN, 1x USB-C, 1x BNC Reference Input, 1x BNC Reference Output Display Size - min. 5" <i>Power</i>I/O - 2x IEC C14 (100 to 240 VAC) Input</p> | 166 666,67 |
| 32320000-2 | Lotul nr. 5 Action Camera | buc | 2 | <p>*Action Camera <i>Imaging</i> - Image Sensor - 1/1.1"-Type CMOS; Image Stabilization - Digital Effective Sensor Resolution - min. 36 Megapixel (min. 7168 x 5376) Display Type - 2x Fixed Touchscreen LED or OLED <i>Optics per Lens</i> - Maximum Aperture - f/2 to 4; Minimum Focus Distance - 0.2 m Field of View - min. 150°; Zoom - Digital: 2x <i>Video Capture</i> - Internal Recording - MP4 via H.265/HEVC or equivalent; Internal Storage - min 50 GB Still Image Support - JPEG / Raw; Audio Recording - AAC: 16 -Bit at 48 kHz <i>Connectivity</i> Wireless - Wi-Fi / Bluetooth Media/Memory Card Slot - Single Slot:</p> | 41 666,67 |

| | | | | | |
|------------|----------------------------|-----|----|--|------------------|
| | | | | <p>microSD/microSDHC/microSDXC Inputs/Outputs - 1x USB-C Power Input/Output <i>Power</i> - Battery Type - Rechargeable Lithium-Ion Battery Pack min 1950 mAh <i>Handlebar Mount</i> - Mounting - Handle Mount: 1x Built-In 3-Prong Mount Clamping Range - 8 to 16 mm Diameter Pipe/Pole, 22 to 35 mm Diameter Pipe/Pole <i>Include</i>: 3 x Extreme Battery Plus, 2 x Dual-Direction Quick Release Adapter Mount, Curved Adhesive Base, 2 x Locking Screw, USB-C PD Charging Cable, Multifunctional Battery Case, Dual-Direction Extension Rod Kit, Anti-Slip Pad, Handlebar Mount. * Action Camera 360 <i>Imaging</i> - Image Sensor - 1/1.1"-Type CMOS (2 Lenses); Image Stabilization - Digital Effective Sensor Resolution - min. 120 Megapixel <i>Optics per Lens</i> - Maximum Aperture - f/1.9; Minimum Focus Distance - 29.5" / 75 cm <i>Video Capture</i> - Stitching Method - In-Camera Stitching; 360 Video Recording - In-Camera Stitching (MP4); Recording - MP4 H.265/HEVC, AAC: 4.0 Surround. Internal Storage - 128 GB <i>Connectivity</i> - Wireless - Wi-Fi 6 / Bluetooth Media/Memory Card Slot - Single Slot: microSD/microSDHC/microSDXC Inputs/Outputs - min. 1x USB-C Data/Power Input/Output Power - Battery Type - Rechargeable Lithium-Ion Battery Pack; Estimated Battery Life - 100 min. Include: Invisible Selfie Stick + Quick Release Mount Kit, Adjustable Quick Release Adapter Mount, Rubber Lens Protection Cover, USB-C PD Charging Cable, 3 x Battery (1950mAh), Multifunctional Battery Case.</p> | |
| | Lotul nr. 6 | | | | |
| 32240000-7 | 6.1. Camera Headset | buc | 15 | <p>Headset Dynamic; Circumaural; Closed; SPL: 96 dB; Impedance: 150 Ω; Frequency range: 10 - 30,000 Hz; Input power: 100 mW; Microphone: Dynamic; Frequency range: 150 - 10000 Hz; SPL: 136 dB; Impedance: 250 Ω 3 m Spiral cable with 3.5 mm stereo mini jack for headphones and 6.3 mm screwable adapter - XLR microphone connection</p>  | 13 916,67 |
| 32240000-7 | 6.2. Camera Headset | buc | 20 | <p>Intercom Headset Transducer principle Dynamic, Closed; Ear coupling Circumaural; Sensitivity 96 dB SPL Frequency Response 20-20,000Hz; Max. Input Power 100 Mw; Rated Impedance 400 Ω (Copper-coated aluminum wire); Earpads Leatherette; Caliper Pressure Approx. 4.5 N Connector 1.5-meter (4.92') straight cord; 4-pin XLR female plug; Finish Black Microphone; Transducer principle Dynamic, Cardioid; Frequency response 50-15,000 Hz Polar Pattern Cardioid; Output voltage-64 dBV/Pa at; 1 kHz; Impedance 250 Ω</p>  | 28 000,00 |
| | | | | Total Lotul nr. 6 | 41 916,67 |

| | | | | | |
|----------------------------------|----------------------|-----|---|--|------------|
| 323500000-1 | Lotul nr. 7 Drone | buc | 2 | <p><i>Aircraft</i> Rotor Configuration – Quadcopter; Aircraft I/O – min.1x USB-C (Power); Operating Conditions – -10 to 40°C; Maximum Horizontal Speed-97.2 km/h; Maximum Ascent Speed-36 km/h; Maximum Descent Speed-10 m/s Maximum Wind Resistance-43.1 km/h; Maximum Take-Off Altitude-6 km; Maximum Flight Time-51 Minutes Maximum Hover Time - 45 Minutes; Maximum Tilt Angle - 35°</p> <p><i>Imaging</i> - Number of Cameras - 3 Camera System – Wide min.100 MP, 4/3"-Type CMOS Sensor with 28mm; Medium Telephoto: min. 48 MP, 1/1.3"-Type CMOS Sensor with 70mm; Telephoto: min. 50 MP, 1/1.5"- Type CMOS Sensor with 168mm. Zoom – Wide min. 2.5x Digital; Medium Telephoto – min. 6x Optical; Telephoto – min. 24x Optical Minimum Focus Distance – Wide – min. 2 m; Medium Telephoto - min.3 m; Telephoto - min.3 m; Maximum Video Resolution – Wide 6016 x 3384 at 60 fps / DCI 4K at 120 fps; Medium Telephoto - UHD 4K at 120 fps; Telephoto - UHD 4K at 100 fps Internal Storage - In Aircraft Body 512 GB SSD <i>Gimbal</i> - Number of Axes - Three: Pitch (Tilt) / Roll / Yaw (Pan) / Vertical; Follow Speed - Tilt/Roll: 100°/s <i>Sensing System</i> - Omnidirectional with Infrared/LiDAR Enhancement <i>Remote Controller</i>. Frequencies: 2.400 to 2.4835 Hz / 5.170 to 5.250 Hz / 5.725 to 5.850 Hz); Wi-Fi 6. Bluetooth 5.2 Frequencies: 2.400 to 2.4835 Hz. Operating Distance – min. 30 km; Operating Temperature --10 to 40°C Transmitter I/O – min. 1x HDMI Output (Video) Battery Type - Built-In Lithium-Ion (6200 mAh) Display – min. 7" (1920 x 1200) Touchscreen LCD, min. 2000 nits/ cd/m2 <i>Include</i>: Remote Controller with HDMI output, 3 x Intelligent Flight Battery, 4 x Pair of Spare Propellers, Storage Cover, USB-C High-Speed Data Cable, 240W Power Adapter, Shoulder Bag, Parallel Charging Hub</p> <p>* Tracker (2 pcs) Splash, Water and Dust Resistance - Rated IP67 Connectivity Bluetooth for proximity finding; second-generation, Ultra Wideband chip and expanded Precision Finding connectivity; NFC tap for Lost Mode; Built-in speaker Battery User-replaceable CR2032 coin cell battery Operating ambient temperature: -20° to 60° C Size - Diameter: 31.9 mm; Height: 8.0 mm; Weight 11.8 grams</p> <p>*Drone flight management software for at least 2 years Display of the drone’s position (GPS/GNSS) on a map in real time. Recording of altitude, speed, flight duration, battery level, and signal status. Automatic saving of all flight data to the cloud or local device. Flight history with the ability to export in standard formats (CSV, PDF) for internal reports or audits. Recording of all incidents (signal loss, jamming, GNSS errors, fail-safe activations). Warranty 2 years</p> | 168 083,33 |
| Valoarea totală fără TVA: | | | | 860 000,00 | |

9. În cazul procedurilor de preselecție se indică numărul minim al candidaților și, dacă este cazul, numărul maxim al acestora. *nu se aplică.*
10. În cazul în care contractul este împărțit pe loturi un operator economic poate depune oferta (se va selecta): *Pentru mai multe loturi.*
11. Admiterea sau interzicerea ofertelor alternative: *nu se admite.*
12. Termenii și condițiile de livrare/prestare solicitate: *Livrarea bunurilor în decurs de 50 zile calendaristice de la semnarea contractului. Cheltuielile de transportare a bunurilor vor fi suportate de către Furnizor până la sediul Cumpărătorului.*
13. Termenul de valabilitate a contractului: *31.12.2026.*
14. Contract de achiziție rezervat atelierelor protejate sau că acesta poate fi executat numai în cadrul unor programe de angajare protejată (după caz): *nu se aplică.*
15. Prestarea serviciului este rezervată unei anumite profesii în temeiul unor legi sau al unor acte administrative (după caz): *nu se aplică.*
16. Scurta descriere a criteriilor privind eligibilitatea operatorilor economici care pot determina eliminarea acestora și a criteriilor de selecție/de preselecție; nivelul minim (nivelurile minime) al (ale) cerințelor eventual impuse; se menționează informațiile solicitate (DUAE, documentație):

| Nr. d/o | Descrierea criteriului/cerinței | Mod de demonstrare a îndeplinirii criteriului/cerinței: | Nivelul minim/Obligativitatea |
|---------|---|--|-------------------------------|
| 1. | (DUAE) - Documentul unic de achiziții european (în cazul în care operatorul economic participă la procedura de achiziții publice împreună cu alți operatori economici, toți participanții urmează să completeze DUAE separat) | Semnat electronic de către operatorul economic | Obligativiu |
| 2. | Oferta - specificații tehnice și de preț (conform Anexelor nr. 22 și nr. 23 la Documentația standard aprobată prin Ordinul Ministrului Finanțelor nr. 115 din 15.09.2021) | Semnată electronic de către operatorul economic | Obligativiu |
| 3. | Garanția pentru ofertă - 1% din valoarea ofertei fără TVA, | a) Garanția pentru ofertă (emisă de o bancă comercială), conform Anexei nr. 9 la Documentația standard aprobată prin Ordinul Ministrului Finanțelor nr. 115 din 15.09.2021 sau b) Transfer la contul (ordin de plată) IP Compania „Teleradio-Moldova: <i>Denumirea Băncii:BC „Moldindconbank” SA</i> <i>Codul fiscal: 1004600050558</i> <i>IBAN: MD47ML000000002251206328</i> <i>Cod bancar: MOLDM2X306</i> Termenul de valabilitate al garanției să fie valabil pe perioada de valabilitate a ofertei. semnată electronic de către operatorul economic | Obligativiu |
| 4. | Intenția de participare în cadrul procedurii de achiziție | Cerere de participare completată, conform <u>Anexei nr. 7</u> la Documentația standard aprobată prin Ordinul Ministrului Finanțelor nr. 115 din 15.09.2021, semnată electronic de către operatorul economic | Obligativiu |
| 5. | Menținerea valabilității ofertei pentru o durată de 90 de zile (calculată din momentul | Declarație privind valabilitatea ofertei, completată conform <u>Anexei nr. 8</u> la Documentația standard aprobată prin Ordinul Ministrului Finanțelor nr. 115 din 15.09.2021, | Obligativiu |

| | | | |
|-----|--|---|---|
| | <i>termenului-limită de depunere a oferte)</i> | semnată electronic de către operatorul economic | |
| 6. | Confirmarea identității beneficiarilor efectivi și neîncadrarea acestora în situația condamnării pentru participarea la activități ale unei organizații sau grupări criminale, pentru corupție, fraudă și/sau spălare de bani (<i>formularul Declarației va fi publicat pe SIA „RSAP” (MTender)</i>) | Declarație pe proprie răspundere - în termen de 5 zile după data comunicării rezultatelor procedurii de achiziție publică, ofertantul desemnat câștigător va prezenta această Declarație autorității contractante și Agenției Achiziții Publice, semnată electronic de către operatorul economic. | *Obligatoriu |
| 7. | Experiență specifică în livrarea bunurilor similare min. 3 ani (<i>art. 22 alin. (1) lit. a) din Legea 131/2015 privind achizițiile publice</i>) | Declarație privind lista principalelor livrări/prestări efectuate în ultimii 3 ani de activitate, completată conform Anexei nr. 12 la Documentația standard aprobată prin Ordinul Ministrului Finanțelor nr. 115 din 15.09.2021. Prestarea serviciilor se confirmă prin prezentarea unor certificate / documente (facturi fiscale) emise sau contrasemnate de către beneficiarii de livrări, semnate electronic de către operatorul economic. | Obligatoriu |
| 8. | Demonstrarea conformării reglementărilor Legii nr. 209/2016 privind deșeurile | Prezentarea numărului de înregistrare din „ <i>Lista producătorilor de produse supuse reglementărilor de responsabilitate extinsă a producătorului</i> ”, în conformitate cu Regulamentul privind deșeurile de echipamente electrice și electronice, aprobat prin Hotărârea Guvernului nr. 212 din 07.03.2018 (https://siamd.gov.md/portal/deee.html) - copia semnată electronic de către operatorul economic. | Obligatoriu |
| 9. | Fișa tehnică și certificatele de conformitate a bunurilor | Prezentarea fișei tehnice/datasheet/ catalogul producătorului în care să se regăsească specificația tehnică propusă - copia în format electronic confirmată prin semnătura electronică a operatorului economic. | Obligatoriu |
| 10. | Situație financiară | Raportul financiar în original/copie pentru ultimul an, aprobat de către Direcția Generală pentru Statistică sau însoțite de recipisa de primire de către Direcția Generală pentru Statistică, semnat electronic de către operatorul economic. | Obligatoriu |
| 11. | Certificat/Decizie de înregistrare a întreprinderii și Extrasul din registrul de Stat. | Copie - semnată electronic de către operatorul economic. | Obligatoriu |
| 12. | Certificat de atribuire a contului bancar. | Eliberat de banca deținătoare de cont, semnat electronic de către operatorul economic. | *Obligatoriu |
| 13. | Informația privind îndeplinirea obligațiilor de plată a impozitelor, taxelor și contribuțiilor de asigurări sociale | Confirmarea lipsei restanțelor față de bugetul public național, semnată electronic de către operatorul economic. | *Obligatoriu |
| 14. | Garanția de bună execuție a contractului - 5% din valoarea contractului, inclusiv TVA | Transfer la contul I.P. Compania „Teleradio-Moldova” <i>Beneficiarul plății:</i> <i>I.P. Compania „Teleradio-Moldova”</i> <i>Denumirea Băncii: B.C., „Moldindconbank” SA</i> | *Obligatoriu <i>(se va prezenta până la</i> |

| | | | |
|--|--|---|-----------------------------------|
| | | Codul fiscal: 1004600050558 Contul de decontare: MD47ML000000002251206328 Contul bancar: MOLDMD2X306 | semnarea contractului) |
|--|--|---|-----------------------------------|

***În cazul în care IP Compania „Teleradio-Moldova” , potrivit prevederilor art. 20 alin. (8) din Legea nr. 131/2015 privind achizițiile publice, va solicita prezentarea anumitor documente justificative, operatorul economic este obligat să le prezinte în termen de 3 zile lucrătoare, conform prevederilor DUAE și cadrului normativ în vigoare. În cazul neprezentării documentelor justificative în termenul-limită stabilit, operatorul economic va fi descalificat.**

***Documentele menționate la pct. 16, subpct. 2 se completează fără nici o modificare sau abatere de la formulare, spațiile goale fiind completate cu informația solicitată. Completarea defectuoasă a formularelor atrage respingerea ofertei.**

***În cazul în care Oferta nu este semnată de către administratorul companiei indicat în Extrasul Registrului de Stat al persoanelor juridice, la Ofertă se anexează actul/documentul de împuternicire a persoanei delegate sau împuternicite să semneze Oferta.**

17. **Garanția pentru ofertă, după caz - Da, cuantumul de 1%, din valoarea ofertei fără TVA.**
18. **Garanția de bună execuție a contractului, după caz - Da, cuantumul 5% din valoarea contractului, inclusiv TVA, transfer la contul I.P. Compania „Teleradio-Moldova”.**
19. **Motivul recurgerii la procedura accelerată (în cazul licitației deschise, restrânse și a procedurii negociate), după caz: nu se aplică.**
20. **Tehnici și instrumente specifice de atribuire (dacă este cazul specificați dacă se va utiliza acordul-cadru, sistemul dinamic de achiziție sau licitația electronică): Licitație electronică, 3 runde, valoarea pasului minim 1%.**
21. **Condiții speciale de care depinde îndeplinirea contractului (indicați după caz): nu se aplică.**
22. **Ofertele se prezintă în valuta: LEI MDL.**
23. **Criteriul de evaluare aplicat pentru atribuirea contractului: prețul cel mai scăzut.**
24. **Factorii de evaluare a ofertei celei mai avantajoase din punct de vedere economic, precum și ponderile lor: nu se aplică.**
25. **Termenul limită de depunere/deschidere a ofertelor: conform SIA RSAP.**
26. **Adresa la care trebuie transmise ofertele sau cererile de participare: Ofertele sau cererile de participare vor fi depuse electronic prin intermediul SIA RSAP.**
27. **Termenul de valabilitate a ofertelor: 90 zile.**
28. **Locul deschiderii ofertelor: SIA RSAP. Ofertele întârziate vor fi respinse.**
29. **Persoanele autorizate să asiste la deschiderea ofertelor: Ofertanții sau reprezentanții acestora au dreptul să participe la deschiderea ofertelor, cu excepția cazului când ofertele au fost depuse prin SIA RSAP.**
30. **Limba sau limbile în care trebuie redactate ofertele sau cererile de participare: Română**
31. **Respectivul contract se referă la un proiect și/sau program finanțat din fonduri ale Uniunii Europene: nu se aplică.**
32. **Denumirea și adresa organismului competent de soluționare a contestațiilor:**
 Agenția Națională pentru Soluționarea Contestațiilor
 Adresa: mun. Chișinău, bd. Ștefan cel Mare și Sfânt nr.124 (et.4), MD 2001;
 Tel/Fax/email:022-820 652, 022 820-651, contestatii@ansc.md.
33. **Data (datele) și referința (referințele) publicărilor anterioare în Jurnalul Oficial al Uniunii Europene privind contractul (contractele) la care se referă anunțul respectiv (dacă este cazul): nu se aplică.**
34. **În cazul achizițiilor periodice, calendarul estimat pentru publicarea anunțurilor viitoare: nu se aplică.**
35. **Data publicării anunțului de intenție sau, după caz, precizarea că nu a fost publicat un astfel de anunț: BAP nr. 40/2026 din 22.05.2026 (publicat 26.05.2026)**
 Link: https://tender.gov.md/ro/system/files/bap/2014/bap_nr_40_1.pdf
36. **Data transmiterii spre publicare a anunțului de participare: Conform SIA RSAP**

37. În cadrul procedurii de achiziție publică se va utiliza/accepta:

| Denumirea instrumentului electronic | Se va utiliza/accepta sau nu |
|--|-------------------------------------|
| Depunerea electronică a ofertelor sau a cererilor de participare | da |
| Sistemul de comenzi electronice | nu |
| Facturarea electronică | da |
| Plățile electronice | da |

38. Contractul intră sub incidența Acordului privind achizițiile guvernamentale al Organizației Mondiale a Comerțului (numai în cazul anunțurilor transmise spre publicare în Jurnalul Oficial al Uniunii Europene): *nu se aplică.*

**Președintele grupului de lucru
pentru achiziții publice**

Veaceslav RUSU