

CAIET DE SARCINI

pentru închirierea echipamentului de revelion,
în perioada 29.11.2022 - 09.12.2022.

N.	Denumirea bunului	Descriere	C-te	Unitatea de măsură
1	Podium	Podium Extruded tube Ø 50 x 2 mm EN AW 6082 T6 Diagonals B: extruded tube Ø 18 x 2 mm EN AW 6082 T6 Ends C: aluminium cashng plate EN AC 42200 T6 UNI ENV 1999-1-1 (Eurocode 9)	48	m2
2	LED Screen	LED DISPLAY 640 mm x 640 mm / cabinet - SMD2727 (WHITE) - 750 W/m2 - 250 W/m2 - Lux 16.7 mln. - 1920 Hz	50	m2
3	Echipament sunet	Echipament sunet (echivalent FBT Muse 210 LA / FBT Mitus 218 SA) SUB: Subwoofer cu banda aerisita, cu sistem bass-reflex. Echipat cu doua difuzoare de frecventa joasa cu diametrul de 18" si bobina de 3.9". Frecventa de raspuns de la 30Hz la 100Hz. Amplificator clasa D cu putere de 2000W RMS TOP: Woofer: 2 X 10" bobina de 2.5" Driver 2 x 1" cu bobina de 1.7" Putere RMS: 900 W Raspuns frecventa: 55Hz-20000Hz SPL Maxim: 135 dB Dispersie driver: 90° x 10° Procesor de semnal digital	16	kw
4	Echipament sunet	Amplificator Bass (echivalent Markbass Little Mark III) Inputs: Unbalanced Jack and Balanced XLR Effects Send and Return EQ: 4-band EQ Variable Pre-shape Filter (VPF) with 380 Hz Center Frequency Vintage Loudspeaker Emulator (VLE) Frequency Range- 250Hz - 20 kHz Outputs: Balanced XLR Line Out, 1/4" Jack Tuner Out, Speakon Combi Speaker Out Output Power: 300W RMS @ 8Ohms, 500W RMS @ 4Ohms	1	buc
5	Echipament sunet	Amplificator Chitara (echivalent Fender Twin Amp) Features: Type Vintage Reissue Series Tube Amp Output 85 watts into 4 ohms Ohms 4 ohms Speakers 1-15" Custom Eminence® 4 ohm Speaker with Ceramic Magnet, (Based on the Now Collectable JBL® D130F Speaker Used by Fender® in the '60s and '70s) Channels Dual Channels (Normal and Vibrato) Features Reverb Vibrato 2-Button Footswitch Tilt Back Legs Controls Normal Channel: Bright Switch, Volume, Treble, Middle, Bass Vibrato Channel: Bright Switch, Volume, Treble, Middle, Bass Reverb Vibrato: Speed, Intensity Covering Black Textured Vinyl with Silver Grille Cloth Weight 64 lbs. (34kg) Dimensions Height: 22" (55.9 cm) Width: 26.15" (66.4 cm) Depth: 10.5" (26.7 cm) Tube Complement 4 X 12AX7 2 X 12AT7 4 X 6L6 Solid State Rectifier Shipping Weight 70 lbs Cover Included Accessories 2-Button Footswitch for Reverb and Vibrato On/Off Footswitch Uses 2-Button Footswitch Accy	1	buc
6	Echipament sunet (set)	Set de tobe (echivalent Drums Pearl's Masters Series) Set Microfoane (echivalent Seenheiser 904) Yamaha Studio Custom SET Set Microfoane (echivalent Shure SM 57)	1	buc
7	Echipament sunet	Wireless In Ear System (echivalent ew IEM G4 Twin) Consists of 2 x UHF bodypack receiver (EK IEM G4), 9.5" transmitter (SR IEM G4) and 2 x IE4 earphones Stereo / focus / mono modes 3.5 mm jack for earphones Adjustable limiter Adjustable 6.3mm headphone jack on the transmitter 1 x BNC antenna socket Inputs 2 x Jack / XLR female balanced combo	3	buc
8	Echipament sunet (set)	Mixer sunet (echivalent SQ5) Mixer digital cu 48 canale Cu procesare FPGA de 96 kHz 17 faders / 6 layers 12x stereo mixes + LR3x stereo matrix 8x stereo FX engines + dedicated stereo returns DEEP procesarea permite integrarea plug-in-urilor direct în intrările mixerului și amestecarea canalelor Ecran tactil de 7 inch Slink port pentru audio / expansiune la distanță 64 port I / O pentru rețele audio 32 x 32 interfață audio USB Înregistrare directă SQ-Drive pe USB StageBox	1	buc

		<p>leșire AES Compatibil cu cardurile de rețea audio ME 1 și ME-500 și Dante sau Waves Monitoare (carcasa din Lemn) Mictrofoane radio Shure QLXD/ Beta 58/ SM 58, Shure SLXD, Sennheiser</p>		
9	Echipament sunet (set)	<p>Mixer sunet (echivalent Digico SD11) 48 Input Channels with full processing 24 Aux/Sub-Group busses with full processing 8 x 8 Matrix with full processing Assignable channel layout User programmable macros Capable of redundantly mirroring with another SD11 console Snapshots for seamlessly changing many parameters at once Offline software iPad control Broadcast software option i software option 12 x 100mm touch-sensitive, motorised faders 1 x 15" LCD high-resolution touchscreen 12 x 8-Segment LED bargraph meters 1 x 1/4" Headphone socket 1 x USB 2.0 slot 1 x PSU 1 x XLR3 1.2 – 12V Light connection 1 x Waves port (Optional) 16 x XLR Mic/Line Inputs 8 x XLR Line Outputs 1 x XLR AES/EBU Input (2 x channels) 1 x XLR AES/EBU Output (2 x channels) 2 x GPI 1/4" Jack 2 x GPO 1/4" Jack 1 x MIDI In/Thru/Out (5 pin DIN) 1 x Word Clock I/O BNC Rack is a 32 input, 8 output 32 Mic/Line Inputs at 48kHz or 28 Mic/Line inputs at 96kHz 8 Line Outputs 1 Output expansion card slot for adding 8 outputs MADI RJ45 Connectivity Optional Optics 7U Rack Mountable with supplied rackmount kit Gain Tracking™ Optional Redundant PSUs Can be used as a standalone rack</p>	1	buc
10	Lumini speciale	<p>Moving Head (echivalent DTS Raptor) beam opening 3.4° unique 8-facet prism 17 fixed gobos smooth filter and frost filter silent operation color wheel (17 filters) 150,000 lux @ 15 m +/- 24 Moving head/ beam/ spot/ wash Chauvet 140 SR/ DTS Raptor/ Chauvet 375Z/ Showtec Q4 Light output: 382.000 lux @ 5m Light source: Osaram Sirius hri 140w Zoom angle (degrees): beam – 3 to 11 degrees Spot – 7 to 21 Wash – 14 to 28 Colors 12+white Prism: 8-facet round, bidirectional rotation at variable speeds. Effects: pixel control, flower effect, virtual colour wheel, tungsten lamp effect, +/- 24 Par led Future light & Showtec 12x10w, 6 in 1 LWD (RGBWA+UV) 18x8w, RGBW</p>	16	buc
11	Lumini speciale	<p>Par (echivalent LED Par 64 Short Q4-18) 18 x 8 W RGBW LED Par 40° fixed beam angle Double bracket for easy floor positioning DMX and manual control in Auto run and Sound-controlled mode RGBW colour mixing, dimmer and strobe function +/- 12 Futurelight par led 12x10 Slim Equipped with 12 high-power LEDs in the colors red, green, blue, amber, white and UV Flat housing form requires minimal space when rigging Extremely compact housing in a beautiful design Second mounting bracket for safe standing installation</p>	50	buc

		<p>Locking possibility at the brackets with large metal butterfly screws</p> <p>Functions: static colors, RGBAW+UV color mixture, automatic color changes, dimmer, strobe effect with adjustable speed, Master/Slave operation</p> <p>Addressing and setting via Control Board with four operating buttons and LED display</p> <p>Switch-mode power supply for operation between 100 and 240 volts</p> <p>P-Con terminals for power linking up to 8 units</p> <p>12 powerful LEDs 10 W high-power 6in1 HCL RGBWA/UV (homogenous color mix)</p> <p>Can be operated in 6; 10 CH mode</p> <p>The device is cooled by passive convection cooling</p> <p>Controlling by stand-alone; DMX; Sound to light via Microphone</p> <p>Preprogrammed in Light'J; LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE</p> <p>Flicker-free</p> <p>Effect: Strobe effect; UV effect</p> <p>With a beam angle of 18°</p>		
12	Lumini speciale	<p>Moving Head (echivalent Intimidator Beam Q60)</p> <p>DMX Channels: 12 or 16</p> <p>DMX Connectors: 3-pin XLR</p> <p>Pan and Tilt: 540°/260°</p> <p>Pan and Tilt Ranges: 540°, 360°, 180° pan/260°, 180°, 90° tilt</p> <p>Light Source: 1 LED (quad-color RGBW) 60 W, (4.5 A), 50,000 hours life expectancy</p> <p>Strobe Rate: 0 to 20 Hz</p> <p>Beam Angle: 3°</p> <p>Illuminance: 45,344 lux @ 2 m</p> <p>Input Voltage: 100 to 240 VAC, 50/60 Hz (auto-ranging)</p> <p>Color Temperature Range: 2000 to 8000 K</p>	8	buc
13	Mașină de fum	<p>Mașină de fum Hazer</p> <p>Lichid de fum Hazer</p>	2	buc
14	Instalare, operare	<p>Lucrările de montare, precum și operațiuni de instalare, ajustare și operare în timpul filmărilor.</p> <p>Materiale și elemente pasive/active necesare pentru interconectarea echipamentelor și punerea în funcțiune a acestora;</p>	1	buc