

Price specifications

[This table shall be filled in by the bidder in columns 5,6,7,8,11, and by the contracting authority – in columns 1,2,3,4,9,10]

Tender number: _____

Name of the tender: _____

CPV code	Name of goods/services	Unit of measurement	Quantity	Unit price (without VAT)	Unit price (with VAT)	Amount without VAT	Amount with VAT	Delivery time/presatire	Budget classification (IBAN)	% Discount
1	2	3	4	5	6	7	8	9	10	11

LOT I Materials and Semi-finished products for dentures lower limbs

1	33183000-6	Bushing adapter	Pcs	4				If necessary, within 5 working days from the receipt of the request, sent electronically, through the interactive flows, made available by the economic operator in the ESPD form	State Budget 2023 MD44TRPCCC518430A01034AA	
2	33183000-6	Double sliding adapter	Pcs	2						
3	33183000-6	Sliding adapter with screws	Pcs	2						
4	33183000-6	Adapter for locking tube	Pcs	400						
5	33183000-6	60 mm double sliding adapter	Pcs	2						
6	33183000-6	75 mm double sliding adapter	Pcs	2						
7	33183000-6	Screw adaptation device	Pcs	2						
8	33183000-6	35 mm double adapter	Pcs	3						
9	33183000-6	60 mm double adapter	Pcs	3						
10	33183000-6	45 mm double adapter	Pcs	4						
11	33183000-6	65 mm double adapter	Pcs	2						
12	33183000-6	75 mm double adapter	Pcs	3						
13	33183000-6	90 mm double adapter	Pcs	2						
14	33183000-6	Self-adhesive ribbon on both sides	Pcs	5						
15	33183000-6	Pvc sticky tape	Pcs	5						
16	33183000-6	Elastic for prostheses 45 mm	m	900						
17	33183000-6	Cosmetic stocking with knitting heel size 50	Pcs	400						
18	33183000-6	Cosmetic stocking with knitting heel size 70	Pcs	300						

19	33183000-6	Cosmetic stocking with knitting heel size 90	Pcs	100					If necessary, within 5 working days from the receipt of the request, sent electronically, through the interactive flows, made available by the economic operator in the ESPD form	State Budget 2023 MD44TRPCCC518430A01034AA	
20	33183000-6	Liner Trans Tibial 22	Pcs	6							
21	33183000-6	Liner Trans Tibial 23,5	Pcs	9							
22	33183000-6	Liner Trans Tibial 26,5	Pcs	18							
23	33183000-6	Liner Trans Tibial 28	Pcs	17							
24	33183000-6	Liner Trans Femural 32	Pcs	4							
25	33183000-6	Liner Trans Femural 36	Pcs	4							
26	33183000-6	Liner Trans Femural 40	Pcs	2							
27	33183000-6	Liner Trans Femural 45	Pcs	4							
28	33183000-6	Liner Trans Femural 50	Pcs	1							
29	33183000-6	Tube adapter for dentures of the lower limbs (lower leg)	Pcs	200							
30	33183000-6	Tube adapter for dentures of the lower limbs (lower leg + thigh)	Pcs	315							
31	33183000-6	Self-locking knee joint	Pcs	5							
32	33183000-6	Knee joint without self-locking	Pcs	5							
33	33183000-6	Knee joint with padlock	Pcs	110							
34	33183000-6	Knee joint without a padlock	Pcs	70							
35	33183000-6	Four-arm lamination anchor	Pcs	250							
36	33183000-6	SACH prosthetic foot adapter	Pcs	70							
37	33183000-6	Rotating three-arm rolling anchor with a rotating core	Pcs	15							
38	33183000-6	Three-arm rolling anchor, rotating	Pcs	150							
39	33183000-6	Card	Pcs	100							
40	33183000-6	Left uniaxial prosthetic foot size-140 mm	Pcs	1							
41	33183000-6	Left uniaxial prosthetic foot size-150 mm	Pcs	1							
42	33183000-6	Right uniaxial prosthetic foot size-150 mm	Pcs	1							

43	33183000-6	Left uniaxial prosthetic foot size-160 mm	Pcs	1					If necessary, within 5 working days from the receipt of the request, sent electronically, through the interactive flows, made available by the economic operator in the ESPD form	State Budget 2023 MD44TRPCCC518430A01034AA	
44	33183000-6	Left uniaxial prosthetic foot size-180 mm	Pcs	1							
45	33183000-6	Left uniaxial prosthetic foot size-200 mm	Pcs	1							
46	33183000-6	Right uniaxial prosthetic foot size-210 mm	Pcs	1							
47	33183000-6	Right carbon prosthetic foot size-220 mm	Pcs	2							
48	33183000-6	Prosthetic foot made of carbon sting size-220 mm	Pcs	2							
49	33183000-6	Prosthetic foot made of left carbon size-230 mm	Pcs	2							
50	33183000-6	Prosthetic foot made of right carbon size-230 mm	Pcs	2							
51	33183000-6	Left carbon prosthetic foot size-240 mm	Pcs	2							
52	33183000-6	Prosthetic foot made of right carbon size-240 mm	Pcs	2							
53	33183000-6	Prosthetic foot made of left carbon size-250 mm	Pcs	4							
54	33183000-6	Prosthetic foot made of right carbon size-250 mm	Pcs	4							
55	33183000-6	Prosthetic foot made of left carbon size-260 mm	Pcs	9							
56	33183000-6	Right carbon prosthetic foot size-260 mm	Pcs	9							
57	33183000-6	Left carbon prosthetic foot size-270 mm	Pcs	11							
58	33183000-6	Right carbon prosthetic foot size-270 mm	Pcs	11							
59	33183000-6	Left carbon prosthetic foot size-280 mm	Pcs	4							
60	33183000-6	Right carbon prosthetic foot size-280 mm	Pcs	4							
61	33183000-6	Right uniaxial prosthetic foot size-220 mm	Pcs	3							
62	33183000-6	Left uniaxial prosthetic foot size-220 mm	Pcs	3							
63	33183000-6	Left uniaxial prosthetic foot size-230 mm	Pcs	6							

64	33183000-6	Right uniaxial prosthetic foot size-230 mm	Pcs	4					If necessary, within 5 working days from the receipt of the request, sent electronically, through the interactive flows, made available by the economic operator in the ESPD form	State Budget 2023 MD44TRPCCC518430A01034AA	
65	33183000-6	Left uniaxial prosthetic foot size-240 mm	Pcs	6							
66	33183000-6	Right uniaxial prosthetic foot size-240 mm	Pcs	4							
67	33183000-6	Left uniaxial prosthetic foot size-250 mm	Pcs	10							
68	33183000-6	Right uniaxial prosthetic foot size-250 mm	Pcs	8							
69	33183000-6	Left uniaxial prosthetic foot size-260 mm	Pcs	18							
70	33183000-6	Right uniaxial prosthetic foot size-260 mm	Pcs	16							
71	33183000-6	Left uniaxial prosthetic foot size-270 mm	Pcs	42							
72	33183000-6	Right uniaxial prosthetic foot size-270 mm	Pcs	37							
73	33183000-6	Left uniaxial prosthetic foot size-280 mm	Pcs	6							
74	33183000-6	Right uniaxial prosthetic foot size-280 mm	Pcs	6							
75	33183000-6	Left uniaxial prosthetic foot size-290 mm	Pcs	2							
76	33183000-6	Right uniaxial prosthetic foot size-290 mm	Pcs	2							
77	33183000-6	Prosthetic foot with adjustment of the height of the right heel size-220 mm	Pcs	1							
78	33183000-6	Prosthetic foot with adjustment of the height of the left heel size-220 mm	Pcs	2							
79	33183000-6	Prosthetic foot with adjustment of the height of the left heel size-230 mm	Pcs	2							
80	33183000-6	Prosthetic foot with adjustment of the height of the right heel size-230 mm	Pcs	2							
81	33183000-6	Prosthetic foot with the adjustment of the height of the left heel size-240 mm	Pcs	2							

82	33183000-6	Prosthetic foot with adjustment of the height of the right heel size-240 mm	Pcs	3					If necessary, within 5 working days from the receipt of the request, sent electronically, through the interactive flows, made available by the economic operator in the ESPD form	State Budget 2023 MD44TRPCCC518430A01034AA	
83	33183000-6	Prosthetic foot with adjustment of the height of the left heel size-250 mm	Pcs	9							
84	33183000-6	Prosthetic foot with adjustment of the height of the right heel size-250 mm	Pcs	9							
85	33183000-6	Prosthetic foot with adjustment of the height of the left heel size-260 mm	Pcs	18							
86	33183000-6	Prosthetic foot with adjustment of the height of the right heel size-260 mm	Pcs	18							
87	33183000-6	Prosthetic foot with adjustment of the height of the left heel size-270 mm	Pcs	20							
88	33183000-6	Prosthetic foot with adjustment of the height of the right heel size-270 mm	Pcs	20							
89	33183000-6	Prosthetic foot with adjustment of the height of the left heel size-280 mm	Pcs	3							
90	33183000-6	Prosthetic foot with adjustment of the height of the right heel size-280 mm	Pcs	3							
91	33183000-6	Prosthetic foot with adjustment of the height of the left heel size-290 mm	Pcs	2							
92	33183000-6	Prosthetic foot with adjustment of the height of the right heel size-290 mm	Pcs	2							
93	33183000-6	Prosthetic foot type SACHI 22L	Pcs	2							
94	33183000-6	Prosthetic foot type SACHI 22R	Pcs	2							
95	33183000-6	Prosthetic foot type SACHI 23R	Pcs	8							
96	33183000-6	Prosthetic foot type SACHI 25L	Pcs	3							
97	33183000-6	Prosthetic foot type SACHI 26L	Pcs	5							

98	33183000-6	Prosthetic foot type SACHI 26R	Pcs	12					If necessary, within 5 working days from the receipt of the request, sent electronically, through the interactive flows, made available by the economic operator in the ESPD form	State Budget 2023 MD44TRPCCC518430A01034AA	
99	33183000-6	Prosthetic foot type SACHI 27R	Pcs	10							
100	33183000-6	Prosthetic foot type SACHI 28L	Pcs	3							
101	33183000-6	Prosthetic foot type SACHI 28R	Pcs	3							
102	33183000-6	Prosthetic foot type SACHI 29L	Pcs	3							
103	33183000-6	Prosthetic foot type SACHI 29R	Pcs	3							
104	33183000-6	Prosthetic foot for 23L leather prostheses	Pcs	2							
105	33183000-6	Prosthetic foot for 23R leather prostheses	Pcs	2							
106	33183000-6	Prosthetic foot for skin prostheses 24R	Pcs	4							
107	33183000-6	Prosthetic foot for leather prostheses 26L	Pcs	13							
108	33183000-6	Prosthetic foot for leather prostheses 26R	Pcs	13							
109	33183000-6	Prosthetic foot for skin prostheses 27L	Pcs	21							
110	33183000-6	Prosthetic foot for leather prostheses 27R	Pcs	12							
111	33183000-6	Prosthetic foot for leather prostheses 28L	Pcs	11							
112	33183000-6	Prosthetic foot for leather prostheses 28R	Pcs	2							
113	33183000-6	Prosthetic foot for leather prostheses 29L	Pcs	2							
114	33183000-6	Prosthetic foot for leather prostheses 29R	Pcs	2							
115	33183000-6	Ankle made of aluminum alloy, designed for making prostheses of the lower limbs from leather size 220-250mm (V = 250 mm, for the length of the foot 240-260 mm)	Pcs	30							

116	33183000-6	Ankle made of aluminum alloy, designed for making prostheses of the lower limbs from leather size 260-300 mm (V = 260 mm, for the length of the foot 265-285 mm)	Pcs	30					If necessary, within 5 working days from the receipt of the request, sent electronically, through the interactive flows, made available by the economic operator in the ESPD form	State Budget 2023 MD44TRPCCC518430A01034AA		
117	33183000-6	Small wooden ankle for dentures of the lower limbs Ankle sizes (mm) K=150 mm, K1=87 mm, K2=70 mm, K3=52 mm, K4=57 mm, K5=52 mm, P=230 mm	Pcs	20								
118	33183000-6	Average wooden ankle for dentures of the lower limbs Ankle sizes (mm) K=150 mm, K1=97 mm, K2=80 mm, K3=59 mm, K4=64 mm, K5=52 mm, P=254mm	Pcs	15								
119	33183000-6	Seminel	Pcs	130								
120	33183000-6	Seminel	Pcs	60								
121	33183000-6	Seminel length 220 mm	Pcs	30								
122	33183000-6	Seminel length 175 mm	Pcs	15								
123	33183000-6	Semi-finished for calf prosthesis	Pcs	2								
124	33183000-6	Metal insole for orthopedic appliances for the left foot length 130 mm	Pcs	1								
125	33183000-6	Metal insole for orthopedic appliances for the left foot, length 150 mm	Pcs	2								
126	33183000-6	Metal insole for orthopedic appliances for the left foot, length 170 mm	Pcs	2								

127	33183000-6	Metal insole for orthopedic apparatus for the right foot, length 170 mm	Pcs	2					If necessary, within 5 working days from the receipt of the request, sent electronically, through the interactive flows, made available by the economic operator in the ESPD form	State Budget 2023 MD44TRPCCC518430A01034AA	
128	33183000-6	Metal insole for orthopedic appliances for the left foot, length 200 mm	Pcs	2							
129	33183000-6	Metal insole for orthopedic apparatus for the right foot, length 200 mm	Pcs	2							
130	33183000-6	Metal trochanter	Boxes	2							
131	33183000-6	Knee-joint splints for leather prostheses and lower limb apparatus (complete)	Pcs	110							
132	33183000-6	Knee-joint splints for leather prostheses and lower limb apparatus (complete)	Pcs	10							
133	33183000-6	Knee-joint splints for leather prostheses and lower limb apparatus (complete)	Pcs	5							
134	33183000-6	Assemble of knee-joint splints for leather prostheses and lower limb apparatus (assembly) (complete)	Pcs	8							
135	33183000-6	Complete splints for prostheses intended in case of Pirogov type amputation (complete)	Pcs	4							
136	33183000-6	Splints with knee joint and padlock for leather prostheses and lower limb apparatus (assembly) (complete)	Pcs	11							

137	33183000-6	Splints for thigh prostheses with unilateral wool and bifurcation at the distal side (complete)	Pcs	2						
138	33183000-6	Splints for orthotics with padlock (complete)	Pcs	2					If necessary, within 5 working days from the receipt of the request, sent electronically, through the interactive flows, made available by the economic operator in the ESPD form	State Budget 2023 MD44TRPCCC518430A01034AA
139	33183000-6	Hinge used in the manufacture of leather prostheses	Pcs	50						
140	33183000-6	Knitted tube made of polyester diameter 8 cm	kg	3						
141	33183000-6	Knitted tube made of polyester diameter 10 cm	kg	18						
142	33183000-6	Knitted tube made of polyester diameter 12 cm	kg	40						
143	33183000-6	Knitted tube made of polyester diameter 15 cm	kg	35						
144	33183000-6	PVA Sleeve 10"	Pcs	11						
145	33183000-6	PVA Sleeve 12"	Pcs	12						
146	33183000-6	PVA Sleeve 14"	Pcs	50						
147	33183000-6	Drilled metal disc	Pcs	2000						
148	33183000-6	Copper rivet	kg	6						
149	33183000-6	Brass staples	kg	4						
150	33183000-6	Valve with vacuum	Pcs	30						
151	33183000-6	Valve with vacuum	Pcs	30						
152	33183000-6	Ring for valve with vacuum	Pcs	30						
153	33183000-6	Pulley for the belt	Pcs	150						
154	33183000-6	Buckthorn with	Pcs	1200						
155	33183000-6	Buckthorn with	Pcs	2000						
156	33183000-6	Semi-finished for flexible sleeve thickness 12 mm	Pcs	10						
157	33183000-6	Semi-finished for flexible sleeve thickness 15 mm	Pcs	20						
158	33183000-6	Semi-finished sample sleeve thickness 12 mm	Pcs	15						
159	33183000-6	Semi-finished sample sleeve thickness 15 mm	Pcs	15						
160	33183000-6	Foamy material for the inner cup	m ²	34						
161	33183000-6	Fastening belt	Pcs	350						

162	33183000-6	Belt for arm's prosthesis (prefabricated)	Pcs	4						
163	33183000-6	Fastening strap Length: 150 mm; Width 16 mm.	Pcs	100						
164	33183000-6	Fastening strap Length: 170 mm; Width 16 mm.	Pcs	400					If necessary, within 5 working days from the receipt of the request, sent electronically, through the interactive flows, made available by the economic operator in the ESPD form	State Budget 2023 MD44TRPCCC518430A01034AA
165	33183000-6	Curelușă de fixare Lungimea: 230 mm; Lățimea 19 mm.	Pcs	1600						
166	33183000-6	Lainer padlock for calf prostheses	Pcs	50						
167	33183000-6	Lainer padlock for thigh prostheses	Pcs	17						
168	33183000-6	Carbon canvas with a width of 100 cm	m	150						
169	33183000-6	Felt thickness 7 mm	kg	8						
170	33183000-6	Ortho-acrylic resin for finished cup (4.6 kg)	Pcs	50						
171	33183000-6	Dust solidifier (150 gr.)	Pcs	50						
172	33183000-6	Cotton stocking for amputation of upper limbs	Pcs	100						
173	33183000-6	Wool stocking for thigh amputation	Pcs	240						
174	33183000-6	Line sock for calf amputation	Pcs	200						
175	33183000-6	Cotton stocking for thigh amputation	Pcs	200						
176	33183000-6	Line sock for calf amputation	Pcs	360						
177	33183000-6	Gypsum bowl	Pcs	10						
178	33183000-6	Screwdriver for prostheses	Pcs	10						
179	33183000-6	Segment for electric saw	Pcs	5						
180	33183000-6	Thigh support bandage size L-90R	Pcs	2						
181	33183000-6	Thigh support bandage size L-90L	Pcs	2						
182	33183000-6	Thigh support bandage size XL-101R	Pcs	2						
183	33183000-6	Thigh support bandage size XL-101L	Pcs	2						

184	33183000-6	Sealing sleeve No. 1 Perimeter distal part 30mm, perimeter proximal part 40mm	Pcs	2							
185	33183000-6	Sealing sleeveNo.2 Perimeter distal part 40mm, perimeter proximal part 50mm	Pcs	4							
186	33183000-6	Sealing sleeve No. 3 Perimeter distal part 50mm, perimeter proximal part 60mm	Pcs	6						If necessary, within 5 working days from the receipt of the request, sent electronically, through the interactive flows, made available by the economic operator in the ESPD form	State Budget 2023 MD44TRPCCC518430A01034AA
187	33183000-6	Sealing sleeve No.4 Perimeter distal part 60mm, proximal part perimeter 70mm	Pcs	2							
188	33183000-6	Donning sheath for transfemoral prostheses size M	Pcs	10							
189	33183000-6	Donning sheath for transfemoral prostheses size L	Pcs	10							
190	33183000-6	Nit for leather prostheses	Pcs	100							
191	33183000-6	Holniten complete foot height 10 mm (complete)	Pcs	5000							
192	33183000-6	Holniten complete foot height 12 mm (complete)	Pcs	3000							
193	33183000-6	Nails for shoes K18	kg	15							
194	33183000-6	Chemical Pencil	Pcs	10							
195	33183000-6	Gypsum strip 15cm×270cm	Pcs	960							
196	33183000-6	Tights	Pcs	200							
197	33183000-6	Short tights	Pcs	200							
198	33183000-6	Carbon fiber tube 150	rolă	1							
199	33183000-6	Carbon fiber tube 225	Roll	1							
200	33183000-6	Revolock system	Roll	3							
201	33183000-6	Paper for thermal printing	m	10							
202	33183000-6	Pedilin for removing the negative	Pcs	50							

LOT II Blanks for upper limb prostheses

1	33183000-6	Hand for prosthesis of the upper limb from medical plastisol for women (right), No.18 fullness 1	Pcs	6					If necessary, within 5 working days from the receipt of the request, sent electronically, through the interactive flows, made available by the economic operator in the ESPD form	State Budget 2023 MD44TRPCCC518430A01034AA	
2	33183000-6	Hand for prosthesis of the upper limb from medical plastisol for women (left), No.18 fullness 1	Pcs	5							
3	33183000-6	Hand for upper limb prosthesis from medical plastisole for men (left), No.19 fullness 1	Pcs	10							
4	33183000-6	Hand for prosthesis of the upper limb from medical plastisol for women (right), No.20 fullness 1	Pcs	5							
5	33183000-6	Hand for prosthesis of the upper limb from medical plastisol for men (left), No.21 fullness 1	Pcs	4							
6	33183000-6	Hand for prosthesis of the upper limb from medical plastisol for men (left), No.22 fullness 1	Pcs	7							
7	33183000-6	Hand for prosthesis of the upper limb from medical plastisol for men (right), No.22 fullness 1	Pcs	4							
8	33183000-6	Hand for prosthesis of the upper limb from medical plastisol for men (left), No.23 fullness 1	Pcs	3							
9	33183000-6	Hand for prosthesis of the upper limb from medical plastisol for men (right), No.23 fullness 1	Pcs	4							
10	33183000-6	Hand for the prosthesis of the upper limb from medical plastisol for men (left), No.24 fullness 1	Pcs	3					If necessary, within 5 working days from the receipt of the request, sent electronically, through the interactive flows, made available by the economic	State Budget 2023 MD44TRPCCC518430A01034AA	




21	33183000-6	Artifice hand for prosthesis of the forearm of the upper limb (active) Tipo-size No. 6 left	Pcs	6						
22	33183000-6	Complete blanks for the right arm prosthesis (complete)	Pcs	3						
23	33183000-6	Complete of blanks for left arm prosthesis (complete)	Pcs	3						





Technical specifications






[This table shall be filled in by the tenderer in columns 3, 4, 5, 7, and by the contracting authority – in columns 1, 2, 5]




Tender number:




Name of the tender:




	Name of goods/services	Name of the model of the good/service	Country of origin	Manufacturer	Full technical specification requested by the contracting authority	Full technical specification proposed by the bidder	Reference standards												
	1	2	3	4	5	6	7												
LOT I Materials and Semi-finished products for dentures lower limbs																			
1	Bushing adapter				Intended for fixing tube adapters. Material: steel; Diameter on the inside: 30 mm; Maximum manageable body mass 125 Kg; Weight: 100 gr. Products in positions from 1 to 25 belong to a single manufacturer and are compatible with each other. Minimum warranty period of 24 months. Packed in PVC bags.														
2	Double sliding adapter				The sliding screw adapter allows translational adjustment at the proximal end of a tubular adapter. Thus, it is possible to move the distal components of the modular prosthesis in parallel, independently of the angle adjustments through the adjustment cores. The adjustments can be made either at the front (medial or lateral) plane or in the sagittal plane (anterior or posterior). This is also possible when the prosthesis is applied. Packed in VACUUM PVC bags. <table border="1" data-bbox="996 893 1456 1013"> <tr> <td>Greutate [g]</td> <td>185</td> </tr> <tr> <td>Înălțime sistem [mm]</td> <td>51</td> </tr> <tr> <td>Material</td> <td>Titan</td> </tr> <tr> <td>Diametru [mm]</td> <td>30</td> </tr> <tr> <td>Deplasare max. [mm]</td> <td>±11</td> </tr> <tr> <td>Greutate corporală max. [kg]</td> <td>85</td> </tr> </table>	Greutate [g]	185	Înălțime sistem [mm]	51	Material	Titan	Diametru [mm]	30	Deplasare max. [mm]	±11	Greutate corporală max. [kg]	85		
Greutate [g]	185																		
Înălțime sistem [mm]	51																		
Material	Titan																		
Diametru [mm]	30																		
Deplasare max. [mm]	±11																		
Greutate corporală max. [kg]	85																		
3	Sliding adapter with screws				The adapter allows for additional sliding adjustments between the prosthetic socket and the tube adapter, even when the prosthesis is worn. These fine adjustments allow a parallel displacement of the distal portion regardless of the angle of adjustment set by the pyramid adapters. The prosthetic leg can be moved medially or laterally in the frontal plane, or dorsal or ventral in the sagittal plane. Material Titan Maximum permissible body weight: 85 kg Diameter: 30 mm Weight 185 g Construction height 78 mm. Warranty term min. 24 months. Packed in PVC bags.														





4	Adapter for locking tube				Intended for fixing tube adapters. Material: aluminum of increased strength (for aircraft); Diameter on the inside: 30 mm; Maximum allowable body mass: 125 Kg; Weight: 100 gr. Products in positions from 1 to 25 belong to a single manufacturer and are compatible with each other. Warranty term min. 24 months. Packed in PVC bags.																				
5	60 mm double sliding adapter				Double sliding adapters serve to assemble 2 adjustment cores. The recesses for the adjustment cores facilitate distal and proximal angular changes of the prosthesis components in the front and sagittal plane. The dovetail guide allows a sliding of the denture components into the front or sagittal plane. In the table are indicated the characteristics of both the left adapters for the 60mm double sliding adapter and the right 75mm double slider adapter.																				
6	75 mm double sliding adapter																								
				<table border="1"> <tr> <td>Greutate (g)</td> <td>215</td> <td>225</td> </tr> <tr> <td>Înălțimea sistemului (mm)</td> <td>97</td> <td>112</td> </tr> <tr> <td>Înălțimea de montare (mm)</td> <td>60</td> <td>75</td> </tr> <tr> <td>Material</td> <td colspan="2">Titan</td> </tr> <tr> <td>Translatare max.(mm)</td> <td colspan="2">±11</td> </tr> <tr> <td>Greutatea corporală max. (kg)</td> <td colspan="2">100</td> </tr> </table>		Greutate (g)	215	225	Înălțimea sistemului (mm)	97	112	Înălțimea de montare (mm)	60	75	Material	Titan		Translatare max.(mm)	±11		Greutatea corporală max. (kg)	100			
Greutate (g)	215	225																							
Înălțimea sistemului (mm)	97	112																							
Înălțimea de montare (mm)	60	75																							
Material	Titan																								
Translatare max.(mm)	±11																								
Greutatea corporală max. (kg)	100																								
7	Screw adaptation device				Screw adapters are used as building blocks of modular foot prostheses. They connect the prosthetic paw together with the tubular adapter with proximate constructive components. The adapter combinations allow for controlled adjustments of angles and translation in the front and sagittal plane, as well as the adjustment of internal and external rotation. Material: titanium; Weight: 145 g; System height: 36 mm; Angle (curvature): 100°; Maximum permissible body weight: 150 kg. Warranty term min. 24 months. Packed in PVC bags.																				
8	35 mm double adapter				The double adapters serve to connect two adjustment cores. Recesses for adjustment cores facilitate distal and proximal angular changes in the front and sagittal planes. Intended for the assembly of calf and thigh prostheses. They are provided with screws (in set) from both sides. Material: aluminum of increased strength; Maximum allowable body mass 125 Kg; Dual adapters belong to a single manufacturer and are compatible with each other. Warranty term min. 24 months. Packed in PVC bags.																				
9	60 mm double adapter																								
10	45 mm double adapter																								
11	65 mm double adapter																								
12	75 mm double adapter																								
13	90 mm double adapter																								


14	Self-adhesive ribbon on both sides				For two-sided gluing of PVC films; No textile as a basis; For the application of reinforcing materials such as carbon; Acrylate adhesive applied on both sides; Transparent material (protected with waxed paper); Adhere very well to the contours; High efficiency with low material consumption. The way of delivering rollers. Roll width 25 mm. Packed in PVC bags.	
15	Pvc sticky tape				For insulation of damaged PVC tube; Basic material: plastic wrap; Rubber-based adhesive; High wear resistance; Resistant to chemical attack; The way of delivering rollers. Roll width 25 mm. Packed in PVC bags.	
16	Elastic for prostheses 45 mm				Elastic band made of cotton for making leather prostheses. Width 45 mm Cotton: min. 80 %	
17	Cosmetic stocking with knitting heel size 50				It is used in the manufacture of prostheses of the lower limbs. And it is aimed at restoring the aesthetic appearance of the finished prosthesis. But it also protects the constructive elements of the prosthesis from penetration and soiling. Resistant in use (term of use min. 1 year). Packed in PVC bags. to read 50 pcs.	
18	Cosmetic stocking with knitting heel size 70					
19	Cosmetic stocking with knitting heel size 90					
20	Liner Trans Tibial 22				Liner linings improve shock absorption and wearing comfort. It is made of silicone mixed with antibacterial substances and provided in the distal part with a fixing pin. Characteristics: addition of antibacterial material; Silicone soft and pleasant to the touch; Resistant to deformations related to volume stretching; In the outer part covered with fabric; Provided in the distal part with a soft pillow; The thickness of the walls at the distal part 5 mm and at the top 3 mm. Packed in cardboard boxes with an indication of the model and the name of the product on them.	
21	Liner Trans Tibial 23,5					
22	Liner Trans Tibial 26,5					
23	Liner Trans Tibial 28					


24	Liner Trans Femural 32				<p>Silicone lining covered with fabric for hip amputations. Activity levels: 1-4 Made of soft, high-density silicone for better residual limb stabilization. Wear-resistant textile cover. It allows you to attach velcro. Fastening with or without locking of the prosthetic sleeve. Peculiarities: Lining covered with fabric (3 mm thick) Cylindrical Silicone of medical quality Aluminum umbrella in the distal part for attaching the locking pin.</p> <p>Packed in cardboard boxes with an indication of the model and the name of the product on them.</p>	
25	Liner Trans Femural 36					
26	Liner Trans Femural 40					
27	Liner Trans Femural 45					
28	Liner Trans Femural 50					
29	Tube adapter for dentures of the lower limbs (lower leg)				<p>Tube adapter for dentures of the lower limbs Outer diameter: 30 mm Thickness of the walls of the wafer: 2.5 mm Material: high-strength aluminum (for aircraft); System min. height: 97 mm; System max. height: 200 mm; System weight: 185 g; Maximum allowable body mass 125 kg; Products in positions from 1 to 25 belong to a single manufacturer and are compatible with each other. Warranty term min. 24 months</p> <p>Technical data refer to the average size of the foot. Each packaged separately in PVC bags.</p>	
30	Tube adapter for dentures of the lower limbs (lower leg + thigh)				<p>Tube adapter for dentures of the lower limbs Outer diameter: 30 mm; The thickness of the walls of the wafer: 2.5 mm; Material: high-strength aluminium (for aircraft); System min. height: 97 mm; System max. height: 300 mm; System weight: 265 g; Maximum allowable body mass: 125 kg; Warranty term min. 24 months. Products in positions from 1 to 25 belong to a single manufacturer and are compatible with each other. Technical data refer to the average size of the foot. Packaged each unit separately in PVC bags.</p>	



31	Self-locking knee joint			<p>Prosthetic knee joint monocentric. Standing phase product components: Adjustable braking mechanism, depending on the load to ensure the extension position Components of the product for impulse phase control: Tensioning device (adjustable by spring force) Material: Alloy steel</p> <p>Degree of mobility: 1;2 Maximum permissible body weight: 100 kg; Fixation in the distal part: pyramid; Fixation in the proximal part: pyramid; Angle of bending of the joint: 150°; System height: 9 mm; Height of the system in the proximal part up to the fixing area: 8 mm; The height of the system in the distal part up to the fixing area: 1 mm; System weight: 490 g</p>		
32	Knee joint without self-locking			<p>The knee module is intended for patients with unilateral or bilateral amputation of the femur at any level, except for the disarticulation at the level of the knee joint, and is recommended for patients of level 2 and 3 of activity, with fixation in a safe in the position phase.</p> <p>Pneumatic damper with ankle folding function and separate flexion adjustment/FLEXION KNEE MODULATOR will allow you to adapt the movement of the prosthesis in the rocking phase to changes in the patient's walking speed in the range of up to 6 km/h. The pneumatic damper has an additional function that allows, at the last 10° until the knee module is fully extended, to extinguish the angular speed and eliminate the impact in the supporting elements.</p> <p>The design of the pneumatic damper ensures the stability of the settings throughout the period of operation of the knee module.</p>		
33	Knee joint with padlock			<p>Knee joint with padlock and a single axis. Intended for thigh prostheses with medium and long abutment length. Intended for patients with activity level 1 and 2; Pyramid: Aluminum, steel, composite materials with carbon content; Mode of fixation in the proximal zone: pyramid; Mode of fixation in the distal zone: pyramid; Angle of bending of the joint: 130°; Mass of the module 270 g.; Maximum allowable body mass: 125 kg; Packaged each piece separately. Products in positions from 1 to 25 belong to a single manufacturer and are compatible with each other.</p>		





34	Knee joint without a padlock			<p>Modular multi-axis knee joint with integrated pusher. The upper and lower parts of the hinge are interconnected by means of a axle lever. The stability of the support in the support phase is ensured by a geometric lock, created by the structure of the multiaxial hinge (adjustable strap stability level). Maximum allowable body mass: 100 kg. Joint weight: 690 g. Fastening to the top: with a pyramid. Fastening to the bottom with a pyramid. Knee joint flexion anointing: 110O. Working height: 41 cm. Proximal working height up to the assembly point: -3 mm. Distal working height up to the assembly point: 44 mm. Material: Stainless steel Warranty term min. 24 months. Packed in PVC bags. Products in positions from 1 to 25 belong to a single manufacturer and are compatible with each other.</p>		
35	Four-arm lamination anchor			<p>The four-arm lamination anchoris intended for the manufacture of sleeves to the calf prostheses with a pyramid-shaped fixing area. Materials: steel; Maximum diameter, including wings: 105 mm; Maximum allowable body mass: 125 Kg; Construction weight: 160 g; Warranty term min. 24 months. Products in positions from 1 to 25 belong to a single manufacturer and are compatible with each other. Fixation in the lower part with ending su pyramid shape. Packed in PVC bags.</p>		
36	SACH prosthetic foot adapter			<p>Screw diameter 10 mm; Maximum allowable body mass: 125 Kg; Adapter weight: 139 g. Warranty term min. 24 months. Products in positions from 1 to 25 belong to a single manufacturer and are compatible with each other. Packed in PVC bags.</p>		






37	Rotating three-arm rolling anchor with a rotating core				The lamination anchors shall be mounted by lamination in a denture cup. They use as connecting elements between the prosthetic cup and the distal prosthetic components. System height: -3 mm; Construction weight: 180 g; Material: stainless alloy steel; Maximum allowable body mass: 125 Kg Warranty term min. 24 months. Packed in PVC bags.	
38	Three-arm rolling anchor, rotating				A three-arm rolling anchor for rotating sleeves shall be used in combination with a pyramid adapter. Fastening at the bottom with a bushing for pyramid adapter. Materials: stainless steel, aluminum; Maximum diameter including wings: 108 mm; Maximum allowable body mass: 125 Kg; Warranty term min. 24 months Construction weight: 160 g; Products in positions from 1 to 25 belong to a single manufacturer and are compatible with each other. Warranty term min. 24 months. Packed in PVC bags.	
39	Card				It has the shape of a drop provided with two holes with a diameter of 4 mm and 2 mm. It is used to make leather prostheses. Material: steel; Thickness: 2 mm. Packed in PVC bags.	
40	Left uniaxial prosthetic foot size-140 mm				Made of polyurethane foam of skin color. The prosthetic foot is a polymeric material. The elastic element is a thermoplastic material. The top portion of the lining has an elastic element made of thermoplastic material for optimal load distribution and walking stability. Packed in PVC bags.	
41	Left uniaxial prosthetic foot size-150 mm					
42	Right uniaxial prosthetic foot size-150 mm					
43	Left uniaxial prosthetic foot size-160 mm					
44	Left uniaxial prosthetic foot size-180 mm					
45	Left uniaxial prosthetic foot size-200 mm					
46	Right uniaxial prosthetic foot size-210 mm					
47	Right carbon prosthetic foot size-220 mm					The carbon fiber leg is intended for patients with activity level 1-3 with unilateral or bilateral amputation of the femur of all levels or of the lower leg at the edge of the upper, middle and lower third and can also be used in prostheses after disarticulation in the knee or hip joints.
48	Prosthetic foot made of carbon sting size-220 mm					
49	Prosthetic foot made of left carbon size-230 mm					






50	Prosthetic foot made of right carbon size-230 mm		<p>The foot is available in right and left versions, 6 categories of stiffness, which are selected depending on the patient's body weight in the range from 45 to 125 kg. It has improved damping qualities in the forward pushing phase, light and smooth running. The use of plastic elements with characteristics of nonlinear rigidity in the design of the foot ensures a return of energy proportional to the pace of walking. The design of the elastic element at the front provides increased stability in the full-foot support phase and energy recovery in the rear pushing phase. Packed in PVC bags.</p>		
51	Left carbon prosthetic foot size-240 mm				
52	Prosthetic foot made of right carbon size-240 mm				
53	Prosthetic foot made of left carbon size-250 mm				
54	Prosthetic foot made of right carbon size-250 mm				
55	Prosthetic foot made of left carbon size-260 mm				
56	Right carbon prosthetic foot size-260 mm				
57	Left carbon prosthetic foot size-270 mm				
58	Right carbon prosthetic foot size-270 mm				
59	Left carbon prosthetic foot size-280 mm				
60	Right carbon prosthetic foot size-280 mm				
61	Right uniaxial prosthetic foot size-220 mm				
62	Left uniaxial prosthetic foot size-220 mm				
63	Left uniaxial prosthetic foot size-230 mm				
64	Right uniaxial prosthetic foot size-230 mm				
65	Left uniaxial prosthetic foot size-240 mm				
66	Right uniaxial prosthetic foot size-240 mm				
67	Left uniaxial prosthetic foot size-250 mm				
68	Right uniaxial prosthetic foot size-250 mm				
69	Left uniaxial prosthetic foot size-260 mm				
70	Right uniaxial prosthetic foot size-260 mm				
71	Left uniaxial prosthetic foot size-270 mm				
72	Right uniaxial prosthetic foot size-270 mm				
73	Left uniaxial prosthetic foot size-280 mm				







74	Right uniaxial prosthetic foot size-280 mm				
75	Left uniaxial prosthetic foot size-290 mm				
76	Right uniaxial prosthetic foot size-290 mm				
77	Prosthetic foot with adjustment of the height of the right heel size-220			<p>The uniaxial joint leg is intended for patients with unilateral or bilateral amputation of the femur of all levels or of the lower leg at the edge of the upper, middle and lower third, and can also be used in prostheses after disarticulation at the level of the knee or hip joints.</p> <p>It has a plastic element built into the front, which ensures its elasticity and durability. Manufactured in right and left versions. It consists of a foot and ankle with a damper adjustable to the heel of medium hardness. Adjusting the heel damper with a screw allows you to fine-tune the heel stiffness without disassembling the prosthesis. Replacement shock absorbers with high and low rigidity should be ordered separately. The foot has a patented heel height switch that allows the foot to be adjusted to one of the two fixed heel height positions. Packed in PVC bags.</p>	
78	Prosthetic foot with adjustment of the height of the left heel size-220 mm				
79	Prosthetic foot with adjustment of the height of the left heel size-230 mm				
80	Prosthetic foot with adjustment of the height of the right heel size-230 mm				
81	Prosthetic foot with the adjustment of the height of the left heel size-240 mm				
82	Prosthetic foot with adjustment of the height of the right heel size-240 mm				
83	Prosthetic foot with adjustment of the height of the left heel size-250 mm				
84	Prosthetic foot with adjustment of the height of the right heel size-250 mm				
85	Prosthetic foot with adjustment of the height of the left heel size-260 mm				
86	Prosthetic foot with adjustment of the height of the right heel size-260 mm				
87	Prosthetic foot with adjustment of the height of the left heel size-270 mm				
88	Prosthetic foot with adjustment of the height of the right heel size-270 mm				
89	Prosthetic foot with adjustment of the height of the left heel size-280 mm				
90	Prosthetic foot with adjustment of the height of the right heel size-280 mm				







91	Prosthetic foot with adjustment of the height of the left heel size-290 mm				
92	Prosthetic foot with adjustment of the height of the right heel size-290 mm				
93	Prosthetic foot type SACHI 22L			<p>Prosthetic foot type SACH. It has an anatomical shape with a smooth surface and a highlighted thumb. It allows the patient to quickly achieve stability in the support phase. For patients with low levels of activity. Designed for patients weighing up to 100 kg. Made of polyurethane foam of skin color. Interior insertion: wooden. Elastic element: thermoplastic material. It has a soft damper present in the heel area. Heel height: 18 mm. Packed in PVC bags.</p>	
94	Prosthetic foot type SACHI 22R				
95	Prosthetic foot type SACHI 23R				
96	Prosthetic foot type SACHI 25L				
97	Prosthetic foot type SACHI 26L				
98	Prosthetic foot type SACHI 26R				
99	Prosthetic foot type SACHI 27R				
100	Prosthetic foot type SACHI 28L				
101	Prosthetic foot type SACHI 28R				
102	Prosthetic foot type SACHI 29L				
103	Prosthetic foot type SACHI 29R				
104	Prosthetic foot for 23L leather prostheses			<p>Intended for the manufacture of leather prostheses. External material: Polyurethane foam of beige color; Interior material: Carbon-based polymer; Heel height: 15 mm; Maximum permissible body mass: 100 kg The products on positions from 80 to 116 belong to a single manufacturer and are compatible with each other. Packed in PVC bags.</p>	
105	Prosthetic foot for 23R leather prostheses				
106	Prosthetic foot for skin prostheses 24R				
107	Prosthetic foot for leather prostheses 26L				
108	Prosthetic foot for leather prostheses 26R				
109	Prosthetic foot for skin prostheses 27L				
110	Prosthetic foot for leather prostheses 27R				
111	Prosthetic foot for leather prostheses 28L				
112	Prosthetic foot for leather prostheses 28R				





113	Prosthetic foot for leather prostheses 29L					
114	Prosthetic foot for leather prostheses 29R					
115	Ankle made of aluminum alloy, designed for making prostheses of the lower limbs from leather size 220-250mm (V = 250 mm, for the length of the foot 240-260 mm)				The construction is provided with a puddle with plastic bearings. The ankle is intended for making leather prostheses and artificial sole with a gusset-shaped shock absorber. They are made of aluminum Height 165 mm. It is delivered in complete with 8 rivets and 2 steel plates. Warranty term min. 24 months Packaging in cardboard boxes and PVC bags and sealed for each piece separately. The products in positions from 80 to 116 belong to a single manufacturer and are compatible with each other.	
116	Ankle made of aluminum alloy, designed for making prostheses of the lower limbs from leather size 260-300 mm (V = 260 mm, for the length of the foot 265-285 mm)					
117	Small wooden ankle for dentures of the lower limbs Ankle sizes (mm) K=150 mm, K1=87 mm, K2=70 mm, K3=52 mm, K4=57 mm, K5=52 mm, P=230 mm				Ankle - intended for making leather prostheses and artificial sole with a gusset-shaped shock absorber. They are made of linden wood. Foot length 255-265 mm; Height 150mm; Warranty term min. 24 months Technical data refer to the average size of the foot. Packed in cardboard boxes and PVC bags and sealed for each piece. The products in positions from 80 to 116 belong to a single manufacturer and are compatible with each other.	
118	Average wooden ankle for dentures of the lower limbs Ankle sizes (mm) K=150 mm, K1=97 mm, K2=80 mm, K3=59 mm, K4=64 mm, K5=52 mm, P=254mm					
119	Seminel				Seminel of metal intended for the manufacture of prostheses and apparatus of the lower limbs. A=340 mm; B=27 mm; a=2 mm Packed in cardboard boxes and PVC bags and sealed for each piece.	






120	Seminel				Seminel configured for the manufacture of calf prostheses, prostheses for amputation after Pirogof with discharge under the knee, as well as for the manufacture of prostheses of the lower limbs after the Hops type amputation. They are used to give stiffness to leather sleeves. Material: steel Products on positions from 80 to 116 belong to a single manufacturer and are compatible with each other.																													
121	Seminel length 220 mm				Seminel configured for the manufacture of calf prostheses, prostheses for amputation after Pirogof with discharge under the knee as well as for the manufacture of prostheses of the lower limbs after the Lizard type amputation or fixed devices. They are used to give stiffness to leather sleeves. Material: steel. Dimensions: c = 20 mm; a=2 mm. Packed in cardboard boxes and PVC bags. The products in positions from 80 to 116 belong to a single manufacturer and are compatible with each other.																													
122	Seminel length 175 mm																																	
123	Semi-finished for calf prosthesis				Used in work prostheses on the knees bent without leg PN3-27. Made of steel grade structure. It is delivered in full. Packaging in cardboard boxes and PVC bags.																													
124	Metal insole for orthopedic appliances for the left foot length 130 mm				Used in children's orthopedics, devices for the lower limbs, when making orthopedic appliances (orthotics). Made of titanium alloy. Supplied to the piece. The mass of one part is 0.03 kg. Packed in cardboard boxes and PVC bags.																													
125	Metal insole for orthopedic appliances for the left foot, length 150 mm				Used in orthopedics in orthotics. Made of corrosion-resistant steel grades. Size range according to a table (according to the table) supplied to the piece. Packaging in cardboard boxes and PVC bags.																													
126	Metal insole for orthopedic appliances for the left foot, length 170 mm																																	
127	Metal insole for orthopedic apparatus for the right foot, length 170 mm																																	
128	Metal insole for orthopedic appliances for the left foot, length 200 mm																																	
129	Metal insole for orthopedic apparatus for the right foot, length 200 mm																																	
				<table border="1"> <thead> <tr> <th>Шифр изделия</th> <th>A, мм</th> <th>Б, мм</th> <th>В, мм</th> <th>а, мм</th> <th>Масса, кг</th> </tr> </thead> <tbody> <tr> <td>1141Л 1141П</td> <td>130</td> <td>65</td> <td>8</td> <td rowspan="5">1,5</td> <td>0,110</td> </tr> <tr> <td>1142Л 1142П</td> <td>150</td> <td>69</td> <td>8</td> <td>0,130</td> </tr> <tr> <td>1143Л 1143П</td> <td>170</td> <td>76</td> <td>11</td> <td>0,155</td> </tr> <tr> <td>1144Л 1144П</td> <td>200</td> <td>93</td> <td>12</td> <td>0,205</td> </tr> </tbody> </table>		Шифр изделия	A, мм	Б, мм	В, мм	а, мм	Масса, кг	1141Л 1141П	130	65	8	1,5	0,110	1142Л 1142П	150	69	8	0,130	1143Л 1143П	170	76	11	0,155	1144Л 1144П	200	93	12	0,205		
Шифр изделия	A, мм	Б, мм	В, мм	а, мм	Масса, кг																													
1141Л 1141П	130	65	8	1,5	0,110																													
1142Л 1142П	150	69	8		0,130																													
1143Л 1143П	170	76	11		0,155																													
1144Л 1144П	200	93	12		0,205																													






130	Metal trochanter				<p>Used in PN6-01 hip prostheses and orthopedic devices all over the leg. Made of steel grades structure without protective coatings in executions of the standard size range according to the table. Supplied as set C (splint with head) and D (plate). B=20mm; B1=28mm; L=143.5mm; L1=160mm; S=4mm; S1=2.2mm; A=510.06mm; Weight: 0.216 Kg.</p>		
131	Knee-joint splints for leather prostheses and lower limb apparatus (complete)				<p>Steel splints with a knee joint are used to make prostheses and lower limb appliances out of leather. A=400mm, B=520 mm, C=22 mm, D=20 mm, a=3 mm, b=3.5 mm Maximum permissible body mass: 90 kg. Packaging in cardboard boxes and PVC bags and sealed for each piece. The products in positions from 80 to 116 belong to a single manufacturer and are compatible with each other.</p>		
132	Knee-joint splints for leather prostheses and lower limb apparatus (complete)				<p>Steel splints with a knee joint are used to make prostheses and lower limb appliances out of leather. A=400mm, B=520 mm, C=24 mm, D=20 mm, a=3 mm, b=4 mm Maximum allowable body mass: 90 kg. Packed in cardboard boxes and PVC bags and sealed for each piece. The products in positions from 80 to 116 belong to a single manufacturer and are compatible with each other.</p>		
133	Knee-joint splints for leather prostheses and lower limb apparatus (complete)				<p>Steel splints with knee joint are used to make prostheses and lower limb apparatus from leather. A=450mm, B=520 mm, C=26 mm, D=26 mm, a=4.5 mm, b=4.5 mm Maximum permissible body mass: 90 kg. Packed in cardboard boxes and PVC bags and sealed for each piece. The products in positions from 80 to 116 belong to a single manufacturer and are compatible with each other.</p>		
134	Assemble of knee-joint splints for leather prostheses and lower limb apparatus (assembly) (complete)				<p>Splints are intended for making calf prostheses with a wooden ankle. Bearings are present in the knee joint. H=6 mm, A=250 mm, Б=100 mm, В=50 mm, Г=14 mm, Д=14 mm, E=14 mm, a=2.5 mm б=5, c=2 mm Material: profiled steel Packed in cardboard boxes and PVC bags and sealed for each piece. Warranty term min. 24 months. The products in positions from 80 to 116 belong to a single manufacturer and are compatible with each other.</p>		





135	Complete splints for prostheses intended in case of Pirogov type amputation (complete)			<p>The splints are intended for the manufacture of calf prostheses for prostheses in the case of Pirogov type amputation without a joint.</p> <p>Material: profiled steel.</p> <p>Packed in cardboard boxes and PVC bags and sealed for each piece. The products in positions from 80 to 116 belong to a single manufacturer and are compatible with each other.</p>		
136	Splints with knee joint and padlock for leather prostheses and lower limb apparatus (assembly) (complete)			<p>Steel splints for the knee joint are used to make prostheses and lower limb apparatus from leather.</p> <p>C=18 mm; a=3 mm; A=400mm; B= 400 mm Maximum allowable body mass: 100 kg. Packed in cardboard boxes and PVC bags and sealed for each piece. The products in positions from 80 to 116 belong to a single manufacturer and are compatible with each other.</p> 		
137	Splints for thigh prostheses with unilateral wool and bifurcation at the distal side (complete)			<p>Steel splints with a joint (with spherical bearings) and unilaterally lacquered are intended for thigh prostheses. The splints are made of steel with a prefabricated shape and provided at the distal part with two horns. On the outer splint is provided the padlock for fixing the joint in the bent position. It is used to make prostheses of the lower limbs with rigid cup (polyamide, orthoacril).</p> <p>Maximum allowable body mass: 100 kg. The products in positions from 80 to 116 belong to a single manufacturer and are compatible with each other. Packed in cardboard boxes and PVC bags and sealed for each piece.</p> 		
138	Splints for orthotics with padlock (complete)			<p>Splints for orthotics with padlock in the knee region with manual locking with ring, flat bar profile, upper and lower sections of aluminum, stainless steel joint. Bar diameter: 18 mm Upper splint length: 300 mm, Lower splint length: 320 mm. Splint width: 14 mm. Splint thickness: 3 mm. It is delivered in full. Packed in film.</p>		






139	Hinge used in the manufacture of leather prostheses				Steel material. Compatible with wooden ankle p. 99 and 100. Packed in cardboard boxes and PVC bags and sealed for each piece.	
140	Knitted tube made of polyester diameter 8 cm				Used to make the cup for prostheses of the upper and lower limbs. Composition: 100% polyester Increased resistance to breakup, 275% elasticity. Packed in cardboard boxes and PVC bags and sealed for each piece.	
141	Knitted tube made of polyester diameter 10 cm					
142	Knitted tube made of polyester diameter 12 cm					
143	Knitted tube made of polyester diameter 15 cm					
144	PVA Sleeve 10"				It is used to make cups from acrylic resins for prostheses of the upper and lower limbs. Material: polyvinyl alcohol of superior quality. It is packed in bags of 20 pcs each.	
145	PVA Sleeve 12"					
146	PVA Sleeve 14"					
147	Drilled metal disc				Metal disc, drilled, is used to protect the skin in skin prostheses during riveting of the brass rivet. Material: stainless steel. Packed in cardboard boxes and PVC bags and sealed for each piece.	
148	Copper rivet				Copper rivet for fixing metal splints to the leather sleeve: Material: copper; Length (l): 21 mm; Diameter of the rivet (d): 3,0 mm; Diameter of the rivet head (D): 5,7 mm Height of the rivet head (h): 1,35 mm Packed in cardboard boxes and PVC bags and sealed for each piece.	
149	Brass staples				Staples are intended for stringing leather prostheses, orthotics and corsets. Material used: thin sheet of brass. Packed in cardboard boxes and PVC bags and sealed for each piece.	






150	Valve with vacuum			<p>It is used to make dentures of the lower limbs with a cup from acrylic resins or thermoformable materials. The valve with the vacuum is suitable for patients with the following requirements: • ease of use (without thread), • prolonged levers to facilitate the opening of the valve when the function of the fingers is limited, • the valve opening is large enough to allow easy removal of the device from the cup, • simplified control of the abutment position, • an acoustic signal when the valve is correctly positioned. It goes into full: Lower ring with thread; Upper ring with thread; Button for evacuating the hanger; Template for spatial thermoforming; Template for lamination; inner head; Thread of the Screw; Key for holes Pack in cardboard boxes and PVC bags and sealed for each piece.</p>		
151	Valve with vacuum			<p>Valve with rubber vacuum for thigh prostheses. Button for removing air from nickel. ,Internal diameter 40 mm. Packed in cardboard boxes and PVC bags and sealed for each piece.</p>		
152	Ring for valve with vacuum			<p>Rubber ring for valve with vacuum. Internal diameter 40 mm. Packed in cardboard boxes and PVC bags and sealed for each piece.</p>		
153	Pulley for the belt			<p>It is used in the manufacture of thigh prostheses, namely it helps to fix with the help of the belt fastening and help of the belt prosthesis. Materials: Wheel: plastic; Support: steel. Packed in cardboard boxes and PVC bags and sealed for each piece.</p>		






154	Buckthorn with portcatarama				It is intended for fixing the prostheses of the lower and upper limbs. Material: leather tanned with mineral salts, steel. The width of the portcataramarama 19 mm., the length of the portcataramarama 60 mm. Buckle width 19 mm., buckle length 20 mm. Packed in cardboard boxes and PVC bags.		
155	Buckthorn with portcatarama				It is intended for fixing the prostheses of the lower and upper limbs. The width of the portcataramarama 16 mm, the length of the portcataramarama 60 mm. Buckle width 16 mm, buckle length 20 mm Material: leather tanned with mineral salts, steel. Packed in cardboard boxes and PVC bags.		
156	Semi-finished for flexible sleeve thickness 12 mm				Used for the manufacture of flexible inner cups for dentures of the lower limbs. It is composed of silicone. With antibacterial characteristics. High flexibility High surface quality It can subsequently be thermoformed Small shrinkage: approx. 3% Comfortable to wear Washable Temperature Recommendation: 160°C/320°F (convection oven, infrared oven). Color: transparent. Board dimensions: 400×400 mm. Packed in PVC bags.		
157	Semi-finished for flexible sleeve thickness 15 mm						
158	Semi-finished sample sleeve thickness 12 mm				Used for the manufacture of sample cups for dentures of the lower limbs. The processing temperature for heating plates, convection and infrared furnaces is 160°C/320°F. Transparency of the test cup facilitates the precise verification of the fit and verification of the pressures exerted by the bucket on the abutment. By heating the bucket, it is possible to reform the thermoplastic, for example, pressure points. Color: transparent. Plate sizes: 400×400 mm. Packed in PVC bags.		
159	Semi-finished sample sleeve thickness 15 mm						
160	Foamy material for the inner cup				Used for the production of insoles, soft linings in the cups of unperforated calf prostheses. Delivered in sheets. Working temperature: 120-130 ° C. Dimensions: 2000×1000×6 mm.; OShor hardness: 40 units; Density: 170 kg/m3; Color: beige.		






161	Fastening belt				<p>It is intended for fixing prostheses of the lower limbs by the belt. Material: raw leather. Packed in PVC bags.</p> 	
162	Belt for arm's prosthesis (prefabricated)				<p>Leather for saddlery iuft type, tanned leather with chrome for prostheses, cotton; Length 850-1300 mm; It is intended for fixing the prostheses of the upper limbs. Packed in PVC bags.</p>	
163	Fastening strap Length: 150 mm; Width 16 mm.				<p>They are intended for fixing the prostheses of the lower and upper limbs. Materials: raw leather. Length: 150 mm; Width 16 mm. Packed in cardboard boxes.</p>	
164	Fastening strap Length: 170 mm; Width 16 mm.				<p>They are intended for fixing the prostheses of the lower and upper limbs. Materials: raw leather. Length: 170 mm; Width 16 mm. Packed in cardboard boxes.</p>	
165	Fastening strap Length: 230 mm; Width 19 mm.				<p>They are intended for fixing the prostheses of the lower and upper limbs. Materials: raw leather. Length: 230 mm; Width 19 mm. Packed in cardboard boxes.</p>	







166	Lainer padlock for calf prostheses			<p>Used in the manufacture of calf potencies. Content of the complement: Lamination anchor; Shuttle Lock housing; Cliche unit; Gypsum protection pin for pin Set template (1 hemispherical shape template, 1 threaded layout, 1 gypsum screw); Threaded stud length: 67.8 mm.</p> <p>System weight: 425g; The height of the system; 25 mm; Rolling anchor material: steel; Material Shuttle Place: aluminum; Maximum allowable body mass: 125 kg. Packed in cardboard boxes.</p>		
167	Lainer padlock for thigh prostheses			<p>Used in the manufacture of thigh potions with liner. Content of the complement: Lamination anchor; Shuttle Lock housing; Cliche unit; Gypsum protection pin for pin Set template (1 hemispherical shape template, 1 threaded layout, 1 gypsum screw); Threaded stud length: 31 mm.</p> <p>System weight: 485g; The height of the system; 79 mm; Rolling anchor material: steel; Material Shuttle Place: aluminum; Maximum allowable body mass: 125 kg. Packed in cardboard boxes.</p>		
168	Carbon canvas with a width of 100 cm			<p>Carbon fiber cloth designed for reinforcement sleeves. Density: 200 g/m2. Packed in cardboard boxes.</p>		
169	Felt thickness 7 mm			<p>It is used to make prostheses and orthotics from the skin. According to GOST 287-68 Semi-open felt for the saddle. Woolen and crescent felts are made of washed wool of dark and light gray color with a content of vegetable impurities not exceeding 1.0-2.5% and mineral impurities not exceeding 0.15-0.20%. The felt has a uniform thickness and density along the entire length of the fabric. It's soft.</p> <p>Packaging in PVC bags.</p>		

170	Ortho-acrylic resin for finished cup (4.6 kg)			<p>Laminating resin for the manufacture of components with a low resin proportion Most versatile of the lamination resins, Orthocryl resins are specially formulated for the manufacture of lamination layers made of carbon fiber, glass or textile. Methyl methacrylate base provides excellent strength for each specific application and use. The family of orthocryl rolling resins includes low viscosity options to increase penetration or produce high-strength adhesive bonds made of carbon, glass or textiles. Versatile lamination resin for use with carbon, glass or textiles: Allows the manufacture of components with a low resin proportion Colorless, transparent, two-component resin Methyl methacrylate base provides excellent strength The family includes options for the use of carbon fiber, rigid or flexible laminates. Metal packaging. Pack volume 4,6 kg</p>		
171	Dust solidifier (150 gr.)			<p>Intended for solidification of ortho-acrylic resins. Packed in plastic bottle. Quantity in the bottle: 150 g</p>		
172	Cotton stocking for amputation of upper limbs			<p>It is intended for the protection of the amputational abutment from exerting the pressures of the denture cup. Composition: 100 % cotton Colour: natural. Length 24 cm Upper width 14 cm Lower width 11 cm Packaged in PVC bags of 20 pcs each.</p>		
173	Wool stocking for thigh amputation			<p>It is intended for the protection of the amputation abutment from exerting the pressures of the sleeve of the prosthesis. Composition: wool – 60%, PA-10%; Color: natural. Length: 40 cm Width upper part: 23.5 cm Width of the lower part: 15 cm. Packaging in PVC bags of 20 pcs each.</p>		
174	Line sock for calf amputation			<p>It is intended for the protection of the amputation abutment from exerting the pressures of the sleeve of the prosthesis. Composition: wool – 60%, PA-10%; Color: natural. Length: 63 cm Upper side width: 22.5 cm Bottom width: 9.5 cm. Packed in PVC bags of 20 pcs each.</p>		


175	Cotton stocking for thigh amputation				It is intended for the protection of the amputational abutment from exerting the pressures of the denture cup. Composition: 100 % cotton Colour: natural. Length: 40 cm Width of the upper part: 23.5cm Width of the bottom: 15 cm Packaging in PVC bags of 20 pcs each.																	
176	Line sock for calf amputation				It is intended for the protection of the amputational abutment from exerting the pressures of the denture cup. Composition: wool – 60%, PA-10%; Color: natural. Length: 40 cm Top width 23.5cm Pinferiolar width 15 cm																	
177	Gypsum bowl				The bowl for gypsum is made of flexible plastic. The volume of these 500 g Packaging in PVC bags.																	
178	Screwdriver for prostheses				Hexagonal screwdriver for making prostheses No.4. Packaging in PVC bags.																	
179	Segment for electric saw				Circular knife for cutting sleeves from ortho-acrylic. <table border="1" data-bbox="987 863 1323 954"> <tr> <td>Article number</td> <td>756Y63=50</td> <td>756Y63=65</td> </tr> <tr> <td>for</td> <td colspan="2">756B7 (old version), 756B12=*, 756B20=* Plaster saws</td> </tr> <tr> <td>Version</td> <td colspan="2">Circular saw blade</td> </tr> <tr> <td>Ø</td> <td>50 mm</td> <td>65 mm</td> </tr> <tr> <td>Weight</td> <td>0.008 kg</td> <td>0.012 kg</td> </tr> </table>	Article number	756Y63=50	756Y63=65	for	756B7 (old version), 756B12=*, 756B20=* Plaster saws		Version	Circular saw blade		Ø	50 mm	65 mm	Weight	0.008 kg	0.012 kg		
Article number	756Y63=50	756Y63=65																				
for	756B7 (old version), 756B12=*, 756B20=* Plaster saws																					
Version	Circular saw blade																					
Ø	50 mm	65 mm																				
Weight	0.008 kg	0.012 kg																				

180	Thigh support bandage size L-90R				To reduce rotational movements and plunger in transfemoral prostheses For the transfer of force and fixation of the prosthesis on the body To improve the guidance and control of the prosthesis Personalized dimensions available (depending, for example, on the side, with socket) Intuitive closure on the pelvic girdle with hook straps and buckles for a customized fit High hook strength and breathable pelvic belt loop, thin, polyamide and spandex, is very comfortable Low weight makes it possible to perceive and control the body High resistance to abrasion of the pelvic belt Additional lining for edge protection Safe grip of the prosthesis thanks to the non-slip band Neoprene® at the distal end of the suspension sleeve Without latex Robust and durable Good shape retention. Packed in PVC bags.		
181	Thigh support bandage size L-90L						
182	Thigh support bandage size XL-101R						
183	Thigh support bandage size XL-101L						
184	Sealing sleeve No. 1 Perimeter distal part 30mm, perimeter proximal part 40mm				The sealing sleeves should be used exclusively for adjusting transtibial prostheses. Genunchera provides improved support for transtibial prostheses, while allowing freedom of movement of the knee. The inner layer made of silicone. The outer layer of knit. Packed in PVC bags.		
185	Sealing sleeve No. 2 Perimeter distal part 40mm, perimeter proximal part 50mm						
186	Sealing sleeve No. 3 Perimeter distal part 50mm, perimeter proximal part 60mm						
187	Sealing sleeve No. 4 Perimeter distal part 60mm, proximal part perimeter 70mm						
188	Donning sheath for transfemoral prostheses size M				The donning sheath facilitates the mounting of dentures of the upper and lower limbs that have a valve hole. The product is made of a particularly slippery, light material (nylon covered with silicone) and prevents the pain that can occur when putting on a prosthesis. Packed in PVC bags of 50 m each.		
189	Donning sheath for transfemoral prostheses size L						
190	Nit for leather prostheses				For fixing the extremities of the splints by the wooden ankles for the prostheses of the lower limbs. Material: steel brand 30. Weight: 0.02 Kg/pcs. D= 9 mm; d=6mm; l=86.5mm; h=1,8mm. 		

191	Holniten complete foot height 10 mm (complete)				<p>Material: metal; Color: nickel; Lower diameter of the head of the foot (D1): 7 mm; Lower diameter of the head of the feet (D2): 3.3 mm; Height of the rivet head (h1): 5 mm; Diameter of the foot(d):3,2; of the foot (D3): 8,8 mm; Packed in PVC bags.</p>		
192	Holniten complete foot height 12 mm (complete)				<p>Material: metal; Color: nickel; Lower diameter of the head of the foot (D1): 7 mm; Lower diameter of the head of the feet (D2): 3.3 mm; Height of the rivet head (h1): 5 mm; Diameter of the foot(d):3,2; of the foot (D3): 8,8 mm; Height of the foot (h2): 12.3 mm Packed in PVC bags.</p>		
193	Nails for shoes K18				<p>According to OCT 17-272-87.</p>		
194	Chemical Pencil				<p>They are intended for the application of inscriptions, patterns, designs on glass, metal, porcelain, plastic surfaces and provide permanent inscriptions on the skin and fabrics. They are also used in many industries. They are suitable as a reliable replacement for pens, they write there (frost, extreme heat) where the pens can not cope. Special lead, when it comes into contact with water, acquires the properties of ink. The pigment is resistant to abrasion and water, does not fade in the sun. The durable conductor does not break even after it has been dropped. Blue or black in color. Graphite diameter 3 mm. Packed in PVC bags.</p>		
195	Gypsum strip 15cm×270cm				<p>It is used to obtain the negative. The term for the formation of a stable form is 5 - 10 minutes. It is packed in a plastic bag. Roll length 270 cm Width 15 cm Packed in PVC bags.</p>		

196	Tights				Capron tights	
197	Short tights				Short capron tights	
198	Carbon fiber tube 150				Used for lamination using acrylic, epoxy and other resins. It is intended for making prosthesis sleeves of the lower limbs - femure to which increased strength characteristics are required.	
199	Carbon fiber tube 225					
200	Revolock system				System used to make prostheses of the lower calf and thigh limbs. It is aimed at regulating the perimeters of the cup of the prosthesis.	
201	Paper for thermal printing				It is used as transfer paper for thermoplastics in the manufacture of orthotics. It is applied to a thermoplastic heated to a transparent state by 45', after which it is removed.	
202	Pedilin for removing the negative				Perfect accuracy. The imprint obtained with the help of foam reflects the relief of the foot with maximum accuracy. The working surface of the foam 330 mm x 145 mm x 38 mm is enough to obtain large-sized prints of the foot. Foam and gypsum can be stored for several years. When the patient returns, a new fingerprint is not required. Indispensable in the manufacture of insoles for patients with diabetes. Due to the peculiarities of the structure of the foot, this method of obtaining gypsum is optimal. The foam is non-toxic and hypoallergenic. It does not have a negative effect on the body.	

LOT II Blanks for upper limb prostheses


1	Hand for prosthesis of the upper limb from medical plastisol for women (right), No.18 fullness 1				Cosmetic hand intended for prostheses in men, women and children, after amputation of the upper limbs. Material: medical plastisol; Color: beige palitra. Monolayer housing; Internal cavity: filled with polyurethane foam with metal frame at all five fingers. Warranty term min. 12 months Packed in PVC bags.	
2	Hand for prosthesis of the upper limb from medical plastisol for women (left), No.18 fullness 1					



Размер для заказа	Полнота	Размеры, мм						
		L, max	C	P	F	D, max	A	
18	1	пр	190-210	105	135	130	175	60
		лев	190-220	105	135	130	175	60
14	1	пр	180-245	110	140	140	180	65

3	Hand for upper limb prosthesis from medical plastisol for men (left), No.19 fullness 1
4	Hand for prosthesis of the upper limb from medical plastisol for women (right), No.20 fullness 1
5	Hand for prosthesis of the upper limb from medical plastisol for men (left), No.21 fullness 1
6	Hand for prosthesis of the upper limb from medical plastisol for men (left), No.22 fullness 1
7	Hand for prosthesis of the upper limb from medical plastisol for men (right), No.22 fullness 1
8	Hand for prosthesis of the upper limb from medical plastisol for men (left), No.23 fullness 1
9	Hand for prosthesis of the upper limb from medical plastisol for men (right), No.23 fullness 1
10	Hand for the prosthesis of the upper limb from medical plastisol for men (left), No.24 fullness 1
11	Hand for prosthesis of the upper limb from medical plastisol for men (right), No.24 fullness 1



Пол	Возраст	Полнота	Размеры (мм)							
			Длина кисти	Ширина кисти	Длина предплечья	Обхват предплечья	Обхват запястья	Обхват ладони		
Женщина	14	1	mean	190-245	110	140	140	180	65	
			up	190-205	110	145	145	165	65	
			down	190-280	110	130	135	195	65	
	15	1	mean	190-310	140	160	165	175	75	
			up	190-310	140	160	165	175	75	
			down	190-310	135	160	165	175	75	
	16	1	mean	190-310	135	160	165	175	75	
			up	190-310	135	160	165	175	75	
			down	190-310	135	160	165	175	75	
	Женщина	17	1	up	280-330	170	170	150	210	100
				mean	280-330	165	170	160	210	100
				down	280-285	160	180	140	210	100
		18	1	mean	280-290	170	180	145	200	100
				up	280-335	170	185	160	230	100
				down	280-335	165	185	165	230	100
		19	1	up	290	165	185	155	210	100
				mean	270	160	185	165	200	100
				down	290-315	185	185	150	220	100
20		1	mean	290-310	170	185	160	205	100	
			up	290-340	170	205	180	240	105	
			down	290-330	170	205	180	230	100	
21	1	up	290	170	205	165	210	105		
		mean	290-300	170	205	170	215	105		
		down	290-370	175	210	185	245	105		
Женщина	19	1	up	290-380	175	210	180	250	105	
			mean	285	170	190	160	190	100	
			down	290-310	170	185	165	225	95	
	20	1	mean	290-320	170	205	165	240	105	
			up	290-365	185	215	165	240	110	
			down	290-380	175	210	165	240	110	
	21	1	mean	295	175	215	200	215	110	
			up	295	180	215	200	215	110	
			down	290-360	180	220	180	230	110	
	22	1	mean	290-360	180	220	175	230	110	
			up	290-360	180	220	175	230	110	
			down	290	185	225	180	210	110	
	23	1	mean	270	185	215	190	220	110	
			up	290-360	190	225	175	265	115	
			down	290-390	195	230	175	260	110	
	24	1	mean	290-315	185	220	185	245	115	
			up	290-315	185	220	185	245	115	
			down	290-360	195	240	210	260	120	






12	Sheathing for upper limb prostheses Tipo-size No.5 left			Sheathing for upper limb prostheses from medicinal plastisol. Wall thickness: 1.0-1.5 mm; Compatible with artificial hand (p. 12-17) Perimeter of the palm: 180 mm. Warranty term min.12 months.	
13	Sheathing for upper limb prostheses Type-size No.5 right			The products in positions from 3-18 belong to a single manufacturer and are compatible with each other. Packed in PVC bags.	
14	Sheathing for upper limb prostheses Type-size No.6 left				
15	Sheath for upper limb prostheses Type-size No.6 right				
16	Artifice hand for prosthesis of the forearm of the upper limb (active) Tipo-size No. 5 right			Artificial plastic hand (active), intended for prosthesis of the upper limb. The casing and fingers are plastic; levers and fasteners of metal. In the construction of the hand, a passive grasping mechanism and an active finger opening is provided, which is activated with the help of levers.	
17	Artifice hand for prosthesis of the forearm of the upper limb (active) Tipo-size No. 5 left			The set includes: support belt-1pcs, staples-2 pcs and ring-2pcs. The products in positions from 3-18 belong to a single manufacturer and are compatible with each other. Warranty term min. 12 months Packed in PVC bags.	
18	Artifice hand for prosthesis of the forearm of the upper limb (active) Tipo-size No.6 right				
19	Artifice hand for prosthesis of the forearm of the upper limb (active) Tipo-size No.6 left				

Размер для заказа	Размеры, мм*	
	L	P
1	160	120
2	160	145
3	160	155
4	200	170
5	210	180
6	220	200

*допустимая погрешность ±0,5 мм

и комплектация 1.05 - 1 шт.

Шифр изделия	Типоразмер	A, мм	B, мм	B, мм	Масса комплекта, кг
9541(П1-52) 9542(П1-52)	1	96	50	52	0,228
9543(П2-60) 9544(П2-60)	2	110	54	60	0,231
9545(П3-66) 9546(П3-66)	3	122	60	66	0,263
9547(П4-72) 9548(П4-72)	4	132	65	72	0,298
9549(П5-78) 9550(П5-78)	5	142	70	78	0,320
9551(П6-84) 9552(П6-84)	6	152	74	84	0,368

20	Artifice hand for prosthesis of the forearm of the upper limb (active) Tipo-size No. 6 right			<p>Artificial plastic hand (active), intended for prosthesis of the upper limb. The housing and fingers are plastic, levers and fasteners made of metal.</p> <p>In the construction of the hand, a passive grasping mechanism and an active finger opening are provided, which is activated with the help of the lever.</p> <p>The products in positions from 3-18 belong to a single manufacturer and are compatible with each other. Warranty term min. 12 months Packed in PVC bags.</p>																																												
21	Artifice hand for prosthesis of the forearm of the upper limb (active) Tipo-size No. 6 left			<table border="1" data-bbox="1256 379 1480 523"> <thead> <tr> <th>Шифр изделия</th> <th>Периметр</th> <th>A, мм</th> <th>B, мм</th> <th>B₁, мм</th> <th>Масса, кг</th> </tr> </thead> <tbody> <tr> <td>8675(71-42) 8676(71-42)</td> <td>1</td> <td>96</td> <td>50</td> <td>52</td> <td>0,108</td> </tr> <tr> <td>8677(72-46) 8678(72-46)</td> <td>2</td> <td>110</td> <td>64</td> <td>66</td> <td>0,130</td> </tr> <tr> <td>8679(73-49) 8680(73-49)</td> <td>3</td> <td>122</td> <td>60</td> <td>66</td> <td>0,174</td> </tr> <tr> <td>8681(74-52) 8682(74-52)</td> <td>4</td> <td>132</td> <td>65</td> <td>72</td> <td>0,205</td> </tr> <tr> <td>8683(75-78) 8684(75-78)</td> <td>5</td> <td>142</td> <td>70</td> <td>78</td> <td>0,225</td> </tr> <tr> <td>8685(76-82) 8686(76-82)</td> <td>6</td> <td>152</td> <td>74</td> <td>80</td> <td>0,270</td> </tr> </tbody> </table>	Шифр изделия	Периметр	A, мм	B, мм	B ₁ , мм	Масса, кг	8675(71-42) 8676(71-42)	1	96	50	52	0,108	8677(72-46) 8678(72-46)	2	110	64	66	0,130	8679(73-49) 8680(73-49)	3	122	60	66	0,174	8681(74-52) 8682(74-52)	4	132	65	72	0,205	8683(75-78) 8684(75-78)	5	142	70	78	0,225	8685(76-82) 8686(76-82)	6	152	74	80	0,270		
Шифр изделия	Периметр	A, мм	B, мм	B ₁ , мм	Масса, кг																																											
8675(71-42) 8676(71-42)	1	96	50	52	0,108																																											
8677(72-46) 8678(72-46)	2	110	64	66	0,130																																											
8679(73-49) 8680(73-49)	3	122	60	66	0,174																																											
8681(74-52) 8682(74-52)	4	132	65	72	0,205																																											
8683(75-78) 8684(75-78)	5	142	70	78	0,225																																											
8685(76-82) 8686(76-82)	6	152	74	80	0,270																																											
22	Complete blanks for the right arm prosthesis (complete)			<p>The module is intended for arm and shoulder prostheses. The sleeve of the arm and forearm are made of plastic, the steering mechanism of metal.</p> <p>Movement in the elbow joint is active, with the fixing of the position of the anti-knife relative to the arm in 7 positions.</p>																																												
23	Complete of blanks for left arm prosthesis (complete)			<p>Special fixation allows a passive rotation of the shoulder and elbow. Basic dimensions: D=70; L=270 Packed in PVC bags.</p>																																												