

ANUNȚ DE PARTICIPARE

privind achiziționarea *Camerele video cu trepied și accesorii*
prin procedura de achiziție *Licitație deschisă*

1. Denumirea autorității contractante: *IP Compania „Teleradio – Moldova”*
2. IDNO: *1004600050558*
3. Adresa: *str. Miorița 1, mun. Chișinău, MD – 2028*
4. Numărul de telefon/fax: *022721047, 068482641*
5. Adresa de e-mail și pagina web oficială ale autorității contractante:
trm@trm.md, www.trm.md
6. Adresa de e-mail sau pagina web oficială de la care se va putea obține accesul la documentația de atribuire: *documentația de atribuire este anexată în cadrul procedurii în SIA RSAP*
7. Tipul autorității contractante și obiectul principal de activitate (dacă este cazul, mențiunea că autoritatea contractantă este o autoritate centrală de achiziție sau că achiziția implică o altă formă de achiziție comună): *Instituție Publică*
8. Cumpărătorul invită operatorii economici interesați, care îi pot satisface necesitățile, să participe la procedura de achiziție privind livrarea bunuri:

Cod CPV	Denumirea bunurilor	Cant.	Unit. m.ăs.	Descrierea bunurilor și specificarea tehnică	Valoarea estimată fără TVA (pentru fiecare lot în parte)
	Camere video cu trepied și accesorii				
	Lotul nr. 1 Camere video cu trepied și accesorii				807 800,00
32240000-7	1.1. Camera (set)	1	buc	Camera - <i>Imaging</i> Sensor Resolution - Actual: 12.9 Megapixel; Effective: 10.2 Megapixel Image Sensor - Full-Frame CMOS Image Stabilization - Supplies Stabilization Metadata Built-In ND Filter - 2 to 7 Stop Electronic ND Filter Capture Type - Video Only <i>Exposure Control</i> Shutter Type - Electronic Rolling Shutter Shutter Speed - 1/8000 to 1 Second ISO Sensitivity Range - 800 to 12,800 (Extended: 409,600) Gain - -3 to 30 dB (Native) Shutter Angle - 5.6 to 360° Advertised Dynamic Range - 15 Stops White Balance - 2000 to 15,000K; Presets: ATW, Set A, Set B <i>Video Capture</i> Internal Recording Modes XAVC-I DCI 4K (4096 x 2160) up to 59.94 fps [240 to 600 Mb/s VBR]	277 500,00

			UHD 4K (3840 x 2160) up to 59.94/100/120 fps [240 to 600 Mb/s VBR] 1920 x 1080p up to 59.94/100/120/150/200/240 fps [89 to 223 Mb/s VBR] XAVC-L UHD 4K (3840 x 2160) up to 59.94/100/120 fps [100 to 150 Mb/s] 1920 x 1080p up to 59.94/100/120/150/200/240 fps [35 to 50 Mb/s] External Recording Modes Raw 16-Bit via SDI/BNC 4096 x 2160 at 23.98/24.00/25/29.97/50/59.94 fps 3840 x 2160 at 23.98/24.00/25/29.97/50/59.94 fps Raw 16-Bit via HDMI 4264 x 2408 at 23.98/25/29.97/50/59.94 fps 4240 x 2385 at 23.98/25/29.97/50/59.94 fps Fast-/Slow-Motion Support Gamma Curve - HDR-HLG, Rec709, S Cinetone, Sony S-Log 3, Standard Built-In Microphone - Mono Audio Recording - 4-Channel 24-Bit 48 kHz LPCM Audio <u>Interface</u> Media/Memory Card Slot - Dual Slot: CFexpress Type A / SD Video I/O - 1x BNC (12G-SDI) Output, 1x HDMI 1.0 Output Audio I/O - 2x XLR 3-Pin Mic/Line (+48 V Phantom Power) Input on Included Handle, 1x 1/8" / 3.5 mm TRS Stereo Microphone Output Power I/O - 1x Barrel (19.5VDC) Input Other I/O - 1x USB-C (USB 3.2 / 3.1 Gen 1), 1x Multi/Micro-USB Data, 1x BNC (Timecode), 1x 2.5 mm Sub-Mini Control, 1x 1/8" / 3.5 mm Control, 1x Proprietary Wireless - 2.4 / 5 GHz Wi-Fi 5 (802.11ac), NFC <u>Monitor</u> Display Type - Included External Touchscreen LCD, Size - 3.5" Resolution - 1280 x 720 (2,760,000 Dot) Include: Handle Unit, 3.5" LCD Monitor, Grip Remote Control, BC-CU1 Battery Cradle, AC Adapter, Power Cord, USB Type-C Cable, Cold Shoe Kit, Lens Mount Cap, Handle Connector Cap * Mirrorless Lens Focal Length - 24 to 70mm Maximum Aperture - f/2.8 Lens Mount - Sony E Lens Format Coverage - Full-Frame Focus Type - Autofocus Filter Size - 82 mm (Front) * Mirrorless Lens Focal Length - 70 to 200mm Maximum Aperture - f/2.8 Lens Format Coverage - Full-Frame Focus Type - Autofocus Image Stabilization Filter Size - 77 mm (Front) * Memory card: 80GB CFexpress Type A (4 pcs) * CFexpress Type 2 and UHS-II SD Card Reader (2 pcs)	
--	--	--	--	--

			* Dual BP-U100 Lithium-Ion Batteries with 2 x D-Tap ports, 1 x USB port (6800mAh) + Dual Charger with 2 pcs. plates for charging BP-U100 (compatible with camera) + 2 pcs L-Series-compatible battery plates. * Carbon Fiber Tripod System with XL Head & Mid-Level Spreader (1 pcs) <i>Tripod - Key Features</i> Fluid Head; Two-Stage Carbon Fiber Tripod 8 kg Load Capacity 9-Step + 0 Counterbalance 3-Step + 0 Pan/Tilt Drag Mid-Level Spreader, Rubber Feet <i>Head</i> Camera Mounting - 1/4"-20 Screw (Quick Release w/ Sliding Balance Plate) Head Type - Fluid Head Base Mount - Flat Base with 3/8"-16 Female (75 mm Half Ball via Included Adapter) Counter Balance - Incremental 9-Step Plus 0 Dimensions - Camera Plate: 140.00 x 50.00 mm Vertical Tilt - +90° to -75° Load Capacity - 8 kg Bubble Level - Illuminated Weight - 1.7 kg <i>Legs</i> Head Mount Type - 75 mm Bowl Primary Material - Carbon Fiber Load Capacity - 20 kg Maximum Working Height - 158 cm Minimum Working Height - 43 cm Closed Length - 71 cm Spreader Support - Ground/Mid-Level Weight - 1.8 kg <i>Items Included:</i> Fluid Head, 75/2 Mark II Carbon Fiber Tripod, Mid-Level Spreader, Rubber Feet, Carry Handle * Kit1: Handheld mic SET Camera-Mount Digital Wireless Omni Lavalier Mic System with Black Outdoor Kit: Camera-Mount Digital Wireless Receiver, Digital Wireless Bodypack Transmitter, Omnidirectional Lavalier Microphone with Locking 3.5mm Connector, SKM-S Digital Wireless Handheld Transmitter with Mute Switch, 835 Cardioid Dynamic Capsule for Handheld Transmitters, TRS Locking 3.5mm TRS to 3.5mm TRS Coiled Cable, XLR Right-Angle Locking 3.5mm TRS to XLR Male Coiled Output Cable, USB-C Charging Cable, BA 70 Rechargeable Battery Pack, Mounting Kit (Cheeseplate, Cold Shoe, Beltclip, Screws), Bubblebee Industries Windbubble Miniature Imitation-Fur Windscreen, 2 x The Microphone Foam for Lavalier, The Cable Saver, The Mic Accessory Case Wireless Technology - Digital UHF Included Transmitters - 1x Bodypack, 1x Plug-On RF Channel Scanning - Auto-Scan Max Operating Range - 100 m (Line of Sight) Built-In Recorder	
--	--	--	---	--

			Sample Rate/Resolution - 24-Bit Latency - 1.9 ms Dynamic Range - 134 dB Receiver Type - Camera-Mount Mounting Options - Belt Clip, Shoe-Mount, 1/4"-20 Female (with Included Hardware) Antenna - 2x 1/4 Wave Rod, Fixed Number of Audio Channels - 1 Audio I/O - 1x 1/8" / 3.5 mm TRS Female Unbalanced Output (Locking), 1x 1/8" / 3.5 mm TRS Female Unbalanced Headphone Output (Locking) Audio Output Level - 1/8" / 3.5 mm Output: 2 dBV (Max, Unbalanced) Frequency Response - 20 Hz to 20 kHz ± 3 dB USB/Lightning Connectivity - 1x USB-C Female (Bus Power, Charging) Display & Indicators - 1x Backlit OLED (AF Level, Frequency, Mute, RF Level, Transmitter Battery Status) <i>Transmitter Type - Bodypack</i> Audio I/O - 1x 1/8" / 3.5 mm TRS Female Input (Locking) Sync Method - Bluetooth Antenna - 1x Flexible Whip, Fixed (Beltpack) Battery Type - 2x AA (Included) Display & Indicators - 1x LED (Mute), 1x LED (Sync) Housing - Metal <i>Microphone Type - Lavalier</i> Color - Black Sound Field - Mono Capsule - Electret Condenser Polar Pattern - Omnidirectional Frequency Range - 50 Hz to 18 kHz Equivalent Noise Level - 32 dB Maximum SPL - 130 dB SPL Sensitivity - 17 mV/Pa at 1 kHz Output Connector - 1x 1/8" / 3.5 mm TRS Male (Locking) Cable Length - 5.2' / 1.6 m Operating Voltage - 7.5 V <i>Transmitter 2</i> Transmitter Type - Handheld RF Output Power - 10 mW (ERP); Up to 10 mW (EIRP) Muting - Mute Switch Audio Input Level - 2 to 4.35 V RMS Frequency Response - 20 Hz to 20 kHz Sync Method - Bluetooth Antenna - 1x Internal (Handheld) Power Requirements - Battery Include: MMD 835 cardioid capsule *Kit2: SET Camera-Mount Digital Wireless Omni Lavalier Mic System with Black Outdoor Kit. Include Camera-Mount Digital Wireless Receiver, Digital Wireless Bodypack Transmitter, Omnidirectional Lavalier Microphone with Locking 3.5mm Connector, TRS Locking 3.5mm TRS to 3.5mm TRS Coiled Cable, XLR Right-Angle Locking 3.5mm TRS to XLR Male Coiled Output Cable, USB-C	
--	--	--	---	--

			Charging Cable, BA 70 Rechargeable Battery Pack, Mounting Kit (Cheeseplate, Cold Shoe, Beltclip, Screws), Bubblebee Industries Windbubble Miniature Imitation-Fur Windscreen, 2 x The Microphone Foam for Lavalier, The Cable Saver, The Mic Accessory Case Wireless Technology - Digital UHF Included Transmitters - 1x Bodypack, 1x Plug-On RF Channel Scanning - Auto-Scan Max Operating Range - 100 m (Line of Sight) Built-In Recorder Sample Rate/Resolution - 24-Bit Latency - 1.9 ms Dynamic Range - 134 dB Receiver Type - Camera-Mount Mounting Options - Belt Clip, Shoe-Mount, 1/4"-20 Female (with Included Hardware) Antenna - 2x 1/4 Wave Rod, Fixed Number of Audio Channels - 1 Audio I/O - 1x 1/8" / 3.5 mm TRS Female Unbalanced Output (Locking), 1x 1/8" / 3.5 mm TRS Female Unbalanced Headphone Output (Locking) Audio Output Level - 1/8" / 3.5 mm Output: 2 dBV (Max, Unbalanced) Frequency Response - 20 Hz to 20 kHz ± 3 dB USB/Lightning Connectivity - 1x USB-C Female (Bus Power, Charging) Display & Indicators - 1x Backlit OLED (AF Level, Frequency, Mute, RF Level, Transmitter Battery Status) <i>Transmitter Type - Bodypack</i> Audio I/O - 1x 1/8" / 3.5 mm TRS Female Input (Locking) Sync Method - Bluetooth Antenna - 1x Flexible Whip, Fixed (Beltpack) Battery Type - 2x AA (Included) 1x Sennheiser Battery Pack (Included, Replaceable) Display & Indicators - 1x LED (Mute), 1x LED (Sync) Housing - Metal <i>Microphone Type - Lavalier</i> Color - Black Sound Field - Mono Capsule - Electret Condenser Polar Pattern - Omnidirectional Frequency Range - 50 Hz to 18 kHz Equivalent Noise Level - 32 dB Maximum SPL - 130 dB SPL Sensitivity - 17 mV/Pa at 1 kHz Output Connector - 1x 1/8" / 3.5 mm TRS Male (Locking) Cable Length - 5.2' / 1.6 m Operating Voltage - 7.5 V * Closed-Back Studio Monitor Headphones (2 pcs.) Wearing Style - Dual Ear with Headband; Foldable; Earpiece Swivel. Open/Closed-Back - Closed-Back Impedance - 32 Ohms Frequency Response - 20 Hz to 20 kHz	
--	--	--	--	--

			Audio Connector - 1x 1/8" / 3.5 mm TRS Included Adapter - 1/4" TRS * Zoom & Focus Control (2 pcs.) Remote controller for video camcorders that connects to the camera's LANC port. The remote control can be attached to a tripod handle and be used to control zoom, focus and start/stop. This added functionality is ideal for live event coverage such as concerts and sports. (Compatible with camera) * Backpack (equivalent Tenba Cineluxe Backpack 21) (1 Pcs.) Camera Gear Capacity Professional camcorders, cinema cameras and ENG rigs up to 18 inches (46 cm) long, with matte box and other accessories attached. Fast Doctor Bag Opening Extra wide opening allows unobstructed access to gear through only one quick zipper down the middle. Camera can be stored with baseplate, microphone and/or matte box attached. Expedition-Grade Harness Pivot-Fit shoulder harness with Airflow channels and padded hip belt provide comfort and support when carrying large camera systems, and high-density foam padding won't compress or break down over time or with heavy use. Hip belt is easily removable when not needed. Flex-Core Dividers Tenba's exclusive dividers made with aluminum reinforcement are both rigid and flexible, providing a secure separation between cameras and lenses while also being bendable and repositionable. Protective Pouch and Wraps Soft padded wraps and zippered pouch protect lenses and delicate accessories and allow them to be safely stored alongside camera rigs to maximize the interior storage space. Warranty: 3 years.	
--	--	--	--	--

322400000-7	1.2. Camera (set)	2	buc	Camera <u>Imaging</u> Sensor Resolution - Actual: 12.9 Megapixel; Effective: 10.2 Megapixel Image Sensor - Full-Frame CMOS Image Stabilization - Supplies Stabilization Metadata Built-In ND Filter - 2 to 7 Stop Electronic ND Filter Capture Type - Video Only <u>Exposure Control</u> Shutter Type - Electronic Rolling Shutter Shutter Speed - 1/8000 to 1 Second ISO Sensitivity Range - 800 to 12,800 (Extended: 409,600) Gain - -3 to 30 dB (Native) Shutter Angle - 5.6 to 360° Advertised Dynamic Range - 15 Stops White Balance - 2000 to 15,000K; Presets: ATW, Set A, Set B <u>Video Capture</u> Internal Recording Modes XAVC-I DCI 4K (4096 x 2160) up to 59.94 fps [240 to 600 Mb/s VBR] UHD 4K (3840 x 2160) up to 59.94/100/120 fps [240 to 600 Mb/s VBR] 1920 x 1080p up to 59.94/100/120/150/200/240 fps [89 to 223 Mb/s VBR] XAVC-L UHD 4K (3840 x 2160) up to 59.94/100/120 fps [100 to 150 Mb/s] 1920 x 1080p up to 59.94/100/120/150/200/240 fps [35 to 50 Mb/s] External Recording Modes Raw 16-Bit via SDI/BNC 4096 x 2160 at 23.98/24.00/25/29.97/50/59.94 fps 3840 x 2160 at 23.98/24.00/25/29.97/50/59.94 fps Raw 16-Bit via HDMI 4264 x 2408 at 23.98/25/29.97/50/59.94 fps 4240 x 2385 at 23.98/25/29.97/50/59.94 fps Fast-/Slow-Motion Support Gamma Curve - HDR-HLG, Rec709, S Cinetone, Sony S-Log 3, Standard Built-In Microphone - Mono Audio Recording - 4-Channel 24-Bit 48 kHz LPCM Audio <u>Interface</u> Media/Memory Card Slot - Dual Slot: CFexpress Type A / SD Video I/O - 1x BNC (12G-SDI) Output, 1x HDMI 1.0 Output Audio I/O - 2x XLR 3-Pin Mic/Line (+48 V Phantom Power) Input on Included Handle, 1x 1/8" / 3.5 mm TRS Stereo Microphone Output Power I/O - 1x Barrel (19.5VDC) Input Other I/O - 1x USB-C (USB 3.2 / 3.1 Gen 1), 1x Multi/Micro-USB Data, 1x BNC (Timecode), 1x 2.5 mm Sub-Mini Control, 1x 1/8" / 3.5 mm Control, 1x Proprietary Wireless - 2.4 / 5 GHz Wi-Fi 5 (802.11ac), NFC <u>Monitor</u>	494 383,33
-------------	-------------------	---	-----	--	------------

			Display Type - Included External Touchscreen LCD, Size - 3.5" Resolution - 1280 x 720 (2,760,000 Dot) Include: Handle Unit, 3.5" LCD Monitor, Grip Remote Control, BC-CU1 Battery Cradle, AC Adapter, Power Cord, USB Type-C Cable, Cold Shoe Kit, Lens Mount Cap, Handle Connector Cap * Mirrorless Lens Focal Length - 70 to 200mm Maximum Aperture - f/2.8 Lens Format Coverage - Full-Frame Focus Type - Autofocus Image Stabilization Filter Size - 77 mm (Front) * Memory card: 80GB CFexpress Type A (4 pcs) * CFexpress Type 2 and UHS-II SD Card Reader (2 pcs) * Dual BP-U100 Lithium-Ion Batteries with 2 x D-Tap ports, 1 x USB port (6800mAh) + Dual Charger with 2 pcs. plates for charging BP-U100 (compatible with camera) + 2 pcs L-Series-compatible battery plates. * Carbon Fiber Tripod System with XL Head & Mid-Level Spreader (1 pcs) Tripod <i>Key Features</i> Fluid Head Two-Stage Carbon Fiber Tripod 8 kg Load Capacity 9-Step + 0 Counterbalance 3-Step + 0 Pan/Tilt Drag Mid-Level Spreader, Rubber Feet <i>Head</i> Camera Mounting - 1/4"-20 Screw (Quick Release w/ Sliding Balance Plate) Head Type - Fluid Head Base Mount - Flat Base with 3/8"-16 Female (75 mm Half Ball via Included Adapter) Counter Balance - Incremental 9-Step Plus 0 Dimensions - Camera Plate: 140.00 x 50.00 mm Vertical Tilt - +90° to -75° Load Capacity - 8 kg Bubble Level - Illuminated Weight - 1.7 kg <i>Legs</i> Head Mount Type - 75 mm Bowl Primary Material - Carbon Fiber Load Capacity - 20 kg Maximum Working Height - 158 cm Minimum Working Height - 43 cm Closed Length - 71 cm Spreader Support - Ground/Mid-Level Weight - 1.8 kg <i>Items Included:</i> Fluid Head, 75/2 Mark II Carbon Fiber Tripod, Mid-Level Spreader, Rubber Feet, Carry Handle	
--	--	--	--	--

			* Kit1: Hendheld mic SET Camera-Mount Digital Wireless Omni Lavalier Mic System with Black Outdoor Kit: Camera-Mount Digital Wireless Receiver, Digital Wireless Bodypack Transmitter, Omnidirectional Lavalier Microphone with Locking 3.5mm Connector, SKM-S Digital Wireless Handheld Transmitter with Mute Switch, 835 Cardioid Dynamic Capsule for Handheld Transmitters, TRS Locking 3.5mm TRS to 3.5mm TRS Coiled Cable, XLR Right-Angle Locking 3.5mm TRS to XLR Male Coiled Output Cable, USB-C Charging Cable, BA 70 Rechargeable Battery Pack, Mounting Kit (Cheeseplate, Cold Shoe, Beltclip, Screws), Bubblebee Industries Windbubble Miniature Imitation-Fur Windscreen, 2 x The Microphone Foam for Lavalier, The Cable Saver, The Mic Accessory Case Wireless Technology - Digital UHF Included Transmitters - 1x Bodypack, 1x Plug-On RF Channel Scanning - Auto-Scan Max Operating Range - 100 m (Line of Sight) Built-In Recorder Sample Rate/Resolution - 24-Bit Latency - 1.9 ms Dynamic Range - 134 dB <i>Receiver Type</i> - Camera-Mount Mounting Options - Belt Clip, Shoe-Mount, 1/4"-20 Female (with Included Hardware) Antenna - 2x 1/4 Wave Rod, Fixed Number of Audio Channels - 1 Audio I/O - 1x 1/8" / 3.5 mm TRS Female Unbalanced Output (Locking), 1x 1/8" / 3.5 mm TRS Female Unbalanced Headphone Output (Locking) Audio Output Level - 1/8" / 3.5 mm Output: 2 dBV (Max, Unbalanced) Frequency Response - 20 Hz to 20 kHz ± 3 dB USB/Lightning Connectivity - 1x USB-C Female (Bus Power, Charging) Display & Indicators - 1x Backlit OLED (AF Level, Frequency, Mute, RF Level, Transmitter Battery Status) <i>Transmitter Type</i> - Bodypack Audio I/O - 1x 1/8" / 3.5 mm TRS Female Input (Locking) Sync Method - Bluetooth Antenna - 1x Flexible Whip, Fixed (Beltpack) Battery Type - 2x AA (Included) Display & Indicators - 1x LED (Mute), 1x LED (Sync) Housing - Metal <i>Microphone Type</i> - Lavalier Color - Black Sound Field - Mono Capsule - Electret Condenser Polar Pattern - Omnidirectional Frequency Range - 50 Hz to 18 kHz Equivalent Noise Level - 32 dB Maximum SPL - 130 dB SPL Sensitivity - 17 mV/Pa at 1 kHz Output Connector - 1x 1/8" / 3.5 mm TRS Male (Locking) Cable Length - 5.2' / 1.6 m	
--	--	--	--	--

			Operating Voltage - 7.5 V <i>Transmitter 2</i> Transmitter Type - Handheld RF Output Power - 10 mW (ERP); Up to 10 mW (EIRP) Muting - Mute Switch Audio Input Level - 2 to 4.35 V RMS Frequency Response - 20 Hz to 20 kHz Sync Method - Bluetooth Antenna - 1x Internal (Handheld) Power Requirements - Battery Include: MMD 835 cardioid capsule *Kit2: SET Camera-Mount Digital Wireless Omni Lavalier Mic System with Black Outdoor Kit. Include Camera-Mount Digital Wireless Receiver, Digital Wireless Bodypack Transmitter, Omnidirectional Lavalier Microphone with Locking 3.5mm Connector, TRS Locking 3.5mm TRS to 3.5mm TRS Coiled Cable, XLR Right-Angle Locking 3.5mm TRS to XLR Male Coiled Output Cable, USB-C Charging Cable, BA 70 Rechargeable Battery Pack, Mounting Kit (Cheeseplate, Cold Shoe, Beltclip, Screws), Bubblebee Industries Windbubble Miniature Imitation-Fur Windscreen, 2 x The Microphone Foam for Lavalier, The Cable Saver, The Mic Accessory Case Wireless Technology - Digital UHF Included Transmitters - 1x Bodypack, 1x Plug-On RF Channel Scanning - Auto-Scan Max Operating Range - 100 m (Line of Sight) Built-In Recorder Sample Rate/Resolution - 24-Bit Latency - 1.9 ms Dynamic Range - 134 dB <i>Receiver Type</i> - Camera-Mount Mounting Options - Belt Clip, Shoe-Mount, 1/4"-20 Female (with Included Hardware) Antenna - 2x 1/4 Wave Rod, Fixed Number of Audio Channels - 1 Audio I/O - 1x 1/8" / 3.5 mm TRS Female Unbalanced Output (Locking), 1x 1/8" / 3.5 mm TRS Female Unbalanced Headphone Output (Locking) Audio Output Level - 1/8" / 3.5 mm Output: 2 dBV (Max, Unbalanced) Frequency Response - 20 Hz to 20 kHz ± 3 dB USB/Lightning Connectivity - 1x USB-C Female (Bus Power, Charging) Display & Indicators - 1x Backlit OLED (AF Level, Frequency, Mute, RF Level, Transmitter Battery Status) <i>Transmitter Type</i> - Bodypack Audio I/O - 1x 1/8" / 3.5 mm TRS Female Input (Locking) Sync Method - Bluetooth Antenna - 1x Flexible Whip, Fixed (Beltpack) Battery Type - 2x AA (Included) 1x Sennheiser Battery Pack (Included, Replaceable) Display & Indicators - 1x LED (Mute), 1x LED (Sync) Housing - Metal	
--	--	--	--	--

			<i>Microphone Type</i> - Lavalier Color - Black Sound Field - Mono Capsule - Electret Condenser Polar Pattern - Omnidirectional Frequency Range - 50 Hz to 18 kHz Equivalent Noise Level - 32 dB Maximum SPL - 130 dB SPL Sensitivity - 17 mV/Pa at 1 kHz Output Connector - 1x 1/8" / 3.5 mm TRS Male (Locking) Cable Length - 5.2' / 1.6 m Operating Voltage - 7.5 V * Closed-Back Studio Monitor Headphones (2 pcs.) Wearing Style - Dual Ear with Headband; Foldable; Earpiece Swivel. Open/Closed-Back - Closed-Back Impedance - 32 Ohms Frequency Response - 20 Hz to 20 kHz Audio Connector - 1x 1/8" / 3.5 mm TRS Included Adapter - 1/4" TRS * Backpack (equivalent Tenba Cineluxe Backpack 24) (2 pcs.) Camera Gear Capacity - Professional camcorders, cinema cameras and ENG rigs up to 20 inches (51 cm) long, from Sony, Canon, RED, Blackmagic and others, with matte box and other accessories attached. Fast Doctor Bag Opening - Extra wide opening allows unobstructed access to gear through only one quick zipper down the middle. Camera can be stored with baseplate, microphone and/or matte box attached. Expedition-Grade Harness - Pivot-Fit shoulder harness with Airflow channels and padded hip belt provide comfort and support when carrying large camera systems, and high-density foam padding won't compress or break down over time or with heavy use. Hip belt is easily removable when not needed. Flex-Core Dividers - Tenba's exclusive dividers made with aluminum reinforcement are both rigid and flexible, providing a secure separation between cameras and lenses while also being bendable and repositionable. Protective Pouch and Wraps - Soft padded wraps and zippered pouch protect lenses and delicate accessories and allow them to be safely stored alongside camera rigs to maximize the interior storage space. Warranty: 3 years.	
--	--	--	---	--

	1.3. LED Light	1	buc	Production 8-Light Kit CCT 2,000K-10,000K; CRI-96; TLCI-96; CQS-95; SSI (D56)-72; SSI (Tungsten)-82; TM-30 RF (Average)- 94; TM-30 RG (Average) - 103; Lumens - 563 lm Max Power Output (Fixture) - 5W; Max Power Output (Case) - 100W; Max Power Consumption (Fixture) - 7W; Max Power Consumption (Case) - 129W. Max Operating Current - 0.84A; Operating Current (Fixture) - 0.84A; Operating Current (Case) - 1.8A. Operating Voltage (Fixture) 3.0-4.2V; Operating Voltage (Case) 12-28V. Charging Input USB Type-C (5V/2A), Contact Charger AC Input Voltage 100-240V, 50/60Hz Lithium-Polymer Battery 4,200mAh / 3.7-4.2V, 15.5Wh Battery Life (Fixture) Approx. 120 Mins @ Max Output Charge Time Approx. 90 Mins (5V/2A) IP Rating IP65 Operating Temperature -20°C~45°C Dimming 0-100% Screen Type TFT Cooling Method Passive Cooling Include: 8x LED Light Panel 8x LED Light Panel Flat Diffuser 8x LED Light Panel Dome Diffuser 8x LED Light Panel 30° Light Control Grid 4x Cold Shoe Ball Head 4x 1/4-20in Screw to Magnetic Plate Adapter 4x 1/4-20in Screw to Baby Pin Adapter 2x 1/4-20in Articulating Arm to Clamp Adapter 2x USB Type-C Charging Cable 32x Adhesive Magnetic Plate 1x Locking IEC C13 AC Power Cable 1x D-Tap to D-Tap Power Cable 1x LED Light Panel 8-Light Charging Case Warranty: 3 years.	35 916,67
--	----------------	---	-----	--	-----------

32240000-7	Lotul nr. 2 Camera (set)	1	buc	Camera <u>Imaging</u> Sensor Resolution - Actual: 12.1 Megapixel; Effective: 10.2 Megapixel Image Sensor - 35.6 x 23.8 mm (Full-Frame) CMOS Crop Factor - 1x Image Stabilization - Sensor-Shift, 5-Axis Capture Type - Stills & Video <u>Exposure Control</u> Shutter Type - Mechanical Focal Plane Shutter and Electronic Rolling Shutter Shutter Speed - 1/8000 to 1/4 Second in Movie Mode; 1/8000 to 1/60 Second in Auto Mode; 1/8000 to 30 Seconds in Manual Mode Bulb/Time Mode - Bulb Mode ISO Sensitivity Range - Video 80 to 102,400 in Manual Mode (Extended: 80 to 409,600) Advertised Dynamic Range - 15 Stops Exposure Modes - Aperture Priority, Auto, Manual, Program, Shutter Priority Metering Range - -3 to 20 EV White Balance - 2500 to 9900K Presets: Auto, Cloudy, Custom, Daylight, Flash, Fluorescent, Incandescent, Shade, Underwater Continuous Shooting - Up to 10 fps <u>Video Capture</u> Internal Recording Modes XAVC Proxy 1920 x 1080 [9 to 16 Mb/s], 1280 x 720 [6 Mb/s] MPEG-4 AVC/XAVC S 4:2:0 8-Bit, 3840 x 2160 at 1/2/3/4/6/8/12/15/23.98/25/29.97/50/59.94/100/120 fps [60 to 200 Mb/s]; 1920 x 1080p at 1/2/3/4/6/8/12/15/23.98/25/29.97/50/59.94/100/120/200/240 fps [16 to 100 Mb/s] H.265 Long GOP/XAVC HS 4:2:2 10-Bit, UHD 4K (3840 x 2160) at 1/2/3/4/6/8/12/15/23.98/25/29.97/50/59.94/100/120 fps [50 to 280 Mb/s] H.265 Long GOP/XAVC HS 4:2:0 10-Bit 3840 x 2160 at 1/2/3/4/6/8/12/15/23.98/25/29.97/50/59.94/100/120 fps [30 to 150 Mb/s] MPEG-4 AVC/XAVC S 4:2:2 10-Bit, 3840 x 2160 at 1/2/3/4/6/8/12/15/23.98/25/29.97/50/59.94/100/120 fps [100 to 280 Mb/s]; 1920 x 1080p at 1/2/3/4/6/8/12/15/23.98/25/29.97/50/59.94/100/120/200/240 fps [50 Mb/s] MPEG-4 AVC/XAVC S-I 4:2:2 10-Bit, 4096 x 2160 at 1/2/3/6/12/23.98/24.00/29.97/48.00/59.94 fps UHD 4K (3840 x 2160) at 1/2/3/4/6/8/12/15/23.98/25/29.97/59.94/100/120 fps [240 to 600 Mb/s]; 1920 x 1080p at 1/2/3/4/6/8/12/15/23.98/25/29.97/50/59.94/100/120/200/240 fps [89 to 222 Mb/s] External Recording Modes	135 000,00
------------	-----------------------------	---	-----	--	------------

			Raw 16-Bit via HDMI; 4264 x 2408 at 23.98/25/50/59.94 fps; 3840 x 2160 at 23.98/25/50/59.94 fps; 1920 x 1080p at 23.98/25/50/59.94 fps; 1920 x 1080i at 50 fps Fast-/Slow-Motion Support Gamma Curve - HDR-HLG, S Cinetone, Sony S-Log 2, Sony S-Log 3, Standard Built-In Microphone - Stereo Audio Recording - 4-Channel 24-Bit LPCM Audio, 2-Channel 24-Bit LPCM Audio <u>Interface</u> Media/Memory Card Slot - Dual Slot: CFexpress Type A / SD Video I/O - 1x HDMI (Unspecified Signal) Output Audio I/O - 2x XLR / 1/4" TRS Combo Mic/Line Input on Included Handle, 1x 1/8" / 3.5 mm TRS Stereo Microphone Input on Camera Body, 1x 1/8" / 3.5 mm TRS Stereo Headphone Output on Camera Body Power I/O - 1x USB-C Input Other I/O - 1x USB-C (Ethernet, USB 3.2 / 3.1 Gen 1) (Shared with Power Input), Multi/Micro-USB Wireless - 2.4 / 5 GHz Wi-Fi 5 (802.11ac), Bluetooth, NFC <u>Monitor</u> Display Type - Articulating Touchscreen LCDm Size - 3" Resolution - 1,440,000 Dot Include: XLR Handle Unit, Accessory Shoe Cap, Accessory Shoe Kit, Battery Charger, Body Cap, Handle Shoe Cap, Power Cord, Rechargeable Lithium-Ion Battery, USB Type-A to Type-C Cable (USB 3.2) * Dual Battery Charger + 2 Rechargeable Lithium-Ion Battery (compatible with camera) * Mirrorless Lens Focal Length - 12 to 24mm Maximum Aperture - f/4 Lens Mount - Sony E Lens Format Coverage - Full-Frame Focus Type - Autofocus * Mirrorless Lens Focal Length - 70 to 200mm Maximum Aperture - f/2.8 Lens Mount - Sony E Lens Format Coverage - Full-Frame Focus Type - Autofocus Image Stabilization Filter Size - 77 mm (Front) * Memory card: 80GB CFexpress Type A (4 pcs) * CFexpress Type 2 and UHS-II SD Card Reader * Aluminum Tripod Kit + Video Head Camera Attachment Camera Mounting Screw - 1x 1/4"-20 Male, 1x 3/8"-16 Male Camera Plate - Quick Release: 504PLONG Head Type - Fluid Head Base Mount - Flat Base with 3/8"-16 Female Counter Balance - Fixed (8.82 lb / 4 kg) Head Dimensions - Base Diameter: 2.95" / 7.49 cm, Height: 5.12" / 13.00 cm Vertical Tilt - +90° to -80° Load Capacity - 22 lb / 10 kg	
--	--	--	--	--

			Accessory Mounting - 1x 3/8"-16 Female Thread, 2x Pan Handle Fitting Bubble Level Weight - 1.69 kg * Video Assist 5" 12G-SDI/HDMI HDR Recording Monitor <u>Display</u> Panel Type - IPS-Type LCD, Touchscreen Display Size - 5.0" / 12.7 cm Native Resolution - 1920 x 1080 Aspect Ratio - 16:9 Maximum Brightness - 2500 nits / cd/m2 Color Support - 1.07 Billion Colors (10-Bit) HDR Support - HDR10/Hybrid Log Gamma Pixels Per Inch (ppi) - 440 ppi Color Gamut - 100% Rec. 709, 100% Rec. 2020 LUT Support Image Controls - Histogram, Picture-in-Picture, RGB Parade, Vectorscope, Waveform <u>Inputs / Outputs</u> Video I/O - 1x HDMI 2.0a Input, 1x Micro BNC (12G-SDI) Input, 1x HDMI 2.0a Output, 1x Micro BNC (12G-SDI) Output Embedded Audio - HDMI: 8-Channel, SDI: 16-Channel Audio I/O - 1x 1/8" / 3.5 mm Headphone Output Built-In Speaker - Mono Power I/O - 1x Barrel (12 VDC) Input Other I/O - 1x USB-C Media/Memory Card Slot - Single Slot: SD/SDHC/SDXC (UHS-II) Video Format SDI (10-Bit 4:2:2 RGB), UHD 4K: 60/59.94/50/30/29.97/25/24/23.98; 1080p: 60/59.94/50/30/29.97/25/24/23.98; 1080i: 60/59.94/50/30/29.97/25/24/23.98; HDMI (10-Bit) UHD 4K: 60/59.94/50/30/29.97/25/24/23.98; 1080p: 60/59.94/50/30/29.97/25/24/23.98; 1080i: 60/59.94/50/30/29.97/25/24/23.98 Gamma Curve - HDR-HLG, Rec709, Rec2020 * Backpack (equivalent Shootout 14L Slim Backpack) Camera Gear Capacity - 1-2 Mirrorless or compact DSLR cameras with 3-5 lenses (up to 70-200mm 2.8). Secure Rear Camera Access - Camera gear is secured up against the user's back so that nothing can be removed from the front or sides of the pack while traveling. Rear access also allows the pack to be swung around to the front to exchange gear without ever removing the pack from your body. Pivot-Fit™ Airflow Harness - Straps automatically adjust to different shoulder and body shapes for a custom fit. Body contact points covered in ventilated, moisture-wicking 3D air mesh for all-day carrying comfort. Durability and Weather Resistance - Built with the finest materials and hardware, including water-repellent nylon, YKK® zippers and clips, and heavily-reinforced stitching. Warranty: 3 years.	
			Valoarea estimativă fără TVA	942 800,00

9. În cazul procedurilor de preselecție se indică numărul minim al candidaților și, dacă este cazul, numărul maxim al acestora. *nu se aplică*
10. În cazul în care contractul este împărțit pe loturi un operator economic poate depune oferta (se va selecta): Pentru mai multe loturi:
11. Admiterea sau interzicerea ofertelor alternative: *nu se admite*
12. Termenii și condițiile de livrare/prestare solicitate: *în termen de 50 (cincizeci) de zile de la semnarea contractului*
13. Termenul de valabilitate a contractului: **31.12.2025**
14. Contract de achiziție rezervat atelierelor protejate sau că acesta poate fi executat numai în cadrul unor programe de angajare protejată (după caz): *nu se aplică*
15. Prestarea serviciului este rezervată unei anumite profesii în temeiul unor legi sau al unor acte administrative (după caz): *nu se aplică*
16. Scurta descriere a criteriilor privind eligibilitatea operatorilor economici care pot determina eliminarea acestora și a criteriilor de selecție/de preselecție; nivelul minim (nivelurile minime) al (ale) cerințelor eventual impuse; se menționează informațiile solicitate (DUAE, documentație):

Nr. d/o	Descrierea criteriului/cerinței	Mod de demonstrare a îndeplinirii criteriului/cerinței:	Nivelul minim/Obligativitatea
1.	(DUAE) – Documentul unic de achiziții european (în cazul în care operatorul economic participă la procedura de achiziții publice împreună cu alți operatori economici, toți participanții urmează să completeze DUAE separat)	Semnat electronic de către operatorul economic	Obligativiu
2.	Oferta - specificații tehnice și de preț (conform Anexelor nr. 22 și nr. 23 la Documentația standard aprobată prin Ordinul Ministrului Finanțelor nr. 115 din 15.09.2021)	Semnată electronic de către operatorul economic	Obligativiu
3.	Garanția pentru ofertă - 1% din valoarea ofertei fără TVA,	a) Garanția pentru ofertă (emisă de o bancă comercială), conform Anexei nr. 9 la Documentația standard aprobată prin Ordinul Ministrului Finanțelor nr. 115 din 15.09.2021 sau b) Transfer la contul (ordin de plată) IP Compania „Teleradio-Moldova: Denumirea Băncii:BC „Moldindconbank” SA Codul fiscal: 1004600050558 IBAN: MD47ML000000002251206328 Cod bancar: MOLDMD2X306 Termenul de valabilitate al garanției să fie valabil pe perioada de valabilitate a ofertei. semnată electronic de către operatorul economic	Obligativiu

4.	Intenția de participare în cadrul procedurii de achiziție	Cerere de participare completată, conform <u>Anexei nr. 7</u> la Documentația standard aprobată prin Ordinul Ministrului Finanțelor nr. 115 din 15.09.2021, semnată electronic de către operatorul economic	Obligativ
5.	Mentținerea valabilității ofertei pentru o durată de 60 de zile (<i>calculată din momentul termenului-limită de depunere a ofertei</i>)	Declarație privind valabilitatea ofertei, completată conform <u>Anexei nr. 8</u> la Documentația standard aprobată prin Ordinul Ministrului Finanțelor nr. 115 din 15.09.2021, semnată electronic de către operatorul economic	Obligativ
6.	Confirmarea identității beneficiarilor efectivi și neîncadrarea acestora în situația condamnării pentru participarea la activități ale unei organizații sau grupări criminale, pentru corupție, fraudă și/sau spălare de bani (<i>formularul Declarației va fi publicat pe SIA „RSAP” (MTender)</i>)	Declarație pe proprie răspundere - în termen de 5 zile după data comunicării rezultatelor procedurii de achiziție publică, ofertantul desemnat câștigător va prezenta această Declarație autorității contractante și Agenției Achiziției Publice, semnată electronic de către operatorul economic	*Obligativ
7.	Experiență specifică în livrarea bunurilor similare (<i>art. 22 alin. (1) lit. a) din Legea 131/2015 privind achizițiile publice</i>)	Declarație privind lista principalelor livrări/prestări efectuate în ultimii 3 ani de activitate, completată conform Anexei nr. 12 la Documentația standard aprobată prin Ordinul Ministrului Finanțelor nr. 115 din 15.09.2021. Prestarea serviciilor se confirmă prin prezentarea unor certificate / documente (facturi fiscale) emise sau contrasemnate de către beneficiarii de livrări, semnate electronic de către operatorul economic.	Obligativ
8.	Demonstrarea conformării reglementărilor Legii nr. 209/2016 privind deșeurile	Prezentarea numărului de înregistrare din „Lista producătorilor de produse supuse reglementărilor de responsabilitate extinsă a producătorului”, în conformitate cu Regulamentul privind deșeurile de echipamente electrice și electronice, aprobat prin Hotărârea Guvernului nr. 212 din 07.03.2018 (https://siamd.gov.md/portal/deee.html) - copia semnată electronic de către operatorul economic	*Obligativ
9.	Situație financiară	Raportul financiar în original/copie pentru ultimul an, aprobat de către Direcția Generală pentru Statistică sau însoțite de recipisa de primire de către Direcția Generală pentru Statistică, semnat electronic de către operatorul economic	*Obligativ
10.	Certificat/Decizie de înregistrare a întreprinderii și Extrasul din registrul de Stat	Copie - semnată electronic de către operatorul economic	Obligativ

11.	Certificat de atribuire a contului bancar	Eliberat de banca deținătoare de cont, semnat electronic de către operatorul economic	*Obligativ
12.	Informația privind îndeplinirea obligațiilor de plată a impozitelor, taxelor și contribuțiilor de asigurări sociale	Confirmarea lipsei restanțelor față de bugetul public național, semnată electronic de către operatorul economic	*Obligativ
13.	Garanția de bună execuție a contractului - 5% din valoarea contractului, inclusiv TVA	Transfer la contul I.P. Compania „Teleradio-Moldova” <i>Beneficiarul plății:</i> <i>I.P. Compania „Teleradio-Moldova”</i> <i>Denumirea Băncii: B.C., „Moldindconbank” SA</i> <i>Codul fiscal: 1004600050558</i> <i>Contul de decontare:</i> <i>MD47ML000000002251206328</i> <i>Contul bancar: MOLDM2X306</i>	*Obligativ (se va prezenta până la semnarea contractului)

**În cazul în care IP Compania „Teleradio-Moldova”, potrivit prevederilor art. 20 alin. (8) din Legea nr. 131/2015 privind achizițiile publice, va solicita prezentarea anumitor documente justificative, operatorul economic este obligat să le prezinte în termen de 3 zile lucrătoare, conform prevederilor DUAE și cadrului normativ în vigoare. În cazul neprezentării documentelor justificative în termenul-limită stabilit, operatorul economic va fi descalificat.*

** Documentele menționate la pct. 16, subpct. 2 se completează fără nici o modificare sau abatere de la formulare, spațiile goale fiind completate cu informația solicitată. Completarea defectuoasă a formularelor atrage respingerea ofertei.*

**În cazul în care Oferta nu este semnată de către administratorul companiei indicat în Extrasul Registrului de Stat al persoanelor juridice, la Ofertă se anexează actul/documentul de împuternicire a persoanei delegate sau împuternicite să semneze Oferta.*

17. Garanția pentru ofertă, după caz - Da, cuantumul de 1%, din valoarea ofertei fără TVA.

18. Garanția de bună execuție a contractului, după caz - Da, cuantumul 5% din valoarea contractului, inclusiv TVA, transfer la contul I.P. Compania „Teleradio-Moldova”.

19. Motivul recurgerii la procedura accelerată (în cazul licitației deschise, restrânse și a procedurii negociate), după caz: nu se aplică.

20. Tehnici și instrumente specifice de atribuire (dacă este cazul specificați dacă se va utiliza acordul-cadru, sistemul dinamic de achiziție sau licitația electronică): nu se aplică

21. Condiții speciale de care depinde îndeplinirea contractului (indicați după caz): nu se aplică.

22. Ofertele se prezintă în valuta LEI MDL

23. Criteriul de evaluare aplicat pentru atribuirea contractului: prețul cel mai scăzut

24. Termenul limită de depunere/deschidere a ofertelor: conform SIA RSAP

25. Adresa la care trebuie transmise ofertele sau cererile de participare: Ofertele sau cererile de participare vor fi depuse electronic prin intermediul SIA RSAP

26. Termenul de valabilitate a ofertelor: 60 zile

27. Locul deschiderii ofertelor: SIA RSAP Ofertele întârziate vor fi respinse.

28. Persoanele autorizate să asiste la deschiderea ofertelor:

Ofertanții sau reprezentanții acestora au dreptul să participe la deschiderea ofertelor, cu excepția cazului când ofertele au fost depuse prin SIA RSAP.

29. Limba sau limbile în care trebuie redactate ofertele sau cererile de participare:
Română

30. Respectivul contract se referă la un proiect și/sau program finanțat din fonduri ale Uniunii Europene: *nu se aplică.*

31. Denumirea și adresa organismului competent de soluționare a contestațiilor:

Agencia Națională pentru Soluționarea Contestațiilor

Adresa: mun. Chișinău, bd. Ștefan cel Mare și Sfânt nr.124 (et.4), MD 2001;

Tel/Fax/email:022-820 652, 022 820-651, contestatii@ansc.md

32.Data (datele) și referința (referințele) publicărilor anterioare în Jurnalul Oficial al Uniunii Europene privind contractul (contractele) la care se referă anunțul respectiv (dacă este cazul): *nu se aplică.*

33. În cazul achizițiilor periodice, calendarul estimat pentru publicarea anunțurilor viitoare: *nu se aplică*

34. Data publicării anunțului de intenție sau, după caz, precizarea că nu a fost publicat un astfel de anunț: BAP nr. 40 din 27.05.2025 link:
https://tender.gov.md/ro/system/files/bap/2014/bap_nr_40_0.pdf

35. Data transmiterii spre publicare a anunțului de participare: *Conform SIA RSAP*

36. În cadrul procedurii de achiziție publică se va utiliza/accepta:

Denumirea instrumentului electronic	Se va utiliza/accepta sau nu
Depunerea electronică a ofertelor sau a cererilor de participare	da
Sistemul de comenzi electronice	nu
Facturarea electronică	da
Plățile electronice	da

37. Contractul intră sub incidența Acordului privind achizițiile guvernamentale al Organizației Mondiale a Comerțului (numai în cazul anunțurilor transmise spre publicare în Jurnalul Oficial al Uniunii Europene): *nu se aplică.*

Președintele grupului de lucru:

Dorian BODIU

