

**Caracteristici tehnice camere video mobile.**

<b>Camera Module</b>				
Formatul senzorului de imagine	1/2.8'' CMOS sau echivalent			
Rezolutie	Min. 4,0 Mpx(2560 × 1440)			
Distanta focala	3.90-178mm, 45x zoom optic			
Zoom Digital	16X			
Focus Mode	Auto / Manual			
DORI Distance, min:	Detectare 3000 m	Observare 1200 m	Recunoastere 630 m	Identificare 300 m
Auto tracking	Suporta			
Face Detection	Suporta			
<b>Pan and Tilt</b>				
Range	Pan:360° endless; Tilt: -15°~90°(Auto Flip) sau echivalent			
Number of Preset	Min 100			
<b>Features</b>				
Detection	Intrusion detection, Line crossing detection, Motion detection			
ROI encoding	Support 4 areas with adjustable levels			
<b>Infrared</b>				
IR Distance	Min 150m			
IR control	Zoom Prio/manual/SmartIR			
<b>Network</b>				
Ethernet	10Base-T / 100Base-TX, RJ45 connector			
Stream	Support three Streams			
Image Compression	min. H.264/MJPEG			
Protocols	Min IPv4/IPv6, HTTP, HTTPS, 802.1X, QoS, FTP, SMTP, UPnP, SNMP, DNS, DDNS, NTP, RTSP, RTP, TCP, UDP, IGMP, ICMP, DHCP, PPPoE			
Security Measures	User authentication (ID and PW); Host authentication (MAC address); IP address filtering			
Application programming	support ONVIF, PSIA and CG , Support cloud P2P			
Web Browser	IE 7+, Chrome 18 +, Firefox 5.0 +, Safari 5.02 +			
Power	AC 24V, POE, Max.25W			
Working Temperature -	-35°C ~ 65°C			
Humidity	90% or less			
Protection Level	IP67, surge protection and voltage transient protection			
Accesorii pentru montare	wall mount bracket: DS-1602ZJ sau echivalent pentru fiecare camera; pole mount: DH-PFA153- sau echivalent pentru fiecare camera; Power box mount:DS-1602ZJ-box sau echivalent pentru fiecare camera; Power Supply pentru fiecare camera;			
Garanție	Min 3 ani			