



PRODUCT CATALOGUE

FOREVER INNOVATION
FOREVER CARE

LEPU MEDICAL TECHNOLOGY (BEIJING) CO., LTD

Head Office:
No.37 Chaoqian Road, Changping
District, Beijing,
China, 102200
Tel: +86-10-80120666
Fax: +86-10-80120600

International Sales and Marketing:
Tel: +86-10-80120601
Fax: +86-10-80123524
Email: international@lepu-medical.com
Web: en.lepumedical.com



Company Profile

Lepu Medical Technology (Beijing) Co., Ltd. was established in 1999. Lepu Medical is specialized in developing, manufacturing and distributing the high-tech medical devices and equipment. Today, Lepu Medical has grown into a global leading group company in the fields of cardiovascular, neurovascular and peripheral vascular interventions, structural heart diseases, surgical cardiology, cardiac rhythm management, anesthesia and critical care, in vitro diagnostics and general surgery with products include coronary stents, dilatation balloon catheters, interventional accessories, occlusion devices, mechanical heart valves, electrophysiology catheters, pacemakers, in vitro diagnostic products, critical care products, angiography systems and surgical staplers. In 2009, Lepu Medical went public in ChiNext Shenzhen Stock Exchange market (stock code: 300003).


Now Lepu Medical totally has 32 primary subsidiary companies worldwide. Currently, there are 123 products have received the CE certificates, and 17 products have got the FDA approvals. As the National Interventional Cardiology Medical Instruments & Engineering Technology Research Center, Lepu Medical Group's top strategy is to build up a 4 in 1 platform includes medical devices, medicines, health services and mobile medicals for cardiac treatments.

Lepu Medical has established three overseas subsidiary companies in Netherland, Turkey and India, obtained local registrations in 27 countries, and built the sales and distribution channels in over 80 countries and regions. Lepu Medical upholds “integrity, quality and scientific innovation” as its spirit, commitments to provide the best quality of products and services to satisfy the needs of healthcare professionals and patients.

This catalogue includes information of products available in certain countries. Availability of these products may vary with locations. Please contact Lepu Medical for more information about the approval in your region.

LEPU MEDICAL

Major Subsidiaries



The **Global Leading Group Company** in the Fields of
High-tech Medical Devices and Equipment

GLOBAL BUSINESS



- ★ Head Office
- 📍 Overseas Subsidiaries
- Major Markets

TABLE OF CONTENTS

01

Cardiovascular
Interventional Products

Coronary Stents

- 07 Nano+™ Polymer-free Sirolimus-eluting Coronary Stent System
- 08 GuReater™ CoCr Sirolimus-eluting Coronary Stent System
- 09 Partner™ Sirolimus-eluting Coronary Stent System CE
- 10 H-Stent™ Coronary Stent System CE

PTCA Balloons

- 11 Hoper™ PTCA Balloon Dilatation Catheter CE FDA
- 12 Mini Tadpole™ Coronary Dilatation Catheter CE
- 13 Tadpole™ Coronary Dilatation Catheter CE
- 14 NC Tadpole™ Coronary Dilatation Catheter CE

Catheters

- 15 Orien™ Guiding Catheter CE
- 17 Thromsweeper™ Thrombus Extraction Catheter
- 18 Deliver™ Infusion Catheter

Guide Wires

- 19 Angiographic Guide Wire
- 20 Ultraskin™ Hydrophilic Guide Wire CE FDA
- 21 Balancium Guide Wire CE

Introducer Sheaths

- 23 Shoocin™ Introducer Kit CE FDA
- 25 Brilliant™ Introducer Kit CE FDA

Accessories

- 27 Rayband™ Radial Artery Compression Tourniquet CE FDA
- 28 Angioway™ Y-Hemostasis Valve Set CE FDA
- 29 Angiopower™ Inflation Device CE FDA
- 30 Inflation Devices Kit CE FDA
- 31 Angioway™ Manifolds CE
- 32 Angioway™ High Pressure Extension Tubings CE
- 33 Introducer Needle CE
- 33 Angiospring™ Angiography Control Syringe CE
- 34 Contrast Medium Injection Manifold Kits CE

02

Neurovascular
Interventional Products

Vascular Protection

- 37 Disposable Embolic Protection Device CE

Embolization

- 38 Embolic Coil System CE

Microcatheter

- 39 Disposable Microcatheter CE

PTA Balloon

- 41 Supercross™ PTA Balloon Dilatation Catheters CE

03

Peripheral
Interventional Products

Occlusion Devices

- 45 MemoPart™ Atrial Septal Defect (ASD) Occluder CE
- 47 MemoPart™ Ventricular Septal Defect (VSD) Occluder CE
- 50 MemoPart™ Patent Ductus Arteriosus (PDA) Occluder CE
- 52 MemoPart™ Patent Foramen Ovale (PFO) Occluder CE
- 53 MemoPart™ Plug CE
- 54 MemoPart™ Occluder Delivery System CE
- 56 MemoPart™ Snare CE

Mechanical Heart Valve

- 57 GKS Bi-leaflet Prosthetic Heart Valve

04

Structural Heart Diseases
Products

Off-pump Coronary Artery Bypass Grafting

- 59 Disposable Tissue stabilizer

05

Surgical Cardiology
Products

06

Cardiac Rhythm Management Products

- Pacemakers and Leads
- 61

Implantable Single Chamber Pacemaker
- 62

Implantable Dual Chamber Pacemaker
- 63

Bipolar Passive Fixation Lead
- 64

Bipolar Active Fixation Lead

- Equipment
- 65

Dual Chamber Pacing System Programmer
- 66

Dual Chamber Pacing System Analyzer

07

Critical Care Products

- IV Catheters
- 69

Safecath™ Disposable Central Venous Catheter Kit
- 71

Antimicrobial Central Venous Catheter Kit

- Needle-free Connectors
- 73

Needle-free Connectors

- Blood Sampler
- 75

Disposable Arterial Blood Sampler

- Pressure Transducer
- 76

Disposable Blood Pressure Transducer

08

In Vitro Diagnostic Products

- IVD Equipment and Biomarkers
- 79

LEPU Quant 800 Colloidal Gold Immunochromatographic Assay Analyzer
- 79

Thrombelastography
- 80

Biomarkers

09

Digital Subtraction Angiography Systems

- Suspended Type
- 83

Vicor-CV300 Digital Subtraction Angiography System

- Floor Type
- 84

Vicor-CV100 Digital Subtraction Angiography System

10

General Surgery Products

- Surgical Staplers
- 87

Staplers
- 93

Disposable Skin Stapler and Remover
- 93

Disposable Purse String Stapler

- Accessories
- 94


Disposable Suction and Irrigation Tube
- 94

Disposable Trocar and Veress Needle
- 95

Disposable Endoscopic Retrieval Bags

01

Cardiovascular Interventional Products



Coronary Stents

- 07 Nano+™ Polymer-free Sirolimus-eluting Coronary Stent System
- 08 GuReater™ CoCr Sirolimus-eluting Coronary Stent System
- 09 Partner™ Sirolimus-eluting Coronary Stent System **CE**
- 10 H-Stent™ Coronary Stent System **CE**

PTCA Balloons

- 11 Hoper™ PTCA Balloon Dilatation Catheter **CE FDA**
- 12 Mini Tadpole™ Coronary Dilatation Catheter **CE**
- 13 Tadpole™ Coronary Dilatation Catheter **CE**
- 14 NC Tadpole™ Coronary Dilatation Catheter **CE**

Catheters

- 15 Orien™ Guiding Catheter **CE**
- 17 Thrombsweeper™ Thrombus Extraction Catheter
- 18 Deliver™ Infusion Catheter

Guide Wires

- 19 Angiographic Guide Wire
- 20 Ultraskin™ Hydrophilic Guide Wire **CE FDA**
- 21 Balancium Guide Wire **CE**

Introducer Sheaths


- 23 Shoocin™ Introducer Kit **CE FDA**
- 25 Brilliant™ Introducer Kit **CE FDA**

Accessories

- 27 Rayband™ Radial Artery Compression Tourniquet **CE FDA**
- 28 Angiway™ Y-Hemostasis Valve Set **CE FDA**
- 29 Angiopower™ Inflation Device **CE FDA**
- 30 Inflation Devices Kit **CE FDA**
- 31 Angiway™ Manifolds **CE**
- 32 Angiway™ High Pressure Extension Tubings **CE**
- 33 Introducer Needle **CE**
- 33 Angiospring™ Angiography Control Syringe **CE**
- 34 Contrast Medium Injection Manifold Kits **CE**

Nano+™

Polymer-free
Sirolimus-eluting
Coronary Stent System



The efficacy of DES

- Nanoporous cavities on strut abluminal surface functioning as drug carrier to ensure the firm adhesion.
- Post-treatment after drug loading helps with sustained drug release.
- Scientific drug releasing period effectively inhibits SMC migration and proliferation.

The safety of BMS

- Polymer-free design significantly reduces the inflammatory response after stent implantation compare to polymer coating stent, which guarantees the long-term safety.
- Polymer-free design facilitates earlier endothelialization which shorten the DAPT time.
- The rough strut surface helps with easier and faster endothelialization to reduce the risk of thrombosis.

New delivery system

- Soft tapered tip provides smooth transition from guidewire to balloon catheter and excellent crossability.
- Short shoulder design at both ends of the balloon reduces the damage to normal vessel next to the lesion.
- Patented hydrophilic coating on distal shaft provides outstanding pushability.

Technical Parameters

Stent Material	316L Stainless Steel
Strut Design	Open cell
Metal to Artery Ratio	15%
Recoil	< 2%
Shortening	< 1%
Crossing Profile	0.035"(0.90mm)

Ordering Information

Stent Diameter (mm)	Stent Length (mm)						
	12	15	18	21	24	29	36
2.5	LPRPS2512	LPRPS2515	LPRPS2518	LPRPS2521	LPRPS2524	LPRPS2529	LPRPS2536
2.75	LPRPS2712	LPRPS2715	LPRPS2718	LPRPS2721	LPRPS2724	LPRPS2729	LPRPS2736
3.0	LPRPS3012	LPRPS3015	LPRPS3018	LPRPS3021	LPRPS3024	LPRPS3029	LPRPS3036
3.5	LPRPS3512	LPRPS3515	LPRPS3518	LPRPS3521	LPRPS3524	LPRPS3529	LPRPS3536
4.0	LPRPS4012	LPRPS4015	LPRPS4018	LPRPS4021	LPRPS4024	LPRPS4029	LPRPS4036

GuReater™

CoCr
Sirolimus-eluting
Coronary Stent System



- 75 μm ultrathin strut thickness and unique strut structure guarantee the excellent compliance of the stent during delivery.
- PLGA biodegradable polymer coating provides precise drug releasing control and scientific degradation period.
- CoCr stent has great radiopacity, biocompatibility, and provides excellent balance between radial strength and flexibility.
- MRI compatible

Technical Parameters

Stent Material	L605 CoCr Alloy
Strut Design	Open cell
Metal to Artery Ratio	15%
Recoil	3.4%
Shortening	< 1%
Crossing Profile	0.035" (0.90mm)

Ordering Information

Stent Diameter (mm)	Stent Length (mm)							
	12	15	18	21	24	29	33	36
2.5	LPRPC 2512	LPRPC 2515	LPRPC 2518	LPRPC 2521	LPRPC 2524	LPRPC 2529	/	/
	LPRPC 2712	LPRPC 2715	LPRPC 2718	LPRPC 2721	LPRPC 2724	LPRPC 2729	/	/
3.0	LPRPC 3012	LPRPC 3015	LPRPC 3018	LPRPC 3021	LPRPC 3024	LPRPC 3029	LPRPC 3033	LPRPC 3036
	LPRPC 3512	LPRPC 3515	LPRPC 3518	LPRPC 3521	LPRPC 3524	LPRPC 3529	LPRPC 3533	LPRPC 3536
4.0	LPRPC 4012	LPRPC 4015	LPRPC 4018	LPRPC 4021	LPRPC 4024	LPRPC 4029	LPRPC 4033	LPRPC 4036

Notice: Please contact the sales for detailed information before placing the order.

Partner™
Sirolimus-eluting
Coronary Stent System

CE



- PBMA/PEVA double layer polymer coating provides optimal drug releasing control.
- Scientific drug releasing period effectively inhibits SMC migration and proliferation.
- The thickness of polymer coating is only 6µm, which ensures the good deliverability.
- Optimal strut thickness provides favorable balance between radial strength and easier endothelialization.
- Large open cell design allows of excellent side branch access.

Technical Parameters


Stent Material	316L Stainless Steel
Strut Design	Open cell
Metal to Artery Ratio	15%
Recoil	< 2%
Shortening	< 1%
Crossing Profile	0.90mm (0.035")

Ordering Information

Stent Diameter (mm)	Stent Length (mm)							
	12	15	18	21	24	29	33	36
2.5	LPRP 2512	LPRP 2515	LPRP 2518	LPRP 2521	LPRP 2524	LPRP 2529	LPRP 2533	LPRP 2536
2.75	LPRP 2712	LPRP 2715	LPRP 2718	LPRP 2721	LPRP 2724	LPRP 2729	LPRP 2733	LPRP 2736
3.0	LPRP 3012	LPRP 3015	LPRP 3018	LPRP 3021	LPRP 3024	LPRP 3029	LPRP 3033	LPRP 3036
3.5	LPRP 3512	LPRP 3515	LPRP 3518	LPRP 3521	LPRP 3524	LPRP 3529	LPRP 3533	LPRP 3536
4.0	LPRP 4012	LPRP 4015	LPRP 4018	LPRP 4021	LPRP 4024	LPRP 4029	LPRP 4033	LPRP 4036

H-Stent™
Coronary Stent
System

CE



- Optimal strut thickness provides favorable balance between radial strength and deliverability.
- Patented double-helix structure design ensures outstanding flexibility and compliance.
- Large open cell design allows of excellent side branch access.

Technical Parameters

Stent Material	316L Stainless Steel
Strut Design	Open cell
Metal to Artery Ratio	15%-18%
Recoil	< 2%
Shortening	< 1%
Strut Thickness	85µm (0.0033")
Crossing Profile	0.90mm (0.035")

Ordering Information

Stent Diameter (mm)	Stent Length (mm)													
	9	12	14*	15*	16	18*	20	21*	22*	24	27*	29	33*	36*
2.5	LPCSRX 2509	LPCSRX 2512	LPCSRX 2514	LPCSRX 2515	LPCSRX 2516	LPCSRX 2518	LPCSRX 2520	LPCSRX 2521	LPCSRX 2522	LPCSRX 2524	LPCSRX 2527	LPCSRX 2529	LPCSRX 2533	LPCSRX 2536
2.75	LPCSRX 2709	LPCSRX 2712	LPCSRX 2714	LPCSRX 2715	LPCSRX 2716	LPCSRX 2718	LPCSRX 2720	LPCSRX 2721	LPCSRX 2722	LPCSRX 2724	LPCSRX 2727	LPCSRX 2729	LPCSRX 2733	LPCSRX 2736
3.0	LPCSRX 3009	LPCSRX 3012	LPCSRX 3014	LPCSRX 3015	LPCSRX 3016	LPCSRX 3018	LPCSRX 3020	LPCSRX 3021	LPCSRX 3022	LPCSRX 3024	LPCSRX 3027	LPCSRX 3029	LPCSRX 3033	LPCSRX 3036
3.5	/	LPCSRX 3512	LPCSRX 3514	LPCSRX 3515	LPCSRX 3516	LPCSRX 3518	LPCSRX 3520	LPCSRX 3521	LPCSRX 3522	LPCSRX 3524	LPCSRX 3527	LPCSRX 3529	LPCSRX 3533	LPCSRX 3536
4.0	/	LPCSRX 4012	LPCSRX 4014	LPCSRX 4015	LPCSRX 4016	LPCSRX 4018	LPCSRX 4020	LPCSRX 4021	LPCSRX 4022	LPCSRX 4024	LPCSRX 4027	LPCSRX 4029	LPCSRX 4033	LPCSRX 4036

Notice: The sizes with *mark require a minimum quantity of 10 pcs per order. Please contact the sales for detailed information before placing the order.

Hoper™
PTCA Balloon
Dilatation Catheter



- Small tip profile for excellent crossability.
- Three-directional memory folding of the balloon allows of size minimization with great withdrawal capability, and ensures the good performance of repeated dilatation.
- Soft tapered tip provides smooth transition from guidewire to balloon catheter to avoid “fish mouth”, and minimize the vessel damage.
- Transparent hub is convenient to observe the air bubble to reduce the operation risk.

Technical Parameters

Material	Nylon
Catheter Design	Rapid Exchange
Balloon Compliance	Semi-compliant
Marker	2
Distal Shaft O.D.	2.8F
Proximal Shaft O.D.	2.3F
Tip Profile	0.017"
Minimum Guiding Catheter Compatibility	5F (0.056")
Guide Wire Compatibility	0.014"
Effective Length	135cm
Nominal Pressure	8 atm (φ1.5mm-3.0mm) / 6 atm (φ3.5mm-4.0mm)
Rated Burst Pressure	16 atm (φ1.5mm-3.5mm) / 14 atm (φ4.0mm)

Ordering Information

Balloon Diameter (mm)	Balloon Length (mm)										
	9	11*	12	14*	16	18	20	22*	24	26*	30
1.5	LPRX	/	LPRX	LPRX	LPRX	LPRX	LPRX	LPRX	LPRX	LPRX	LPRX
	15009		15012	15014	15016	15018	15020	15022	15024	15026	15030
1.75	LPRX	/	LPRX	LPRX	LPRX	LPRX	LPRX	LPRX	LPRX	LPRX	LPRX
	17009		17012	17014	17016	17018	17020	17022	17024	17026	17030
2.0	LPRX	/	LPRX	LPRX	LPRX	LPRX	LPRX	LPRX	LPRX	LPRX	LPRX
	20009		20012	20014	20016	20018	20020	20022	20024	20026	20030
2.5	LPRX	LPRX	LPRX	LPRX	LPRX	LPRX	LPRX	LPRX	LPRX	LPRX	LPRX
	25009	25011	25012	25014	25016	25018	25020	25022	25024	25026	25030
2.75	LPRX	LPRX	LPRX	LPRX	LPRX	LPRX	LPRX	LPRX	LPRX	LPRX	LPRX
	27009	27011	27012	27014	27016	27018	27020	27022	27024	27026	27030
3.0	LPRX	LPRX	LPRX	LPRX	LPRX	LPRX	LPRX	LPRX	LPRX	LPRX	LPRX
	30009	30011	30012	30014	30016	30018	30020	30022	30024	30026	30030
3.5	LPRX	LPRX	LPRX	LPRX	LPRX	LPRX	LPRX	LPRX	LPRX	LPRX	LPRX
	35009	35011	35012	35014	35016	35018	35020	35022	35024	35026	35030
4.0	LPRX	LPRX	LPRX	LPRX	LPRX	LPRX	LPRX	LPRX	LPRX	LPRX	LPRX
	40009	40011	40012	40014	40016	40018	40020	40022	40024	40026	40030

Notice: The sizes with * mark require a minimum quantity of 10 pcs per order. Please contact the sales for detailed information before placing the order.

Mini Tadpole™
Coronary Dilatation
Catheter



- Small tip and crossing profiles ensure the better performance for CTO lesions.
- Capable for kissing balloon under 6F guiding catheter.
- Patented hydrophilic coating on distal shaft and Hypotube proximal shaft provide outstanding deliverability.
- Three-directional memory folding of the balloon allows of size minimization with great withdrawal capability, and ensures the good performance of repeated dilatation.
- Soft tapered tip provides smooth transition from guidewire to balloon catheter to avoid “fish mouth”, and minimize the vessel damage.
- Short shoulder design at both ends of the balloon ensures the precise dilatation, and reduces the damage to normal vessel next to the lesion.

Technical Parameters

Material	Pebax
Catheter Design	Rapid Exchange
Balloon Compliance	Semi-compliant
Marker	2
Distal Shaft O.D.	2.6F
Proximal Shaft O.D.	1.9F
Tip Profile	0.017"
Minimum Guiding Catheter Compatibility	5F (0.056")
Guide Wire Compatibility	0.014"
Effective Length	142cm
Nominal Pressure	8 atm
Rated Burst Pressure	16 atm

Ordering Information


Balloon Diameter (mm)	Balloon Length (mm)						
	8	10	12	15	20	25	30
1.5	LPMRX	LPMRX	LPMRX	LPMRX	/	LPMRX	/
	15008	15010	15012	15015		15025	
1.75	/	/	LPMRX	/	LPMRX	/	LPMRX
			17012		17020		17030
2.0	LPMRX	LPMRX	LPMRX	LPMRX	LPMRX	LPMRX	/
	20008	20010	20012	20015	20020	20025	

Notice: Please contact the sales for detailed information before placing the order.

Tadpole 可以生产的规格长度为国内长度，与 CE 长度有出入，国内长度不包含 8mm/10mm/15mm/25mm。
国内生产长度与 CE 不匹配的包括：9mm/16mm/24mm。
球囊生产存在 ±1mm 误差，所以 CE 规格中 8mm, 10mm 可以用 9mm 往上靠，15mm 可以用 16mm 往上靠，25mm 可以用 24mm 往上靠。
各位销售请务必将此情况与客户说明，并征得生产质量与客户同意后再引导客户下单。
现保留规格为可生产及有模具的规格，但以万一还需与生产确认好再下单。

Tadpole™
Coronary Dilatation
Catheter

CE



- Outstanding performance for kissing balloon under 6F guiding catheter.
- Patented hydrophilic coating on distal shaft and Hypotube proximal shaft provide outstanding deliverability.
- Three-directional memory folding of the balloon allows of size minimization with great withdrawal capability, and ensures the good performance of repeated dilatation.
- Soft tapered tip provides smooth transition from guidewire to balloon catheter to avoid “fish mouth”, and minimize the vessel damage.
- Short shoulder design at both ends of the balloon ensures the precise dilatation, and reduces the damage to normal vessel next to the lesion.

Technical Parameters

Material	Pebax
Catheter Design	Rapid Exchange
Balloon Compliance	Semi-compliant
Marker	2
Distal Shaft O.D.	2.6F
Proximal Shaft O.D.	1.9F
Tip Profile	0.017”
Minimum Guiding Catheter Compatibility	5F (0.056”)
Guide Wire Compatibility	0.014”
Effective Length	142cm
Nominal Pressure	8 atm (φ2.25mm-3.0mm) / 6 atm (φ3.5mm-4.0mm)
Rated Burst Pressure	16 atm (φ2.25mm-3.5mm) / 14 atm (φ4.0mm)

Ordering Information

Balloon Diameter (mm)							
	8	10	12	15	20	25	30
2.5	/	/	LPCR 25012	LPCR 25015	LPCR 25020	LPCR 25025	LPCR 25030
2.75	LPCR 27008	LPCR 27010	LPCR 27012	LPCR 27015	LPCR 27020	LPCR 27025	LPCR 27030
3.0	LPCR 30008	LPCR 30010	LPCR 30012	LPCR 30015	LPCR 30020	LPCR 30025	LPCR 30030
3.5*	LPCR 35008	LPCR 35010	/	LPCR 35015	LPCR 35020	LPCR 35025	LPCR 35030
4.0	LPCR 40008	LPCR 40010	LPCR 40012	LPCR 40015	LPCR 40020	/	LPCR 40030

* Notice: Please contact the sales for detailed information before placing the order.

Tadpole 可以生产的规格长度为国内长度，与 CE 长度有出入，国内长度不包含 8mm/10mm/15mm/25mm。国内生产长度与 CE 不匹配的包括：9mm/16mm/24mm。球囊生产存在 ±1mm 误差，所以 CE 规格中 8mm, 10mm 可以用 9mm 往上靠，15mm 可以用 16mm 往上靠，25mm 可以用 24mm 往上靠。各位销售请务必将此情况与客户说明，并征得生产质量与客户的同意后再引导客户下单。现保留规格为可生产及有模具的规格，但以万一还需与生产确认好再下单。3.5 的规格有模具，但生产暂时说不可生产。

NC Tadpole™
Coronary Dilatation
Catheter

CE



- Strong radial strength with high RBP (22 atm) contributes to excellent stent apposition for post-dilatation.
- Patented hydrophilic coating on distal shaft provides outstanding deliverability.
- Three-directional memory folding of the balloon allows of size minimization with great withdrawal capability, and ensures the good performance of repeated dilatation.
- Soft tapered tip provides smooth transition from guidewire to balloon catheter to avoid “fish mouth”, and minimize the vessel damage.
- Short shoulder design at both ends of the balloon ensures the precise dilatation, and reduces the damage to normal vessel next to the lesion.

Technical Parameters

Material	Nylon
Catheter Design	Rapid Exchange
Balloon Compliance	Non-compliant
Marker	2
Distal Shaft O.D.	2.7F
Proximal Shaft O.D.	2.3F
Tip Profile	0.018”
Minimum Guiding Catheter Compatibility	5F (0.056”)
Guide Wire Compatibility	0.014”
Effective Length	135cm
Nominal Pressure	14 atm
Rated Burst Pressure	22 atm


Ordering Information

Balloon Diameter (mm)	Balloon Length (mm)							
	6	8	10	12	15	20	25	30
1.5	LPNRX15006	LPNRX15008	LPNRX15010	LPNRX15012	LPNRX15015	LPNRX15020	LPNRX15025*	LPNRX15030*
2.0	LPNRX20006	LPNRX20008	LPNRX20010	LPNRX20012	LPNRX20015	LPNRX20020	LPNRX20025	LPNRX20030
2.25	LPNRX22006	LPNRX22008	LPNRX22010	LPNRX22012	LPNRX22015	LPNRX22020	LPNRX22025	LPNRX22030
2.5	LPNRX25006	LPNRX25008	LPNRX25010	LPNRX25012	LPNRX25015	LPNRX25020	LPNRX25025	LPNRX25030
2.75	LPNRX27006	LPNRX27008	LPNRX27010	LPNRX27012	LPNRX27015	LPNRX27020	LPNRX27025	LPNRX27030
3.0	LPNRX30006	LPNRX30008	LPNRX30010	LPNRX30012	LPNRX30015	LPNRX30020	LPNRX30025	LPNRX30030
3.25	LPNRX32006	LPNRX32008	LPNRX32010	LPNRX32012	LPNRX32015	LPNRX32020	LPNRX32025	LPNRX32030
3.5	LPNRX35006	LPNRX35008	LPNRX35010	LPNRX35012	LPNRX35015	LPNRX35020	LPNRX35025	LPNRX35030
3.75	LPNRX37006	LPNRX37008	LPNRX37010	LPNRX37012	LPNRX37015	LPNRX37020	LPNRX37025	LPNRX37030
4.0	LPNRX40006	LPNRX40008	LPNRX40010	LPNRX40012	LPNRX40015	LPNRX40020	LPNRX40025	LPNRX40030
4.5	LPNRX45006*	LPNRX45008	LPNRX45010	LPNRX45012	LPNRX45015	LPNRX45020	LPNRX45025*	LPNRX45030*

* Notice: Please contact the sales for detailed information before placing the order.

* 标规格为有模具，但不一定能生产的规格，需确认。


Orien™
Guiding Catheter
CE



- Flat wire braided middle layer offers outstanding flexibility and excellent kink resistance.
- 1:1 torque for easy operation and accurate placement.
- Robust secondary curve provides great backup support and curve retention.
- Soft and flexible tip minimize the damage to the vessel wall.
- PTFE internal wall provides smooth lumen to ensure the excellent trackability.
- Large lumen guarantees the good performance for kissing balloon.

Ordering Information


Right Coronary Curves						
Curve Type	Catalogue No.	Distal End Shape	Catheter O.D.	Catheter I.D.	Length (cm)	
Judkins Right	CL5JR35	JR 3.5	5F	0.056"	100	 JR
	CL5JR40	JR 4.0				
	CL5JR45	JR 4.5				
	CL5JR50	JR 5.0				
	CL6JR35	JR 3.5	6F	0.071"		
	CL6JR40	JR 4.0				
	CL6JR45	JR 4.5				
	CL6JR50	JR 5.0				
	CL7JR35	JR 3.5	7F	0.078"		
	CL7JR40	JR 4.0				
CL7JR45	JR 4.5					
CL7JR50	JR 5.0					
Amplatz Right	CL5AR10	AR 1.0	5F	0.056"	100	 AR
	CL5AR20	AR 2.0				
	CL6AR10	AR 1.0	6F	0.071"		
	CL6AR20	AR 2.0				
	CL7AR10	AR 1.0	7F	0.078"		
	CL7AR20	AR 2.0				

Left Coronary Curves						
Curve Type	Catalogue No.	Distal End Shape	Catheter O.D.	Catheter I.D.	Length (cm)	
Judkins Left	CL5JL35	JL 3.5	5F	0.056"	100	
	CL5JL40	JL 4.0				
	CL5JL45*	JL 4.5				
	CL5JL50*	JL 5.0				
	CL6JL35	JL 3.5	6F	0.071"		
	CL6JL40	JL 4.0				
	CL6JL45*	JL 4.5				
	CL6JL50*	JL 5.0				
	CL7JL35	JL 3.5	7F	0.078"		
	CL7JL40	JL 4.0				
CL7JL45*	JL 4.5					
CL7JL50*	JL 5.0					
Amplatz Left	CL5AL075	AL 0.75	5F	0.056"	100	
	CL5AL10	AL 1.0				
	CL5AL20	AL 2.0				
	CL6AL075	AL 0.75	6F	0.071"		
	CL6AL10	AL 1.0				
	CL6AL20	AL 2.0				
	CL7AL075	AL 0.75	7F	0.078"		
	CL7AL10	AL 1.0				
	CL7AL20	AL 2.0				
Extra Backup	CL5XB30	XB 3.0	5F	0.056"	100	
	CL5XB35	XB 3.5				
	CL5XB40	XB 4.0				
	CL6XB30	XB 3.0				
	CL6XB35	XB 3.5	6F	0.071"		
	CL6XB40	XB 4.0				
	CL6XBC35	XBC 3.5				
	CL6XBLAD35	XBLAD 3.5				
	CL7XB30	XB 3.0	7F	0.078"		
	CL7XB35	XB 3.5				
CL7XB40	XB 4.0					
CL7XBLAD35	XBLAD 3.5					

* Notice: Please contact the sales for detailed information before placing the order. More CE and OEM distal shapes are available. Guiding catheter with hydrophilic coating is available.
* 标规格为有模具，但不一定能生产的规格，需确认。

Thromsweeper™

Thrombus Extraction
Catheter



- Large suction lumen minimizes the flow resistance and boosts the extraction performance.
- Low crossing profile is designed for the compatibility with the smallest 6F guiding catheter.
- Hydrophilic coating on distal shaft provides great crossability and deliverability.
- Embedded Platinum marker empowers smooth-feeling of delivery and visualization.
- Removable support-wire helps rapidly and easily reach to the lesion.

Technical Parameters

Design	Rapid Exchange	
Guiding Catheter Compatibility (minimum)	6F (0.070")	
Guide Wire Compatibility	0.014"	
Effective Length	1450mm	
Extraction Lumen Area	1.03mm²	
Guide wire Lumen Length	113mm	
Catheter O.D.	Proximal	1.27mm
	Distal	1.50mm

Ordering Information

Catalogue No.	Specification
XS500001	150

Notice: Please contact the sales for detailed information before placing the order.

Deliver™

Infusion Catheter



- Combined liquid perfusion lumen and guide wire lumen fulfills the perfusion to target lesion without withdrawing the guide wire.
- Rapid exchange design, convenient for operation.
- Pt-Ir marker provides excellent visibility under X-ray.

Technical Parameters

Material	Stainless steel filmed with Nylon
Marker	Pt-Ir Alloy
Tip O.D.	1.5F (0.50mm)
Distal O.D.	3.3F (1.09mm)
Proximal O.D.	3.1F (1.03mm)
Guide Wire Lumen I.D.	0.015" (0.38mm)
Effective Length	1390mm
Guiding Catheter Compatibility	5F/ 6F/ 7F
Guide Wire Compatibility	0.014"

Ordering Information

Catalogue No.	LPRX139
---------------	---------

Notice: Please contact the sales for detailed information before placing the order.

Angiographic
Guide Wire



- Stainless steel core wire offers excellent torque transmission and kink resistance.
- Over-the-wire coil offers outstanding deliverability and radiopacity.

Ordering Information

Catalogue No.	Tip Shape	Outer Diameter	Length (cm)	Type
MMNSF35150	Straight	0.035"	150	Teflon coating, coiled
MMNSF35260	Straight	0.035"	260	Teflon coating, coiled
MMNJF35150	J	0.035"	150	Teflon coating, coiled
MMNJF35260	J	0.035"	260	Teflon coating, coiled
MMNSF38150	Straight	0.038"	150	Teflon coating, coiled
MMNSF38260	Straight	0.038"	260	Teflon coating, coiled
MMNJF38150	J	0.038"	150	Teflon coating, coiled
MMNJF38260	J	0.038"	260	Teflon coating, coiled

Notice: Please contact the sales for detailed information before placing the order.
外购产品，下单前请先与生产采购确认好。

Ultraskin™
Hydrophilic Guide Wire
CE FDA



- Nitinol core wire guarantees great tip shape retention, outstanding kink resistance and 1:1 torque control.
- PU Jacket incorporated with tungsten provides highly radiopacity.
- Super smooth hydrophilic coating reduces friction, and provides excellent navigation in and out the catheter.
- Soft tapered tip increases distal flexibility, contributes to smooth vessel insertion, and minimizes the risk of trauma.

Ordering Information

Catalogue No.	Outer Diameter	Guide Wire Length (cm)	Distal Curve	Note
SD-S18150	0.018"	150	Straight	Standard
SD-A18150	0.018"	150	135° Angled	Standard
SD-S32150	0.032"	150	Straight	Standard
SD-A32150	0.032"	150	135° Angled	Standard
SD-S32180	0.032"	180	Straight	Standard
SD-A32180	0.032"	180	135° Angled	Standard
SD-S32260	0.032"	260	Straight	Standard
SD-A32260	0.032"	260	135° Angled	Standard
SD-S35150	0.035"	150	Straight	Standard
SD-A35150	0.035"	150	135° Angled	Standard
SD-S35180	0.035"	180	Straight	Standard
SD-A35180	0.035"	180	135° Angled	Standard
SD-S35260	0.035"	260	Straight	Standard
SD-A35260	0.035"	260	135° Angled	Standard
SP-S35150	0.035"	150	Straight	Reshapable Tip
SP-A35150	0.035"	150	135° Angled	Reshapable Tip
SP-S35180	0.035"	180	Straight	Reshapable Tip
SP-A35180	0.035"	180	135° Angled	Reshapable Tip
ST-S35150	0.035"	150	Straight	Stiff Shaft
ST-A35150	0.035"	150	135° Angled	Stiff Shaft

Balancium

Guide Wire



Two Types of Core Design for Different Clinical Needs

- **Core-to-Tip** design provides great tip stiffness, good touch feedback and moderate support for easy control and better crossability and accessibility.
- **Shaping Ribbon** design provides softer tip stiffness for minimized damage to the vessels, and outstanding tip shaping flexibility and stability for easy navigation.
- Nitinol + stainless steel cores provide superior flexibility and durability, improves the torque response.
- 3cm Platinum coil at distal tip provides excellent radiopacity.
- A hydrophilic coating is applied to the 30cm coiled distal end to increase the crossability and deliverability.
- PTFE coating on middle and proximal parts reduces friction, and improves pushability and catheter trackability.

Core-to-Tip



Shaping Ribbon




Ordering Information

Core-to-Tip						
Catalogue No.	Outer Diameter	Length (cm)	Tip Flexibility	Tip Shape	Core Material	Radial Support
GW B185-0	0.014"	185	Floppy (0.6g)	Straight	NiTi + SS	Moderate
GW B185-0J	0.014"	185	Floppy (0.6g)	J	NiTi + SS	Moderate
GW B300-0	0.014"	300	Floppy (0.6g)	Straight	NiTi + SS	Moderate
GW B300-0J	0.014"	300	Floppy (0.6g)	J	NiTi + SS	Moderate
GW B185-1	0.014"	185	Super soft (1g)	Straight	NiTi + SS	Moderate
GW B185-1J	0.014"	185	Super soft (1g)	J	NiTi + SS	Moderate
GW B300-1	0.014"	300	Super soft (1g)	Straight	NiTi + SS	Moderate
GW B300-1J	0.014"	300	Super soft (1g)	J	NiTi + SS	Moderate
GW B185-2	0.014"	185	Soft (2g)	Straight	NiTi + SS	Moderate
GW B185-2J	0.014"	185	Soft (2g)	J	NiTi + SS	Moderate
GW B300-2	0.014"	300	Soft (2g)	Straight	NiTi + SS	Moderate
GW B300-2J	0.014"	300	Soft (2g)	J	NiTi + SS	Moderate

Shaping Ribbon						
Catalogue No.	Outer Diameter	Length (cm)	Tip Flexibility	Tip Shape	Core Material	Radial Support
GW B185-S0	0.014"	185	Floppy (0.6g)	Straight	NiTi + SS	Moderate
GW B185-S0J	0.014"	185	Floppy (0.6g)	J	NiTi + SS	Moderate
GW B300-S0	0.014"	300	Floppy (0.6g)	Straight	NiTi + SS	Moderate
GW B300-S0J	0.014"	300	Floppy (0.6g)	J	NiTi + SS	Moderate
GW B185-S1	0.014"	185	Super soft (1g)	Straight	NiTi + SS	Moderate
GW B185-S1J	0.014"	185	Super soft (1g)	J	NiTi + SS	Moderate
GW B300-S1	0.014"	300	Super soft (1g)	Straight	NiTi + SS	Moderate
GW B300-S1J	0.014"	300	Super soft (1g)	J	NiTi + SS	Moderate
GW B185-S2	0.014"	185	Soft (2g)	Straight	NiTi + SS	Moderate
GW B185-S2J	0.014"	185	Soft (2g)	J	NiTi + SS	Moderate
GW B300-S2	0.014"	300	Soft (2g)	Straight	NiTi + SS	Moderate
GW B300-S2J	0.014"	300	Soft (2g)	J	NiTi + SS	Moderate

Shoocin™
Introducer Kit
CE FDA

Standard Type (Radial / Femoral / Long Sheaths)



- Advanced material improves bendability and flexibility without gapping or kinking.
- Special designed lock and silicon hemostatic valve provide outstanding hemostatic function, while guaranteeing the operational ability for the catheter.
- Smooth tapered tip helps with easy access to the artery, reducing trauma to patients.
- Smooth transition from dilator to sheath greatly reduces puncture resistance, providing easy and non-traumatic insertion.
- Minimized possibility of damaging tissue upon sheath entry, advancement and withdrawal, providing smoother and easier vascular access even through difficult access sites.

Full kit includes:

- Introducer Sheath (1)
- Dilator (1)
- Stainless Steel Guide Wire (1)
- Introducer Needle (1)
- Scalpel (1)
- Syringe (1)

The Introducer Kit can be customized by:

- Remove the every single component includes guide wire, introducer needle (IN), scalpel (K) and syringe (S).
- Replace the stainless steel guide wire (straight SS/J tip SJ) into hydrophilic guide wire (straight HS/135° angled HW) or nitinol guide wire (straight NS/J tip NJ).
- Replace the introducer needle (IN) into intravascular catheter (IC). Intravascular catheter is mandatory to be a set with hydrophilic guide wire.

Please contact the sales for more information about the selections of customized kit.

Ordering Information*

Long Sheath								
Catalogue No. (Stainless Steel Guide Wire)	Sheath I.D.	Sheath Length	Guide Wire Diameter	Guide Wire Length	Introducer Needle	Scalpel	Syringe	
LS061638-SJ80-IN18-K-S	6F	16cm	0.038"	80cm	18G	1	1	
LS062338-SJ80-IN18-K-S	6F	23cm	0.038"	80cm	18G	1	1	
LS071638-SJ80-IN18-K-S	7F	16cm	0.038"	80cm	18G	1	1	
LS072338-SJ80-IN18-K-S	7F	23cm	0.038"	80cm	18G	1	1	
LS081638-SJ80-IN18-K-S	8F	16cm	0.038"	80cm	18G	1	1	
LS082338-SJ80-IN18-K-S	8F	23cm	0.038"	80cm	18G	1	1	

Radial Sheath								
Catalogue No. (Stainless Steel Guide Wire)	Sheath I.D.	Sheath Length	Guide Wire Diameter	Guide Wire Length	Introducer Needle	Scalpel	Syringe	
RS040518-SS45-IN20-K-S	4F	5cm	0.018"	45cm	20G	1	1	
RS040521-SS45-IN20-K-S	4F	5cm	0.021"	45cm	20G	1	1	
RS040525-SS45-IN20-K-S	4F	5cm	0.025"	45cm	20G	1	1	
RS040718-SS45-IN20-K-S	4F	7cm	0.018"	45cm	20G	1	1	
RS040721-SS45-IN20-K-S	4F	7cm	0.021"	45cm	20G	1	1	
RS040725-SS45-IN20-K-S	4F	7cm	0.025"	45cm	20G	1	1	
RS050518-SS45-IN20-K-S	5F	5cm	0.018"	45cm	20G	1	1	
RS050521-SS45-IN20-K-S	5F	5cm	0.021"	45cm	20G	1	1	
RS050525-SS45-IN20-K-S	5F	5cm	0.025"	45cm	20G	1	1	
RS050718-SS45-IN20-K-S	5F	7cm	0.018"	45cm	20G	1	1	
RS050721-SS45-IN20-K-S	5F	7cm	0.021"	45cm	20G	1	1	
RS050725-SS45-IN20-K-S	5F	7cm	0.025"	45cm	20G	1	1	
RS060518-SS45-IN20-K-S	6F	5cm	0.018"	45cm	20G	1	1	
RS060521-SS45-IN20-K-S	6F	5cm	0.021"	45cm	20G	1	1	
RS060525-SS45-IN20-K-S	6F	5cm	0.025"	45cm	20G	1	1	
RS060718-SS45-IN20-K-S	6F	7cm	0.018"	45cm	20G	1	1	
RS060721-SS45-IN20-K-S	6F	7cm	0.021"	45cm	20G	1	1	
RS060725-SS45-IN20-K-S	6F	7cm	0.025"	45cm	20G	1	1	
RS041121-SS45-IN20-K-S	4F	11cm	0.021"	45cm	20G	1	1	
RS042421-SS70-IN20-K-S	4F	24cm	0.021"	70cm	20G	1	1	
RS051121-SS45-IN20-K-S	5F	11cm	0.021"	45cm	20G	1	1	
RS052421-SS70-IN20-K-S	5F	24cm	0.021"	70cm	20G	1	1	
RS061121-SS45-IN20-K-S	6F	11cm	0.021"	45cm	20G	1	1	
RS062421-SS70-IN20-K-S	6F	24cm	0.021"	70cm	20G	1	1	
RS070521-SS45-IN20-K-S	7F	5cm	0.021"	45cm	20G	1	1	
RS070521-SS70-IN20-K-S	7F	5cm	0.021"	70cm	20G	1	1	
RS071121-SS45-IN20-K-S	7F	11cm	0.021"	45cm	20G	1	1	
RS072421-SS70-IN20-K-S	7F	24cm	0.021"	70cm	20G	1	1	
RS070718-SS45-IN20-K-S	7F	7cm	0.018"	45cm	20G	1	1	
RS070718-SS70-IN20-K-S	7F	7cm	0.018"	70cm	20G	1	1	
RS071118-SS45-IN20-K-S	7F	11cm	0.018"	45cm	20G	1	1	
RS071118-SS70-IN20-K-S	7F	11cm	0.018"	70cm	20G	1	1	

Femoral Sheath								
Catalogue No. (Stainless Steel Guide Wire)	Sheath I.D.	Sheath Length	Guide Wire Diameter	Guide Wire Length	Introducer Needle	Scalpel	Syringe	
FS040525-SS45-IN20-K-S	4F	5cm	0.025"	45cm	20G	1	1	
FS041125-SS45-IN20-K-S	4F	11cm	0.025"	45cm	20G	1	1	
FS041135-SJ45-IN18-K-S	4F	11cm	0.035"	45cm	18G	1	1	
FS050535-SJ45-IN18-K-S	5F	5cm	0.035"	45cm	18G	1	1	
FS050538-SJ45-IN18-K-S	5F	5cm	0.038"	45cm	18G	1	1	
FS051135-SJ45-IN18-K-S	5F	11cm	0.035"	45cm	18G	1	1	
FS051138-SJ45-IN18-K-S	5F	11cm	0.038"	45cm	18G	1	1	
FS060535-SJ45-IN18-K-S	6F	5cm	0.035"	45cm	18G	1	1	
FS060538-SJ45-IN18-K-S	6F	5cm	0.038"	45cm	18G	1	1	
FS061135-SJ45-IN18-K-S	6F	11cm	0.035"	45cm	18G	1	1	
FS061138-SJ45-IN18-K-S	6F	11cm	0.038"	45cm	18G	1	1	
FS070535-SJ45-IN18-K-S	7F	5cm	0.035"	45cm	18G	1	1	
FS070538-SJ45-IN18-K-S	7F	5cm	0.038"	45cm	18G	1	1	
FS071135-SJ45-IN18-K-S	7F	11cm	0.035"	45cm	18G	1	1	
FS071138-SJ45-IN18-K-S	7F	11cm	0.038"	45cm	18G	1	1	
FS080535-SJ45-IN18-K-S	8F	5cm	0.035"	45cm	18G	1	1	
FS080538-SJ45-IN18-K-S	8F	5cm	0.038"	45cm	18G	1	1	
FS081135-SJ45-IN18-K-S	8F	11cm	0.035"	45cm	18G	1	1	
FS081138-SJ45-IN18-K-S	8F	11cm	0.038"	45cm	18G	1	1	
FS090538-SJ45-IN18-K-S	9F	5cm	0.038"	45cm	18G	1	1	
FS091138-SJ45-IN18-K-S	9F	11cm	0.038"	45cm	18G	1	1	

* The Yellow Marks indicate the components which can be customized as mentioned before.
(e.g. radial sheath/6F/7cm, 0.021" straight stainless steel guide wire/45cm, 20G introducer needle, without scalpel and syringe: RS060721-SS45-IN20)

Please contact the sales for detailed catalogue numbers of customized kits.

Brilliant™
Introducer Kit
CE FDA

Advanced Type (Radial Sheaths)



- Hydrophilic coated radial sheath and guidewire lead to smoother navigation and easier vascular access, reducing the risk of damage to the vessel.
- Advanced material improves bendability and flexibility without gapping or kinking.
- Special designed lock and silicon hemostatic valve provide outstanding hemostatic function, while guaranteeing the operational ability for the catheter.
- Smooth tapered tip helps with easy access to the artery, reducing trauma to the patients.
- Smooth transition from dilator to sheath greatly reduces puncture resistance, providing easy and non-traumatic insertion.

Full kit includes:

- Introducer Sheath (1)
- Dilator (1)
- Hydrophilic Guide Wire (1)
- Intravascular Catheter (1)
- Scalpel (1)
- Syringe (1)

The Introducer Kit can be customized by:

- a) Remove the every single component includes guide wire, intravascular catheter (IC), scalpel (K) and syringe (S).
- b) Replace the hydrophilic guide wire (straight HS/135° angled HW) into stainless steel guide wire (straight SS) or nitinol guide wire (straight NS).
- c) Replace the intravascular catheter (IC) into introducer needle (IN). Intravascular catheter is mandatory to be a set with hydrophilic guide wire.

Please contact the sales for more information about the selections of customized kit.

Ordering Information*

Radial Sheath							
Catalogue No. (Hydrophilic Guide Wire)	Sheath I.D.	Sheath Length	Guide Wire Diameter	Guide Wire Length	Intravascular Catheter	Scalpel	Syringe
RSC040521-HS45-IC22-K-S	4F	5 cm	0.021"	45 cm	22G	1	1
RSC040525-HS45-IC20-K-S	4F	5 cm	0.025"	45 cm	20G	1	1
RSC040721-HS45-IC22-K-S	4F	7 cm	0.021"	45 cm	22G	1	1
RSC040725-HS45-IC20-K-S	4F	7 cm	0.025"	45 cm	20G	1	1
RSC041121-HS45-IC22-K-S	4F	11 cm	0.021"	45 cm	22G	1	1
RSC041125-HS45-IC20-K-S	4F	11 cm	0.025"	45 cm	20G	1	1
RSC041621-HS70-IC22-K-S	4F	16 cm	0.021"	70 cm	22G	1	1
RSC041625-HS70-IC20-K-S	4F	16 cm	0.025"	70 cm	20G	1	1
RSC042421-HS70-IC22-K-S	4F	24 cm	0.021"	70 cm	22G	1	1
RSC042425-HS70-IC20-K-S	4F	24 cm	0.025"	70 cm	20G	1	1
RSC050521-HS45-IC22-K-S	5F	5 cm	0.021"	45 cm	22G	1	1
RSC050525-HS45-IC20-K-S	5F	5 cm	0.025"	45 cm	20G	1	1
RSC050721-HS45-IC22-K-S	5F	7 cm	0.021"	45 cm	22G	1	1
RSC050725-HS45-IC20-K-S	5F	7 cm	0.025"	45 cm	20G	1	1
RSC051121-HS45-IC22-K-S	5F	11 cm	0.021"	45 cm	22G	1	1
RSC051125-HS45-IC20-K-S	5F	11 cm	0.025"	45 cm	20G	1	1
RSC051621-HS70-IC22-K-S	5F	16 cm	0.021"	70 cm	22G	1	1
RSC051625-HS70-IC20-K-S	5F	16 cm	0.025"	70 cm	20G	1	1
RSC052421-HS70-IC22-K-S	5F	24 cm	0.021"	70 cm	22G	1	1
RSC052425-HS70-IC20-K-S	5F	24 cm	0.025"	70 cm	20G	1	1
RSC060521-HS45-IC22-K-S	6F	5 cm	0.021"	45 cm	22G	1	1
RSC060525-HS45-IC20-K-S	6F	5 cm	0.025"	45 cm	20G	1	1
RSC060721-HS45-IC22-K-S	6F	7 cm	0.021"	45 cm	22G	1	1
RSC060725-HS45-IC20-K-S	6F	7 cm	0.025"	45 cm	20G	1	1
RSC061121-HS45-IC22-K-S	6F	11 cm	0.021"	45 cm	22G	1	1
RSC061125-HS45-IC20-K-S	6F	11 cm	0.025"	45 cm	20G	1	1
RSC061621-HS70-IC22-K-S	6F	16 cm	0.021"	70 cm	22G	1	1
RSC061625-HS70-IC20-K-S	6F	16 cm	0.025"	70 cm	20G	1	1
RSC062421-HS70-IC22-K-S	6F	24 cm	0.021"	70 cm	22G	1	1
RSC062425-HS70-IC20-K-S	6F	24 cm	0.025"	70 cm	20G	1	1
RSC070521-HS45-IC22-K-S	7F	5 cm	0.021"	45 cm	22G	1	1
RSC070525-HS45-IC20-K-S	7F	5 cm	0.025"	45 cm	20G	1	1
RSC070721-HS45-IC22-K-S	7F	7 cm	0.021"	45 cm	22G	1	1
RSC070725-HS45-IC20-K-S	7F	7 cm	0.025"	45 cm	20G	1	1
RSC071121-HS45-IC22-K-S	7F	11 cm	0.021"	45 cm	22G	1	1
RSC071125-HS45-IC20-K-S	7F	11 cm	0.025"	45 cm	20G	1	1
RSC071621-HS70-IC22-K-S	7F	16 cm	0.021"	70 cm	22G	1	1
RSC071625-HS70-IC20-K-S	7F	16 cm	0.025"	70 cm	20G	1	1
RSC072421-HS70-IC22-K-S	7F	24 cm	0.021"	70 cm	22G	1	1
RSC072425-HS70-IC20-K-S	7F	24 cm	0.025"	70 cm	20G	1	1

* The Yellow Marks indicate the components which can be customized as mentioned before.
(e.g. radial sheath/6F/7cm, 0.021" straight hydrophilic guide wire/45cm, 22G intravascular catheter, without scalpel and syringe: RSC060721-HS45-IC22)

Please contact the sales for detailed catalogue numbers of customized kits.

Rayband™

Radial Artery Compression Tourniquet

CE FDA



- Specially designed for radial artery hemostasis of post percutaneous puncture.
- Transparent material ensures clear visual control of hemostasis procedure.
- Unilateral valve connected to the balloon allows of accurate pressure adjustment to provide personalized hemostasis procedure.
- Adjustable band length is convenient to fit for patient's comfort.
- Stopcock on syringe helps with easy and accurate deflation.

Ordering Information

Catalogue No.	Balloon Structure	Bandage Length (cm)	Max Injection Air Volume (mL)	Connector
LPYP15S	1	21	15	Push-pull
LPYP15	1	24.5	15	Push-pull
LPYP15L	1	27	15	Push-pull
LPYP15XL	1	29	15	Push-pull
LPYP20S	2	21	20	Push-pull
LPYP20	2	24.5	20	Push-pull
LPYP20L	2	27	20	Push-pull
LPYP20XL	2	29	20	Push-pull
YPR15S	1	21	15	Luer
YPR15	1	24.5	15	Luer
YPR15L	1	27	15	Luer
YPR15XL	1	29	15	Luer
YPR20S	2	21	20	Luer
YPR20	2	24.5	20	Luer
YPR20L	2	27	20	Luer
YPR20XL	2	29	20	Luer

Angioway™

Y-Hemostasis Valve Set

CE FDA



- Effectively minimize blood loss and provide a smooth channel for interventional device delivery.
- Easy push-pull mechanism allows to operate with one hand.

Whole set package includes:

Y-valve (1)
Guide Wire Torquer (1)
Guide Wire Introducer (1)

Technical Parameters

Connector Type	Push-Pull / Rotating
Inner Diameter	0.118" (3.0mm)
Body Material	Polycarbonate
Extension Tubing	Optional
Sterilization	ETO

Ordering Information

Catalogue No.	Connector Type	Package Type	Length of the Extension Tubing (cm)
YNP	Push-Pull	Whole set	/
YNP20	Push-Pull	Whole set	20
YNP25	Push-Pull	Whole set	25
YNP40	Push-Pull	Whole set	40
YNP50	Push-Pull	Whole set	50
YNPH	Push-Pull	Y-valve only	/
YNP20H	Push-Pull	Y-valve only	20
YNP25H	Push-Pull	Y-valve only	25
YNP40H	Push-Pull	Y-valve only	40
YNP50H	Push-Pull	Y-valve only	50
YNR	Rotating	Whole set	/
YNRH	Rotating	Y-valve only	/

Angiopower™

Inflation Device

CE FDA



- Fluorescence clock face for clearer display.
- Smooth fine adjustment for accurate inflation.
- Barrier screw pivot provides precise pressure placement.
- The internal multi-buckle structure ensures more secure lock.
- Ergonomic grip fits comfortably in either hand.
- Petal-shaped handle ensures torque control without slipping.

Technical Parameter

Display	Analog/Fluorescent
Pressure	30 atm (440psi)
Barrel Volume	20mL
Stopcock	3-way 500psi
Extension Tubing	33cm, 1200psi, male rotating Luer connector

Ordering Information

Catalogue No.	Inflation Range (atm)	Stopcock
LP-P-30	30	/
LP-P-30S	30	Included

Inflation
Devices Kit

CE FDA



Inflation Device Kit includes:


- Inflation Device (1)
- Y-Hemostasis Valve Set (1)

Ordering Information

Catalogue No.	Inflation Device Model			Y-Hemostasis Valve Set Model		
	Type	Inflation Range	Type	Mode	Contains	Extension Tubing
LP-P-30-YNP	LP-P-30	30atm	YNP	Push-Pull	Whole set	/
LP-P-30-YNP20	LP-P-30	30atm	YNP20	Push-Pull	Whole set	20cm
LP-P-30-YNP25	LP-P-30	30atm	YNP25	Push-Pull	Whole set	25cm
LP-P-30-YNP40	LP-P-30	30atm	YNP40	Push-Pull	Whole set	40cm
LP-P-30-YNP50	LP-P-30	30atm	YNP50	Push-Pull	Whole set	50cm
LP-P-30-YNPH	LP-P-30	30atm	YNPH	Push-Pull	Y-valve only	/
LP-P-30-YNP20H	LP-P-30	30atm	YNP20H	Push-Pull	Y-valve only	20cm
LP-P-30-YNP25H	LP-P-30	30atm	YNP25H	Push-Pull	Y-valve only	25cm
LP-P-30-YNP40H	LP-P-30	30atm	YNP40H	Push-Pull	Y-valve only	40cm
LP-P-30-YNP50H	LP-P-30	30atm	YNP50H	Push-Pull	Y-valve only	50cm
LP-P-30-YNR	LP-P-30	30atm	YNR	Rotating	Whole set	/
LP-P-30-YNRH	LP-P-30	30atm	YNRH	Rotating	Y-valve only	/
LP-P-30S-YNP	LP-P-30S	30atm	YNP	Push-Pull	Whole set	/
LP-P-30S-YNP20	LP-P-30S	30atm	YNP20	Push-Pull	Whole set	20cm
LP-P-30S-YNP25	LP-P-30S	30atm	YNP25	Push-Pull	Whole set	25cm
LP-P-30S-YNP40	LP-P-30S	30atm	YNP40	Push-Pull	Whole set	40cm
LP-P-30S-YNP50	LP-P-30S	30atm	YNP50	Push-Pull	Whole set	50cm
LP-P-30S-YNPH	LP-P-30S	30atm	YNPH	Push-Pull	Y-valve only	/
LP-P-30S-YNP20H	LP-P-30S	30atm	YNP20H	Push-Pull	Y-valve only	20cm
LP-P-30S-YNP25H	LP-P-30S	30atm	YNP25H	Push-Pull	Y-valve only	25cm
LP-P-30S-YNP40H	LP-P-30S	30atm	YNP40H	Push-Pull	Y-valve only	40cm
LP-P-30S-YNP50H	LP-P-30S	30atm	YNP50H	Push-Pull	Y-valve only	50cm
LP-P-30S-YNR	LP-P-30S	30atm	YNR	Rotating	Whole set	/
LP-P-30S-YNRH	LP-P-30S	30atm	YNRH	Rotating	Y-valve only	/

Angioway™

Manifolds



- Visible handle makes the flow control easy and accurate
- On / Off types are available for different user habits

Technical Parameters

Side Ports	One / Two / Three
Pressure	500psi
Valve Type	On / Off
Extension Tubing	Optional
Sterilization	ETO

Ordering Information

Catalogue No.	Pressure	Side Port	Valve Type	Extension Tubing
LPJD502N	500psi	2	On	/
LPJD502F	500psi	2	Off	/
LPJD503N	500psi	3	On	/
LPJD503F	500psi	3	Off	/
LPJD503NX	500psi	3	On	Included
LPJD503FX	500psi	3	Off	Included

Angioway™

High Pressure
Extension Tubings



- High pressure transparent material ensures the need for large flow
- Customized length is available

Technical Parameters

Material	PVC/TPU
Inner Diameter	0.056" (1.44mm)
Pressure Resistance	500psi / 1200psi
Sterilization	ETO

Ordering Information

Pressure	Length					
	30cm	60cm	90cm	120cm	150cm	180cm
500psi	LPJG30N	LPJG60N	LPJG90N	LPJG120N	LPJG150N	LPJG180N
1200psi	LPJG30H	LPJG60H	LPJG90H	LPJG120H	LPJG150H	LPJG180H

Introducer
Needle

CE



Ordering Information

Catalogue No.	Gauge	Guide Wire Compatibility	Working Length (mm)
MMN 1870	18	0.035"	70
MMN 2038	20	0.021"	38
MMNI 1870	18	0.038"	70

Angiospring™

Angiography
Control Syringe

CE



- Solid and smooth plunger with unique push button make it easy for operation
- Clear scale, accurate control of infusion volume
- Latex free

Technical Parameters

Luer Connector Type	Rotating
Sterilization	ETO

Ordering Information

Catalogue No.	Connector Type	Nominal Capacity (mL)
LPHB112	Rotating	12

Contrast Medium
Injection
Manifold Kits

CE



Contrast Medium Injection Manifold Kit includes:

- Manifold (1)
- Angiography Control Syringe (1)
- High Pressure Extension Tubing (1)
- Infusion set (2)

Ordering Information

Catalogue No.	Manifold Model	Control Syringe Model	High Pressure Extension Tubing Model	Infusion Set Model	
MK-005	LPJD253N	LPHB112	LPJG30	IS-G-V	IS-G-V3
MK-006	LPJD253N	LPHB112	LPJG60	IS-G-V	IS-G-V3
MK-007	LPJD253N	LPHB112	LPJG90	IS-G-V	IS-G-V3
MK-008	LPJD253N	LPHB112	LPJG120	IS-G-V	IS-G-V3
MK-017	LPJD253F	LPHB112	LPJG30	IS-G-V	IS-G-V3
MK-018	LPJD253F	LPHB112	LPJG60	IS-G-V	IS-G-V3
MK-019	LPJD253F	LPHB112	LPJG90	IS-G-V	IS-G-V3
MK-020	LPJD253F	LPHB112	LPJG120	IS-G-V	IS-G-V3



02

Neurovascular Interventional Products

Vascular Protection

37 Disposable Embolic Protection Device **CE**

Embolization

38 Embolic Coil System **CE**

Microcatheter

39 Disposable Microcatheter **CE**

Disposable
Embolic Protection
Device

CE



- Nitinol material with great hemocompatibility. Soft braided filter and round distal tip minimize the risk of trauma to the vessel.
- Excellent axial control and kink resistance provide superior deliverability and crossability through tortuous anatomy.
- Gold loop marker could identify the release status of the filter, which ensures the optimal positioning of the filter in the vessel.
- The unique design of guidewire casing on the filter prevents from its displacement caused by the movement of guidewire.
- Gradient pore diameter from distal to proximal end guarantees efficient embolus capturing while maintaining continuous blood flow.
- Integrated sheaths for delivery and retrieval are compatible with 5F/6F catheters and 0.014" guidewire, which could achieve rapid exchange during the procedure.

Ordering Information

Catalogue No.	Filter Diameter (mm)	Guide Wire Length (cm)	Delivery Shaft O.D.	Retrieval Shaft O.D.
TJEP03-190	3	190	3.2F	4.2F
TJEP04-190	4	190	3.2F	4.2F
TJEP05-190	5	190	3.2F	4.2F
TJEP06-190	6	190	3.2F	4.2F
TJEP07-190	7	190	3.2F	4.2F
TJEP08-190	8	190	3.2F	4.2F
TJEP03-320	3	320	3.2F	4.2F
TJEP04-320	4	320	3.2F	4.2F
TJEP05-320	5	320	3.2F	4.2F
TJEP06-320	6	320	3.2F	4.2F
TJEP07-320	7	320	3.2F	4.2F
TJEP08-320	8	320	3.2F	4.2F

Notice: Please contact the sales for detailed information before placing the order.

Embolic
Coil System

CE



2D Helical Structure

3D Complex Structure

- Gradient primary diameter ranges from 0.010" to 0.014", providing different softness with better compliance.
- Anti-unwinding structure prevents from coil unwinding which is caused by over-stretching during the embolization process.
- Markers on proximal end of the coil and the distal end of the delivery shaft provide accurate positioning.
- Stable detachment leads to safer operation. One single coil could be detached completely within 1 second.
- This product is compatible with most of the microcatheters in the market.

Ordering Information

Minimal microcatheter inner diameter compatibility: 0.0165"

Catalogue No. (helical)	Catalogue No. (complex)	Loop Dia. (mm)	Effective Length (cm)	Catalogue No. (helical)	Catalogue No. (complex)	Loop Dia. (mm)	Effective Length (cm)
TJCST1.502-2D	TJCST1.502-3D	1.5	2	TJCST0509-2D	TJCST0509-3D	5	9
TJCST1.503-2D	TJCST1.503-3D	1.5	3	TJCST0510-2D	TJCST0510-3D	5	10
TJCST1.504-2D	TJCST1.504-3D	1.5	4	TJCST0515-2D	TJCST0515-3D	5	15
TJCST0201-2D	TJCST0201-3D	2	1	TJCST0520-2D	TJCST0520-3D	5	20
TJCST0202-2D	TJCST0202-3D	2	2	TJCST0610-2D	TJCST0610-3D	6	10
TJCST0203-2D	TJCST0203-3D	2	3	TJCST0611-2D	TJCST0611-3D	6	11
TJCST0204-2D	TJCST0204-3D	2	4	TJCST0615-2D	TJCST0615-3D	6	15
TJCST0206-2D	TJCST0206-3D	2	6	TJCST0620-2D	TJCST0620-3D	6	20
TJCST0208-2D	TJCST0208-3D	2	8	TJCST0715-2D	TJCST0715-3D	7	15
TJCST2.502-2D	TJCST2.502-3D	2.5	2	TJCST0720-2D	TJCST0720-3D	7	20
TJCST2.504-2D	TJCST2.504-3D	2.5	4	TJCST0730-2D	TJCST0730-3D	7	30
TJCST2.506-2D	TJCST2.506-3D	2.5	6	TJCST0815-2D	TJCST0815-3D	8	15
TJCST2.508-2D	TJCST2.508-3D	2.5	8	TJCST0820-2D	TJCST0820-3D	8	20
TJCST0304-2D	TJCST0304-3D	3	4	TJCST0830-2D	TJCST0830-3D	8	30
TJCST0306-2D	TJCST0306-3D	3	6	TJCST0920-2D	TJCST0920-3D	9	20
TJCST0308-2D	TJCST0308-3D	3	8	TJCST0930-2D	TJCST0930-3D	9	30
TJCST0310-2D	TJCST0310-3D	3	10	TJCST1020-2D	TJCST1020-3D	10	20
TJCST0312-2D	TJCST0312-3D	3	12	TJCST1030-2D	TJCST1030-3D	10	30
TJCST3.506-2D	TJCST3.506-3D	3.5	6	TJCST1130-2D	TJCST1130-3D	11	30
TJCST3.508-2D	TJCST3.508-3D	3.5	8	TJCST1230-2D	TJCST1230-3D	12	30
TJCST3.510-2D	TJCST3.510-3D	3.5	10	TJCST1330-2D	TJCST1330-3D	13	30
TJCST3.512-2D	TJCST3.512-3D	3.5	12	TJCST1430-2D	TJCST1430-3D	14	30
TJCST0404-2D	TJCST0404-3D	4	4	TJCST1530-2D	TJCST1530-3D	15	30
TJCST0406-2D	TJCST0406-3D	4	6	TJCST1630-2D	TJCST1630-3D	16	30
TJCST0408-2D	TJCST0408-3D	4	8	TJCST1830-2D	TJCST1830-3D	18	30
TJCST0410-2D	TJCST0410-3D	4	10	TJCST2030-2D	TJCST2030-3D	20	30
TJCST4.506-2D	TJCST4.506-3D	4.5	6				
TJCST4.508-2D	TJCST4.508-3D	4.5	8				
TJCST4.510-2D	TJCST4.510-3D	4.5	10				
TJCST4.512-2D	TJCST4.512-3D	4.5	12				
TJCST4.515-2D	TJCST4.515-3D	4.5	15				

Notice: Please contact the sales for detailed information before placing the order.

Disposable
Microcatheter
CE



- Three-layer structure of the microcatheter contributes to the high static pressure resistance, which could reach up to 600psi (4137KPa).
- Multi-segments design with smooth transition ensures excellent flexibility, crossability and pushability during delivery.
- The long distal soft segment improves the sensitivity of the catheter during delivery.
- Soft segment is covered by coiled Pt-W alloy, which provides great radiopacity and better trackability in the vessel.
- Ultra-soft tip ensures better plasticity even for multiple times of tip shaping.
- Hydrophilic coating on the whole catheter provides outstanding deliverability.

Ordering Information

Catalogue No.	Catheter I.D.	Catheter Distal O.D.	Catheter Proximal O.D.	Effective Length	Max. Guide Wire O.D.	Tip Shape	Markers
TJMC10	0.015"	1.8F	2.2F	150cm	0.012"	Straight, Steam Shapeable	2
TJMC14	0.0165"	1.9F	2.3F	150cm	0.014"	Straight, Steam Shapeable	2
TJMC16	0.021"	2.3F	2.8F	150cm	0.018"	Straight, Steam Shapeable	2
TJMC18	0.027"	2.5F	2.8F	140cm	0.021"	Straight, Steam Shapeable	1

Notice: Please contact the sales for detailed information before placing the order.


03 Peripheral
Interventional Products

PTA Balloon

41 Supercross™ PTA Balloon Dilatation Catheter CE

Supercross™

PTA Balloon Dilatation
Catheter



- The flexible tapered tip ensures consistently smooth insertion and atraumatic navigation.
- Low crossing profile guarantees excellent crossability to pass through narrow lesions.
- Over the wire (OTW) design provides great torque control, kink resistance and pushability to ensure the outstanding deliverability.
- Dual-lumen shaft design of the OTW catheter separates the inflation lumen and guide wire lumen to ensure the rapid deflation performance.
- Special memory folding technique provides great withdrawal capability, and allows of repeated dilatation.

Technical Parameters

Catheter Design	Rapid Exchange (RX)
Balloon Compliance	Semi-compliant
Marker	2
Material	Nylon
Nominal Pressure	7 atm
Distal Shaft O.D.	2.8F
Proximal Shaft O.D.	2.3F
Lowest Crossing Profile	0.025"
Effective Length	135cm
Minimum Guiding Catheter Compatibility	5F (0.056")
Guide wire Compatibility	0.014"

Catheter Design	Over the Wire (OTW)
Balloon Compliance	Semi-compliant
Marker	2
Material	Nylon
Nominal Pressure	7 atm
Distal Shaft O.D.	5F
Lowest Crossing Profile	0.060"
Effective Length	80cm / 135cm
Minimum Introducer Sheath Compatibility	5F / 6F / 7F
Guide Wire Compatibility	0.035"

Ordering Information

Rapid Exchange							
Balloon Diameter (mm)	Balloon Length (mm)						
	20	30	40	60	80	100	120
1.5	PTAR15020	/	/	/	/	/	/
2.0	PTAR20020	PTAR20030	PTAR20040	PTAR20060	PTAR20080	PTAR20100	PTAR20120
2.5	PTAR25020	PTAR25030	PTAR25040	PTAR25060	PTAR25080	PTAR25100	PTAR25120
3.0	PTAR30020	PTAR30030	PTAR30040	PTAR30060	PTAR30080	PTAR30100	PTAR30120
3.5	PTAR35020	PTAR35030	PTAR35040	PTAR35060	PTAR35080	PTAR35100	PTAR35120
4.0	PTAR40020	PTAR40030	PTAR40040	PTAR40060	PTAR40080	PTAR40100	PTAR40120
4.5	PTAR45020	PTAR45030	PTAR45040	PTAR45060	PTAR45080	PTAR45100	PTAR45120
5.0	PTAR50020	PTAR50030	PTAR50040	PTAR50060	PTAR50080	PTAR50100	PTAR50120
5.5	PTAR55020	PTAR55030	PTAR55040	PTAR55060	PTAR55080	PTAR55100	PTAR55120
6.0	PTAR60020	PTAR60030	PTAR60040	PTAR60060	PTAR60080	PTAR60100	PTAR60120
7.0	PTAR70020	PTAR70030	PTAR70040	PTAR70060	PTAR70080	PTAR70100	PTAR70120

Over the Wire (Effective length is 80cm)							
Balloon Diameter (mm)	Balloon Length (mm)						
	20	30	40	60	80	100	120
3.0	PTAO30020	PTAO30030	PTAO30040	PTAO30060	PTAO30080	PTAO30100	PTAO30120
3.5	PTAO35020	PTAO35030	PTAO35040	PTAO35060	PTAO35080	PTAO35100	PTAO35120
4.0	PTAO40020	PTAO40030	PTAO40040	PTAO40060	PTAO40080	PTAO40100	PTAO40120
4.5	PTAO45020	PTAO45030	PTAO45040	PTAO45060	PTAO45080	PTAO45100	PTAO45120
5.0	PTAO50020	PTAO50030	PTAO50040	PTAO50060	PTAO50080	PTAO50100	PTAO50120
5.5	PTAO55020	PTAO55030	PTAO55040	PTAO55060	PTAO55080	PTAO55100	PTAO55120
6.0	PTAO60020	PTAO60030	PTAO60040	PTAO60060	PTAO60080	PTAO60100	PTAO60120
7.0	PTAO70020	PTAO70030	PTAO70040	PTAO70060	PTAO70080	PTAO70100	PTAO70120
8.0	PTAO80020	PTAO80030	PTAO80040	PTAO80060	PTAO80080	PTAO80100	PTAO80120
9.0	PTAO90020	PTAO90030	PTAO90040	PTAO90060	PTAO90080	PTAO90100	PTAO90120
10.0	PTAO10020	PTAO10030	PTAO10040	PTAO10060	PTAO10080	PTAO10100	PTAO10120
12.0	PTAO12020	/	/	/	/	/	/

Over the Wire (Effective length is 135cm)							
Balloon Diameter (mm)	Balloon Length (mm)						
	20	30	40	60	80	100	120
3.0	PTAO30020 L	PTAO30030 L	PTAO30040 L	PTAO30060 L	PTAO30080 L	PTAO30100 L	PTAO30120 L
3.5	PTAO35020 L	PTAO35030 L	PTAO35040 L	PTAO35060 L	PTAO35080 L	PTAO35100 L	PTAO35120 L
4.0	PTAO40020 L	PTAO40030 L	PTAO40040 L	PTAO40060 L	PTAO40080 L	PTAO40100 L	PTAO40120 L
4.5	PTAO45020 L	PTAO45030 L	PTAO45040 L	PTAO45060 L	PTAO45080 L	PTAO45100 L	PTAO45120 L
5.0	PTAO50020 L	PTAO50030 L	PTAO50040 L	PTAO50060 L	PTAO50080 L	PTAO50100 L	PTAO50120 L
5.5	PTAO55020 L	PTAO55030 L	PTAO55040 L	PTAO55060 L	PTAO55080 L	PTAO55100 L	PTAO55120 L
6.0	PTAO60020 L	PTAO60030 L	PTAO60040 L	PTAO60060 L	PTAO60080 L	PTAO60100 L	PTAO60120 L
7.0	PTAO70020 L	PTAO70030 L	PTAO70040 L	PTAO70060 L	PTAO70080 L	PTAO70100 L	PTAO70120 L
8.0	PTAO80020 L	PTAO80030 L	PTAO80040 L	PTAO80060 L	PTAO80080 L	PTAO80100 L	PTAO80120 L
9.0	PTAO90020 L	PTAO90030 L	PTAO90040 L	PTAO90060 L	PTAO90080 L	PTAO90100 L	PTAO90120 L
10.0	PTAO10020 L	PTAO10030 L	PTAO10040 L	PTAO10060 L	PTAO10080 L	PTAO10100 L	PTAO10120 L
12.0	PTAO12020 L	/	/	/	/	/	/

04

Structural Heart Diseases Products

Occlusion Devices

- 45 MemoPart™ Atrial Septal Defect (ASD) Occluder CE
- 47 MemoPart™ Ventricular Septal Defect (VSD) Occluder CE
- 50 MemoPart™ Patent Ductus Arteriosus (PDA) Occluder CE
- 52 MemoPart™ Patent Foramen Ovale (PFO) Occluder CE
- 53 MemoPart™ Plug CE
- 54 MemoPart™ Occluder Delivery System CE
- 56 MemoPart™ Snare CE

Mechanical Heart Valve


- 57 GKS Bi-leaflet Prosthetic Heart Valve

MemoPart™

Atrial Septal Defect
(ASD) Occluder



ASD Occluder



Hubless
ASD Occluder

- Modified rigidity and flexibility for different type of occluders - greater stiffness of ASDO offers excellent supporting force for big disks.
- Uniform and smooth oxide film on nitinol wire effectively prevents from the release of nickel ion to guarantee the great biocompatibility and long-term safety.
- Hubless design helps with earlier endothelialization to minimize the risk of thrombosis.

Ordering Information

ASD Occluder

Catalogue No.	Device Size	A Waist Diameter (mm)	B LA Disc Diameter (mm)	C RA Disc Diameter (mm)	H Waist Length (mm)
FQFDQ- I 06	06	6	16	14	3.0
FQFDQ- I 07	07	7	21	17	3.0
FQFDQ- I 08	08	8	18	16	3.0
FQFDQ- I 09	09	9	23	19	3.0
FQFDQ- I 10	10	10	20	18	3.0
FQFDQ- I 11	11	11	25	21	3.0
FQFDQ- I 12	12	12	22	20	3.0
FQFDQ- I 13	13	13	27	23	3.0
FQFDQ- I 14	14	14	24	22	3.0
FQFDQ- I 15	15	15	29	25	4.0
FQFDQ- I 16	16	16	30	26	4.0
FQFDQ- I 17	17	17	31	27	4.0
FQFDQ- I 18	18	18	32	28	4.0
FQFDQ- I 19	19	19	33	29	4.0
FQFDQ- I 20	20	20	34	30	4.0
FQFDQ- I 22	22	22	36	32	4.0
FQFDQ- I 24	24	24	38	34	4.0
FQFDQ- I 26	26	26	40	36	4.0
FQFDQ- I 28	28	28	42	38	4.0
FQFDQ- I 30	30	30	44	40	4.0
FQFDQ- I 32	32	32	47	42	4.0
FQFDQ- I 34	34	34	49	44	4.0
FQFDQ- I 36	36	36	51	46	4.0
FQFDQ- I 38	38	38	54	50	4.5
FQFDQ- I 40	40	40	56	52	4.5
FQFDQ- I 42	42	42	58	54	4.5
FQFDQ- I 44	44	44	60	56	4.5
FQFDQ- I 46	46	46	62	58	4.5
FQFDQ- I 48	48	48	64	60	4.5
FQFDQ- I 50	50	50	66	62	4.5

Hubless ASD Occluder




Catalogue No.	Device Size	A Waist Diameter (mm)	B LA Disc Diameter (mm)	C RA Disc Diameter (mm)	H Waist Length (mm)
WTFQFDQ- I 06	06	6	16	14	3.0
WTFQFDQ- I 07	07	7	21	17	3.0
WTFQFDQ- I 08	08	8	18	16	3.0
WTFQFDQ- I 09	09	9	23	19	3.0
WTFQFDQ- I 10	10	10	20	18	3.0
WTFQFDQ- I 11	11	11	25	21	3.0
WTFQFDQ- I 12	12	12	22	20	3.0
WTFQFDQ- I 13	13	13	27	23	3.0
WTFQFDQ- I 14	14	14	24	22	3.0
WTFQFDQ- I 15	15	15	29	25	4.0
WTFQFDQ- I 16	16	16	30	26	4.0
WTFQFDQ- I 17	17	17	31	27	4.0
WTFQFDQ- I 18	18	18	32	28	4.0
WTFQFDQ- I 19	19	19	33	29	4.0
WTFQFDQ- I 20	20	20	34	30	4.0
WTFQFDQ- I 22	22	22	36	32	4.0
WTFQFDQ- I 24	24	24	38	34	4.0

Multi-Fenestrated ASD Occluder


Catalogue No.	Device Size	A Waist Diameter (mm)	B LA Disc Diameter (mm)	C RA Disc Diameter (mm)	H Waist Length (mm)
FQFDQ- II 06	06	6	30	22	3.0
FQFDQ- II 08	08	8	32	24	3.0
FQFDQ- II 10	10	10	34	26	3.0
FQFDQ- II 12	12	12	36	28	3.0
FQFDQ- II 14	14	14	38	30	3.0
FQFDQ- II 16	16	16	40	32	4.0
FQFDQ- II 18	18	18	42	34	4.0
FQFDQ- II 20	20	20	44	36	4.0
FQFDQ- II 22	22	22	46	38	4.0
FQFDQ- II 24	24	24	48	40	4.0

Hubless Multi-Fenestrated ASD Occluder

Catalogue No.	Device Size	A Waist Diameter (mm)	B LA Disc Diameter (mm)	C RA Disc Diameter (mm)	H Waist Length (mm)
WTFQFDQ- II 06	06	6	30	22	3.0
WTFQFDQ- II 08	08	8	32	24	3.0
WTFQFDQ- II 10	10	10	34	26	3.0
WTFQFDQ- II 12	12	12	36	28	3.0
WTFQFDQ- II 14	14	14	38	30	3.0



MemoPart™
Ventricular Septal Defect
(VSD) Occluder



- Modified rigidity and flexibility for different type of occluders - less stiffness of VSDO reduces the holding force to minimize the risk of third degree atrioventricular block.
- Different waist lengths of VSD occluders minimize the negative impact of compress force to the patients.
- Uniform and smooth oxide film on nitinol wire effectively prevents from the release of nickel ion to guarantee the great biocompatibility and long-term safety.
- Hubless design helps with earlier endothelialization to minimize the risk of thrombosis.

Ordering Information

Muscular VSD Occluder






Catalogue No.	Device Size	A Waist Diameter (mm)	B LV Disc Diameter (mm)	C RV Disc Diameter (mm)	H Waist Length (mm)
SQFDQ- I a04	04	4	8	8	5.0
SQFDQ- I a05	05	5	9	9	5.0
SQFDQ- I a06	06	6	10	10	5.0
SQFDQ- I a07	07	7	11	11	5.0
SQFDQ- I a08	08	8	12	12	5.0
SQFDQ- I a09	09	9	13	13	5.0
SQFDQ- I a10	10	10	14	14	5.0
SQFDQ- I a12	12	12	16	16	5.0
SQFDQ- I a14	14	14	18	18	5.0
SQFDQ- I a16	16	16	20	20	5.0
SQFDQ- I a18	18	18	22	22	5.0
SQFDQ- I b04	04	4	10	8	7.0
SQFDQ- I b05	05	5	11	9	7.0
SQFDQ- I b06	06	6	12	10	7.0
SQFDQ- I b07	07	7	13	11	7.0
SQFDQ- I b08	08	8	14	12	7.0
SQFDQ- I b09	09	9	15	13	7.0
SQFDQ- I b10	10	10	16	14	7.0
SQFDQ- I b12	12	12	18	16	7.0
SQFDQ- I b14	14	14	20	18	7.0
SQFDQ- I b16	16	16	22	20	7.0
SQFDQ- I b18	18	18	24	22	7.0
SQFDQ- I c04	04	4	14	10	10.0
SQFDQ- I c05	05	5	15	11	10.0
SQFDQ- I c06	06	6	16	12	10.0
SQFDQ- I c07	07	7	17	13	10.0
SQFDQ- I c08	08	8	18	14	10.0
SQFDQ- I c09	09	9	19	15	10.0
SQFDQ- I c10	10	10	20	16	10.0
SQFDQ- I c12	12	12	22	18	10.0
SQFDQ- I c14	14	14	24	20	10.0
SQFDQ- I c16	16	16	26	22	10.0
SQFDQ- I c18	18	18	28	24	10.0


Hubless Muscular VSD Occluder

Catalogue No.	Device Size	A Waist Diameter (mm)	B LV Disc Diameter (mm)	C RV Disc Diameter (mm)	H Waist Length (mm)
WTSQFDQ- I a04	04	4	8	8	5.0
WTSQFDQ- I a05	05	5	9	9	5.0
WTSQFDQ- I a06	06	6	10	10	5.0
WTSQFDQ- I a07	07	7	11	11	5.0
WTSQFDQ- I a08	08	8	12	12	5.0
WTSQFDQ- I a09	09	9	13	13	5.0
WTSQFDQ- I a10	10	10	14	14	5.0
WTSQFDQ- I a12	12	12	16	16	5.0
WTSQFDQ- I a14	14	14	18	18	5.0
WTSQFDQ- I a16	16	16	20	20	5.0
WTSQFDQ- I a18	18	18	22	22	5.0
WTSQFDQ- I b04	04	4	10	8	7.0
WTSQFDQ- I b05	05	5	11	9	7.0
WTSQFDQ- I b06	06	6	12	10	7.0
WTSQFDQ- I b07	07	7	13	11	7.0
WTSQFDQ- I b08	08	8	14	12	7.0
WTSQFDQ- I b09	09	9	15	13	7.0
WTSQFDQ- I b10	10	10	16	14	7.0
WTSQFDQ- I b12	12	12	18	16	7.0
WTSQFDQ- I b14	14	14	20	18	7.0
WTSQFDQ- I b16	16	16	22	20	7.0
WTSQFDQ- I b18	18	18	24	22	7.0
WTSQFDQ- I c04	04	4	14	10	10.0
WTSQFDQ- I c05	05	5	15	11	10.0
WTSQFDQ- I c06	06	6	16	12	10.0
WTSQFDQ- I c07	07	7	17	13	10.0
WTSQFDQ- I c08	08	8	18	14	10.0
WTSQFDQ- I c09	09	9	19	15	10.0
WTSQFDQ- I c10	10	10	20	16	10.0
WTSQFDQ- I c12	12	12	22	18	10.0
WTSQFDQ- I c14	14	14	24	20	10.0
WTSQFDQ- I c16	16	16	26	22	10.0
WTSQFDQ- I c18	18	18	28	24	10.0

Membranous Symmetric VSD Occluder


Catalogue No.	Device Size	A Waist Diameter (mm)	B LV Disc Diameter (mm)	C RV Disc Diameter (mm)	H Waist Length (mm)
SQFDQ- II b04	04	4	8	8	3.5
SQFDQ- II b05	05	5	9	9	4.0
SQFDQ- II b06	06	6	10	10	4.0
SQFDQ- II b07	07	7	11	11	4.0
SQFDQ- II b08	08	8	12	12	4.0
SQFDQ- II b09	09	9	13	13	4.5
SQFDQ- II b10	10	10	14	14	4.5
SQFDQ- II b12	12	12	16	15	4.5
SQFDQ- II b14	14	14	18	17	4.5
SQFDQ- II b16	16	16	22	20	5.0
SQFDQ- II b18	18	18	24	22	5.0
SQFDQ- II b20	20	20	26	24	5.0






Hubless Membranous Symmetric VSD Occluder

Catalogue No.	Device Size	A Waist Diameter (mm)	B LV Disc Diameter (mm)	C RV Disc Diameter (mm)	H Waist Length (mm)
WTSQFDQ- II b04	04	4	8	8	3.5
WTSQFDQ- II b05	05	5	9	9	4.0
WTSQFDQ- II b06	06	6	10	10	4.0
WTSQFDQ- II b07	07	7	11	11	4.0
WTSQFDQ- II b08	08	8	12	12	4.0
WTSQFDQ- II b09	09	9	13	13	4.5
WTSQFDQ- II b10	10	10	14	14	4.5
WTSQFDQ- II b12	12	12	16	15	4.5
WTSQFDQ- II b14	14	14	18	17	4.5
WTSQFDQ- II b16	16	16	22	20	5.0
WTSQFDQ- II b18	18	18	24	22	5.0
WTSQFDQ- II b20	20	20	26	24	5.0




Membranous Asymmetric VSD Occluder for Multi-Fenestrated Defects

Catalogue No.	Device Size	A Waist Diameter (mm)	B LV Disc Diameter (mm)	C RV Disc Diameter (mm)	H Waist Length (mm)
SQFDQ- III 04	04	4	12	8	3.5
SQFDQ- III 05	05	5	13	9	4.0
SQFDQ- III 06	06	6	14	10	4.0
SQFDQ- III 07	07	7	15	11	4.0
SQFDQ- III 08	08	8	16	12	4.0
SQFDQ- III 09	09	9	17	13	4.5
SQFDQ- III 10	10	10	18	14	4.5
SQFDQ- III 12	12	12	20	16	4.5
SQFDQ- III 14	14	14	22	18	4.5
SQFDQ- III 16	16	16	24	20	5.0
SQFDQ- III 18	18	18	26	22	5.0



Hubless Membranous Asymmetric VSD Occluder for Multi-Fenestrated Defects

Catalogue No.	Device Size	A Waist Diameter (mm)	B LV Disc Diameter (mm)	C RV Disc Diameter (mm)	H Waist Length (mm)
WTSQFDQ- III 04	04	4	12	8	3.5
WTSQFDQ- III 05	05	5	13	9	4.0
WTSQFDQ- III 06	06	6	14	10	4.0
WTSQFDQ- III 07	07	7	15	11	4.0
WTSQFDQ- III 08	08	8	16	12	4.0
WTSQFDQ- III 09	09	9	17	13	4.5
WTSQFDQ- III 10	10	10	18	14	4.5
WTSQFDQ- III 12	12	12	20	16	4.5
WTSQFDQ- III 14	14	14	22	18	4.5
WTSQFDQ- III 16	16	16	24	20	5.0
WTSQFDQ- III 18	18	18	26	22	5.0



Zero Rim Eccentric VSDO for the Defect Close to Aortic Valve

Catalogue No.	Device Size	A Waist Diameter (mm)	B LV Disc Diameter (mm)	C RV Disc Diameter (mm)	H Waist Length (mm)
SQFDQ- IV 04	04	4	9	8	3.5
SQFDQ- IV 05	05	5	10	9	3.5
SQFDQ- IV 06	06	6	11	10	4.0
SQFDQ- IV 07	07	7	12	11	4.0
SQFDQ- IV 08	08	8	13	12	4.5
SQFDQ- IV 09	09	9	14	13	5.0
SQFDQ- IV 10	10	10	17	15	5.0
SQFDQ- IV 12	12	12	20	18	5.0
SQFDQ- IV 14	14	14	22	20	5.0
SQFDQ- IV 16	16	16	24	22	5.0



PDA Occluder



Hubless
PDA Occluder

MemoPart™

Patent Ductus Arteriosus
(PDA) Occluder



- Modified rigidity and flexibility for different type of occluders - balanced stiffness of PDAO ensures the optimal occlusion performance.
- Uniform and smooth oxide film on nitinol wire effectively prevents from the release of nickel ion to guarantee the great biocompatibility and long-term safety.
- Hubless design helps with earlier endothelialization to minimize the risk of thrombosis.

Ordering Information


Cone Shape PDA Occluder

Catalogue No.	Device Size	B Aortic Waist Diameter (mm)	C Pulmonic Waist Diameter (mm)	A Aortic Disc Diameter (mm)	H Waist Length (mm)
WBFDDQ- II 06	0406	6	4	10	6.0
WBFDDQ- II 08	0608	8	6	12	6.5
WBFDDQ- II 10	0810	10	8	14	7.5
WBFDDQ- II 12	1012	12	10	16	8.5
WBFDDQ- II 14	1214	14	12	18	9.5
WBFDDQ- II 16	1416	16	14	20	10.5
WBFDDQ- II 18	1618	18	16	23	10.5
WBFDDQ- II 20	1820	20	18	25	12.0
WBFDDQ- II 22	2022	22	20	27	12.0




Hubless Cone Shape PDA Occluder

Catalogue No.	Device Size	B Aortic Waist Diameter (mm)	C Pulmonic Waist Diameter (mm)	A Aortic Disc Diameter (mm)	H Waist Length (mm)
WTWBFDDQ- II 06	0406	6	4	10	6.0
WTWBFDDQ- II 08	0608	8	6	12	6.5
WTWBFDDQ- II 10	0810	10	8	14	7.5
WTWBFDDQ- II 12	1012	12	10	16	8.5
WTWBFDDQ- II 14	1214	14	12	18	9.5
WTWBFDDQ- II 16	1416	16	14	20	10.5
WTWBFDDQ- II 18	1618	18	16	23	10.5
WTWBFDDQ- II 20	1820	20	18	25	12.0
WTWBFDDQ- II 22	2022	22	20	27	12.0



MemoPart™
Patent Foramen Ovale
(PFO) Occluder



Cylinder Shape PDA Occluder

Catalogue No.	Device Size	B Aortic Waist Diameter (mm)	C Pulmonic Waist Diameter (mm)	A Aortic Disc Diameter (mm)	H Waist Length (mm)
WBFDQ- I 04	04	4	4	8	4.0
WBFDQ- I 05	05	5	5	9	5.0
WBFDQ- I 06	06	6	6	10	6.0
WBFDQ- I 07	07	7	7	11	6.5
WBFDQ- I 08	08	8	8	12	6.5
WBFDQ- I 09	09	9	9	13	7.0
WBFDQ- I 10	10	10	10	14	7.5
WBFDQ- I 11	11	11	11	15	8.0
WBFDQ- I 12	12	12	12	16	8.5
WBFDQ- I 13	13	13	13	17	8.5
WBFDQ- I 14	14	14	14	18	9.5
WBFDQ- I 16	16	16	16	21	10.5
WBFDQ- I 18	18	18	18	23	10.5
WBFDQ- I 20	20	20	20	25	12.0
WBFDQ- I 22	22	22	22	27	12.0



Hubless Cylinder Shape PDA Occluder

Catalogue No.	Device Size	B Aortic Waist Diameter (mm)	C Pulmonic Waist Diameter (mm)	A Aortic Disc Diameter (mm)	H Waist Length (mm)
WTWBFDQ- I 04	04	4	4	8	4.0
WTWBFDQ- I 05	05	5	5	9	5.0
WTWBFDQ- I 06	06	6	6	10	6.0
WTWBFDQ- I 07	07	7	7	11	6.5
WTWBFDQ- I 08	08	8	8	12	6.5
WTWBFDQ- I 09	09	9	9	13	7.0
WTWBFDQ- I 10	10	10	10	14	7.5
WTWBFDQ- I 11	11	11	11	15	8.0
WTWBFDQ- I 12	12	12	12	16	8.5
WTWBFDQ- I 13	13	13	13	17	8.5
WTWBFDQ- I 14	14	14	14	18	9.5
WTWBFDQ- I 16	16	16	16	21	10.5
WTWBFDQ- I 18	18	18	18	23	10.5
WTWBFDQ- I 20	20	20	20	25	12.0
WTWBFDQ- I 22	22	22	22	27	12.0



PFO Occluder



Hubless
PFO Occluder

- Modified rigidity and flexibility for different type of occluders - greater stiffness of PFOO offers excellent supporting force for big disks.
- Uniform and smooth oxide film on nitinol wire effectively prevents from the release of nickel ion to guarantee the great biocompatibility and long-term safety.
- Optional hubless design helps with earlier endothelialization to minimize the risk of thrombosis.



Ordering Information

PFO Occluder

Catalogue No.	Device Size	C LA Disc Diameter (mm)	B RA Disc Diameter (mm)	A Waist Diameter (mm)	H Waist Length (mm)
LYKFDQ- I 1818	1818	18	18	3.5	6.0
LYKFDQ- I 1824	1824	18	24	4.0	7.0
LYKFDQ- I 2424	2424	24	24	4.0	7.0
LYKFDQ- I 2228	2228	22	28	4.5	7.0
LYKFDQ- I 2828	2828	28	28	4.5	7.0
LYKFDQ- I 2534	2534	25	34	5.0	7.0
LYKFDQ- I 3434	3434	34	34	5.0	7.0

Hubless PFO Occluder

Catalogue No.	Device Size	C LA Disc Diameter (mm)	B RA Disc Diameter (mm)	A Waist Diameter (mm)	H Waist Length (mm)
WTLYKFDQ- I 1818	1818	18	18	3.5	6.0
WTLYKFDQ- I 1824	1824	18	24	4.0	7.0
WTLYKFDQ- I 2424	2424	24	24	4.0	7.0
WTLYKFDQ- I 2228	2228	22	28	4.5	7.0
WTLYKFDQ- I 2828	2828	28	28	4.5	7.0
WTLYKFDQ- I 2534	2534	25	34	5.0	7.0
WTLYKFDQ- I 3434	3434	34	34	5.0	7.0




MemoPart™

Plug



Vascular Plug



Hubless
Vascular Plug

MemoPart™ Plug is a percutaneous, transcatheter device applied to the closure of a wide variety of veins and arteries, reducing or eliminating blood flow by blocking the target vessel. The vascular plug can be used for the patients with clinical symptoms of abnormal blood vessels, such as:

- Aortopulmonary collaterals
- Arteriovenous malformation
- Surgical aortopulmonary shunts
- Anomalous venovenous connections
- Arteriovenous fistulas
- Peripheral vessels

Ordering Information

Vascular Plug


Catalogue No.	Device Size	A Waist Diameter (mm)	B Waist Length (mm)
XGSFDQ- I 04	04	4	5.0
XGSFDQ- I 06	06	6	6.5
XGSFDQ- I 08	08	8	7.5
XGSFDQ- I 10	10	10	8.5
XGSFDQ- I 12	12	12	9.5
XGSFDQ- I 14	14	14	10.5
XGSFDQ- I 16	16	16	11.0
XGSFDQ- I 18	18	18	11.0
XGSFDQ- I 20	20	20	12.0
XGSFDQ- I 22	22	22	13.0

Hubless Vascular Plug

Catalogue No.	Device Size	A Waist Diameter (mm)	B Waist Length (mm)
WTXGSFDQ- I 04	04	4	5.0
WTXGSFDQ- I 06	06	6	6.5
WTXGSFDQ- I 08	08	8	7.5
WTXGSFDQ- I 10	10	10	8.5
WTXGSFDQ- I 12	12	12	9.5
WTXGSFDQ- I 14	14	14	10.5
WTXGSFDQ- I 16	16	16	11.0
WTXGSFDQ- I 18	18	18	11.0
WTXGSFDQ- I 20	20	20	12.0
WTXGSFDQ- I 22	22	22	13.0

MemoPart™

Occluder Delivery
System



- Two different lengths of the sheath for adults and children.
- Anti-kink delivery system is also available for VSD occluders.

The delivery system includes:

- Loader (1)
- Long Sheath (1)
- Dilator (1)
- Pusher (1)
- Y-connector with tubing (1)

Ordering Information

Delivery System for Adult ASD and PFO Occluders

Catalogue No.	Loader		Long sheath			Dilator	Pusher	
	I.D. (mm)	Effective Length (mm)	I.D. (mm)	Effective Length (mm)	Angle		Effective Length (mm)	Diameter (mm)
ODS-A-I-5F	5F/1.85	130	5F/1.85	800	45°	920	1200	1.4
ODS-A-I-6F	6F/2.0	130	6F/2.0	800	45°	920	1200	1.6
ODS-A-I-7F	7F/2.33	130	7F/2.33	800	45°	920	1200	1.8
ODS-A-I-8F	8F/2.67	130	8F/2.67	800	45°	920	1200	1.8
ODS-A-I-9F	9F/3.0	130	9F/3.0	800	45°	920	1200	1.8
ODS-A-I-10F	10F/3.33	130	10F/3.33	800	45°	920	1200	1.9
ODS-A-I-12F	12F/4.0	160	12F/4.0	800	45°	920	1200	2.0
ODS-A-I-14F	14F/4.67	160	14F/4.67	800	45°	920	1200	2.0

MemoPart™

Snare



MemoPart™ Snare is composed by Nitinol coated Tungsten coil and the Nitinol shaft, which provides great radiopacity, biocompatibility and shape memory ability. This is a widely used device to:

- Establish the femoral artery-vein loop
- Retrieve the dislocated occluder
- Retrieve stent or guide wire
- Retrieve the blood filter
- Help with control navigation, etc.

Ordering Information

Catalogue No.	Effective Length (mm)	Diameter of Snare Circle (mm)	Angle
Snare-15	1240	15	90°
Snare-20	1240	20	90°

Delivery System for Adult VSD, PDA Occluders and Plug

Catalogue No.	Loader		Long sheath			Dilator	Pusher	
	I.D. (mm)	Effective Length (mm)	I.D. (mm)	Effective Length (mm)	Angle		Effective Length (mm)	Diameter (mm)
ODS-P/V-II-5F	5F/1.85	130	5F/1.85	800	180°	920	1200	1.4
ODS-P/V-II-6F	6F/2.0	130	6F/2.0	800	180°	920	1200	1.6
ODS-P/V-II-7F	7F/2.33	130	7F/2.33	800	180°	920	1200	1.8
ODS-P/V-II-8F	8F/2.67	130	8F/2.67	800	180°	920	1200	1.8
ODS-P/V-II-9F	9F/3.0	130	9F/3.0	800	180°	920	1200	1.8
ODS-P/V-II-10F	10F/3.33	130	10F/3.33	800	180°	920	1200	1.9
ODS-P/V-II-12F	12F/4.0	160	12F/4.0	800	180°	920	1200	2.0
ODS-P/V-II-14F	14F/4.67	160	14F/4.67	800	180°	920	1200	2.0

Delivery System for Children ASD and PFO Occluders

Catalogue No.	Loader		Long sheath			Dilator	Pusher	
	I.D. (mm)	Effective Length (mm)	I.D. (mm)	Effective Length (mm)	Angle		Effective Length (mm)	Diameter (mm)
ODS-A-III-5F	5F/1.85	130	5F/1.85	600	45°	680	1200	1.4
ODS-A-III-6F	6F/2.0	130	6F/2.0	600	45°	680	1200	1.6
ODS-A-III-7F	7F/2.33	130	7F/2.33	600	45°	680	1200	1.8
ODS-A-III-8F	8F/2.67	130	8F/2.67	600	45°	680	1200	1.8
ODS-A-III-9F	9F/3.0	130	9F/3.0	600	45°	680	1200	1.8
ODS-A-III-10F	10F/3.33	130	10F/3.33	600	45°	680	1200	1.9
ODS-A-III-12F	12F/4.0	160	12F/4.0	600	45°	680	1200	2.0
ODS-A-III-14F	14F/4.67	160	14F/4.67	600	45°	680	1200	2.0

Delivery System for Children VSD, PDA Occluders and Plug

Catalogue No.	Loader		Long sheath			Dilator	Pusher	
	I.D. (mm)	Effective Length (mm)	I.D. (mm)	Effective Length (mm)	Angle		Effective Length (mm)	Diameter (mm)
ODS-P/V-IV-5F	5F/1.85	130	5F/1.85	600	180°	680	1200	1.4
ODS-P/V-IV-6F	6F/2.0	130	6F/2.0	600	180°	680	1200	1.6
ODS-P/V-IV-7F	7F/2.33	130	7F/2.33	600	180°	680	1200	1.8
ODS-P/V-IV-8F	8F/2.67	130	8F/2.67	600	180°	680	1200	1.8
ODS-P/V-IV-9F	9F/3.0	130	9F/3.0	600	180°	680	1200	1.8
ODS-P/V-IV-10F	10F/3.33	130	10F/3.33	600	180°	680	1200	1.9
ODS-P/V-IV-12F	12F/4.0	160	12F/4.0	600	180°	680	1200	2.0
ODS-P/V-IV-14F	14F/4.67	160	14F/4.67	600	180°	680	1200	2.0

GKS Bi-leaflet
Prosthetic
Heart Valve



High Performance Material

- The leaflets and hinge ring are made by pyrolytic carbon, which guarantees the excellent biocompatibility and superior safety.

Open Pivot Design

- Open pivot design ensures the sufficient blood washing to reduce the risk of thrombosis.
- This design reduces the shear stress that acts on the blood cells to minimize the damage.

85° Leaflet Opening

- The 85° leaflet opening provides improved laminar flow, reduces the turbulence, and optimizes the transvalvular gradients.

Suspending Leaflets

- Suspending leaflets design enables the fast open and close to guarantee the physiological needs.

Lower Noise

- Smooth buffering reduces the noise when the leaflets open and close, providing quieter impact for better life.

Ordering Information

Aortic Valves					
	Catalogue No.	Tissue Annulus Diameter (mm)	Orifice Inner Diameter (mm)	Geometric Orifice Area (cm ²)	Opening Angle
Standard Model - Intra Annular	GKS 19A	19.8	14.8	1.55	85°
	GKS 21A	21.8	16.8	2.02	85°
	GKS 23A	23.8	18.8	2.56	85°
	GKS 25A	25.8	20.8	3.17	85°
	GKS 27A	27.8	22.8	3.84	85°
Advanced Performance Model - Supra Annular	GKS 16AP	16.2	14.8	1.55	85°
	GKS 18AP	18.2	16.8	2.02	85°
	GKS 20AP	20.2	18.8	2.56	85°

Mitral Valves				
Catalogue No.	Tissue Annulus Diameter (mm)	Orifice Inner Diameter (mm)	Geometric Orifice Area (cm ²)	Opening Angle
GKS 23M	23.8	18.8	2.56	85°
GKS 25M	25.8	20.8	3.17	85°
GKS 27M	27.8	22.8	3.84	85°
GKS 29M	29.8	24.8	4.59	85°
GKS 31M	31.8	26.8	5.37	85°
GKS 33M	33.8	26.8	5.37	85°

05 / Surgical
Cardiology Products

Off-pump Coronary Artery Bypass Grafting

59 Disposable Tissue stabilizer

06

Cardiac Rhythm Management Products

Disposable
Tissue Stabilizer



Indication
Apply to off-pump coronary artery bypass graft (OPCABG), help with fixing the heart to minimize the influence of the surgery that caused by heart beating.

- Easy to set up
- Free to turn 360°
- Excellent flexibility and reliable stabilization
- Compatible with most of the sternal retractor in the market

Ordering Information

Catalogue No.	Application
SDTS001	Attached to pericardial tissue
SDTS002	Attached to heart apex

Notice: Please contact the sales for detailed information before placing the order.

- Pacemakers and Leads**
- 61 Implantable Single Chamber Pacemaker
 - 62 Implantable Dual Chamber Pacemaker
 - 63 Bipolar Passive Fixation Lead
 - 64 Bipolar Active Fixation Lead
- Equipment**
- 65 Dual Chamber Pacing System Programmer
 - 66 Dual Chamber Pacing System Analyzer

Implantable
Single Chamber
Pacemaker



- Patent technology of RF power supply provides safe program control without consuming the battery power.
- 9 technical parameters contribute to the accuracy of stored program control.
- Events counter and program control tests are convenient.
- Multiple protections effectively avoid the interference.
- Ergonomic design with small size, light weight and long lifetime.
- Compatible with the major programmers in the market.

Specifications

Connector	IS-1
Size	48.5mm x 41mm x 6mm
Weight	20.8g
Volume	8.8cm ³
Battery	1.0Ah, 2.8V
Battery Lifetime	10.2years (100% pace-making)

Technical Parameters

Parameter	Range
Pacing Mode	SSI /SST/SOO
Basic Rate (ppm)	30...(1)... 60 ...(1)...100...(10)...160
Max. Rate Limitation (ppm)	180
Pulse Amplitude (V)	0.1...(0.1)... 3.8 ...(0.1)...8.1
Pulse Width (ms)	0.06...(0.06)...0.18, 0.25...(0.06)... 0.37 ...(0.06)...0.79, 0.86...(0.06)...1.40, 1.47...(0.06)...1.59
Sensing Sensitivity (mV)	0.5...(0.5)... 2.5 ...(0.5)...10.0
Refractory Period (ms)	200...(25)... 325 ...(25)...500
Hysteresis (ms)	0 ...(50)...350
Pacing Polarity	Unipolar /Bipolar
Sensing Polarity	Unipolar /Bipolar

Note: Bold parameters are factory settings.

Ordering Information

Catalogue No.	2312M
---------------	-------

Notice: Please contact the sales for detailed information before placing the order.

Implantable
Dual Chamber
Pacemaker



- Chinese first dual-chamber pacemaker series with independent intellectual property.
- Patent technology of RF power supply provides safe program control without consuming the battery power.
- New generation programmer provides accurate control of the parameters.
- Imported lithium-iodine battery ensures the durable lifetime.
- Optimized ergonomic design makes it comfortable after implantation.
- Multiple protections effectively avoid the interference to guarantee the patients safety.

Technical Parameters

Parameter	Range
Pacing Mode	DDD (R)/VDD(R)/DDI(R)/DVI(R)/DOO(R)/AAI(R)/AAT(R)/AOO(R)/VVI(R)/VVT(R)/VOO(R)
Basic Rate (ppm)	30...(1)... 60 ...(1)...100...(10)...180
Ventricular Pulse Amplitude (V)	0.1...(0.1)... 3.6 ...(0.1)...8.1
Ventricular Pulse Width (ms)	0.06...(0.06)...0.24, 0.31...(0.06)... 0.37 ...(0.06)...0.85, 0.92...(0.06)...1.46, 1.53
Ventricular Sensing Sensitivity (mV)	0.5...(0.5)... 2.5 ...(0.5)...10.0
Ventricular Refractory Period (ms)	150...(25)... 250 ...(25)...500
Hysteresis (ms)	0 ...(50)...350
Ventricular Pacing Polarity	Unipolar /Bipolar
Ventricular Sensing Polarity	Unipolar /Bipolar
Atrial Pulse Amplitude (V)	0.1...(0.1)... 3.6 ...(0.1)...8.1
Atrial Pulse Width (ms)	0.06...(0.06)...0.24, 0.31...(0.06)... 0.37 ...(0.06)...0.85, 0.92...(0.06)...1.46, 1.53
Atrial Sensing Sensitivity (mV)	0.25...(0.25)... 1.0 ...(0.25)...5.0
Postventricular Atrial Refractory Period (PVARP) (ms)	150...(25)... 250 ...(25)...500
AV Period (ms)	30...(10)... 180 ...(10)...350
Atrial Refractory Period Extended (ms)	0 ...(25)...350
Sensor	Accelerometer


Note: Bold parameters are factory settings.

Ordering Information

Catalogue No.	8631DR	8631D
---------------	--------	-------

Notice: Please contact the sales for detailed information before placing the order.

Bipolar
Passive Fixation
Lead



Technical Parameters


Lead Type	Bipolar, Passive fixation, Drug releasing
Drug Containing	Dexamethasone sodium phosphate (0.75mg)
Application	Ventricle / Atrium
Lead Connector	IS-1 BI
Length	45cm / 53cm / 60cm
Diameter	1.9mm
Minimum Introducer Compatibility	7F
Tip Electrode Surface Area	3.4mm ²
Electrode Space	13mm
Electrode Material (Cathode)	Pt-Ir
Conductor Material	MP35N
Insulator Material	Medical silicone rubber

Ordering Information

Catalogue No.	Length (cm)	Lead Type	Application
7231-45	45	Passive	Ventricle
7231-53	53		
7231-60	60		
7222-45	45	Passive	Atrium
7222-53	53		
7222-60	60		

Notice: Please contact the sales for detailed information before placing the order.

Bipolar
Active Fixation
Lead



Technical Parameters

Lead Type	Bipolar, Active fixation, Drug releasing
Drug Containing	Dexamethasone sodium phosphate (0.75mg)
Application	Ventricle
Lead Connector	IS-1 BI
Length	45cm / 53cm / 60cm
Diameter	2.1mm
Minimum Introducer Compatibility	7F
Tip Electrode Surface Area	6.8mm ²
Electrode Space	10mm
Electrode Material (Cathode)	Pt-Ir
Conductor Material	MP35N
Insulator Material	Medical silicone rubber

Ordering Information

Catalogue No.	Length (cm)	Lead Type	Application
7211-45	45	Active	Ventricle
7211-53	53		
7211-60	60		

Notice: Please contact the sales for detailed information before placing the order.

Dual Chamber
Pacing System
Programmer



- 12" LCD touch screen
- User-friendly UI design
- Display of intracardiac electrogram
- Scroll display of electrocardiosignal
- Storage of follow-up data

Ordering Information

Catalogue No.	QM8631
---------------	--------

Notice: Please contact the sales for detailed information before placing the order.

Dual Chamber
Pacing System
Analyzer



Pacing System Analysis

- 10 types of testing modes
- One-key test design
- High precision of pacing threshold testing
- Exact adjustments of pacing parameters
- Real-time ECG

Pacemaker Testing

- One-key test of pacemaker basic parameters
- Global waveforms of sensitivity test

Built-in printer, self-check and self-test are available

Technical Parameters


Parameter	Range	Step
Basic Rate (ppm)	31-180 (Dual chamber 31-90)	1
Pacing Interval (ms)	333-1935 (Dual chamber 667-1935)	1
Max. Rate Limitation (ppm)	100-180 (Only for dual chamber DDD/VDD)	1
Pulse Amplitude (V)	0.10-10.0	0.1
Pulse Width (ms)	0.05-2.50	0.01
Sensing Sensitivity (mV)	0.5-10.0	0.25
Refractory Period (ms)	200-500	25
A-V Interval (ms)	50-300 (Only for dual chamber pacing mode)	1
Hysteresis (ms)	0-400	1
Quick Stimulate Rate (ppm)	31-800 (Dual chamber 31-350)	1
Pacing Mode	VVI/VVT/VOO/AAI/AAT AOO/DDD/DVI/DOO/VDD	/

Ordering Information

Catalogue No.	QM2352A
---------------	---------

Notice: Please contact the sales for detailed information before placing the order.

07 Critical Care Products



IV Catheters

- 69 Safecath™ Disposable Central Venous Catheter Kit
- 71 Antimicrobial Central Venous Catheter Kit

Needle-free Connectors

- 73 Needle-free Connectors

Blood Sampler

- 75 Disposable Arterial Blood Sampler

Pressure Transducer

- 76 Disposable Blood Pressure Transducer

Safecath™

Disposable Central
Venous Catheter Kit



- The latex-free material provides excellent safety.
- Excellent radiopacity of the catheter makes it easier and safer for operation.
- Soft blue tip provides less harm to the vessel, makes it easier to enter into the puncture point.
- The patented design of the connector makes it smooth and firm, effectively prevent the product from infection, leakage and shedding.
- The transparent extension tubes with detachable clamps and printed marks allow to maintain the catheter away from the insertion site, reduce the risk of air embolism.
- Standard package and full package of the CVC Kit are available.

Standard Package:

- Central Venous Catheter (1)
- Guide Wire (1)
- Tissue Dilator (1)
- Scalpel (1)
- Introducer Needle / Y-Shape Needle (1)
- Blue Introducer Syringe (1/0)
- Syringe with Needle (1/2)
- Heparin Cap (1/2/3)
- Catheter Fastener (1)
- Extension Line Clamp (1/2/3)

Full Package:

- Central Venous Catheter (1)
- Guide Wire (1)
- Tissue Dilator (1)
- Scalpel (1)
- Introducer Needle / Y-Shape Needle (1)
- Blue Introducer Syringe (1/0)
- Syringe with Needle (1/2)
- Heparin Cap (1/2/3)
- Catheter Fastener (1)
- Extension Line Clamp (1/2/3)
- Gauze Pad (2)
- Prep Sponge Swab (3)
- Applicator case (2)
- Silk Suture with Straight and Bended Needles (2)
- Wound Closure Strip (1)
- Dressings (1)
- Fenestrated Drape (1)
- Small Drape (1)
- Middle Drape (1)
- Gloves (1)



Ordering Information

Central Venous Catheter			
Catalogue No.	Lumen Type	Catheter Size	Catheter Length (cm)
MMCVCBJ1-14-15	Single-lumen	14G	15
MMCVCBJ1-14-20	Single-lumen	14G	20
MMCVCBJ1-14-30	Single-lumen	14G	30
MMCVCBJ1-16-15	Single-lumen	16G	15
MMCVCBJ1-16-20	Single-lumen	16G	20
MMCVCBJ1-16-30	Single-lumen	16G	30
MMCVCBJ1-18-15	Single-lumen	18G	15
MMCVCBJ1-18-20	Single-lumen	18G	20
MMCVCBJ1-18-30	Single-lumen	18G	30
MMCVCBJ1-20-13	Single-lumen	20G	13
MMCVCBJ1-20-20	Single-lumen	20G	20
MMCVCBJ2-40-05	Double-lumen	4F	5
MMCVCBJ2-40-08	Double-lumen	4F	8
MMCVCBJ2-40-13	Double-lumen	4F	13
MMCVCBJ2-50-08	Double-lumen	5F	8
MMCVCBJ2-50-13	Double-lumen	5F	13
MMCVCBJ2-50-20	Double-lumen	5F	20
MMCVCBJ2-70-15	Double-lumen	7F	15
MMCVCBJ2-70-20	Double-lumen	7F	20
MMCVCBJ2-70-30	Double-lumen	7F	30
MMCVCBJ2-70-50	Double-lumen	7F	50
MMCVCBJ3-55-08	Triple-lumen	5.5F	8
MMCVCBJ3-55-13	Triple-lumen	5.5F	13
MMCVCBJ3-70-15	Triple-lumen	7F	15
MMCVCBJ3-70-20	Triple-lumen	7F	20
MMCVCBJ3-70-30	Triple-lumen	7F	30

Hemodialysis Catheter*			
Catalogue No.	Lumen Type	Catheter Size	Catheter Length (cm)
MMCVCBJ2-115-13	Double-lumen	11.5F	13
MMCVCBJ2-115-16	Double-lumen	11.5F	16
MMCVCBJ2-115-20	Double-lumen	11.5F	20

Peripheral Inserted Central Catheter*			
Catalogue No.	Lumen Type	Catheter Size	Catheter Length (cm)
MMCVCBJ1-40-45	Single-lumen	4F	45
MMCVCBJ1-40-60	Single-lumen	4F	60
MMCVCBJ1-50-45	Single-lumen	5F	45
MMCVCBJ1-50-60	Single-lumen	5F	60

* Notice: More specifications are available for Hemodialysis Catheter and Peripheral Inserted Central Catheter. Please contact the sales for detailed information before placing the order.



Antimicrobial
Central Venous
Catheter Kit

Safecath Plus



- Antimicrobial coating of Minocycline and Rifampicin effectively prevents the catheter related bloodstream infection (CRBSI).
- Gradually released drug coating after implantation guarantees the durable and reliable antibacterial performance.
- Standard package and full package of the antimicrobial CVC Kit are available.

Standard Package:

- Antimicrobial Central Venous Catheter (1)
- Guide Wire (1)
- Tissue Dilator (1)
- Scalpel (1)
- Introducer Needle / Y-Shape Needle (1)
- Blue Introducer Syringe (1/0)
- Syringe with Needle (1/2)
- Heparin Cap (1/2/3)
- Catheter Fastener (1)
- Extension Line Clamp (1/2/3)

Full Package:

- Antimicrobial Central Venous Catheter (1)
- Guide Wire (1)
- Tissue Dilator (1)
- Scalpel (1)
- Introducer Needle / Y-Shape Needle (1)
- Blue Introducer Syringe (1/0)
- Syringe with Needle (1/2)
- Heparin Cap (1/2/3)
- Catheter Fastener (1)
- Extension Line Clamp (1/2/3)
- Gauze Pad (2)
- Prep Sponge Swab (3)
- Applicator case (2)
- Silk Suture with Straight and Bended Needles (2)
- Wound Closure Strip (1)
- Dressings (1)
- Fenestrated Drape (1)
- Small Drape (1)
- Middle Drape (1)
- Gloves (1)



Ordering Information

Catalogue No.	Lumen Type	Catheter Size	Catheter Length (cm)
LPPCVC1-14-15	Single-lumen	14G	15
LPPCVC1-14-20	Single-lumen	14G	20
LPPCVC1-14-30	Single-lumen	14G	30
LPPCVC1-16-15	Single-lumen	16G	15
LPPCVC1-16-20	Single-lumen	16G	20
LPPCVC1-16-30	Single-lumen	16G	30
LPPCVC1-18-15	Single-lumen	18G	15
LPPCVC1-18-20	Single-lumen	18G	20
LPPCVC1-18-30	Single-lumen	18G	30
LPPCVC1-20-13	Single-lumen	20G	13
LPPCVC1-20-20	Single-lumen	20G	20
LPPCVC2-40-05	Double-lumen	4F	5
LPPCVC2-40-08	Double-lumen	4F	8
LPPCVC2-40-13	Double-lumen	4F	13
LPPCVC2-50-05	Double-lumen	5F	5
LPPCVC2-50-08	Double-lumen	5F	8
LPPCVC2-50-13	Double-lumen	5F	13
LPPCVC2-50-20	Double-lumen	5F	20
LPPCVC2-70-15	Double-lumen	7F	15
LPPCVC2-70-20	Double-lumen	7F	20
LPPCVC2-70-30	Double-lumen	7F	30
LPPCVC2-70-50	Double-lumen	7F	50
LPPCVC3-55-08	Triple-lumen	5.5F	8
LPPCVC3-55-13	Triple-lumen	5.5F	13
LPPCVC3-70-15	Triple-lumen	7F	15
LPPCVC3-70-20	Triple-lumen	7F	20
LPPCVC3-70-30	Triple-lumen	7F	30

Hemodialysis Catheter

Catalogue No.	Lumen Type	Catheter Size	Catheter Length (cm)
LPPCVC2-115-15	Double-lumen	11.5F	15
LPPCVC2-115-20	Double-lumen	11.5F	20

Notice: Please contact the sales for detailed information before placing the order.

Needle-free
Connectors

CE



- Metal-free design ensures the compatibility of MRI.
- The smooth and flat top can be effectively sterilized, inhibiting the growth of bacteria.
- Small dead space ensures the accuracy of drug dosage, avoiding the waste of expensive drugs.
- The positive pressure design effectively prevents the blood reflux, and avoids clotting inside the tube.
- This connector is available for all kinds of standard medical accessories.

Technical Parameters

Average Flow Rate	240 - 250mL/min
Average Positive Pressure Volume	0.05mL
Dead Space Volume	< 0.2mL

Ordering information

Catalogue No.	Positive Pressure or Not	Extension Tubing Length (cm)
LP-JZ-10	Yes	/
LP-JZ-10X	Yes	20



- Tiny size, easy to be fixed, and convenient to manipulate.
- The whole connector is made of antibacterial material, which ensures the inner aseptic condition, inhibits the growth of bacteria, and avoids the infection effectively.
- Small dead space ensures the accuracy of drug dosage, avoiding the waste of expensive drugs.
- The positive pressure design effectively prevents the blood reflux, and avoids clotting inside the tube.
- This connector is available for all kinds of standard medical accessories.

Technical Parameters

Average Flow Rate	120 - 180mL/min
Average Positive Pressure Volume	0.05mL
Dead Space Volume	< 0.06mL

Ordering information

Catalogue No.	Positive Pressure or Not	Extension Tubing Length (cm)
LP-JZ-11	Yes	/
LP-JZ-11X	Yes	20

- High flow rate. Maximum flow rate reaches up to 540mL/min. It enable to transfer high viscosity nutrient solution and blood products with higher flow rate.
- Excellent safety. Split-septum design guarantees no air gap at the edges of the split-septum Luer access, which allows the seamless joint with syringe to reduce infection.
- Effective drug delivery. The zero dead space and straight fluid channel avoid the residual blood and drug.
- Better visibility. Transparent design and tiny size make it easy to manipulate.
- Multi-function. This access can be applied to blood sampling.

Ordering information

Catalogue No.	Positive Pressure or Not	Extension Tubing Length (cm)
LP-JP-11	No	/
LP-JP-11X	No	20



Disposable
Arterial Blood
Sampler



Standard Type

- Two sampling methods: Preset Type / Pumping Type
- The syringe plunger is made of anti-tear, high-elastic ventilated silicon membrane, which ensures its excellent sliding performance and reduce the leakage at the same time.
- The unique build-in ventilated plunger could expel the residual air automatically, then self-seal when touching with blood so that the blood sample could be sealed effectively.
- The special technique of heparin coating inside the syringe ensures the sufficient mixture of heparin and blood, providing more accurate result.
- The sealing cap design could seal the sampler completely, totally avoid test error caused by the mixed air, and provide better condition for sample's storage and transportation.

Ordering information

Standard Type						
Catalogue No.	Syringe Volume (mL)	Recommended Fill Volume (mL)	Units of Heparin (IU)	Gauge	Needle Length (mm)	Applications
007-2232	3	1 (1.6 max.)	80	22G	32	Adult femoral artery
007-2225	3	1 (1.6 max.)	80	22G	25	Adult radial artery
007-2315	3	1 (1.6 max.)	80	23G	15	Children
007-2615	3	1 (1.6 max.)	80	26G	15	Infant
007-0000	3	1 (1.6 max.)	80	/	/	Without needle

Safety Type

- Same syringe with standard type.
- Special structure makes the safety shield an integral part of the needle.
- Fully integrated shield offers enhanced safety for healthcare operators.
- Single-handed activation of the safety design provides simple and safe manipulation.
- After taking the blood sample, push or knock the shield gently to lock.
- The shield engages over the needle with an audible click and irreversibly locking, which avoids other people's injuries if the needle is exposed.

Ordering information

Safety Type						
Catalogue No.	Syringe Volume (mL)	Recommended Fill Volume (mL)	Units of Heparin (IU)	Gauge	Needle Length (mm)	Applications
007-2232(S)	3	1 (1.6 max.)	80	22G	32	Adult femoral artery
007-2225(S)	3	1 (1.6 max.)	80	22G	25	Adult radial artery
007-2315(S)	3	1 (1.6 max.)	80	23G	15	Children
007-2615(S)	3	1 (1.6 max.)	80	26G	15	Infant

Disposable
Blood Pressure
Transducer

CE



- Continuously auto-monitoring of the real-time hemodynamic changes guarantees the accurate measurement.
- Advanced CMOS chip provides superior sensitivity.
- Multiple types of popular connectors are suitable for most of the monitors in the market.

Technical Parameters

Connector	Utah/Edwards/Abbot/BD/Philips/Crystal/Plate Connectors
Flush Speed	(3±1)ml/h/300mmHg
Pressure Measurement Range	-30~300mmHg
Sensitivity	5.0µv/v/mmHg ± 1%
Zero Drift	±10mmHg
Current Leakage	≤ 10µA
Marker	Artery-red / Vena-blue

Ordering information

Catalogue No.	Channel Type	Catheter Length (cm)
MMBPTSA20	Single channel	20
MMBPTSA30	Single channel	30
MMBPTSB20	Double channel	20
MMBPTSB30	Double channel	30
MMBPTSC20	Triple channel	20
MMBPTSC30	Triple channel	30



08

In Vitro Diagnostic Products



IVD Equipment and Biomarkers

- 79 LEPU Quant 800 Colloidal Gold Immunochromatographic Assay Analyzer CE
- 79 Thrombelastography CE
- 80 Biomarkers CE



LEPU Quant 800
Colloidal Gold
Immunochromatographic
Assay Analyzer



Fast

- Result is available in 15 minutes.

Accurate

- Patent analyzing technology guarantees the accurate results.

Convenient

- Whole blood can be used directly without centrifugation.
- Full set of diagnostic covers forecast, diagnosis and prognosis.
- 7" touch screen with great touch feeling and simple graphic interface.
- Built-in lithium battery and printer provide high movability for first aid and ambulance.
- Pocketable size makes it convenient to take along.
- Internal and external modes for different clinical needs.
- Available to connect with LIS/HIS for visual results.

Applications

- Community Hospitals
- First Aid & Ambulance
- ICU/CCU
- Clinical Laboratory
- Department of Emergency
- Department of Cardiology
- Department of Respiration
- Department of Thoracic Surgery

Suitable for patients with

- Symptoms of chest pain, stuffy or dyspnea
- High risk of cardiovascular disease
- Bacterial infection or sepsis

Ordering Information

Catalogue No.	Quant 800
---------------	-----------

Thrombelastography



Antiplatelet Drugs (1 test/box)

- Platelet Mapping Assay Kit – ADP pathway of platelet activation
- Platelet Mapping Assay Kit – ADP and AA pathways of platelet activation
- Platelet Mapping Assay Kit – AA pathway of platelet activation

Heparin Residues (5 tests/box)

- Disposable Heparinase Cups and Assay Kits (method for determination of viscosity)

The Whole Picture of the Blood Hemostasis Process (10 tests/box)

- Ordinary Cups and Assay Kits (method for determination of viscosity).
- Provide comprehensive whole blood hemostasis testing that can help to identify bleeding and thrombosis risks.
- Monitor anti-thrombotic therapies.
- Help doctors to identify the bleeding and thrombosis risks, and deliver more targeted treatments.
- Through usage of the Platelet Mapping Assay, the device can help to provide a picture ("tracing") of patients' potential response to antiplatelet therapy which is relative to their overall hemostasis.
- Two independent sample channels.

Ordering Information


Catalogue No.	CFMS LEPU-8800
---------------	----------------



Biomarkers



- High stability, the accuracy is more than 98%.
- Whole blood can be applied directly without centrifugation.
- High purity antibody ensures the high specificity and sensitivity.
- Imported chromatographic membrane provides clear background with uniform chromatographic.
- Unique usage of h-FABP ensures the reliable result based on the outstanding specificity and earlier increased concentration.



Technical Parameters

Biomarker	Corresponding Disease	Inspection Scope	Testing Threshold
h-FABP	Myocardial Infarction	2.5-50ng/ml	7ng/ml
cTnI	Myocardial Infarction	0.5-50ng/ml	0.5ng/ml
cTnI/h-FABP	Myocardial Infarction	cTnI: 0.5-50ng/ml h-FABP: 2.5-50ng/ml	cTnI: 0.5ng/ml h-FABP: 7ng/ml
cTnI/Myo/CK-MB	Myocardial Infarction	cTnI: 0.5-50ng/ml Myo: 25-500ng/ml CK-MB: 2.5-300ng/ml	cTnI: 0.5ng/ml Myo: 50ng/ml CK-MB: 5ng/ml
NT-proBNP	Heart Failure	0.1-10ng/ml	Low: 0.3ng/ml High: 1.8ng/ml
D-Dimer	Thrombus	200-5000ng/ml	500ng/ml
MPO	Inflammation	25-500ng/ml	50ng/ml
CRP	Inflammation	0.5-100µg/ml	10µg/ml
PCT	Inflammation Bacterial Infection Sepsis	0.1-50ng/ml	0.25ng/ml

Ordering Information

h-FABP quantitative cassette	NT-proBNP one step test cassette
cTnI quantitative cassette	D-Dimer one step test cassette
cTnI/h-FABP one step test cassette	MPO one step test cassette
cTnI/Myo/CK-MB one step test cassette	CRP quantitative cassette
	PCT quantitative cassette

A large, white, C-arm style medical imaging system is shown in the foreground, angled towards the right. In the background, another similar system is visible, and a patient table with a control panel is partially seen. The background is a soft, out-of-focus light blue.

09

Digital Subtraction Angiography System

Suspended Type

83 Vicor-CV300 Digital Subtraction Angiography System

Floor Type

84 Vicor-CV100 Digital Subtraction Angiography System

Vicor-CV300

Digital Subtraction
Angiography System



Vicor-CV300 provides all-electric control experience and comprehensive clinical applications to satisfy with multiple interventions in surgery and interventional radiology such as cardiovascular, neurovascular and peripheral vascular diagnosis and treatments.

- Ceiling-suspended structure with five degrees of freedom
- Advanced images chain configuration
- Imported X-ray tube
- High-resolution images

Three stages of protection ensure the safety of operation:

- Collision Detection System. The built-in 3D model simulator is able to monitor the status of the equipment to detect the distances of components, decelerating timely to avoid collision.
- Collision Brake System. Installed at the locations with high risk of collision. The system will automatically discontinue the movement to prevent damages.
- Movement Limitation Protection System. Each movement is protected by primary and secondary limitation protections to prevent over travel.

Movement Range:

The C-arm Opening Diameter: 1900mm

L-arm Rotating Range		-110°~110°
L-arm Longitudinal Movement		0~1900mm
L-arm at the Head End of Patient	LAO/RAO	135°/135°
	CRAN/CAUD	50°/90°
L-arm on the Right Side of Patient	LAO/RAO	90°/50°
	CRAN/CAUD	60°/60°
L-arm on the Left Side of Patient	LAO/RAO	50°/90°
	CRAN/CAUD	60°/60°
Source to Image-receptor Distance (SID)		850mm~1150mm
Catheter Bed		
Vertical Movement Range		725mm~1025mm
Longitudinal Movement Range		≥1200mm
Lateral Movement Range		-180mm~180mm

Ordering Information

Catalogue No.	Vicor-CV300
---------------	-------------

Vicor-CV100

Digital Subtraction
Angiography System



- Floor C Arm with multi-degree of freedom
- Varian digital flat panel detector
- Imported X-ray tube
- Advanced images chain configuration
- High-resolution images

Advanced digital imaging system:

- Super noise reduction filtration (SNRF): no damage to the image information; significantly increased signal to noise ratio (SNR) and decreased X-ray dosage for image capturing.
- Digital pattern recognition filtration (DPRF): intelligently recognized foreground image (contrast agent and interventional devices, etc.) for enhancement.
- Automatic density compensation filtration (ADCF): Automatic density equalization for background image to highlight the foreground image.

Three stages of protection ensure the safety of operation:

- Collision Detection System. The built-in 3D model simulator is able to monitor the status of the equipment to detect the distances of components, decelerating timely to avoid collision.
- Collision Brake System. Installed at the locations with high risk of collision. The system will automatically discontinue the movement to prevent damages.
- Movement Limitation Protection System. Each movement is protected by primary and secondary limitation protections to prevent over travel.

Movement Range:


L-arm Rotating Range		-90° ~ 90°
C-arm Movement Range	Longitudinal Rotating	-45° ~ 90°
	Transversal Rotating	-90° ~ 90°
Source to Image-receptor Distance (SID)		870mm ~ 1200mm
Catheter Bed		
Vertical Movement Range		780mm ~ 1100mm
Longitudinal Movement Range		≥ 1250mm
Lateral Movement Range		-150mm ~ 150mm

Ordering Information

Catalogue No.	Vicor-CV100
---------------	-------------

10

General Surgery Products



Surgical Staplers

- 87 Staplers CE
- 93 Disposable Skin Stapler and Remover CE
- 93 Disposable Purse String Stapler CE

Accessories

- 94 Disposable Suction and Irrigation Tube CE
- 94 Disposable Trocar and Veress Needle CE
- 95 Disposable Endoscopic Retrieval Bags CE

Staplers

CE

Disposable Circular Stapler



- Ultrathin anvil is more convenient for the procedure.
- Larger inner cutting diameter effectively minimizes anastomosis stenosis.
- Rational arrangement of staples reduces bleeding after procedure.
- High-quality titanium staple guarantees greater tension-resistance on anastomosis.

Ordering Information

Catalogue No.	Protector Color	O.D. (mm)	Cutting Diameter (mm)	Staple Height (mm)	Quantity of Staples
DH14	Orange	14	8.5	3.8	20
DH17	White	17	10	4.5	16
DH19	Black	19	12	4.5	18
DH21	Yellow	21	14	4.5	20
DH24	Grey	24	15	4.5	18
DH26	Red	26	17	4.5	20
DH29	Blue	29	20	4.8	24
DH32	Green	32	22	5.0	26
DH34	Purple	34	24	5.0	28

Disposable Double-hand Circular Stapler



- Ultrathin anvil and the scaled shaft make the procedure more convenient.
- Larger inner cutting diameter effectively minimizes anastomosis stenosis.
- Rational arrangement of staples reduces bleeding after procedure.
- Special safety design ensures the safe procedure.
- Butterfly-shape adjusting nut avoids slippery turning.

Ordering Information

Catalogue No.	Protector Color	O.D. (mm)	Cutting Diameter (mm)	Staple Height (mm)	Quantity of Staples
SGH14	Orange	14	8.5	3.8	20
SGH17	White	17	10	4.5	16
SGH19	Black	19	12	4.5	18
SGH21	Yellow	21	14	4.5	20
SGH24	Grey	24	15	4.5	18
SGH26	Red	26	17	5.0	20
SGH29	Blue	29	20	5.0	24
SGH32	Green	32	22	5.0	26
SGH34	Purple	34	24	5.0	28

Disposable Auto Linear Stapler and Cartridge



- Middle closing stage helps to adjust the thickness of tissue.
- Large opening space allows of better tissue arrangement.
- Auto-adjusting tissue press is convenient for one-hand manipulation.

Ordering Information

Catalogue No.	Cartridge Model	Cartridge Color	Suture Thickness (mm)	Staple Height (mm)
CKH303	CH303	Blue	1.5	3.8
CKH304	CH304	Green	2.0	4.5
CKH453	CH453	Blue	1.5	3.8
CKH454	CH454	Green	2.0	4.5
CKH603	CH603	Blue	1.5	3.8
CKH604	CH604	Green	2.0	4.5
CKH903	CH903	Blue	1.5	3.8
CKH904	CH904	Green	2.0	4.5

Disposable Double-hand Auto Linear Stapler and Cartridge



- Retaining pin avoids tissue over-flow.
- Automatic tissue clamping is easy for one-hand manipulation.
- Two triggers make it convenient for the operator and safe for the patient.

Ordering Information

Catalogue No.	Cartridge Model	Cartridge Color	Suture Thickness (mm)	Staple Height (mm)
SAF303	SF303	Blue	1.5	3.8
SAF304	SF304	Green	2.0	4.5
SAF453	SF453	Blue	1.5	3.8
SAF454	SF454	Green	2.0	4.5
SAF603	SF603	Blue	1.5	3.8
SAF604	SF604	Green	2.0	4.5
SAF903	SF903	Blue	1.5	3.8
SAF904	SF904	Green	2.0	4.5

Disposable Linear Stapler
and Cartridge



- Adjustable suture thickness
- Multiple sizes are available for different procedure requirements.

Ordering Information

Catalogue No.	Cartridge Model	Cartridge Color	Suture Thickness (mm)	Staple Height (mm)
HAF303	HF303	Blue	1.5	3.8
HAF304	HF304	Green	2.0	4.5
HAF453	HF453	Blue	1.5	3.8
HAF454	HF454	Green	2.0	4.5
HAF603	HF603	Blue	1.5	3.8
HAF604	HF604	Green	2.0	4.5
HAF903	HF903	Blue	1.5	3.8
HAF904	HF904	Green	2.0	4.5

Disposable Linear Cutter and Cartridge



- Reloadable for ten times
- Accurate positioning function avoids tissue damage.
- Multiple sizes are available for different procedure requirements.

Ordering Information

Catalogue No.	Cartridge Model	Cartridge Color	Cutting Length (mm)	Suture Length (mm)	Suture Thickness (mm)	Staple Height (mm)
GH553	GK553	Blue	55	57	1.5	3.85
GH554	GK554	Green	55	57	2.0	4.5
GH753	GK753	Blue	75	77	1.5	3.85
GH754	GK754	Green	75	77	2.0	4.5
GH1003	GK1003	Blue	100	102	1.5	3.85
GH1004	GK1004	Green	100	102	2.0	4.5

Disposable Linear Cutter
and Linear Cutter Cartridge



- Scalpel on the cartridge avoids cross infection.
- Integration design of the blade and cartridge creates better cutting performance.
- Large opening space allows of better tissue arrangement.

Ordering Information

Catalogue No.	Cartridge Model	Cartridge Color	Cutting Length (mm)	Suture Length (mm)	Suture Thickness (mm)	Staple Height (mm)
QAB603	QB603	Blue	60	65	1.5	3.85
QAB604	QB604	Green	60	65	2.0	4.5
QAB803	QB803	Blue	80	85	1.5	3.85
QAB804	QB804	Green	80	85	2.0	4.5

Disposable Curved Cutter Stapler



- Four curvilinear rows of staples with single cut contributes to the better performance.
- Lower pelvic access provides better procedure result.
- Simultaneous cutting and suturing simplify the resection of distal rectum.

Ordering Information

Catalogue No.	Suture Length (mm)	Staple Height (mm)	Quantity of Staples
QX45	48	4.5	46

Disposable Hemorrhoids Stapler
and Accessories



- Rational arrangement of staples reduces bleeding after procedure.
- Big volume of cartridge housing provides enough space for prolapsed tissue.
- Transparent anoscope with scales helps for better visibility.
- Adjustable cutting thickness allows of different prolapse situations.
- Non-slip adjusting nut provides better control.

Surgical Accessories:



Anorectal Introducer



Anorectal Dilator



Anorectal Transfixion Tool



Hook

Ordering Information

Catalogue No.	O.D. (mm)	Staple Height (mm)	Quantity of Staples
PAH32	32	3.8	30
PAH34	34	3.8	32
PAH36	36	3.8	34

Disposable Endo Linear Cutter Stapler
and Cartridge



Multiple choices for your requirements:

- Standard/short type of endocutter device
- Straight/rotatable type of cartridge
- Four staple heights are available

Scope of applications:

Suitable for tissue cutting under open surgery or endoscopic surgery include lungs, stomach, and intestines.

Contraindication:

Gastrointestinal submucosal edema, over thick muscular layer, poor healing capability, cancerous tissue residue.

Ordering Information

Catalogue No.		Cartridge Color	Staple Effective Length (mm)	Staple Height (mm)
Straight Type	Rotatable Type			
JQZ-30-2.5	JQD-30-2.5	White	30	2.5
JQZ-45-2.5	JQD-45-2.5	White	45	2.5
JQZ-45-3.5	JQD-45-3.5	Blue	45	3.5
JQZ-45-4.0	JQD-45-4.0	Golden	45	4.0
JQZ-45-4.8	JQD-45-4.8	Green	45	4.8
JQZ-60-2.5	JQD-60-2.5	White	60	2.5
JQZ-60-3.5	JQD-60-3.5	Blue	60	3.5
JQZ-60-4.0	JQD-60-4.0	Golden	60	4.0
JQZ-60-4.8	JQD-60-4.8	Green	60	4.8

Disposable
Skin Stapler
and Remover

CE



Skin Stapler

Staple Remover

Ordering Information

Catalogue No.	Cartridge Specifications (mm)	Staple Number	Staple Diameter (mm)	Staple Remover
PFW	7.0 × 4.5	15/25/35/45/55	0.6	PQW

Disposable
Purse String
Stapler

CE



- Preloaded purse needle and string makes it easy for the operators.
- Free of manual operation for purse string helps to reduce the risk of damage on surrounding tissue.

Ordering Information

Catalogue No.	Specification (mm)	Suture Length (mm)
CBHB-45	45	35
CBHB-65	65	56

Disposable
Suction and
Irrigation Tube

CE




Ordering Information

Catalogue No.	Cannula Diameter (mm)	Cannula Effective Length (mm)	Irrigation Tubing Length (mm)	Suction Tubing Length (mm)
BCX-330-II	5	330	600	2800
BCX-430-II	5	430	600	2800
BCX-330-III	5	330	2800	2800
BCX-430-III	5	430	2800	2800

Disposable
Trocars and
Veress Needle

CE



Trocar

Veress Needle

Ordering Information

Catalogue No.	Puncture Core Diameter (mm)	Puncture Core Length (mm)	Sheath I.D. (mm)	Sheath Length (mm)
BCW 5	5.5	200	5.8	100
BCW 10	10	200	10.5	100
BCW 11	11	200	11.4	100
BCW 12	12	200	12.8	100
BCW 13	13	200	13.5	100
BCW 15	15	200	15.6	100

Veress Needle Code No.	Needle Length (mm)	Needle O.D. (mm)	Needle I.D. (mm)
Y1	120	2.2	1.6
Y2	150	2.2	1.6

Disposable
Endoscopic
Retrieval Bags

CE



- Bag material of PU effectively prevent from osmosing of tissue fluid and remaining of tissue fragments during the procedure.
- Self-expanded bag makes it easy to collect the excision.
- “Up” marker on shaft indicates the direction of bag opening, which ensures safe operation.

Ordering Information

Catalogue No.	Type	Flat Width (mm)	Flat Depth (mm)	Shaft O.D. (mm)
QD-A-1	A	80	100	10
QD-A-2	A	90	190	10
QD-A-3	A	100	100	10
QD-A-4	A	100	150	10
QD-A-5	A	120	200	10
QD-A-6	A	170	240	12
QD-A-7	A	200	260	15
QD-B-1	B	80	100	10
QD-B-2	B	90	190	10
QD-B-3	B	100	100	10
QD-B-4	B	100	150	10
QD-B-5	B	120	200	10
QD-B-6	B	170	240	10
QD-B-7	B	200	260	10
QD-C-1	C	80	100	10
QD-C-2	C	90	190	10
QD-C-3	C	100	100	10
QD-C-4	C	100	150	10
QD-C-5	C	110	200	10
QD-C-6	C	170	240	10
QD-C-7	C	200	260	10
QD-C-8	C	95	195	10
QD-C-9	C	130	195	10
QD-C-10	C	160	200	10

Notice: OEM is available for this product.