

Camerano, April 2024

Certificate of Conformity

TWISTED SIGNAL CABLES

We, **ELAN s.r.l.**, **CERTIFY** that the cables marked with:

ELAN A.F. CEI 20-22 III – CEI 36762 C-4 (U₀=400V) – CE “data”



are manufactured in accordance with the following Standards:

CEI 20-11; CEI 20-29; CEI 20-20; CEI 20-22III (IEC 60332; BSEN 50265); CEI 36762

MANUFACTURING TECHNICAL FEATURES

1. UNIPOLAR WIRES:

The unipolar wires (0,50 – 1,00 – 1,50) are insulated in **PVC** type R2. They pass the test of voltage according to CEI 20-20 standard: 5 minutes with 2000 V. in dry current without any crack of insulation covering.

1. SHIELDING:

The shielding is made of:

- Coupled ribbon of aluminium/polyester foil 9/12 microns.
- Drainage wire in tinned copper braid conductor
- Polyester ribbon 12 micron thick, placed on joined cables according to CEI 46-5 standard.

2. JACKET:

The jacket in red colour is made of flexible PVC type RZ and flame retardant according to CEI 20/22-III (IEC 60332;BSEN 50265) Standard.

Alarm cables marked as C-4 (U₀=400V) owing to their technical characteristics and the positive results obtained by passing the tests and can be installed with electrical power cables marked both 450/750V, and 0,6/1 Kv according to CEI UNEL 36762.

Cristina Andreoni
CEO
Elan Srl



CANALE INTERRATO /
BURIED TROUGH



TUBO INTERRATO /
BURIED DUCT



INTERRATO CON
PROTEZIONE /
BURIED WITH
PROTECTION



INTERNO/
INDOOR



FIRE RETARDANT



CON CAVI ELETT.
WITH POWER CABLES