Paper suitable for offset printing. End use as newsletters, reports, product sheets and manuals.

| Technical information | | | | | | |
|--|------|------|------|------|------|------|
| Grammage, g/m ^{2,} ISO 536 | 70 | 80 | 90 | 100 | 115 | 130 |
| Thickness, µm, ISO 534 | 92 | 106 | 119 | 130 | 149 | 166 |
| Bulk, g/cm ³ , ISO 534 | 1,30 | 1,30 | 1,30 | 1,30 | 1,30 | 1,30 |
| Smoothness Bendtsen, ml/min ISO 8791-2 | 250 | 250 | 250 | 250 | 250 | 250 |
| Opacity, % ISO 2471 | 90 | 93 | 94 | 95 | 97 | 98 |
| CIE Whiteness, % ISO 11475 | 150 | 150 | 150 | 150 | 150 | 150 |
| ISO Brightness, % ISO 2470-2 | 105 | 105 | 105 | 105 | 105 | 105 |

Lumiset is labelled with the Nordic Ecolabel (Nordic Swan), licence No 3044 044 and the EU Ecolabel, licence No SE/011/001.

Nymölla Mill is certified according to ISO 9001 and ISO 14001 and EMAS registered (EU's Eco Management and Audit Scheme). The mill also has Chain of Custody certification according to FSC® (FSC® trademark license code: FSC® C015932) and PEFC™ logo license registration number: PEFC/02-31-86).

Product information: Date of issue February 15, 2023 Valid until an update is available, however only up to December 31, 2023

