Shunting System












Ventricular Catheter 01101

Barium-impregnated silicone catheter provides resistance to kinking and compression. Stainless steel stylet allows catheter to be directed during catheter placement. The catheter is fabricated from silicone elastomer tubing impregnated with barium to provide radiopacity.

- Barium impregnation allows for visualization of the catheter on x-ray.
- non-ferrous design won't interfere with CT scans or MRI.



Included with product

1ea. Ventricular Catheter Barium Impregnated

I.D.: 1.3 mm

O.D.: 2.5 mm

Length: 20 cm

1ea. Stainless Steel Stylet (20 cm)


Peritoneal Catheter (L.M. H) 03103, 03105

Peritoneal Catheter, Small, Barium Impregnated, 90cm, a pressure valve at the tip, 4 slit openings at the distal end. High, Medium, Low pressure are available according to the size of slit.



03103

I.D.: 1.3 mm /O.D.: 2.5 mm/Length: 75-100 cm



03105

I.D.: 1.3 mm /O.D.: 2.5 mm/Length: 90-100 cm

Features

- 1. Tubing impregnated with white barium to provide radiopacity.
- 2. Ppressure control valve.
- 3. Enable the surgeon to gauge and adjust its length.



CSF Valve Burr Hole (L.M. H) 02512, 02514

Two sizes are available: 12mm/14mm. (Pediatric/Adult) High, Medium, Low pressure are available.

Features

- 1.Flexible silicone elastomer eliminating valve sticking and deformation.
- 2.Connector included.
- 3.Internal flow path is uncomplicated.
- 4.Two-way flushing eliminates separate reservoirs or antechambers.
- 5. Non-metallic design will neo interfere with CT scans or MRI.
- 6.Polypropylene needle guard prevents complete penetration of the valve by needles.
- 7. Slicone elastomer dome is injectable.

