



HEXOL CA 2 STANDARD

GREASE

PRODUCT DESCRIPTION

HEXOL CA 2 Standard is a calcium-based general purpose, water resistant, lubricating grease. Produced from highly refined mineral oils and calcium thickener, with a well balanced additive package, it is suitable for lubricating points where, among water resistance, sealing ability is required, loads are moderate and the operating temperature does not exceed +60°C. Especially suitable for lubrication of pivots, joints in agriculture and industries where dust and water is typical.

PERFORMANCE FEATURES

- meets ISO 6743-9: L-X-BAHA 2; DIN 51502: K2C-20; NLGI 2 specifications;
- good water resistance;
- good lubricating characteristic;
- good sealing-ability;
- long-lasting corrosion protection.

APPLICATION

Suitable for lubricating points where, among water resistance, sealing ability is required and the operating temperature does not exceed +60°C. Recommended to be used with axles, joints, screw threads, small gear wheels and other mechanical parts exposed to water and dust.

PROPERTIES

Appearance	homogeneous
Dropping point [°C]	85
Penetration after 60 strokes at 25 °C [0,1 mm]	280
Corrosion at 100°C/24 h (steel)	pass
Corrosion at 60 °C/ 3 h (copper) [grade]	1
EMCOR test, distilled water [grade]	1

PACKAGING

<input checked="" type="checkbox"/> 0.4Kg	<input checked="" type="checkbox"/> 1Kg	<input checked="" type="checkbox"/> 4Kg	<input checked="" type="checkbox"/> 15Kg	<input checked="" type="checkbox"/> 180Kg		
<input type="checkbox"/> 0.23L	<input type="checkbox"/> 0.45L	<input type="checkbox"/> 0.5L	<input type="checkbox"/> 0.6L	<input type="checkbox"/> 0.9L	<input type="checkbox"/> 1L	<input type="checkbox"/> 3L
<input type="checkbox"/> 4L	<input type="checkbox"/> 5L	<input type="checkbox"/> 10L	<input type="checkbox"/> 20L	<input type="checkbox"/> 60L	<input type="checkbox"/> 208L	<input type="checkbox"/> 1000L

HEXOL INTERNATIONAL LTD