



with new
MPR system
Multi Purpose Rail

MAIN APPLICATIONS

Emergency Dept.

General Surgery

Gynecology

Neurosurgery

Obstetrics

Operating Theatre

Dental Practice

CE 0123

Available in its three configurations, BASIC, FS and FULL, NEW HOSPIVAC 350 has been designed for professional aspiration of bodily fluids, tissues or bones of patients during or after surgery. The state-of-the-art 60 l/min oilless and maintenance-free pump provides high performances with excellent suction capacities and max vacuum built up within a few seconds. A clear dashboard along with a full range of accessories and antistatic castors with brakes make it the ideal device for surgical suction. The new MPR (Multi Purpose Rail) system enhances the versatility of the Hospivac series for easy and quick exchange of different accessories, with no need for tools. In fact, being equipped with five connections, all CA-MI accessories can be easily accommodated, such as rings of various diameters to fit jars of different sizes and types (2L, 3L, 5L), cannula holders or a medical stainless steel rail where to hook any other type of accessory by means of clamps. The new safety trap bottle is also a new standard accessory in the Hospivac series.

The new safety trap bottle is also a new standard accessory in the Hospivac series, bringing up to three the overflow protection systems, besides the valve integrated in the jar and the hydrophobic filter, thus providing the Hospivac series with the highest standards of safety.

AVAILABLE MODELS AND ACCESSORIES INCLUDED	BASIC	FS	FULL
Liquid Collection Jar with overflow valve system (different options, see below)	2	2	2
Rings to accommodate jars (3 sizes depending on the jar)	2	2	2
Safety Trap Bottle (220ml)	1	1	2
Antibacterial & Hydrophobic Filter (single-patient)	1	1	2
Silicone Tubes \varnothing 8x14mm (autoclavable) - Patient Tube length 150cm	1	1	2
Conical Connector \varnothing 10-11-12mm	1	1	2
Air suction inlet	1	1	2
Footswitch with intermittent or continuous operation		1	1
Change-Over System from jar to jar by soft-touch keys			1
Power Cord with Schuko plug	1	1	1

OPTIONAL ACCESSORIES

Rings available in three sizes:

- 2000 ml autoclavable jars
- 2000 ml and 3000 ml Flovac® disposable systems
- 5000 ml autoclavable jars

Cannula holder to store safely suction tube during operation

Footswitch with vacuum regulation function

Silicone Fetal Vacuum Cups

Standard medical stainless steel rail (25x10 or 30x10) and clamps

TECHNICAL FEATURES

Motor	Oilless and maintenance-free piston pump
Power Feeding	220-230V / 50-60Hz or 110-127V / 60Hz
Max Vacuum (adjustable)	-0.90 bar -90 kPa -675 mmHg (value at sea level - different altitudes may affect it)
ISO 10079-1 Classification	HIGH VACUUM / HIGH FLOW
Max free air flow rate	60 l/min
Noise Level	51,7 dBA
Duty cycle	Non-stop operation
Weight	20 kg (unit alone without accessories)
Size	cm 46 x 42 x 85
Years of Warranty	2
Shipping carton	1
Place of Manufacturing	Italy

Italian
Medical
Touch
MADE IN ITALY

NEW HOSPIVAC 350		AUTOCLAVABLE JARS						DISPOSABLE LINERS		FOOT SWITCH	CHANGE OVER
		Makrolon® 2858 (max 121°C)		Polysulfone (PSU)		Apec® (max 143°C)		Flovac® systems			
REF.	MODEL	2 Jars 2000 ml	2 Jars 5000 ml	2 Jars 2000 ml	2 Jars 5000 ml	2 Jars 2000 ml	2 Jars 5000 ml	2 Jars 2000 ml	2 Jars 3000 ml		
RE 410356	BASIC 2										
RE 410356/06	FS 2										
RE 410356/01	FULL 2										
RE 410356/39	BASIC 5										
RE 410356/40	FS 5										
RE 410356/41	FULL 5										
RE 410356/59	BASIC PSU 2										
RE 410356/60	FS PSU 2										
RE 410356/61	FULL PSU 2										
RE 410356/62	BASIC PSU 5										
RE 410356/63	FS PSU 5										
RE 410356/64	FULL PSU 5										
RE 410356/56	BASIC AP 2										
RE 410356/38	FS AP 2										
RE 410356/55	FULL AP 2										
RE 410356/58	BASIC AP 5										
RE 410356/54	FS AP 5										
RE 410356/43	FULL AP 5										
RE 410356/27	BASIC FLOVAC 2										
RE 410356/29	FS FLOVAC 2										
RE 410356/28	FULL FLOVAC 2										
RE 410356/02	BASIC FLOVAC 3										
RE 410356/09	FS FLOVAC 3										
RE 410356/30	FULL FLOVAC 3										