

ТОВ «СП ЮКОЙЛ». Завод технічних олів.
 Україна, 09100, Київська обл., Білоцерківський р-н, місто Біла Церква, вул.Пулюя Івана, будинок 48-А
 Телефон приймальні: +38 (0612) 65 46 81
 Телефон ВТК: +38 (061) 222 80 25
 ЄДРПОУ 31852954



Випробувальна лабораторія ТОВ «СП ЮКОЙЛ» атестована на проведення вимірювань показників якості нафтопродуктів, технічних рідин та мастильних матеріалів. Свідоцтво про визнання технічної компетентності № АВ 43-22 від 22.11.2022р. видане ДП «ЗАПОРІЖЖЯСТАНДАРТМЕТРОЛОГІЯ», чинне до: 16.11.2024 р

Паспорт якості фасованої продукції №27091.01.01.1

Олива трансмісійна YUKO TRANS HD 75W-90 GL-5

ТУ У 19.2-31852954-115:2021

Виробник: ТОВ «СП ЮКОЙЛ»
 Розфасовано: ТОВ «СП ЮКОЙЛ» за ТУ У 23.2-31852954-027:2006
 Клас в'язкості: **SAE 75W-90**
 Клас експлуатаційних властивостей: **API GL-5**

Дата виготовлення: Липень 2023р.
 Тара: каністра 1л ПЕ
 Номер партії: 27091.06.07.23.01.

Ф.5 СТП014

Назва показника	Вимоги НД	Фактично	Метод випробувань
Густина при 20°C, кг/м ³	900	871,5	ГОСТ 3900 або ASTM D1298
В'язкість кінематична при 100°C, мм ² /с	13,5 - 18,5	16,17	ДСТУ ГОСТ 33 або ASTM D445
Індекс в'язкості, не менше	145	178	ДСТУ ГОСТ 25371 або ASTM D2270
Температура спалаху, визначена у відкритому тиглі, °C, не нижче	200	212	ДСТУ ГОСТ 4333 або ASTM D92
Температура застигання, °C, не вище	- 40	Мінус 42	ГОСТ 20287 або ASTM D97
Масова частка механічних домішок, %, не більше	Відсутність	Відсутність	ГОСТ 6370
Масова частка води, %, не більше	Сліди	Сліди	ГОСТ 2477 або ASTM D95
Масова частка сірки, %	Не менше 1,0	1,515	ГОСТ 1431 та ГОСТ 13538 або ASTM D6481 або ASTM D6443 або ASTM D4927
Випробування на корозію пластинок із сталі та міді	Витримує	Витримує	ГОСТ 2917 або ASTM D130
Трибологічні характеристики на 4-х кульковій машині при (20±5)°C:			ГОСТ 9490 [20] або ASTM D2783
- показник зношування при осьовому навантаженні 392Н, 1 год, мм, не більше	0,5	0,50	
- навантаження зварювання (Рзв), Н, не менше (для аналогу)	3 685	3 920	
Колір на колориметрі ЦНТ, одиниць ЦНТ, не більше	5,0	2,0	ГОСТ 20284 або ASTM D1500
Схильність до піноутворення, см ³ , не більше, при температурі:			ДСТУ 8420 або ASTM D892
- при 24°C	50	5	
- при 94°C	50	20	
- при 24°C після іспиту при 94°C	50	10	
Температура, за якої динамічна в'язкість не перевищує 150000 мПа·с, не вище (для аналогу)	Мінус 40	Мінус 40	ГОСТ 1929 або ASTM D2983


Паспорт якості дійсний тільки за наявності печатки.

Висновок: якість продукції відповідає вимогам ТУ У 19.2-31852954-115:2021 і ТУ У 23.2-31852954-027:2006

Гарантійний термін зберігання - 5 років
 М. П.

Начальник ВТК

Анна ПАРЧЕНКО



	<p style="text-align: center;">ALCO QUALITY ASSURANCE LABORATORY TEST REPORT</p> <p style="text-align: center;">Accreditation No: AZS ISO/IEC 17025:2020/AZ 01.0571.01.21</p>	 <p style="text-align: center;">AZERBAIJAN ACCREDITATION CENTER</p>
---	--	--

Company: ALCO LLC
3, Vali Mammadov st., Sabail dist.
AZ1095, Baku, Azerbaijan

Certificate No.: 2024624
Date of issue: 25/04/2024

Test sample

Product: AVTOIL 80W90 GL-5
Batch number: 2404624
Tank ID: T41.2

Manufacture date: 25/04/2024
Date of sampling: 25/04/2024
Date of analysis: 25/04/2024

Test result

Parameters	Unit	Test method	Limit	Test result	Conclusion
Appearance	-	Visual	Bright & Clear	Bright & Clear	Pass
Kinematic viscosity at 100 °C	mm ² /s	ASTM D445	13.5-18.5	14.69	Pass
Viscosity index	-	ASTM D2270	Min. 90	93	Pass
Water content	%	ASTM D95	Max. 0.05	None	Pass
Flash Point, COC	°C	ASTM D92	Min. 200	218	Pass
Pour Point	°C	ASTM D97	Max. -30	-33	Pass
Color.	-	ASTM D1500	Max. 6.0	3.9	Pass
Density at 15 °C	g/cm ³	ASTM D4052	Test & Report	0.8952	Pass

ALCO QUALITY ASSURANCE LABORATORY accredited by AzAK for AZS ISO/IEC 17025:2020 at test laboratory.

Shelf life: 5 years from the date of manufacture of the product if proper storage conditions are followed.

This product meets the specification set out in its product data sheet (PDS) and has been manufactured in a facility fully complying with the requirements of Integrated Management System standards.

Notes & Instructions:

- Tests conducted according to International Standard Test Methods are routinely verified to be in compliance with the latest published versions. Minor changes may be made where they have no material impact on test results and are necessitated by reasons such as safety, environmental standards and method effectiveness.
- This certificate is only valid in its entirety.
- This certificate shall not be reproduced except in full, without the written approval of the laboratory.

Authorised signatory



Allahverdiyeva Aytan
Head of Laboratory



Isgandarli Nazrin
Lead Chemical Engineer



SAFETY DATA SHEET

According to OSHA Hazard Communication Standard, 29 CFR
1910.1200

JCB EP Transmission Fluid 10W

Version 1.0 Revision Date: 11/25/2020 SDS Number: 800010048025 Print Date: 11/26/2020
Date of last issue: -

SECTION 1. IDENTIFICATION

Product name : JCB EP Transmission Fluid 10W

Product code : 001J1349

Manufacturer or supplier's details

Manufacturer/Supplier : **Shell Oil Products US**
PO Box 4427
Houston TX 77210-4427
USA

SDS Request : (+1) 877-276-7285
Customer Service :

Emergency telephone number

Spill Information : 877-504-9351
Health Information : 877-242-7400

Recommended use of the chemical and restrictions on use

Recommended use : Transmission oil.

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Based on available data this substance / mixture does not meet the classification criteria.

GHS label elements

Hazard pictograms : No Hazard Symbol required

Signal word : No signal word

Hazard statements : **PHYSICAL HAZARDS:**
Not classified as a physical hazard under GHS criteria.
HEALTH HAZARDS:
Not classified as a health hazard under GHS criteria.
ENVIRONMENTAL HAZARDS:
Not classified as an environmental hazard under GHS criteria.

Precautionary statements : **Prevention:**
No precautionary phrases.
Response:
No precautionary phrases.
Storage:
No precautionary phrases.

SAFETY DATA SHEET

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

JCB EP Transmission Fluid 10W

Version 1.0 Revision Date: 11/25/2020 SDS Number: 800010048025 Print Date: 11/26/2020
Date of last issue: -

Disposal:

No precautionary phrases.

Other hazards which do not result in classification

Prolonged or repeated skin contact without proper cleaning can clog the pores of the skin resulting in disorders such as oil acne/folliculitis.

Used oil may contain harmful impurities.

Not classified as flammable but will burn.

The classification of this material is based on OSHA HCS 2012 criteria.

Under normal conditions of use or in a foreseeable emergency, this product does not meet the definition of a hazardous chemical when evaluated according to the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Chemical nature : Highly refined mineral oils and additives.
The highly refined mineral oil contains <3% (w/w) DMSO-extract, according to IP346.

* contains one or more of the following CAS-numbers: 64742-53-6, 64742-54-7, 64742-55-8, 64742-56-9, 64742-65-0, 68037-01-4, 72623-86-0, 72623-87-1, 8042-47-5, 848301-69-9, 68649-12-7, 151006-60-9, 163149-28-8.

Hazardous components

Chemical name	Synonyms	CAS-No.	Concentration (% w/w)
Interchangeable low viscosity base oil (<20,5 cSt @40°C) *		Not Assigned	0 - 90
Overbased sulphurised calcium phenate	Phenol, dodecyl-, sulfurized, carbonates, calcium salts, over-based	68784-26-9	1 - 3
Zinc dialkyldithiophosphate	zinc bis[O,O-bis(2-ethylhexyl)]bis(dithiophosphate)	4259-15-8	1 - 2.49
Alkylphenol	dodecylphenol	27193-86-8	0.1 - 0.249

SECTION 4. FIRST-AID MEASURES

If inhaled : No treatment necessary under normal conditions of use.
If symptoms persist, obtain medical advice.

In case of skin contact : Remove contaminated clothing. Flush exposed area with water and follow by washing with soap if available.

SAFETY DATA SHEET

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

JCB EP Transmission Fluid 10W

Version 1.0 Revision Date: 11/25/2020 SDS Number: 800010048025 Print Date: 11/26/2020
Date of last issue: -

-
- If persistent irritation occurs, obtain medical attention.
- In case of eye contact : Flush eye with copious quantities of water. Remove contact lenses, if present and easy to do. Continue rinsing. If persistent irritation occurs, obtain medical attention.
- If swallowed : In general no treatment is necessary unless large quantities are swallowed, however, get medical advice.
- Most important symptoms and effects, both acute and delayed : Oil acne/folliculitis signs and symptoms may include formation of black pustules and spots on the skin of exposed areas. Ingestion may result in nausea, vomiting and/or diarrhoea.
- Protection of first-aiders : When administering first aid, ensure that you are wearing the appropriate personal protective equipment according to the incident, injury and surroundings.
- Indication of any immediate medical attention and special treatment needed : Treat symptomatically.

SECTION 5. FIRE-FIGHTING MEASURES

- Suitable extinguishing media : Foam, water spray or fog. Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only.
- Unsuitable extinguishing media : Do not use water in a jet.
- Specific hazards during fire-fighting : Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide may be evolved if incomplete combustion occurs. Unidentified organic and inorganic compounds.
- Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
- Special protective equipment for firefighters : Proper protective equipment including chemical resistant gloves are to be worn; chemical resistant suit is indicated if large contact with spilled product is expected. Self-Contained Breathing Apparatus must be worn when approaching a fire in a confined space. Select fire fighter's clothing approved to relevant Standards (e.g. Europe: EN469).

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Avoid contact with skin and eyes.

SAFETY DATA SHEET

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

JCB EP Transmission Fluid 10W

Version 1.0 Revision Date: 11/25/2020 SDS Number: 800010048025 Print Date: 11/26/2020
Date of last issue: -

Environmental precautions : Use appropriate containment to avoid environmental contamination. Prevent from spreading or entering drains, ditches or rivers by using sand, earth, or other appropriate barriers.

Local authorities should be advised if significant spillages cannot be contained.

Methods and materials for containment and cleaning up : Slippery when spilt. Avoid accidents, clean up immediately. Prevent from spreading by making a barrier with sand, earth or other containment material. Reclaim liquid directly or in an absorbent. Soak up residue with an absorbent such as clay, sand or other suitable material and dispose of properly.

Additional advice : For guidance on selection of personal protective equipment see Section 8 of this Safety Data Sheet. For guidance on disposal of spilled material see Section 13 of this Safety Data Sheet.

SECTION 7. HANDLING AND STORAGE

Technical measures : Use local exhaust ventilation if there is risk of inhalation of vapours, mists or aerosols. Use the information in this data sheet as input to a risk assessment of local circumstances to help determine appropriate controls for safe handling, storage and disposal of this material.

Advice on safe handling : Avoid prolonged or repeated contact with skin. Avoid inhaling vapour and/or mists. When handling product in drums, safety footwear should be worn and proper handling equipment should be used. Properly dispose of any contaminated rags or cleaning materials in order to prevent fires.

Avoidance of contact : Strong oxidising agents.

Product Transfer : Proper grounding and bonding procedures should be used during all bulk transfer operations to avoid static accumulation.

Further information on storage stability : Keep container tightly closed and in a cool, well-ventilated place. Use properly labeled and closable containers.

Store at ambient temperature.

Packaging material : Suitable material: For containers or container linings, use mild steel or high density polyethylene. Unsuitable material: PVC.

Container Advice : Polyethylene containers should not be exposed to high tem-

SAFETY DATA SHEET

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

JCB EP Transmission Fluid 10W

Version
1.0

Revision Date:
11/25/2020

SDS Number:
800010048025

Print Date: 11/26/2020
Date of last issue: -

peratures because of possible risk of distortion.

SECTION 8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Oil mist, mineral	Not Assigned	TWA (Mist)	5 mg/m ³	OSHA Z-1
Oil mist, mineral		TWA (Inhalable particulate matter)	5 mg/m ³	ACGIH

Biological occupational exposure limits

No biological limit allocated.

Monitoring Methods

Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls. For some substances biological monitoring may also be appropriate.

Validated exposure measurement methods should be applied by a competent person and samples analysed by an accredited laboratory.

Examples of sources of recommended exposure measurement methods are given below or contact the supplier. Further national methods may be available.

National Institute of Occupational Safety and Health (NIOSH), USA: Manual of Analytical Methods <http://www.cdc.gov/niosh/>

Occupational Safety and Health Administration (OSHA), USA: Sampling and Analytical Methods <http://www.osha.gov/>

Health and Safety Executive (HSE), UK: Methods for the Determination of Hazardous Substances <http://www.hse.gov.uk/>

Institut für Arbeitsschutz Deutschen Gesetzlichen Unfallversicherung (IFA), Germany <http://www.dguv.de/inhalt/index.jsp>

L'Institut National de Recherche et de Sécurité, (INRS), France <http://www.inrs.fr/accueil>

Engineering measures

- : The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Select controls based on a risk assessment of local circumstances. Appropriate measures include:
Adequate ventilation to control airborne concentrations.

Where material is heated, sprayed or mist formed, there is greater potential for airborne concentrations to be generated.

General Information:

Define procedures for safe handling and maintenance of controls.

Educate and train workers in the hazards and control measures relevant to normal activities associated with this product.

Ensure appropriate selection, testing and maintenance of equipment used to control exposure, e.g. personal protective

SAFETY DATA SHEET

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

JCB EP Transmission Fluid 10W

Version
1.0

Revision Date:
11/25/2020

SDS Number:
800010048025

Print Date: 11/26/2020
Date of last issue: -

equipment, local exhaust ventilation.
Drain down system prior to equipment break-in or maintenance.
Retain drain downs in sealed storage pending disposal or subsequent recycle.
Always observe good personal hygiene measures, such as washing hands after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Discard contaminated clothing and footwear that cannot be cleaned.
Practice good housekeeping.

Personal protective equipment

Respiratory protection : No respiratory protection is ordinarily required under normal conditions of use.
In accordance with good industrial hygiene practices, precautions should be taken to avoid breathing of material.
If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker health, select respiratory protection equipment suitable for the specific conditions of use and meeting relevant legislation.
Check with respiratory protective equipment suppliers.
Where air-filtering respirators are suitable, select an appropriate combination of mask and filter.
Select a filter suitable for the combination of organic gases and vapours and particles [Type A/Type P boiling point >65°C (149°F)].

Hand protection
Remarks

: Where hand contact with the product may occur the use of gloves approved to relevant standards (e.g. Europe: EN374, US: F739) made from the following materials may provide suitable chemical protection. PVC, neoprene or nitrile rubber gloves. Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced. Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturizer is recommended. For continuous contact we recommend gloves with breakthrough time of more than 240 minutes with preference for > 480 minutes where suitable gloves can be identified. For short-term/splash protection we recommend the same but recognize that suitable gloves offering this level of protection may not be available and in this case a lower breakthrough time maybe acceptable so long as appropriate maintenance and replacement regimes are followed. Glove thickness is not a good predictor of glove resistance to a chemical as it is dependent on the exact composition of the glove material. Glove thickness should be typically greater than 0.35 mm depending on the glove make and model.

SAFETY DATA SHEET

According to OSHA Hazard Communication Standard, 29 CFR
1910.1200

JCB EP Transmission Fluid 10W

Version 1.0 Revision Date: 11/25/2020 SDS Number: 800010048025 Print Date: 11/26/2020
Date of last issue: -

- Eye protection : If material is handled such that it could be splashed into eyes, protective eyewear is recommended.
- Skin and body protection : Skin protection is not ordinarily required beyond standard work clothes.
It is good practice to wear chemical resistant gloves.
- Protective measures : Personal protective equipment (PPE) should meet recommended national standards. Check with PPE suppliers.
- Thermal hazards : Not applicable

Environmental exposure controls

- General advice : Take appropriate measures to fulfill the requirements of relevant environmental protection legislation. Avoid contamination of the environment by following advice given in Section 6. If necessary, prevent undissolved material from being discharged to waste water. Waste water should be treated in a municipal or industrial waste water treatment plant before discharge to surface water.
Local guidelines on emission limits for volatile substances must be observed for the discharge of exhaust air containing vapour.
-

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

- Appearance : Liquid at room temperature.
- Colour : amber
- Odour Threshold : Data not available
- pH : Not applicable
- pour point : -36 °C / -33 °F
Method: ISO 3016
- Initial boiling point and boiling range : > 280 °C / 536 °F
estimated value(s)
- Flash point : 200 °C / 392 °F
Method: ISO 2592
- Evaporation rate : Data not available
- Flammability (solid, gas) : Data not available
- Upper explosion limit / upper flammability limit : Typical 10 %(V)
- Lower explosion limit / Lower : Typical 1 %(V)
-

SAFETY DATA SHEET

According to OSHA Hazard Communication Standard, 29 CFR
1910.1200

JCB EP Transmission Fluid 10W

Version 1.0 Revision Date: 11/25/2020 SDS Number: 800010048025 Print Date: 11/26/2020
Date of last issue: -

flammability limit

Vapour pressure : < 0.5 Pa (20 °C / 68 °F)
estimated value(s)

Relative vapour density : > 1
estimated value(s)

Relative density : 0.884 (15 °C / 59 °F)

Density : 884 kg/m³ (15.0 °C / 59.0 °F)
Method: ISO 12185

Solubility(ies)

Water solubility : negligible

Solubility in other solvents : Data not available

Partition coefficient: n-octanol/water : log Pow: > 6
(based on information on similar products)

Auto-ignition temperature : > 320 °C / 608 °F

Decomposition temperature : Data not available

Viscosity

Viscosity, dynamic : Data not available

Viscosity, kinematic : 36 mm²/s (40.0 °C / 104.0 °F)

Method: ISO 3104

6 mm²/s (100 °C / 212 °F)

Method: ISO 3104

Explosive properties : Not classified

Oxidizing properties : Data not available

Conductivity : This material is not expected to be a static accumulator.

SECTION 10. STABILITY AND REACTIVITY

Reactivity : The product does not pose any further reactivity hazards in addition to those listed in the following sub-paragraph.

Chemical stability : Stable.

Possibility of hazardous reactions : Reacts with strong oxidising agents.

SAFETY DATA SHEET

According to OSHA Hazard Communication Standard, 29 CFR
1910.1200

JCB EP Transmission Fluid 10W

Version 1.0 Revision Date: 11/25/2020 SDS Number: 800010048025 Print Date: 11/26/2020
Date of last issue: -

Conditions to avoid : Extremes of temperature and direct sunlight.

Incompatible materials : Strong oxidising agents.

Hazardous decomposition products : No decomposition if stored and applied as directed.

SECTION 11. TOXICOLOGICAL INFORMATION

Basis for assessment : Information given is based on data on the components and the toxicology of similar products. Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for individual component(s).

Information on likely routes of exposure

Skin and eye contact are the primary routes of exposure although exposure may occur following accidental ingestion.

Acute toxicity

Product:

Acute oral toxicity : LD50 (rat): > 5,000 mg/kg
Remarks: Low toxicity:
Based on available data, the classification criteria are not met.

Acute inhalation toxicity : Remarks: Based on available data, the classification criteria are not met.

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg
Remarks: Low toxicity:
Based on available data, the classification criteria are not met.

Skin corrosion/irritation

Product:

Remarks: Slightly irritating to skin., Prolonged or repeated skin contact without proper cleaning can clog the pores of the skin resulting in disorders such as oil acne/folliculitis., Based on available data, the classification criteria are not met.

Serious eye damage/eye irritation

Product:

Remarks: Slightly irritating to the eye., Based on available data, the classification criteria are not met.

Components:

Zinc dialkyldithiophosphate:

Remarks: Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation

Product:

SAFETY DATA SHEET

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

JCB EP Transmission Fluid 10W

Version
1.0

Revision Date:
11/25/2020

SDS Number:
800010048025

Print Date: 11/26/2020
Date of last issue: -

Remarks: Not a skin sensitiser.
Based on available data, the classification criteria are not met.

Germ cell mutagenicity

Product:

: Remarks: Non mutagenic, Based on available data, the classification criteria are not met.

Carcinogenicity

Product:

Remarks: Not a carcinogen., Based on available data, the classification criteria are not met.

Remarks: Product contains mineral oils of types shown to be non-carcinogenic in animal skin-painting studies., Highly refined mineral oils are not classified as carcinogenic by the International Agency for Research on Cancer (IARC).

IARC

No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

OSHA

No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

Reproductive toxicity

Product:

: Remarks: Not a developmental toxicant., Does not impair fertility., Based on available data, the classification criteria are not met.

STOT - single exposure

Product:

Remarks: Based on available data, the classification criteria are not met.

STOT - repeated exposure

Product:

Remarks: Based on available data, the classification criteria are not met.

SAFETY DATA SHEET

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

JCB EP Transmission Fluid 10W

Version
1.0

Revision Date:
11/25/2020

SDS Number:
800010048025

Print Date: 11/26/2020
Date of last issue: -

Aspiration toxicity

Product:

Not an aspiration hazard.

Further information

Product:

Remarks: Used oils may contain harmful impurities that have accumulated during use. The concentration of such impurities will depend on use and they may present risks to health and the environment on disposal., ALL used oil should be handled with caution and skin contact avoided as far as possible.

Remarks: Slightly irritating to respiratory system.

SECTION 12. ECOLOGICAL INFORMATION

Basis for assessment : Ecotoxicological data have not been determined specifically for this product.
Information given is based on a knowledge of the components and the ecotoxicology of similar products.
Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for individual component(s).(LL/EL/IL50 expressed as the nominal amount of product required to prepare aqueous test extract).

Ecotoxicity

Product:

Toxicity to fish (Acute toxicity) :
Remarks: LL/EL/IL50 > 100 mg/l
Practically non toxic:
Based on available data, the classification criteria are not met.

Toxicity to daphnia and other aquatic invertebrates (Acute toxicity) :
Remarks: LL/EL/IL50 > 100 mg/l
Practically non toxic:
Based on available data, the classification criteria are not met.

Toxicity to algae (Acute toxicity) :
Remarks: LL/EL/IL50 > 100 mg/l
Practically non toxic:
Based on available data, the classification criteria are not met.

Toxicity to fish (Chronic toxicity) : Remarks: Data not available

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : Remarks: Data not available

Toxicity to microorganisms (Acute toxicity) : Remarks: Data not available

SAFETY DATA SHEET

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

JCB EP Transmission Fluid 10W

Version
1.0

Revision Date:
11/25/2020

SDS Number:
800010048025

Print Date: 11/26/2020
Date of last issue: -

Components:

Alkylphenol:

M-Factor (Acute aquatic toxicity) : 10

M-Factor (Chronic aquatic toxicity) : 10

Persistence and degradability

Product:

Biodegradability : Remarks: Not readily biodegradable.
Major constituents are inherently biodegradable, but contains components that may persist in the environment.
Persistent per IMO criteria.
International Oil Pollution Compensation (IOPC) Fund definition: "A non-persistent oil is oil, which, at the time of shipment, consists of hydrocarbon fractions, (a) at least 50% of which, by volume, distills at a temperature of 340°C (645°F) and (b) at least 95% of which, by volume, distills at a temperature of 370°C (700°F) when tested by the ASTM Method D-86/78 or any subsequent revision thereof."

Bioaccumulative potential

Product:

Bioaccumulation : Remarks: Contains components with the potential to bioaccumulate.

Mobility in soil

Product:

Mobility : Remarks: Liquid under most environmental conditions.
If it enters soil, it will adsorb to soil particles and will not be mobile.

Remarks: Floats on water.

Other adverse effects

Product:

Additional ecological information : Does not have ozone depletion potential, photochemical ozone creation potential or global warming potential.
Product is a mixture of non-volatile components, which will not be released to air in any significant quantities under normal conditions of use.

Poorly soluble mixture.
Causes physical fouling of aquatic organisms.

SAFETY DATA SHEET

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

JCB EP Transmission Fluid 10W

Version
1.0

Revision Date:
11/25/2020

SDS Number:
800010048025

Print Date: 11/26/2020
Date of last issue: -

Mineral oil does not cause chronic toxicity to aquatic organisms at concentrations less than 1 mg/l.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues

: Recover or recycle if possible.
It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste classification and disposal methods in compliance with applicable regulations.
Waste product should not be allowed to contaminate soil or ground water, or be disposed of into the environment.
Do not dispose into the environment, in drains or in water courses
Do not dispose of tank water bottoms by allowing them to drain into the ground. This will result in soil and groundwater contamination.
Waste arising from a spillage or tank cleaning should be disposed of in accordance with prevailing regulations, preferably to a recognised collector or contractor. The competence of the collector or contractor should be established beforehand.

Contaminated packaging

: Dispose in accordance with prevailing regulations, preferably to a recognized collector or contractor. The competence of the collector or contractor should be established beforehand.
Disposal should be in accordance with applicable regional, national, and local laws and regulations.

Local legislation

Remarks

: Disposal should be in accordance with applicable regional, national, and local laws and regulations.

SECTION 14. TRANSPORT INFORMATION

National Regulations

US Department of Transportation Classification (49 CFR Parts 171-180)

Not regulated as a dangerous good

International Regulations

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied. MARPOL Annex 1 rules apply for bulk shipments by sea.

Special precautions for user

SAFETY DATA SHEET

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

JCB EP Transmission Fluid 10W

Version 1.0 Revision Date: 11/25/2020 SDS Number: 800010048025 Print Date: 11/26/2020
Date of last issue: -

Remarks : Special Precautions: Refer to Section 7, Handling & Storage, for special precautions which a user needs to be aware of or needs to comply with in connection with transport.

SECTION 15. REGULATORY INFORMATION

EPCRA - Emergency Planning and Community Right-to-Know Act

*: This material does not contain any components with a CERCLA RQ., Shell classifies this material as an "oil" under the CERCLA Petroleum Exclusion, therefore releases to the environment are not reportable under CERCLA.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : No SARA Hazards

SARA 313 : The following components are subject to reporting levels established by SARA Title III, Section 313:

Zinc dialkyldithiophosphate	4259-15-8	>= 1 - < 5 %
-----------------------------	-----------	--------------

Clean Water Act

This product does not contain any Hazardous Chemicals listed under the U.S. CleanWater Act, Section 311, Table 117.3.

US State Regulations

Pennsylvania Right To Know

Distillates, petroleum, solvent-dewaxed light paraffinic	64742-56-9
Zinc dialkyldithiophosphate	4259-15-8
Distillates (petroleum), solvent-dewaxed heavy paraffinic	64742-65-0
Distillates (petroleum), hydrotreated light	64742-47-8

California Prop. 65

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

California List of Hazardous Substances

Distillates, petroleum, solvent-dewaxed light paraffinic	64742-56-9
Zinc dialkyldithiophosphate	4259-15-8

Other regulations:

The regulatory information is not intended to be comprehensive. Other regulations may apply to this material.

The components of this product are reported in the following inventories:

EINECS : Not established.

SAFETY DATA SHEET

According to OSHA Hazard Communication Standard, 29 CFR
1910.1200

JCB EP Transmission Fluid 10W

Version 1.0 Revision Date: 11/25/2020 SDS Number: 800010048025 Print Date: 11/26/2020
Date of last issue: -

TSCA : All components listed.

DSL : All components listed.

SECTION 16. OTHER INFORMATION

Further information

NFPA Rating (Health, Fire, Reactivity) 0, 1, 0

Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)
OSHA Z-1 : USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
ACGIH / TWA : 8-hour, time-weighted average
OSHA Z-1 / TWA : 8-hour time weighted average
Abbreviations and Acronyms : The standard abbreviations and acronyms used in this document can be looked up in reference literature (e.g. scientific dictionaries) and/or websites.

ACGIH = American Conference of Governmental Industrial Hygienists
ADR = European Agreement concerning the International Carriage of Dangerous Goods by Road
AICS = Australian Inventory of Chemical Substances
ASTM = American Society for Testing and Materials
BEL = Biological exposure limits
BTEX = Benzene, Toluene, Ethylbenzene, Xylenes
CAS = Chemical Abstracts Service
CEFIC = European Chemical Industry Council
CLP = Classification Packaging and Labelling
COC = Cleveland Open-Cup
DIN = Deutsches Institut für Normung
DMEL = Derived Minimal Effect Level
DNEL = Derived No Effect Level
DSL = Canada Domestic Substance List
EC = European Commission
EC50 = Effective Concentration fifty
ECETOC = European Center on Ecotoxicology and Toxicology Of Chemicals
ECHA = European Chemicals Agency
EINECS = The European Inventory of Existing Commercial Chemical Substances
EL50 = Effective Loading fifty
ENCS = Japanese Existing and New Chemical Substances Inventory
EWC = European Waste Code
GHS = Globally Harmonised System of Classification and Labelling of Chemicals
IARC = International Agency for Research on Cancer

SAFETY DATA SHEET

According to OSHA Hazard Communication Standard, 29 CFR
1910.1200

JCB EP Transmission Fluid 10W

Version 1.0 Revision Date: 11/25/2020 SDS Number: 800010048025 Print Date: 11/26/2020
Date of last issue: -

IATA = International Air Transport Association
IC50 = Inhibitory Concentration fifty
IL50 = Inhibitory Level fifty
IMDG = International Maritime Dangerous Goods
INV = Chinese Chemicals Inventory
IP346 = Institute of Petroleum test method N° 346 for the
determination of polycyclic aromatics DMSO-extractables
KECI = Korea Existing Chemicals Inventory
LC50 = Lethal Concentration fifty
LD50 = Lethal Dose fifty per cent.
LL/EL/IL = Lethal Loading/Effective Loading/Inhibitory loading
LL50 = Lethal Loading fifty
MARPOL = International Convention for the Prevention of
Pollution From Ships
NOEC/NOEL = No Observed Effect Concentration / No Ob-
served Effect Level
OE_HP V = Occupational Exposure - High Production Volume
PBT = Persistent, Bioaccumulative and Toxic
PICCS = Philippine Inventory of Chemicals and Chemical
Substances
PNEC = Predicted No Effect Concentration
REACH = Registration Evaluation And Authorisation Of
Chemicals
RID = Regulations Relating to International Carriage of Dan-
gerous Goods by Rail
SKIN_DES = Skin Designation
STEL = Short term exposure limit
TRA = Targeted Risk Assessment
TSCA = US Toxic Substances Control Act
TWA = Time-Weighted Average
vPvB = very Persistent and very Bioaccumulative

A vertical bar (|) in the left margin indicates an amendment from the previous version.

Sources of key data used to compile the Safety Data Sheet : The quoted data are from, but not limited to, one or more sources of information (e.g. toxicological data from Shell Health Services, material suppliers' data, CONCAWE, EU IUCLID date base, EC 1272 regulation, etc).

Revision Date : 11/25/2020

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN



MANNOL MTF-3 8115

Universal energy-saving all-season transmission fully synthetic oil of the latest generation specially developed for use in robotic and manual gearboxes of TOYOTA and FORD cars (Attention! Not for all manual transmissions). Applicable for transfer cases and differentials. Developed based on the requirements of the TOYOTA group.

Product properties:

- A unique synthetic base of the highest quality, with ideal viscosity in a wide temperature range, combined with the latest generation additive package, provide unsurpassed antifriction properties, which provides significant fuel economy and very smooth gear shifting;
- Due to its unique composition, it provides excellent anti-wear and extreme pressure properties, which significantly extends the life of the equipment in all, even the most extreme, operating modes in a wide range of ambient temperatures. It has increased resistance of the oil film to high pressures and increased shear stability;
- Provides excellent low-temperature properties, which ensures easy start-up, reliable lubrication, as well as smooth, easy and accurate gear shifting at any ambient temperature (up to -45 °C) and under any operating conditions;
- Effectively protects against varnish and clogging of the synchronizer ring;
- Effectively resists aeration, foaming, has excellent cooling properties. Has low evaporation loss;
- It has increased thermal, thermo-oxidative and chemical stability and resistance to high-temperature thermal degradation over the entire life cycle. This allows to reduce the formation of sludge, varnish, soot and other carbon deposits, significantly increase the oil change interval and ensure the durability of the transmission parts, which reduces maintenance costs;
- Due to the addition of special inhibitors, it effectively protects metal parts from ferrous and non-ferrous alloys from corrosion both during operation and inoperative;
- Provides excellent compatibility with seal materials, prevents them from swelling, hardening and shrinkage, which reduces the cost of spare parts and prevents leakage;
- Reduces noise.

Recommended for use in manual transmission of TOYOTA, BMW, Volkswagen, VOLVO, FORD cars, etc. in accordance with the above requirements of car manufacturers.

Follow the manufacturer's instructions in the instruction manual.

Specifications

SAE 75W

Recommendation

API GL-4

TOYOTA LV

NISSAN LV MTF-1

MB 235.71

VOLKSWAGEN G 052 798

VOLKSWAGEN G 052 727

VOLKSWAGEN G 052 749

VOLKSWAGEN TL 521 71 (G 052 171 A1)

VOLKSWAGEN TL 521 71 (G 052 171 A2)

VOLKSWAGEN TL 521 78 (G 052 178 A2)

VOLKSWAGEN TL 525 12 (G 052 512 A2)

VOLKSWAGEN TL 726 (G 052 726 A2)

VOLKSWAGEN TL 726 (G 055 726 A2)

VOLKSWAGEN TL 726 (G 060 726 A2)

VOLKSWAGEN TL 726 (G 070 726 A2)

BMW 83 220 396 706

BMW 83 22 7 533 818

BMW 2300 7533 818

BMW MTF LT-3

BMW MTF LT-2

FORD WSS-M2C200-D2

PSA 9730 A8

TOYOTA 08885-81081

VOLVO 1161838

VOLVO 1161839

Others JWS 2271

PACKAGING

	MN8115-1		
1000L	MN8115-IBC	Pallet tank	
208L	MN8115-DR	Drum	
60L	MN8115-60	Drum	
20L	MN8115-20	Plastic	

	<p style="text-align: center;">ALCO QUALITY ASSURANCE LABORATORY TEST REPORT</p> <p style="text-align: center;">Accreditation No: AZS ISO/IEC 17025:2020/AZ 01.0571.01.21</p>	 <p style="text-align: center;">AZERBAIJAN ACCREDITATION CENTER</p>
---	--	--

Company: ALCO LLC
3, Vali Mammadov st., Sabail dist.
AZ1095, Baku, Azerbaijan

Certificate No.: 20241807
Date of issue: 23/10/2024

Test sample

Product: AVTOIL TAD-17
Batch number: 24101807
Tank ID: T41.1

Manufacture date: 23/10/2024
Date of sampling: 23/10/2024
Date of analysis: 23/10/2024

Test result

Parameters	Unit	Test method	Limit	Test result	Conclusion
Appearance	-	Visual	Bright & Clear	Bright & Clear	Pass
Kinematic viscosity at 100 °C	mm ² /s	ASTM D445	Min. 17.50	18.30	Pass
Viscosity Index	-	ASTM D1500	Min. 100	122	Pass
Water content	%	ASTM D95	Max. 0.05	None	Pass
Pour Point	°C	ASTM D97	Max. -25	-27	Pass
Color	-	ASTM D1500	Test & Report	4.4	Pass
Density at 15°C	g/cm ³	ASTM D4052	Test & Report	0.8839	Pass

ALCO QUALITY ASSURANCE LABORATORY accredited by AzAK for AZS ISO/IEC 17025:2020 at test laboratory.

Shelf life: 5 years from the date of manufacture of the product if proper storage conditions are followed.

This product meets the specification set out in its product data sheet (PDS) and has been manufactured in a facility fully complying with the requirements of Integrated Management System standards.



ALCO QUALITY ASSURANCE LABORATORY
TEST REPORT
Accreditation No: AZS ISO/IEC 17025:2020/AZ 01.0571.01.21



Notes & Instructions:

- Tests conducted according to International Standard Test Methods are routinely verified to be in compliance with the latest published versions. Minor changes may be made where they have no material impact on test results and are necessitated by reasons such as safety, environmental standards and method effectiveness.
- This certificate is only valid in its entirety.
- This certificate shall not be reproduced except in full, without the written approval of the laboratory.

Approved by

Allahverdiyeva Aytan
Head of Laboratory



	<p style="text-align: center;">ALCO QUALITY ASSURANCE LABORATORY TEST REPORT</p> <p style="text-align: center;">Accreditation No: AZS ISO/IEC 17025:2020/AZ 01.0571.01.21</p>	
---	--	---

Company: ALCO LLC
3, Vali Mammadov st., Sabail dist.
AZ1095, Baku, Azerbaijan

Certificate No.: 2024613
Date of issue: 23/04/2024

Test sample

Product: AVTOIL TSP-15K
Batch number: 2404613
Tank ID: T41.1

Manufacture date: 23/04/2024
Date of sampling: 23/04/2024
Date of analysis: 23/04/2024

Test result

Parameters	Unit	Test method	Limit	Test result	Conclusion
Appearance	-	Visual	Bright & Clear	Bright & Clear	Pass
Kinematic viscosity at 100 °C	mm ² /s	ASTM D445	14.0-16.0	14.61	Pass
Viscosity index	-	ASTM D2270	Min. 90	99	Pass
Water content	%	ASTM D95	Max. 0.05	None	Pass
Flash Point, COC	°C	ASTM D92	Min. 185	238	Pass
Pour Point	°C	ASTM D97	Max. -25	<-25	Pass
Color.	-	ASTM D1500	Test & Report	4.0	Pass
Density at 15 °C	g/cm ³	ASTM D4052	Test & Report	0.8888	Pass

ALCO QUALITY ASSURANCE LABORATORY accredited by AzAK for AZS ISO/IEC 17025:2020 at test laboratory.

Shelf life: 5 years from the date of manufacture of the product if proper storage conditions are followed.

This product meets the specification set out in its product data sheet (PDS) and has been manufactured in a facility fully complying with the requirements of Integrated Management System standards.

Notes & Instructions:

- Tests conducted according to International Standard Test Methods are routinely verified to be in compliance with the latest published versions. Minor changes may be made where they have no material impact on test results and are necessitated by reasons such as safety, environmental standards and method effectiveness.
- This certificate is only valid in its entirety.
- This certificate shall not be reproduced except in full, without the written approval of the laboratory.

Authorised singnatory



Allahverdiyeva Aytan
Head of Laboratory



Isgandarli Nazrin
Lead Chemical Engineer

