

Ordering information

Z-5™

REF	Balloon Diameter (mm)	Balloon Length (cm)	Introducer Size (FR)	Shaft Size (FR)	Usable Length (cm)	Guide Wire (Inches)	Maximum Volume (CC)
SPT002	9.5	0.95	5	4	50	0.014	1
SPT003	13.5	1.35	6	5	50	0.021	2

PTS®

REF	Balloon Diameter (mm)	Balloon Length (cm)	Introducer Size (FR)	Shaft Size (FR)	Usable Length (cm)	Guide Wire (Inches)	Rated Burst (ATM)
PTS203	20.0	3.0	8	8	80	0.035	1.5
PTS204	20.0	3.0	8	8	110	0.035	1.5
PTS253	25.0	3.0	8	8	80	0.035	1.5
PTS254	25.0	3.0	8	8	110	0.035	1.5
PTS303	30.0	3.0	8	8	80	0.035	1.0
PTS304	30.0	4.0	8	8	80	0.035	1.0
PTS305	30.0	5.0	8	8	80	0.035	1.0
PTS306	30.0	3.0	8	8	110	0.035	1.0
PTS307	30.0	4.0	8	8	110	0.035	1.0
PTS308	30.0	5.0	8	8	110	0.035	1.0
PTS403	40.0	3.0	9	8	80	0.035	0.5
PTS404	40.0	4.0	9	8	80	0.035	0.5
PTS405	40.0	5.0	9	8	80	0.035	0.5
PTS406	40.0	3.0	9	8	110	0.035	0.5
PTS407	40.0	4.0	9	8	110	0.035	0.5
PTS408	40.0	5.0	9	8	110	0.035	0.5

PTS-X™

REF	Balloon Diameter (mm)	Balloon Length (cm)	Introducer Size (FR)	Shaft Size (FR)	Usable Length (cm)	Guide Wire (Inches)	Rated Burst (ATM)
PTSX101	10.0	1.0	6	6	80	0.035	2.5
PTSX102	10.0	2.0	6	6	80	0.035	2.5
PTSX103	10.0	3.0	6	6	80	0.035	2.5
PTSX104	10.0	1.0	6	6	110	0.035	2.5
PTSX105	10.0	2.0	6	6	110	0.035	2.5
PTSX106	10.0	3.0	6	6	110	0.035	2.5
PTSX122	12.0	2.0	6	6	80	0.035	2.0
PTSX123	12.0	3.0	6	6	80	0.035	2.0
PTSX124	12.0	2.0	6	6	110	0.035	2.0
PTSX125	12.0	3.0	6	6	110	0.035	2.0
PTSX152	15.0	2.0	6	6	80	0.035	2.0
PTSX153	15.0	3.0	6	6	80	0.035	2.0
PTSX154	15.0	4.0	6	6	80	0.035	2.0
PTSX155	15.0	2.0	6	6	110	0.035	2.0
PTSX156	15.0	3.0	6	6	110	0.035	2.0
PTSX157	15.0	4.0	6	6	110	0.035	2.0
PTSX203	20.0	3.0	8	8	80	0.035	1.5