



Trinocular brightfield microscope, 1000x, PLAN, multi-plug

Observation Mathed	Prightfield	Voc
Observation Method - Transmitted Light	Brightfield	Yes
Transmitted Light	Simple polarized light	As optional
Main Padu	T. m. a	I low-look
Main Body	Type	Upright
	Construction material	Aluminum die-cast
	Trasportation handle	Yes
II I	-	T : (0: 1 (0)
Head	Type	Trinocular (Siedentopf)
	Split ratio	50/50
	Inclination	30°
	360° rotating	Yes
	Interpupillary distance (mm)	48-75
	Dioptric adjustement	On left tube
	Fixing screw for eyepieces	Yes
	Tube inner diameter (mm)	23
_		
Eyepieces	Field number (mm)	18
	Magnification	10x
	High eyepoint (for glass wearers)	Yes
	Pointer	As optional
	Micrometric scale	As optional
	Diameter of micrometer glass (mm)	20
Nosepiece	Positions	Quadruple
	Reversed	Yes
	Bi-directional	Yes
	Rotation on ball bearings	Yes
	Objective thread	RMS
Objectives	Optical system	160
	Anti-fungus treatment	Yes
	Parfocal distance (mm)	45
	Standard magnifications	40x-1000x
	Туре	N-PLAN
	Objectives included	4x/0.10, W.D. 15.2 mm
		10x/0.25, W.D. 5.5 mm
		40x/0.65, W.D. 0.45 mm
		100x/1.25 (Oil/Water), W.D. 0.13 mm
Stage	Туре	Double layer
	Dimensions (mm)	125x115
	Moving mechanism	Rack and pinion
	Moving range (mm)	70x30
	Moving range (mm) Material	70x30 Anti-scratch painting
	Moving range (mm)  Material  Specimen holder	
	Moving range (mm) Material	Anti-scratch painting
	Moving range (mm)  Material  Specimen holder	Anti-scratch painting Yes
	Moving range (mm)  Material  Specimen holder  Slide number	Anti-scratch painting Yes 1

Condenser - Single	Туре	Abbe
Position	Removable	No
	Numerical aperture (N.A.)	1.25
		Iris
	Diaphragms Centrable	
		Pre-centered
	Focusable	By rotation
Focusing System	Type	Coaxial coarse & fine
rocusing System	Type	18
	Coarse total travel (mm)	
	Fine total travel (per single rotation) (mm)	0.4
	Fine graduations	100
	Fine resolution (µm)	4
	Upper stop to prevent contact	Yes
	Adjustable tension	Yes
Transmitted	Туре	X-LED
Illumination	X-LED type	X-LED2
	Light source power (W)	3
	Brightness control	Manual
	Lifetime (hours)	> 65,000
	Temperature (K)	6,300
	Max. required power (W)	6
Power Supply for	Туре	External
Transmitted	Microscope connector	Jack, 2.1 mm
Illumination	Power plug type	Multi-plug (EU, UK, US)
	Input voltage	100/240 Vac, 50/60 Hz
	Output voltage	6 Vdc 2.5 A
Accessories Included	Dust cover	Yes
	Immersion oil (10ml)	Yes
	Tension adjustment tool	Yes
	User Manual	Digital version (downloadable)
<b>Additional Information</b>		External rechargeable battery pack (as optional).
		External rechargeable battery pack (as optional).
		1110
Product Dimensions	Height (mm)	440
	Width (mm)	235
	Depth (mm)	320
Product Weight	(kg)	6.5