Lenovo V530-24ICB AIO Platform Specifications

Processor	Intel® Pentium® Gold or 8th Generation Intel Core™ i3 / i5 / i7 Processor						Manageability	None	
	Processor	Cores /	Frequency	Cache	DDR4-2400	Integrated Graphics UHD 610		Firmware TPM 2.0	
		 	Base/Max(GHz)				Security features	 Security slot (in rear for attachment of optional Kensington® MicroSaver® cable; Boot sequence control Kensington lock also locks back cover) Smart USB protection, allows keyboard/mouse only, blocks all storage devices 	
	Pentium Gold G5400T Core i3-8100T	2/4	3.1G 3.1G	4 MB 6 MB					
	Core i5-8400T	6/6	1.7G / 3.3G	9 MB					
	Core i7-8700T	6/12	2.4G / 4.0G	12 MB					
Manager			<u> </u>		la alcal abancal		Keyboard	Some: Lenovo Calliope Keyboard (USB connector), black Some: Lenovo Calliope Wireless Keyboard (2.4GHz via USB receiver), black	
Memory	32GB max, DDR4-2666*, two 260-pin SO-DIMM sockets, dual-channel capable * System clocks down for the processors with lower memory controller						Mouse	Some: Lenovo Calliope Mouse (USB connector), black Some: Lenovo Calliope Mouse (USB connector), black Some: Lenovo Calliope Wireless Mouse (2.4GHz via USB receiver), black	
Disk	Some: 500GB Hard Drive / SATA 6.0Gb/s, 2.5", 7200 rpm Some: 1TB Hard Drive / SATA 6.0Gb/s, 2.5", 5400 rpm Some: 256GB M.2 Solid State Drive (SSD) / PCIe NVMe, PCIe 3.0 x 4						Mechanical	Black	
								Support VESA mount (100mm)	
	Some: 16GB Intel Optane™ Memory (not support Celeron							Dimensions (WxDxH) Max weight Adjustments	
/ Pentium Processor), M.2							(lb / kg)		
Media reader								Without stand: 21.4 X 2.1 X 14.5 (inch); 542.7 X 54.1 X 367.4 (mm) 12.3 / 5.60 N/A	
Graphics Intel UHD Graphics 610/630 in processor, uses main memory, DirectX® 12, and optional AMD Radeon 1530 GDDR5, 2GB memory,						[*] 12,		With Monitor stand: 21.4 X 9.0 X 17.2 (inch); 542.7 X 227.95 X 437.4 (mm) 15.4 / 7.00 Tilt: 65° back, -5° forward Swivel: +/-45°	
	external monitor support via HDMI out Max resolution: 1920x1080 (HDMI)@60Hz 23.8" (604.5mm), FHD (1920x1080), Wide Viewing Angle (horizontal: +/- 89°; vertical: +/- 89°), LED backlight, IPS, 250 nits, 16:9 aspect ratio 1000:1 contrast ratio, anti-glare, borderless design, work as standalone monitor via HDMI in						Power supply	Some: 90 watts external adapter, autosensing, 88% PSU (for integrated models)	
Display								Some: 120 watts external adapter, autosensing, 89% PSU (for discrete models)	
							Limited warranty	Some: 1-year, depot repair service Some: 1-year or 3-year, limited onsite service	
Multi-touch	Optional multi-touch (10-point), Advanced In-Cell Touch (AIT) technology Some: 720p camera, with one digital microphone, LED indicator, with privacy camera cover Some: 1080p IR camera, with one digital microphone, LED indicator, with privacy camera cover					ıv	Preload	Preloaded operating system Some: Windows 10 Pro 64-bit	
Camera						,,			
(Optional)								Some: Windows 10 Home 64-bit Preloaded applications (only some listed) • Lenovo Vantage	
Controls	Power on/off button on right side							Lenovo App Explorer	
Chipset	Intel B360 chipset]	 McAfee® LiveSafe™ (30-day trial) Microsoft® Office preloaded; 	
Rear ports	One USB 3.1 gen 2, three USB 2.0, ethernet (RJ-45), HDMI-in, HDMI-out, DC-in					ut, DC-in	purchase a product key to activate		
Side ports Bottom ports	One USB 3.1 gen 1 One USB 3.1 gen 1, card reader, headphone / microphone combo jack (3.5mm) Two M.2 Card slots (one for WLAN, one for M.2 SSD)				one combo jack ((3.5mm)	Environment	ENERGY STAR® 7.0; Low blue light certified; EPEAT™ Silver compliant;	
M.2 card slot					ono combo jaon ((0.011111)	Accessories	For compatible accessories, please go to http://smartfind.lenovo.com/	
Audio support	High Definition (HD) Audio, Realtek ALC274-VB / Conexant CX20726, two internal speakers (3W x 2)					wo internal			
WLAN	Some: 11ac wireless, M.2 Card, Realtek RTL8821CE (dual band), Wi-Fi + Bluetooth 4.0 combo adapter, 1x1								
	Some: 11ac wireless, M.2 Card, Realtek RTL8822BE (dual band), Wi-Fi + Bluetooth 4.0 combo adapter, 2x2								
	Some: 11ac wireless,	M.2 Card		d Wirele	ess-AC 3165,				
	Some: 11ac wireless,	M.2 Card		d Wirele	ess-AC 8265,				
Bluetooth™ Ethernet	Some: Bluetooth 4.0 v One gigabit ethernet p	vireless, ir	ntegrated in Wi-F	i + Blue	etooth combo ad	apter			
Emerner	One gigabit ethernet p	Joil, Reall	EK MILÖIIIG, V	vake or	I LAIN"				
Note: The specifications above may not be available in all regions.									