

WATER DISTILLER



TECHNICAL SPECIFICATIONS FOR MODEL MSD-8008

Distilled Water Capacity 8 lt/hr Storage Tank Capacity 16 litres

Cooling Water Consumption 80 lt/hr

High purity distilled water - conductivity approx 2,3 μ S/cm

The unit is suitable for both bench and wall mounting.

Fully Automatic:

- Automatic power cut-off, in case of low water, to protect the heating element
- Automatic start when the water at sufficient level in the evaporator tank
- Automatic thermostatic cut-off

Electronic level switch:

- Stop automatically in case of water level in storage tank is full
- Start automatically when distillate water is withdrawn from storage tank

Water Supply:

- Solenoid valve built-in connection for evaporator and condenser
- Automatic solenoid valve switching on in case of low water level on evaporator tank
- Automatic solenoid valve switching off in case of high water level on evaporator tank

Internal surface:

- Evaporator tank made of stainless steel material no. EN 1.4301
- Condenser (cooler) made of stainless steel, material no. EN 1.4301
- Heating element made of stainless steel, material no. EN 1.4876
- Storage tank made of stainless steel material no. EN 1.4301

MİKROTEST LABORATUVAR CİH.MAK.İMALAT GIDA AHŞAP ÜR.SAN.TİC.LTD.ŞTİ

Adres: Saray Mahallesi 676. Cadde No:22 Kahramankazan-ANKARA **Telefon:**0312 395 65 24 **Faks:**0312 395 65 01

Web: www.mikrotestcihazlari.com **Mail:** info@mikrotestcihazlari.com



External surface: Housing material made of galvanized steel, electrostatically powder coated

Degassing system: Degassing system through a vent in the top of the unit

Accessing interior: Easily accessed evaporator and storage tanks for cleaning and maintenance

Installation: All parts and tools for installation included

Distillate water withdrawal: The drain tap can be opened in either continuous or touch position

Main switch: Main switch button on the front of the unit

Led light: Two led lights on the front of the unit, green light for ready operation and red light to indicate that heating element is switching on

Mounting: Suitable for bench and wall mounting

Safety

Water: Low water cut-off to protect heating element

Heating: Overheating cut-off

Led light: Led light alarm

Degassing: Low-gas, bacteria and pyrogen free

Power connection: Power cable with shock-proof type (Schuko) plug

Optional

Water filters of different types: 10 microns, 5 microns, 3 microns, 1 micron, Carbon 10/Chlorine, Anti-limescale for heating equipment with polyphosphate granules.

All filters are delivered with transparent flask, wall mounting bracket, flask opening key

Connection

Water inlet:

- Cooling water inlet on the right-hand side of the unit
- Water inlet diameter 3/4 inch (\varnothing 19.05 mm)

Water pressure: From 2 bar to max 7 bar

Water outlet:

- Cooling water outlet on the right-hand side of the unit
- Water outlet diameter 2/5 inch (inner \varnothing 10 mm)

Distillate water: Distillate withdrawal through drain tap on the front of the unit

MİKROTEST LABORATUVAR CİH.MAK.İMALAT GIDA AHŞAP ÜR.SAN.TİC.LTD.ŞTİ

Adres: Saray Mahallesi 676. Cadde No:22 Kahramankazan-ANKARA **Telefon:**0312 395 65 24 **Faks:**0312 395 65 01

Web: www.mikrotestcihazlari.com **Mail:** info@mikrotestcihazlari.com

mikrotest

Power: Main connection cable on the left-hand side of the unit

Voltage 380 V / 3ph 50...60 Hz

Watt 6000 watt

MİKROTEST LABORATUVAR CİH.MAK.İMALAT GIDA AHŞAP ÜR.SAN.TİC.LTD.ŞTİ

Adres: Saray Mahallesi 676. Cadde No:22 Kahramankazan-ANKARA **Telefon:**0312 395 65 24 **Faks:**0312 395 65 01

Web: www.mikrotestcihazlari.com **Mail:** info@mikrotestcihazlari.com