


LABORATOR LUBRIFIANTI/ LUBRICANTS LABORATORY				acreditat pentru INCERCARE		
Ploiesti, Str. Mihai Bravu, Nr. 235, Jud.Prahova; Tel: +40244 504 358; Fax: +40244 504 679; Laborator.llee@eu.lukoil.com				 SR EN ISO IEC 17025:2018 CERTIFICAT DE ACREDITARE LI 1200		
RAPORT DE INCERCARE (TEST REPORT)		Nr.:	1070	Data:	26.08.2022	
Client (Customer)	Sectia Amestec/Blending Sector		LUKOIL LUBRICANTS EAST EUROPE			
Produs (Product)	Ulei pentru transmisii LUKOIL TRANSMISSION SYNTH MPV 75W-80 Transmission oil LUKOIL TRANSMISSION SYNTH MPV 75W-80					
Document normativ (Normative doc)	ST-10,ed.3/2020					
Numar Comanda (Order number)	1025					
Cod proba (Cod sample) / Lot(Batch)	4409/ Lot/Batch 2610					
Proba prelevata de (Sampling by)	Client (By customer)					
Data primire proba (Receive date)	25.08.2022					
Nr. crt. No	Caracteristici (Characteristics)	U.M. (U.M.)	Valoare prevazuta (Standard limits)	Valoare determinata (Obtained value)	Metoda de incercare (Test Method)	Incertitudine (Uncertainty) **
1	Viscozitatea cinematica la 100°C Kinematic viscosity at 100°C	mm ² /s	9,0 + 11,0	9,384	ASTM D 7042-21a	
2	Viscozitatea cinematica la 40°C Kinematic viscosity at 40°C	mm ² /s	max. 65	54,78	ASTM D 7042-21a	
3	Indice de viscozitate Viscosity index	-	min 150	155	ASTM D 7042-21a ASTM D 2270-10(16) SR ISO 2909-12	
4	*Viscozitate dinamica Brookfield la - 40 °C Brookfield viscosity at -40 °C	cP	max 150000	43780	ASTM D 2983-21	
5	# Punct de inflamare in vas deschis Flash point, COC	°C	min 190	226	SR EN ISO 2592-18 ASTM D 92-18	
6	Punct de curgere Pour point	°C	max. -42	-42	SR 13552-12 ASTM D 97-17b	
7	Actiune coroziva pe lama de cupru 3 ore la 120°C Copper strip corrosion at 120°C, 3h	-	max. 2a	1b	SR EN ISO 2160-02 ASTM D 130-19	
8	*Caracteristici de spumare: tendinta-stabilitate Foaming characteristics: tendency-stability - la 24°C / at 24°C - la 93,5°C / at 93,5°C - la 24°C, dupa 93,5°C / at 24°C, after test at 93,5°C	ml	max	20-0 20-0 20-0	ASTM D 892-18	
9	* Proprietăți de extrema presiune / Extreme pressure properties: -Sarcina de sudura loading of weld - uzura mecanica 329N,(40kgf)1h / mechanical wear 392 N(40kgf)1h	N (kgf) mm	se raporteaza report	2000 0,7	STAS 8618-79	
10	Densitate la 15°C / Density at 15°C Densitate la 20°C / Density at 20°C	g/cm ³	se raporteaza / report	0,8545 0,8515	ASTM D 7042-21	

Observatii (Remarks) :

* Garantate prin tehnologie (Guaranteed by technology).

** Incertitudinea raportata la solicitarea clientului (Uncertainty related to customer demand).

***Aceasta caracteristica se raporteaza la cerere / This feature relates to customer

Incercare neacreditata (Test not accredited).

Verificat/Aprobat (Approved by):

Sef Laborator (Laboratory Chief)

Lungu Cristina

Intocmit: (Performed by):

Popa Adriana

LUKOIL LUBRICANTS EAST EUROPE S.R.L.

LABORATOR LUBRIFIANTI

Note: 1) Raportul de incercari se refera numai la proba supusa incercarii/ The test report refer only to tested sample.

2) Reproducerea partiala a raportului de incercari este interzisa/ Any partial reproduction of report is forbidden.

Cod FL-7.8-01,ed.1

DECLARATIE DE CONFORMITATE/CONFORMITY STATEMENT
Nr./No: 1040 Data/Date: 26.08.2022

Noi,

Numele furnizorului: LUKOIL LUBRICANTS EAST EUROPE S.R.L

Adresa furnizorului: Str. Mihai Bravu, nr. 235, Ploiesti, jud. Prahova, Romania

Nr. de inregistrare la Registrul Comertului: J29/1451/0810.2015

Declarăm ca produsul la care se refera aceasta declaratie este in conformitate cu cerintele specificate in documentul normativ specificat mai jos, respecta standardele pentru protectia vietii, a sanatatii si a securitatii muncii, nu produce impact negativ asupra mediului, in conditiile in care sunt respectate cerintele privind manipularea, depozitarea, transportul si destinatia/utilizarea specificata in Fisa cu Date de Securitate.

De asemenea, produsul respecta Regulamentul (CE) nr.765/2008 si Directiva 2001/95/CE, transpusa in legislatia interna prin Legea nr. 245/2004.

We,

Supplier Name: LUKOIL LUBRICANTS EAST EUROPE S.R.L

Supplier Address: Ploiesti, 235 Mihai Bravu Street, Prahova County, Romania

Registration number at the Commerce Registry: J29/1451/0810.2015

Declare that the product to which this declaration relates is in accordance with the requirements specified in the normative document specified below, complies with the standards for the protection of life, health and security, does not produce a negative impact on the environment, provided that the requirements for handling, storage, transport and destination / use specified in the Safety Data Sheet are complied with.

Also, the product complies with Regulation (EC) no. 765/2008 and Directive 2001/95 / EC, transposed into Romanian legislation by Law no. 245/2004:


Denumire produs <i>Product name</i>	Lot, Rez./Lot, Tank <i>Ambalaj/Pack</i>	Titlul si numarul documentului normativ <i>Title end no. of the normative document</i>	
LUKOIL TRANSMISSION SYNTH MPV 75W-80	Lot 2610	Ulei pentru transmisii <i>Transmission oil</i>	ST-10,ed. 3/2020
Raport de Incercare / <i>Test report</i>	1070	Data / <i>Date</i>	26.08.2022

Certificat de Valabilitate <i>Certificate of Validity</i>	Perioada de valabilitate a produsului in depozitare este 5 ani de la data fabricatiei, in conditiile respectarii cerintelor de ambalare, depozitare, transport si manipulare. <i>Shelf life of product in storage is 5 years from date of manufacture, in compliance with the requirements for packaging, storage, transport and handling.</i>
---	---

Certificat de Conformitate RAR-OCP <i>Certificate of statement RAR-OCP</i>	Nr. 719, valabil pana la 22.03.2026 <i>No. 719, valid to 22.03.2026</i>
---	--

LUKOIL LUBRICANTS EAST EUROPE SRL

PANAIT Luminita



Strada Mihai Bravu, Nr. 235 - CP 100410
Ploiesti, Prahova, Romania
Intrare: Poarta 5 - Centura de Est DN1A

Registrul Comertului Nr.: J29/1451/08.10.2015
Cod Unic Inregistrare: RO19737772

Tel.: +4 0244 504 802
Fax: +4 0244 504 801

Membru al

Web: www.lukoil-lubricants.ro
Mail: office.llee@eu.lukoil.com

