

Conductivity meter, handheld, Eutech CON 150

*Conductivity meter, Eutech CON 150*

Catalog # 663-0343

This portable meter features a waterproof design with IP67 rating.

Large, three line LCD displays conductivity or TDS measurement with temperature as well as cell efficiency

Grip-Clip™: Quickly and easily secures the pH electrode to a beaker or container

Stores up to 150 measurements along with temperature

Adjustable temperature coefficient – Set to 0,0 % to meet USP methods for non compensated measurements

Calibrate using automatically recognised standards or manually; calibration due alarm

Can be used with two AA batteries or with optional universal power adapter (not included)

Built-in stand with wall-mount option allows for easy bench top measurement or storage

The meter accepts probes with a 0,1; 1,0 or 10 cell constant.

Delivery information: Meter is supplied with conductivity cell (K = 1.0), Grip-Clip™ and two AA batteries.

The kit includes meter, conductivity cell (K = 1.0), Grip-Clip™, two AA batteries, hard carrying case and calibration solution.

Description:

Conductivity meter, Eutech CON 150

Compliance:IP67

Conductivity resolution:0,01 µS - 0,1 mS

Data logging capacity:150 data sets

Power supply:Two AA batteries (included),

Temperature compensation:

Automatic or manual (-10...+110 °C)

Temperature resolution:0,1 °C

TDS resolution:0,01 ppm - 0,1 ppt

Temperature accuracy:±0,5 °C

TDS accuracy:±1 % full scale

Weight:0,5 kg

Cat. No.:663-0343

Conductivity accuracy:±1 % full scale

Conductivity calibration:Auto/manual; 1 point/range

Temperature coefficient:0,0 - 10,0 %/°C

Model:Eutech CON 150

Conductivity range:0 - 200 mS

TDS range:0 - 200 ppt

W×D×H:200×83×57 mm

Temperature range:-10,0...+110,0 °C

Temperature calibration:Off set in 0,1 increments, ±10 °C

Display:LCD

