

2. TECHNICAL DATA

2.1 TECHNICAL DATA LIST

Table 3 TECHNICAL DATA

Items			Rated value	
Nominal X-ray tube Voltage		Fluoroscopy	125 kV	
IEC 60613:2010		Radiography	150 kV	
X-ray tube assembly	Max. heat content		1100kJ {1600kHU}	
	Nominal continuous input power IEC 60613:2010		470W{660HU/s} : with fan 235W{330HU/s} : without fan	
X-ray tube	Max. anode heat content		280kJ { 400kHU}	
	Max. anode heat dissipation rate		1600W {2200HU/s}	
	Max. continuous heat dissipation rate		300W { 420HU/s}	
	Continuous anode input power IEC 60613:2010		100W (Repetition of radiographic exposure)	
Nominal focal spot value IEC 60336			0.6	1.2
Measuring method of focal spot size			Slit camera	Slit camera
X-ray tube max. Fluoroscopic load(10min.)		Anode stationary	355W {500HU/s}	425W{600HU/s}
		Anode rotating	425W {600HU/s}	425W{600HU/s}
Nominal anode input power (0.1sec)		50Hz (164DK)	12.7kW	34.3kW
		60Hz (164DK)	13.8kW	37.3kW
		180Hz (364DK)	24kW	65kW
Nominal radiographic anode input power IEC 60613:2010		50Hz (164DK)	12.7kW	34.3kW
		60Hz (164DK)	13.8kW	37.3kW
		180Hz (364DK)	24kW	65kW
Max. filament voltage			7.6 V	12.1 V
Max. filament current *1			5.6 A	5.6 A
Anode target	material		Rhenium-tungsten faced molybdenum	
	angle/diameter		16°/100mm	
Anode rotation *2			Direction of anode rotation is counter-clockwise as viewed from the cathode side, and R.P.M as follows. 2700 min. ⁻¹ {R.P.M.} at 50 Hz 3200 min. ⁻¹ {R.P.M.} at 60 Hz 9700 min. ⁻¹ {R.P.M.} at 180 Hz	
Minimum total filtration IEC 60601-2-28:2017			1.7 mm Al/75 kV (Including added filter*3)	
Permanent filtration *4		IEC 60601-2-28:2017	1.0 mm Al/75 kV IEC 60522:1999 (without added filter)	
		JIS Z 4751-2-28:2008 (IEC 60601-2-28:1993)	Min. 1.5 mm Al at 70kV *5 (Including added filter)	
Leakage radiation *6 IEC 60601-1-3:2008+A1:2013			Leakage radiation in hour from the X-ray tube assembly and collimator is less than 0.87mGy at a distance of 1 meter from the focal spot. However, leakage radiation in an hour from the collimator is less than 0.30mGy.	
X-ray radiation field			350mm × 350mm (at distance of 650mm from focal spot)	
IEC classification IEC 60601-1:2005+A1:2012			CLASS I	
Mode of operation			Continuous operation with intermittent loading	
Mass *7			21 kg	
High voltage connector			IEC 60526 type	