




Husqvarna 135 Mark II

Lightweight and easy to use – Husqvarna 135 Mark II is a chainsaw ideal for cutting tasks around the garden, such as cutting firewood and felling small trees. It has an X-Torq® engine that provides great power and torque thanks to highly efficient combustion. Easy to start and equipped with anti-vibration dampeners for sparing the user's arms and hands. Inertia chain brake for extra safety and the chain is easily adjusted using the side-mounted chain tensioner.



Air Injection™ Technology

Centrifugal air cleaning system for reduced wear and longer operating time between filter cleaning.



Powerful and Efficient X-TORQ® Engine

Delivers lower fuel consumption and reduced exhaust emission levels in accordance with the world's most stringent environmental regulations.

Side Chain Tensioning

Quickly and easily adjust the chain



Inertia-Activated Chain Brake

In case of a kickback, the effective inertia-activated chain brake immediately stops the chain to reduce the likelihood of injury.



FEATURES

- Quickly and easily adjust the chain
- Great power and efficiency
- Centrifugal air cleaning system expels larger dust and debris particles before they reach the air filter to help improve engine life
- Effective inertia-activated chain brake reduces the likelihood of injury due to kickback.
- Air purge removes air from carburetor and fuel system for easy starting
- Provides easier starting and reduces the risk of engine flooding
- Effective LowVib® dampeners absorb vibration, sparing the user's arms and hands.
- Specially-designed engine and starter for easy and fast starting with minimum effort

Technical Specifications	
CAPACITY	
Chain speed at 133% of maximum engine power speed	22.3 m/s
Chain speed at max power	16.8 m/s
Clutch engagement speed (±120)	4000 rpm
Clutch engagement upper limit	4500 rpm
Idling speed	3000 rpm
Idling upper limit	3200 rpm
Ignition module air gap	0.3 mm
Maximum power speed	9000 rpm
Output shaft power	1.6 kW
Racing speed lower limit	11200 rpm
Torque, max.	1.84 Nm
Torque, max. at rpm	8000 rpm
CERTIFICATIONS	
Cert machine dir. 2006/42/EC Decl. No.	Yes
DIMENSIONS	
Article gross weight	7300 g
Article net weight	6000 g
Bar length (inch)	16 in
Bar length	40 cm
Weight (excl. cutting equipment)	4.7 kg
ENGINE	
Cylinder bore	39 mm
Cylinder displacement	38 cm ³
Cylinder stroke	32 mm
Electrode gap	0.55 mm
Engine Family CARB	*PWES.0384CX
Engine Family EPA	-PWES.0384CX
Ignition module air gap	0.3 mm
Spark Plug	NGK BPMR7A
EQUIPMENT	
Bar mount type	HSM
Chain type	S93G
Chainsaw sub-group	Occasional use chainsaws
Handle type	Standard
Pitch	3/8" mini
Sprocket type	Spur 6
LUBRICANTS	
Fuel consumption	725 g/kWh
Fuel consumption	0.725 kg/h
Fuel tank volume	0.37 l
Lubricant type (Engine)	Husqvarna 2 stroke or equiv. at 50:1
Oil pump type	Automatic
Oil tank volume	0.26 l
Power/fuel type	Gasoline
MATERIALS	
Master pack: Paper material	0 g
Metal total	0 g
Paper material total	840 g
HDPE (02) total	0 g
PET (01) total	0 g
Plastic foil total	12 g
Plastic rigid total	0 g
Plastic total	12 g
PS/EPS/HIPS (06) total	0 g
PACKAGING	
Packaging height	333 mm
Packaging length	495 mm
Packaging width	285 mm
Quantity in Master pack	1
EMISSION DATA CARB	
Engine Family CARB	*PWES.0384CX
Exhaust emissions (CO average) CARB	330.7 g/kWh
Exhaust emissions (CO average) CARB	877 g/kWh

Technical Specifications

Exhaust emissions (HC average) CARB	40.85 g/kWh
Exhaust emissions (NOx average) CARB	1.14 g/kWh

EMISSION DATA EPA

Engine Family EPA	-PWES.0384CX
Exhaust emissions (CO average) EPA	331 g/kWh
Exhaust emissions (CO FEL) EPA	536 g/kWh
Exhaust emissions (CO average) EPA	877 g/kWh
Exhaust emissions (HC average) EPA	40.85 g/kWh
Exhaust emissions (NOx average) EPA	1.14 g/kWh

EMISSION DATA EU

Exhaust emissions (CO average) EU	278.5 g/kWh
Exhaust emissions (CO average) EU	804 g/kWh
Exhaust emissions (CO EU V)	804 g/kWh
Exhaust emissions (HC average) EU	41.7 g/kWh
Exhaust emissions (NOx average) EU	1.11 g/kWh

SOUND AND NOISE

Sound power level, guaranteed (LWA)	116 dB(A)
Sound power level, measured	114.34 dB(A)
Sound pressure (15m)	102 dB(A)
Sound pressure level at operators ear	102 dB(A)

VIBRATIONS

Equivalent vibration level (ahv, eq) front handle	3.72 m/s ²
Equivalent vibration level (ahv, eq) rear handle	5.5 m/s ²

DREMEL® VersaTip (2000-6)



Contents

DREMEL® VersaTip
Soldering Tip
Cutting Knife
Hot Knife
Flat Wide Flame Head
Reflector
Hot Blower Head
Soldering Tin with Blue Cap
Soldering Sponge + sponge box
2 wrenches:
1 x 7 mm wrench
1 x 8 mm wrench

Technical specifications

Weight	0,135 kg
Ignition	Piézo
Burn time	30 - 60 min



Order information

Ordernumber: F0132000JA

EAN: 8710364037582



AMHB2791



PRODUCTS > Cordless tools

HOT



CKLI2019 **INDUSTRIAL**

5 Pcs Cordless industrial combo kit

Voltage:20V

With 1pcs lithium-ion cordless drill (CDLI20051)

With 1pcs lithium-ion impact wrench (CIWLI2038)

INGCO Stores



INFORMATION

Voltage:20V

With 1pcs lithium-ion impact wrench (CIWLI2038)

Privacy Policy

INGCO TOOLS and its affiliates (collectively, "INGCO", "we", "us", and "our") respect your privacy. Please read the following to learn more about our Privacy Policy ("this Policy"). This Policy applies to INGCO TOOLS, products, and services that display or provide links to this Policy.



This Policy describes how INGCO processes your personal data, but it may not address all possible data processing scenarios. INGCO may inform you of product or service specific data collection through supplementary policies or notices provided before collection.

This Policy describes:

[Learn More](#)

Max torque:300Nm

Lithium-ion cordless drill(CDLI200528):

No-load speed:0-400/0-1500rpm

Max torque:45Nm

Plastic chuck

Chuck capacity:0.8-10mm

Torque settings:15+1

Mechanical 2-speed gear

Lithium-ion rotary hammer(CRHLI20228):

Brushless motor

No-load speed:0-1100rpm

Impact rate:0-5000bpm

Impact energy:2.5J

Max drilling capacity: diameter 26mm in concrete

Integrated LED work light

SDS plus chuck system

Lithium-ion angle grinder(CAGLI201158):

Brushless Motor

No-load speed:3000/8500rpm

Disc diameter:115mm

Spindle thread:M14

Work lamp(CWLI2023)

LED power dissipation:1.5W

Lumens:150±10%

Include:

Privacy Policy

INGCO TOOLS and its affiliates (collectively, "INGCO", "we", "us", and "our") respect your privacy. Please read the following to learn more about our Privacy Policy ("this Policy"). This Policy applies to INGCO TOOLS, products, and services that display or provide links to this Policy.



This Policy describes how INGCO processes your personal data, but it may not address all possible data processing scenarios. INGCO may inform you of product or service specific data collection through supplementary policies or notices provided before collection.

This Policy describes:

 +961 5 810 109

 info@ghazzawibros.co

 Beirut, Lebanon

Follow us!



©2020-2026 INGCO All rights reserved

Privacy Policy

INGCO TOOLS and its affiliates (collectively, "INGCO", "we", "us", and "our") respect your privacy. Please read the following to learn more about our Privacy Policy ("this Policy"). This Policy applies to INGCO TOOLS, products, and services that display or provide links to this Policy.



This Policy describes how INGCO processes your personal data, but it may not address all possible data processing scenarios. INGCO may inform you of product or service specific data collection through supplementary policies or notices provided before collection.

This Policy describes:



Cordless Blower Vacuum DUB187



Blower Mode

Max air volume

4.2 m³/min

Max air velocity

64 m/s

Vacuum Mode

Max air volume

6.1 m³/min

Max sealed suction

3.3 kPa



Vacuum



Cordless Blower

Vacuum Mode

Max air volume

6.1 m³/min

Max sealed suction

3.3 kPa

Blower Mode

Max air volume

4.2 m³/min

Max air velocity

64 m/s

Continuous run time (approx.)

on a full battery charge: minutes

Vacuum Mode / Blower Mode

14 min

With BL1860B battery

BL
MOTOR

XPT

eXtreme Protection
Technology

Blower



Two casters

Vacuum powered by 18V LXT Li-Ion battery

Variable speed control by trigger + Cruise control

Cruise control lever allows user to lock the variable speed control trigger at the desired power level.



Vacuum



Shredder blade

Metal shredder blade is attached on the fan to chip fallen leaves or twigs for mulching.



Before

After



Vacuum / Blower

Single action lever

for blower / vacuum mode selection



Blower



Dust bag capacity

25L

dust bag with a large inlet opening



* These models are not compatible with Portable Power Pack (PDC1200, PDC01) / Only rear handle type chainsaws are compatible

** These models are not compatible with Portable Power Pack (PDC1200)

Accessories

T shape vacuum nozzle assy

Part No. GB00000165

Dust collection can be efficiently performed on flat ground, etc.



Portable Power Pack

PDC01

432 Wh high capacity (with 4 pcs. of BL1860B)



Adapter set

Part No. 191J50-7



Charging Time

	Fast Charging	
	DC18RC	DC18SD
BL1815N 1.5Ah	15 min	30 min
BL1820B 2.0Ah	24 min	45 min
BL1830B 3.0Ah	22 min	60 min
BL1840B 4.0Ah	36 min	90 min
BL1850B 5.0Ah	45 min	110 min
BL1860B 6.0Ah	55 min	130 min

Cordless Blower Vacuum

DUB187

Variable Speed

Soft Start

No load speed (RPM) 9,000-13,500

Max air volume (Vacuum) 6.1 m³/min

Max sealed suction 3.3 kPa

Dust bag capacity 25 L

Max air volume Blower: 4.2 m³/min

Vacuum: 6.1 m³/min

Max air velocity Blower: 64.0 m/s

Vacuum: 3.3 kPa

Sound pressure level 81.8 dB (A)

Sound power level 94.32 dB (A)

Vibration Level Operation w/o Load (Blowing): 2.5 m/s² or less

Operation w/o Load (Vacuuming): 2.5 m/s² or less

Dimensions (L x W x H) 1,168 x 164 x 416 mm (46 x 6-1/2 x 16-3/8")

Net weight 3.7 - 4.0 kg (8.2 - 8.8 lbs.)

Standard Equipment : Dust bag, Shoulder belt, Battery, Charger

The weight may differ depending on the attachment(s), including the battery cartridge. The lightest and heaviest combination, according to EPTA-Procedure 01/2014, are shown in the table.

Items of standard equipment and specifications may vary by country or area.

Makita Corporation

3-11-8 Sumiyoshi-cho, Anjo, Aichi, 446-8502 Japan

PRINTED IN JAPAN 202211

FS 250 PETROL BRUSH CUTTERS



Technical Parameter	Technical Specification
Brand	“STIHL” Germany
Model	FS 250
Power output (Kw/ hp)	1.6/2.2
Displacement (cm ³)	40.2
Weight (kg)	6.3