




PILLARS OF PERFORMANCE

Stiff Shaft Construction

- Flat wire outer coil allows a larger inner core to provide additional shaft support
- Increased wire stiffness provides stability within the vasculature for enhanced navigation
- Push and navigation without compromising tip flexibility



HIGHLY RADIOPAQUE

Compatibility

Compatible with 0.035" & 0.038" devices

Device Placement Support

- Proprietary PTFE coating reduces friction along the wire
- Added stiffness provides extra support to facilitate advancement of devices such as dilatation catheters, stent catheters and other percutaneous devices
- Provides extra support and stability during catheter placement and exchange during contralateral access

Atraumatic Tip Design

A smooth tapered transition from the shaft to the flexible tip allows atraumatic negotiation of the most difficult anatomy



Multiple Tip Configurations


Straight tip wires in a variety of flexible profiles including 1.0cm, 3.5cm, 4.0cm, 6cm, and 7cm. A J3mm tip configuration is also available

Improved Lubricity

Proprietary PTFE coating provides improved lubricity along the entire wire surface ensuring smooth manipulation throughout the vasculature



Lubricity comparison between Merit Amplatz and the leading competitor



Lower force grams equals a more lubricious wire, improving wire navigation throughout the vasculature Improved lubricity allows catheters to move more easily over the wire

Higher force grams equals more resistance felt during wire and catheter manipulation in the vasculature

Merit Amplatz is 20% more lubricious than the leading competitor.¹

¹ Data on File. Merit takes no responsibility to update the test data.


ORDERING INFORMATION

Catalog Number	Diameter	Length	Flexible Tip Length	Description
IQA513	0.035" (0.89 mm)	75 cm (29")	1.0 cm	Straight, Short Tip
IQA511	0.035" (0.89 mm)	180 cm (71")	1.0 cm	Straight, Short Tip
IQA512	0.038" (0.97 mm)	180 cm (71")	1.0 cm	Straight, Short Tip
IQA509	0.035" (0.89 mm)	260 cm (102")	1.0 cm	Straight, Short Tip
IQA510	0.038" (0.97 mm)	260 cm (102")	1.0 cm	Straight, Short Tip
IQA527	0.035" (0.89 mm)	145 cm (57")	3.5 cm	Straight, Short Tip
IQA528	0.038" (0.97 mm)	145 cm (57")	3.5 cm	Straight, Short Tip
IQA521	0.035" (0.89 mm)	75 cm (29")	4.0 cm	Straight, Short Tip
IQA524	0.035" (0.89 mm)	145 cm (57")	4.0 cm	Straight, Short Tip
IQA518	0.038" (0.97 mm)	145 cm (57")	4.0 cm	Straight, Short Tip
IQA522	0.035" (0.89 mm)	180 cm (71")	4.0 cm	Straight, Short Tip
IQA564	0.038" (0.97 mm)	75 cm (29")	6.0 cm	Straight
IQA517	0.038" (0.97 mm)	145 cm (57")	6.0 cm	Straight
IQA519	0.038" (0.97 mm)	180 cm (71")	6.0 cm	Straight
IQA520	0.038" (0.97 mm)	260 cm (102")	6.0 cm	Straight
IQA563	0.035" (0.89 mm)	75 cm (29")	7.0 cm	Straight
IQA523	0.035" (0.89 mm)	145 cm (57")	7.0 cm	Straight
IQA525	0.035" (0.89 mm)	180 cm (71")	7.0 cm	Straight
IQA526	0.035" (0.89 mm)	260 cm (102")	7.0 cm	Straight
IQA500	0.035" (0.89 mm)	145 cm (57")	J 3.0 mm	3mm J
IQA501	0.035" (0.89 mm)	180 cm (71")	J 3.0 mm	3mm J
IQA502	0.035" (0.89 mm)	260 cm (102")	J 3.0 mm	3mm J
IQA503	0.038" (0.97 mm)	145 cm (57")	J 3.0 mm	3mm J
IQA504	0.038" (0.97 mm)	180 cm (71")	J 3.0 mm	3mm J

InQwire® Amplatz

Guide Wire

AMPLATZ TIP DETAIL



To protect the intellectual property, these diagrams are symbolic rather than specific engineering renders. Wire construction varies between product sizes. Diagram not to scale

Before using, refer to Instructions for Use for indications, contraindications, warnings, precautions and directions for use.



Understand. Innovate. Deliver.™

Merit Medical Systems, Inc. 1600 West Merit Parkway South Jordan, Utah 84095 1.801.208.4300 1.800.35.MERIT

merit.com

Merit Medical Europe, Middle East, & Africa (EMEA)

Amerikalaan 42, 6199 AE Maastricht-Airport The Netherlands

+31 43 358 82 22

Merit Medical Ireland Ltd.

Parkmore Business Park West Galway, Ireland +353 (0) 91 703 733 Australia +61 (0) 3 8373 4943

+01 (0) 3 63/3 492

Austria 0800 295 374

Belgium 0800 72 906 (Dutch) 0800 73 172 (Français)

Brazil

+55 11 4561 - 0062

Canada

1.800.364.4370

China

+86-10 8561 0788

Denmark 80 88 00 24

Finland 0800 770 586

France 0800 91 60 30

Germany 0800 182 0871

Hong Kong +852-2207 6888

India +91-80-41223376

Ireland (Republic) 1800 553 163 Italy 800 897 005

Korea +8210 2205 0707

Luxembourg 8002 25 22 Netherlands

0800 022 81 84 Norway 800 11629

Portugal 308 801 034

Russia +7 495 221 89 02 Spain +34 911238406

Sweden 020 792 445

Switzerland (Deutsch) +41 22 518 02 30

(Français) +41 22 518 02 52

(Italiano) +41 22 518 00 35

UK 0800 973 115

703932001/002 ID 122217