

# Radifocus™ Guide Wire

| Description | M Non-Vascular |
|-------------|----------------|
|             |                |

## Characteristics Guide Wire

## General specifications

### Item specifications



### Description

The RADIFOCUS™ Guide Wire M Non-Vascular is a standard and stiff Nitinol guidewire covered with polyurethane containing tungsten and a hydrophilic polymer coating (Mcoat™) for non-vascular procedures.

Intended to assist in the placement or exchange of devices during non-vascular procedures in endo-urology and for the cannulation or insertion of devices into the bile ducts and pancreatic duct.

## Characteristics

- Rounded tip of Nitinol core combined with flexible tapered design ensure atraumatic navigation through the (non-vascular) vessels
- Nitinol core:



INTERVENTIONAL  
SYSTEMS

- Durable shape memory of super-elastic Nitinol core provides distal tip shape prolonged performance
- Balanced transition from tapered distal core to the more rigid proximal shaft for good crossability
- One piece construction

Products ▾

Events

Learning

Q Search

Home > Medical field > Peripheral Intervention > Basileus™ Guidewire M Gui...

- Coating Mcoat™:

- Excellent durability of hydrophilic Mcoat™ for sustained ease of navigation throughout the procedure
- Terumo's Mcoat™ superior lubricity combined with the most flexible distal tip ensure high trackability through any vasculature.

Description

Characteristics

General specifications

Item specifications

## General specifications

|                               |                                                                                                                                                                                   |
|-------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Core material</b>          | Nitinol                                                                                                                                                                           |
| <b>Radiopaque jacket</b>      | Polyurethane layer containing tungsten                                                                                                                                            |
| <b>Hydrophilic coating</b>    | MCoat™                                                                                                                                                                            |
| <b>Guidewire diameters</b>    | 0.018" (0.46 mm + 0.02 mm)* / 0.020" (0.51 mm + 0.01 mm)* / 0.025" (0.64 mm + 0.00 mm)* / 0.032" (0.81 mm + 0.00 mm)* / 0.035" (0.89 mm + 0.01 mm)* / 0.038" (0.97 mm + 0.02 mm)* |
| <b>Guidewire lengths</b>      | 80 cm / 120 cm / 150 cm / 180 cm / 260 cm / 400 cm / 450 cm                                                                                                                       |
| <b>Distal flexible length</b> | 3 cm                                                                                                                                                                              |
| <b>Distal curves</b>          | Straight / Angled                                                                                                                                                                 |
| <b>Units per box</b>          | 5                                                                                                                                                                                 |

\* Nominal OD + upper tolerance, reflecting Maximal OD.

## Item specifications

Description

Characteristics

General specifications

Item specifications

| Product code | Wire type | Outer diameter              | Length | Flexible tip length | Tip shape  |
|--------------|-----------|-----------------------------|--------|---------------------|------------|
| NV-GS18153M  | Standard  | 0.018" (0.46 mm + 0.02 mm)* | 150 cm | 3 cm                | Straight   |
| NV-GA18153M  | Standard  | 0.018" (0.46 mm + 0.02 mm)* | 150 cm | 3 cm                | 45° Angled |
| NV-PA18153M  | Stiff     | 0.020" (0.51 mm + 0.01 mm)* | 150 cm | 3 cm                | 45° Angled |
| NV-PS18453M  | Stiff     | 0.020" (0.51 mm + 0.01 mm)* | 450 cm | 3 cm                | Straight   |
| NV-PA18453M  | Stiff     | 0.020" (0.51 mm + 0.01 mm)* | 450 cm | 3 cm                | 45° Angled |
| NV-GS25153M  | Standard  | 0.025" (0.64 mm + 0.00 mm)* | 150 cm | 3 cm                | Straight   |
| NV-GA25153M  | Standard  | 0.025" (0.64 mm + 0.00 mm)* | 150 cm | 3 cm                | 45° Angled |
| NV-PA25153M  | Stiff     | 0.025" (0.64 mm + 0.00 mm)* | 150 cm | 3 cm                | 45° Angled |
| NV-PS25453M  | Stiff     | 0.025" (0.64 mm + 0.00 mm)* | 450 cm | 3 cm                | Straight   |
| NV-PA25453M  | Stiff     | 0.025" (0.64 mm + 0.00 mm)* | 450 cm | 3 cm                | 45° Angled |
| NV-GS32153M  | Standard  | 0.032" (0.81 mm + 0.00 mm)* | 150 cm | 3 cm                | Straight   |
| NV-GA32153M  | Standard  | 0.032" (0.81 mm + 0.00 mm)* | 150 cm | 3 cm                | 45° Angled |
| NV-GS32263M  | Standard  | 0.032" (0.81 mm + 0.00 mm)* | 260 cm | 3 cm                | Straight   |
| NV-GA32263M  | Standard  | 0.032" (0.81 mm + 0.00 mm)* | 260 cm | 3 cm                | 45° Angled |
| NV-GS32403M  | Standard  | 0.032" (0.81 mm + 0.00 mm)* | 400 cm | 3 cm                | Straight   |
| NV-GA32403M  | Standard  | 0.032" (0.81 mm + 0.00 mm)* | 400 cm | 3 cm                | 45° Angled |

## Description

## Characteristics

## General specifications

## Item specifications

| NV-GA35083M | Standard | 0.035" (0.89 mm + 0.01 mm)* | 80 cm  | 3 cm | 45° Angled |
|-------------|----------|-----------------------------|--------|------|------------|
| NV-PS35083M | Stiff    | 0.035" (0.89 mm + 0.01 mm)* | 80 cm  | 3 cm | Straight   |
| NV-GS35123M | Standard | 0.035" (0.89 mm + 0.01 mm)* | 120 cm | 3 cm | Straight   |
| NV-GA35123M | Standard | 0.035" (0.89 mm + 0.01 mm)* | 120 cm | 3 cm | 45° Angled |
| NV-GS35153M | Standard | 0.035" (0.89 mm + 0.01 mm)* | 150 cm | 3 cm | Straight   |
| NV-GA35153M | Standard | 0.035" (0.89 mm + 0.01 mm)* | 150 cm | 3 cm | 45° Angled |
| NV-PS35153M | Stiff    | 0.035" (0.89 mm + 0.01 mm)* | 150 cm | 3 cm | Straight   |
| NV-PA35153M | Stiff    | 0.035" (0.89 mm + 0.01 mm)* | 150 cm | 3 cm | 45° Angled |
| NV-GS35183M | Standard | 0.035" (0.89 mm + 0.01 mm)* | 180 cm | 3 cm | Straight   |
| NV-PS35183M | Stiff    | 0.035" (0.89 mm + 0.01 mm)* | 180 cm | 3 cm | Straight   |
| NV-GS35263M | Standard | 0.035" (0.89 mm + 0.01 mm)* | 260 cm | 3 cm | Straight   |
| NV-GA35263M | Standard | 0.035" (0.89 mm + 0.01 mm)* | 260 cm | 3 cm | 45° Angled |
| NV-PA35263M | Stiff    | 0.035" (0.89 mm + 0.01 mm)* | 260 cm | 3 cm | 45° Angled |
| NV-GS35403M | Standard | 0.035" (0.89 mm + 0.01 mm)* | 400 cm | 3 cm | Straight   |
| NV-GA35403M | Standard | 0.035" (0.89 mm + 0.01 mm)* | 400 cm | 3 cm | 45° Angled |
| NV-PS35403M | Stiff    | 0.035" (0.89 mm + 0.01 mm)* | 400 cm | 3 cm | Straight   |
| NV-PA35403M | Stiff    | 0.035" (0.89 mm + 0.01 mm)* | 400 cm | 3 cm | 45° Angled |
| NV-GS35453M | Standard | 0.035" (0.89 mm + 0.01 mm)* | 450 cm | 3 cm | Straight   |
| NV-GA35453M | Standard | 0.035" (0.89 mm + 0.01 mm)* | 450 cm | 3 cm | 45° Angled |
| NV-GS38153M | Standard | 0.038" (0.97 mm + 0.02 mm)* | 150 cm | 3 cm | Straight   |
| NV-PS38153M | Stiff    | 0.038" (0.97 mm + 0.02 mm)* | 150 cm | 3 cm | Straight   |
| NV-PS38183M | Stiff    | 0.038" (0.97 mm + 0.02 mm)* | 180 cm | 3 cm | Straight   |

[Products ▾](#)
[Events](#)
[Learning](#)
[Q Search](#)

Home > Medical field > Peripheral Intervention > **Nominal OD + upper tolerance reflecting Maximal OD.**

Description

Characteristics

General specifications

Item specifications

## Do you need more info about this product?

Our sales representatives are here for you.

Contact us

## Related products



[Home](#) > [Medical field](#) > [Peripheral Intervention](#) > [Radifocus™ Guide Wire M Gui...](#)

Description

Characteristics

General specifications

#### TR Band™

Item specifications  
Radial Artery Compression Device

#### FemoSeal™

Vascular Closure System

#### Progreat™

Micro Catheter System

#### NaviCross™

Support Ca

## Didn't find your product?

Consult our products in our [Product Index](#)

#### Terumo Europe

[Products A-Z](#)

[Sitemap](#)

[Privacy and cookies notice](#)

[Terms of use](#)

#### Menu

[Products](#)

[About](#)

[Events](#)

[News](#)

[Contact](#)

[Careers](#)

#### Contact us

For information on products or services available, for technical support, or to report a complaint.

[Contact us](#)

#### Follow us



Safety and performance