



rompetrol

KazMunayGcs
Group
Member

Statement of Compliance

No:68532 ;Date: 18/12/2025 Time:19:25:19

Manufacturer's name: ROMPETROL RAFINARE S.A.

Manufacturer's address: Navodari, 215 Navodari Boulevard, Administrative Building, Constanta County

Registration No. with the Register of Commerce: J1991000534130

Unique registration Code: 1860712

Hereby duly assure, guarantee, and state that:

Name of product: Gasoil EN 590 - 10PPM

of (batch/lot/tank): M92/16.12.2025.20:00-LPP106526 for barge Gilla

Transported with: BARGE GILLA

Delivered from: **Petromidia Secondary place of business (Navodari City, 1-283 Navodari Boulevard, Constanta County)**

Quantity: Kg

Beneficiary: IM ROMPETROL MOLDOVA SA

Drawn according to standard: ASTM D 4057-2022*

In compliance with:

Specification/Standard/Contract no.: SS-2.6.6 T Title:Euro 5 Diesel Edition/Revision/Date of issuance:
- / 10 / 01/09/2023/

above-described product does not threaten life, health, labor safety and does not have a negative impact upon the environment, are maintaining characteristics if respect the requirements of :

Safety data sheet No. FDS 2.6 T Title: Edition/Revision/Date of issuance: / 11 / 20/11/2025

Derogation: It's not necessary

Validity period: 3 Months Warranty period: 1 month from delivery date

Additional information:

The tests performed are listed in the test report no.: 70281 of date: 18/12/2025 7:24:13PM, in attach.

- Rompetrol Rafinare S.A. has the Quality-Environment-Health and Occupational Health and Safety Management Integrated System certified by DNV, according to standards: ISO 9001, ISO 14001, ISO 45001, ISO 50001.
- Rompetrol Refining has registered/ notified the product, according with the Regulation 1907/2006, REACH.
- Rompetrol Rafinare S.A. has empowered Rompetrol Quality Control SRL by a Contract of Representation Mandate to issue on its behalf the Conformity Statement.
- Material testing laboratories owned by Rompetrol Quality Control SRL are accredited by RENAR(Romanian Accreditation

For and on behalf of Rompetrol Rafinare SA

Rompetrol Quality Control SRL -

Head of RQ Control Products Laboratory

 ROMPETROL

Eleha Lucia Pop

ROMPETROL RAFINARE S.A.



Tel: +(40)241 506 158;241 506 700,

Fax: +(40)241 506 916;241 506 929

www.rompetrol-rafinare.ro

www.rompetrol.com

office.rafinare@rompetrol.com

Rev.24/2025

ROMPETROL RAFINARE SA

215 Navodari Blvd. Administrative Building, 905700, Navodari, Constanta, ROMANIA
fax: + (40) 241 506 930 | phone: + (40) 241 506 207 | email: office.rafinare@rompetrol.com

www.rompetrol.com

page 1 of 1

Testing report no:70281; date:18/12/2025 19:24:09

Customer: ROMPETROL RAFINARE SA
 Sample: Gasoil EN 590 - 10PPM
 Receiving date: 18/12/2025 18:15:00
 Completion date: 18/12/2025
 Sampling method: ASTM D 4057-2022*
 Tanks: M92/16.12.2025.20:00-LPP106526 for barge Gilla
 Sampled by: RQC-UTI
 Contract/Order: Contract RR nr. 5/ 07.01.2019/ Pl- rev.7 RRC.P&E
 Ship: BARGE GILLA/LPP107361
 Sample tested: 4 L
 Customer address: Navodari,B-dul Navodari nr. 215, Pavilion Administrativ,Constanta

No.	Property	Test Method	UM	Required value	Determined value	Uncertainty ³⁾
1	Cetane Number	EN ISO 5165:20		min. 51.0	51,3	-
2	Cetane Index	EN ISO 4264:2018		min. 46.0	51,2	-
3	Density At 15°C	EN ISO 12185:2024	kg/m ³	min. 815 max. 845	840,9	-
4	Polycyclic Aromatic Hydrocarbons	EN 12916:2019+A1:2024	% (m/m)	max. 8.0	5,1	-
5	Sulfur Content	EN ISO 20846:20	mg/kg	max. 10.0	8,5	-
6	Flash Point, Pm	EN ISO 2719:2016,EN ISO 2719:2016/A1:2021:21	°C	min. >55	60,5	-
7	Carbon Residue(In 10% Distillation Residue)	EN ISO 10370:15	% (m/m)	max. 0.30	<0.10	-
8	Ash Content	EN ISO 6245:03	% (m/m)	max. 0.010	0,001	-
9	Water Content	SR EN ISO 12937:01, SR EN ISO 12937:01/C91:14	% (m/m)	max. 0.020	0,010	-
10	Total Contamination	EN 12662:2024	mg/kg evaluation	max. 24	<12	-
11	Corrosion, Copper Strip (3H At 50°C)	EN ISO 2160:03		clasa 1	1b	-
12	Fatty Acid-Methyl Ester (Fame) Content	EN 14078:14	% (v/v)	max. 7	<0.05	-
13	Oxidation Stability	EN ISO 12205:1999	g/m ³	max. 25	6,0	-
14	Lubricity, Wear Scar Diameter (Wsd) At 60°C	EN ISO 12156-1:2023	µm	max. 460	450	-
15	Viscosity At 40°C	EN ISO 3104:2023	mm ² /s	min. 2.000 max. 4.500	2,925	-
16	%(V/V) Recovered At 250°C	EN ISO 3405:19	% (v/v)	<65	32,7	-
17	%(V/V) Recovered At 350°C	EN ISO 3405:19	% (v/v)	min. 85	92,7	-
18	95 %(V/V) Recovered At	EN ISO 3405:19	°C	max. 360	358,5	-
19	Cold Filter Plugging Point (Cfpp): Winter Grade, Class E	EN 116:16	°C	max. -15	-17,0	-
20	Manganese(S)	SR EN 16576:15*	mg/l	max. 2.0	<0.5	-
21	Cloud Point	EN ISO 23015:19	°C	-	-2	-

Amendment: not applicable

Remarks: S) Testing performed by SC TUV AUSTRIA ROMANIA SRL
 Fatty Acid Methyl Ester (EMAG) Content - Test Performed in RQC - Environmental Laboratory



- The Rompetrol Quality Control SRL laboratory is accredited by RENAR for testing activity in compliance with SR EN ISO/CEI 17025:2018 as specified in the accreditation certificate no. LI 333. The tests covered by the accreditation are available at www.renar.ro
- *** The marked tests are not covered by the RENAR accreditation.
- Expanded uncertainty of 95% confidence level with coverage factor k=2.
- The testing report cannot be partially reproduced without explicit written approval of the testing laboratory.
- The testing results refer to the tested sample and not the entire lot.
- The observations contained in this report are not covered by the Renar accreditation

ROMPETROL QUALITY CONTROL SRL
 215 Navodari Blvd., 2nd floor, room 220, Navodari - Constanta, Postal Code 905700 ROMANIA
 phone: + (40) 241 50 6700 | fax: +(40) 241 506 916 , email: Comercial.RQC@rompetrol.com
www.rqc.ro

cod: F. LPP_02-PG_07

ed.5/rev.4/04.2023

page 1 of 1