

KEOR LINE RT

SINGLE-PHASE
UPS
from 1000 to 3000 VA





KEOR LINE RT

Convertible UPS that can
be used in both tower
and rack configurations

- Sinusoidal output
- Convertible display for tower and rack configurations
- Advanced control interface
- Emergency shutdown remotely
- Microprocessor control
- MODEM/LAN telephone protection
- RS-232 or USB interface
- Cold start function
- Protection against voltage peaks
- Integrated self-diagnostics
- Intelligent battery management
- Overload and short-circuit protection
- Excellent voltage regulation

KEOR LINE RT

Line Interactive UPS - Single phase VI-SS




3 100 45

| Pack | Cat. Nos. | UPS | | | | |
|------|-----------------|------------------|----------------|-------------------|------------------------------|---------------------|
| | | NOMINAL POWER VA | ACTIVE POWER W | BACKUP TIME (min) | NO. OF SOCKETS IEC (10A/16A) | COMMUNICATION PORTS |
| | 3 100 45 | 1000 | 900 | 10 | 8/- | USB-RS232 |
| | 3 100 46 | 1500 | 1350 | 8 | 8/- | USB-RS232 |
| | 3 100 47 | 2200 | 1980 | 8 | 8/1 | USB-RS232 |
| | 3 100 48 | 3000 | 2700 | 8 | 8/1 | USB-RS232 |


| Cat. Nos. | 3 100 45 | 3 100 46 | 3 100 47 | 3 100 48 |
|-------------------------------------|--|------------|------------|------------|
| General characteristics | | | | |
| Nominal power (VA) | 1000 | 1500 | 2200 | 3000 |
| Active power (W) | 900 | 1350 | 1980 | 2700 |
| Technology | Line interactive VI-SS | | | |
| Waveform | Sinusoidal | | | |
| Input characteristics | | | | |
| Input voltage | 230 V ± 10 % | | | |
| Input frequency | 45-65 Hz | | | |
| Input voltage range | 165 V-300 V | | | |
| Output characteristics | | | | |
| Output voltage | 230 V ± 10 % | | | |
| Output frequency (nominal) | 50/60 Hz +/-0,5 % autosensing | | | |
| THD of output voltage | < 3 % with linear load | | | |
| Batteries | | | | |
| Number of batteries | 3 | 3 | 6 | 6 |
| Battery range type/voltage | 12 V, 7 Ah | 12 V, 9 Ah | 12 V, 7 Ah | 12 V, 9 Ah |
| Communication and management | | | | |
| Screen and signalling | Three buttons, display and three LEDs for real-time control of the status of the UPS | | | |
| Telephone protection | RJ11/RJ45 | | | |
| Remote control | SNMP Slot | | | |
| Mechanical characteristics | | | | |
| Dimensions W x D x H (mm) | 440x405x88 | | 440x650x88 | |
| Net weight (kg) | 19 | 20 | 34 | 37 |
| Ambient conditions | | | | |
| Ambient operating temperature (°C) | 0 ÷ 40 °C | | | |
| Relative humidity (%) | 0÷95 % non-condensing | | | |
| Noise at 1 m (dBA) | < 40 | | | |
| Certifications | | | | |
| Reference product standards | EN62040-1, EN62040-2, EN62040-3 | | | |

NOTE: The stated back-up times in minutes are estimated and may vary according to the load characteristics, operating conditions and environment.

1000-1500 VA



2200-3000 VA





**World Headquarters and
International Department**
87045 Limoges Cedex - France
☎ : + 33 (0) 5 55 06 87 87
Fax : + 33 (0) 5 55 06 74 55

In accordance with its policy
of continuous improvement, the
Company reserves the right to change
specifications and designs without
notice. All illustrations, descriptions,
dimensions and weights in this
catalogue are for guidance and cannot
be held binding on the Company.