



*NITECH* s.r.l.



Str. Grenoble, nr. 106 A, ap. 2, mun. Chișinău  
Tel: (+373) 22 92 02 20; Fax: (+373) 22 63 28 61  
Mobil: 079920220; e-mail: office@nitech.md; www.nitech.md

**Anexa A**  
**la Termenii și condițiile de furnizare**

**Detalii specifice și standarde tehnice**

**LOT „Centrifugă cu refrigerare”:**

N <sup>o</sup>	Name of product	Minimal technical specifications	Offered specifications; <b>ROTINA 380R with accessories , HETTICH GMBH - GERMANY</b>
1	<b>Centrifugă cu refrigerare</b>	<p>Refrigerated centrifuge for daily use in research or analytical laboratories. It has a capacity of 4 x 290 ml at a maximum RCF of 4.863; High-performance cooling in the range -20 °C to +40 °C, with a rapid cool program; High RCF: up to 16.504 for 50 ml tubes and 94 ml tubes /up to 24,400 for reaction tubes.</p> <ul style="list-style-type: none"> <li>- Protection against aerosols through the TUV-tested accessories with bio seals; Compact benchtop centrifuge; Ergonomic C control panel allows complex centrifugation programs to be entered, stored and called up as required; 90 programmable memories;</li> <li>- 9 braking and acceleration ramps, unbraked run-down, or a cut-off speed can be selected. Ramp 9 represents the shortest braking and acceleration time; High capacity: max..4 x 290 ml/ max. 36 x 15 ml</li> </ul>	<p>Refrigerated centrifuge for daily use in research or analytical laboratories. It has a capacity of maximum 4 x 290 ml at a maximum RCF of 4863 with offered rotor 1754 ; High-performance cooling in the range -20 °C to +40 °C, with a rapid cool program; High RCF: up to 16.504 for 50 ml tubes and 94 ml tubes /up to 24,400 for reaction tubes with special rotors</p> <ul style="list-style-type: none"> <li>- Protection against aerosols through the TUV-tested accessories with bio seals; Compact benchtop centrifuge; Ergonomic C control panel allows complex centrifugation programs to be entered, stored and called up as required; 98 programmable memories;</li> <li>- 10 braking and 9 acceleration ramps, unbraked run-down, or a cut-off speed can be selected. Ramp 9 represents the shortest braking and acceleration time; High capacity: max..4 x 290 ml/ max. 36 x 15 ml</li> </ul>

			Delivered with : Rotor 1754 for 16 x 50ml and 36x 15 ml Falcon tubes 4 x 1751 biosil lid for bucket 4 x 1752 bucket 4 x 1771-A- adapter for 15ml Falcon tubes 4 x 1772-A- adapter for 50ml Falcon tubes
	<b>Mandatory requirements</b>	<ul style="list-style-type: none"> <li>- Original manufacturer packing for all items;</li> <li>- Quality Certificates (CE and/or DC) or any other equivalent;</li> <li>- ISO 9001-2015</li> </ul>	<ul style="list-style-type: none"> <li>- Original manufacturer packing for all items;</li> <li>- Quality Certificates (CE and/or DC) or any other equivalent;</li> </ul> ISO 9001-2015

- **Toate bunurile vor fi testate de beneficiar. Acceptarea bunurilor și semnarea actelor de recepție va avea loc după testarea pozitivă efectuată de beneficiar.**

NUMELE FURNIZORULUI SC NITECH SRL      Semnătura și ștampila autorizate \_\_\_\_\_

Locul: CHISINAU- Rep. Of MOLDOVA

Data: 17.02.2023