Specificaţii tehnice (F4.1)

Numărul procedurii de achiziție_____din_____

Denumirea procedurii de achiziție:

Cod CPV	Denumirea bunurilor/serviciilor	Modelul articolului	Țara de origine	Producătorul	Specificarea tehnică deplină solicitată de către autoritatea contractantă	Specificarea tehnică deplină propusă de către ofertant	Standarde de referință
1	2	3	4	5	6	7	8
30200000-1	**Acumulator UPS plumb acid 12 V, 7Ah.(151x65x94 mm)**	Yucel, Y7-12	Indonesia	YUASA	**Acumulator UPS plumb acid 12 V, 7Ah.(151x65x94 mm)**	**1. Type** Valve Regulated Lead Acid Battery, 12V, 7Ah; **2. Model** Yucel- VRLA Battery Y7-12 **3. Nominal voltage 12V**; 4. 20-hr rate Capacity to 1.75VPC at 20°C **7Ah**; 5. **Weight /** Mass (typical) **2,45 kg;** 6. **Internal resistance** (according to EN IEC 60896-21) N/A mΩ; 7. **Maximum Discharge Current for 1 minute Approx 48A** 8. **Charging Methods at 20^{0}C** Cycle use: Charging Voltage **2.42V/cell @ 20°C; 14,5 V** Mximum Charging current **1.75 A** Standby use: Float charge voltage at 20°C **13.65 (±1%) V; 2.275 (±1%) V/cell** **9. OPERATING TEMPERATURE RANGE** Storage -20°C to +60°C Charge -15°C to +50°C Discharge -20°C to +60°C **10. CASE MATERIAL** Standard Option - ABS (UL.94:HB) Flame retardant option (FR) - ABS (UL94:V0)	

						11. **Yuasa design life @ 20°C up to 5 years** 12. **TERMINAL TYPE** FASTON (Quickfit / release) 4,75 mm 13. **DIMENSIONS** Length - 151 (±1) mm Width - 65 (±1) mm Height - 94,5 (±1) mm (height over terminals) - 100 (±2) mm **TERMEN DE GARANTIE 18 LUNI DE LA DATA LIVRARII**	

Semnat _____

Numele, Prenumele: Otorcea Oleg

În calitate de: Director

Ofertantul: „SEOL-GROUP" SRL

Adresa: Chișinău, șos. Muncești 380