## New Edition Improved hardware Compact design

- Gold Plated BNC
- Multichannel
- Pre-programmed standards
   pH: 11 preprogrammed + 5 user editable
   Conductivity: 3 preprogrammed + 3 user editable
- No interference between electrodes
- Stability algorithm with intuitive indicator
- Hold function
- Selectable resolution
- Range lock
- Capacitive compensation
- Galvanic isolated USB interface
- High Accuracy
- Free software and firmware updates





The C3210 and C3230 are all full-parameter multi-channel instruments. 2 channels with each channel having it's own dedicated measurement hardware without interference between the channels. All values can be displayed simultaneously on the screen.

New SZ20T: maintainance free DO probe

## Specifications depending on model

Measurement Channels 2
Temperature Channels 2

-2.000...+16.000 pH mV ±2000.0 mV

**mV** ±2000.0 mV lon 0.01 ng/l...100 g/l (C3230 only)

 Dissolved oxygen
 0...60.00 mg/l 0...600%

 Air pressure
 600...1300 hPa

Temperature -5.0...+105.0°C
Warranty 36 months
Made in Belgium

Code	Description
C3210	2 channel pH/conductivity/DO meter
C32 <mark>30</mark>	2 channel pH/lon/conductivity/DO meter



## Artistic in science

Consort byba Parklaan 36 B-2300 Turnhout Belgium Telephone (+32) (0)14 41 12 79
Email info@consort.be
Sales sales@consort.be
Support support@consort.be
Website www.consort.be