

Specificații tehnice

[Acest tabel va fi completat de către ofertant în coloanele 2, 3, 4, 6, 7, iar de către autoritatea contractantă – în coloanele 1, 5,]

Numărul procedurii de achiziție: ocds-b3wdp1-MD-1679412085754 din 22.03.2023

Obiectul achiziției: Echipament Audio

Denumirea bunurilor/serviciilor	Denumirea modelului bunului/serviciului	Țara de origine	Producătorul	Specificarea tehnică deplină solicitată de către autoritatea contractantă	Specificarea tehnică deplină propusă de către ofertant	Standarde de referință
1	2	3	4	5	6	7
Digital Audio Mixer	SQ-5, SQ-Slink, Galaxy Tab S8+, 88685-50	China, Vietnam	Allen Heath, Samsung, Prosnake	48-Channel Digital Mixer 19" Rack mountable With 96 kHz FPGA processing 17 Faders / 6 Layers 12 x Stereo mixes (perfect for in-ear monitoring setups) + LR 3 x Stereo matrix 8 x Internal stereo FX engines with stereo returns DEEP processing enables the integration of plug-ins directly into the mixer inputs and mix channels 7" Touch screen SLink port for remote audio networking 64ch I/O port for audio networking 32 x 32 USB audio interface SQ-Drive direct recording to USB AES output Chromatic channel metering Integrated LED illumination per fader Dedicated physical controls 8 assignable SoftKeys Channel LCD displays Include SLink Network Interface Card Include tablet (equivalent Tab S8+) Size 12.4" inches Super AMOLED, 120Hz Resolution 2800 x 1752 pixels, 16:10 ratio (~266 ppi density) Protection Corning Gorilla Glass 5 Chipset Qualcomm SM8450 Snapdragon 8 Gen 1 (4 nm) CPU Octa-core, GPU Adreno 730 Internal min 128GB 8GB RAM	48-Channel Digital Mixer 19" Rack mountable With 96 kHz FPGA processing 17 Faders / 6 Layers 12 x Stereo mixes (perfect for in-ear monitoring setups) + LR 3 x Stereo matrix 8 x Internal stereo FX engines with stereo returns DEEP processing enables the integration of plug-ins directly into the mixer inputs and mix channels 7" Touch screen SLink port for remote audio networking 64ch I/O port for audio networking 32 x 32 USB audio interface SQ-Drive direct recording to USB AES output Chromatic channel metering Integrated LED illumination per fader Dedicated physical controls 8 assignable SoftKeys Channel LCD displays Include SLink Network Interface Card Include tablet Size 12.4" inches Super AMOLED, 120Hz Resolution 2800 x 1752 pixels, 16:10 ratio (~266 ppi density) Protection Corning Gorilla Glass 5 Chipset Qualcomm SM8450 Snapdragon 8 Gen 1 (4 nm) CPU Octa-core, GPU Adreno 730 Internal min 128GB 8GB RAM	-

				<p>stereo speakers (4 speakers)  Wi-Fi 802.11 a/b/g/n/ac/ax 2.4G+5GHz+6GHz,  HE160, MIMO, 1024-QAM  Bluetooth 5.2, A2DP, AVRCP, DI, HFP, HID, HOGP,  HSP, MAP, OPP, PAN, PBAP  Positioning GPS, Glonass, Beidou, Galileo, QZSS  USB Type-C 3.2  Sensors Accelerometer, Fingerprint Sensor, Gyro  Sensor, Geomagnetic Sensor, Hall Sensor.  BATTERY 10090 mAh.  Stylus, 6.2ms latency (Bluetooth integration,  accelerometer, gyro)  Colors Graphite  Include tablet case book, gray or black color, magnetic  closure.  Include Cat5e Cable  Length: 50 m  On cable reel with winding assistance  2x RJ45 Hirose connector with Neutrik NE8MX1  4x 2x AWG26 / 7 double shielded with foil metal  braided shield  Cable can be unwound completely  Housing / Bushing shielded by contact with metal plug  Warranty hardware 2 years</p>	<p>stereo speakers (4 speakers)  Wi-Fi 802.11 a/b/g/n/ac/ax 2.4G+5GHz+6GHz,  HE160, MIMO, 1024-QAM  Bluetooth 5.2, A2DP, AVRCP, DI, HFP, HID,  HOGP, HSP, MAP, OPP, PAN, PBAP  Positioning GPS, Glonass, Beidou, Galileo, QZSS  USB Type-C 3.2  Sensors Accelerometer, Fingerprint Sensor, Gyro  Sensor, Geomagnetic Sensor, Hall Sensor.  BATTERY 10090 mAh.  Stylus, 6.2ms latency (Bluetooth integration,  accelerometer, gyro)  Colors Graphite  Include tablet case book, gray or black color,  magnetic closure.  Include Cat5e Cable  Length: 50 m  On cable reel with winding assistance  2x RJ45 Hirose connector with Neutrik NE8MX1  4x 2x AWG26 / 7 double shielded with foil metal  braided shield  Cable can be unwound completely  Housing / Bushing shielded by contact with metal  plug  Warranty hardware 2 years</p>	
Combo de chitara electrica	VT40X	Vietnam	VOX	<p>Combo for Electric Guitar  Power: 40 W @ 5 Ohm  Equipped with: 1x 10" Speaker  Valvetronix tube preamp  11 Amp models (20 when using Tone Room -  editor/librarian software): Deluxe CL, Tweed 4x10,  Vox AC30, Boutique OD, VOX AC30TB, Brit 800,  Brit OR MKII, Double Rec, Boutique CL.  Effects: Pedal 1-type: 4 (Comp, Chorus, Overdrive,  Distortion)  Pedal 2-type: 4 (Flanger, Phaser, Tremolo, Delay)  Reverb type: 4 (Room, Spring, Hall, Plate)  Memory slots: 33 (60 when using Tone Room -  editor/librarian software)  User programs: 8 (2 banks x 4 channels)  6.3 mm Jack input, AUX in  Headphone connector  Foot pedal connector  Mini USB port (type B)  Including power adapter  Warranty hardware 2 years</p>	<p>Combo for Electric Guitar  Power: 40 W @ 5 Ohm  Equipped with: 1x 10" Speaker  Valvetronix tube preamp  11 Amp models (20 when using Tone Room -  editor/librarian software): Deluxe CL, Tweed 4x10,  Vox AC30, Boutique OD, VOX AC30TB, Brit 800,  Brit OR MKII, Double Rec, Boutique CL.  Effects: Pedal 1-type: 4 (Comp, Chorus, Overdrive,  Distortion)  Pedal 2-type: 4 (Flanger, Phaser, Tremolo, Delay)  Reverb type: 4 (Room, Spring, Hall, Plate)  Memory slots: 33 (60 when using Tone Room -  editor/librarian software)  User programs: 8 (2 banks x 4 channels)  6.3 mm Jack input, AUX in  Headphone connector  Foot pedal connector  Mini USB port (type B)  Including power adapter  Warranty hardware 2 years</p>	-
Combo de chitara electrica	Rumble LT25	China	Fender	<p>Bass Combo  Power: 25 Watt  1x 8" Loudspeaker  15 Amplifier models  20 Effects, 50 Factory and 30 user presets  Gain, Bass, Mid, Treble, Master controls</p>	<p>Bass Combo  Power: 25 Watt  1x 8" Loudspeaker  15 Amplifier models  20 Effects, 50 Factory and 30 user presets  Gain, Bass, Mid, Treble, Master controls</p>	-

				Preset Select, Back, Save Button, Menu Button, Tap Tempo/Tuner Button USB Output for recording and firmware updates Stereo aux Headphone output Foot-switch connection Warranty hardware 2 years	Preset Select, Back, Save Button, Menu Button, Tap Tempo/Tuner Button USB Output for recording and firmware updates Stereo aux Headphone output Foot-switch connection Warranty hardware 2 years	
Combo de chitara electrica	HB-40MFX	China	Harley Benton	Electric Guitar Modelling Combo 40 W Speaker configuration: 1x 10" 5 Amp voicings, incl. Clean, Crunch, Lead, OD1 and OD2 4 Fully programmable presets Multi-FX DSP with 5 individual digital effects: Reverb, Delay, Chorus, Tremolo and Phaser, each with adjustable parameters Controls for gain, volume, treble, mid, bass and FX as well as a master volume Mini-jack connection for aux line and headphones Bluetooth audio receiver for playing backing tracks from an external source Digital guitar tuner with LED display Output for external speaker 240 V 50/60 HZ switching power supply 12 mm wooden cabinet Warranty hardware 2 years	Electric Guitar Modelling Combo 40 W Speaker configuration: 1x 10" 5 Amp voicings, incl. Clean, Crunch, Lead, OD1 and OD2 4 Fully programmable presets Multi-FX DSP with 5 individual digital effects: Reverb, Delay, Chorus, Tremolo and Phaser, each with adjustable parameters Controls for gain, volume, treble, mid, bass and FX as well as a master volume Mini-jack connection for aux line and headphones Bluetooth audio receiver for playing backing tracks from an external source Digital guitar tuner with LED display Output for external speaker 240 V 50/60 HZ switching power supply 12 mm wooden cabinet Warranty hardware 2 years	-
Microfon set pentru tobe	PGA Drumkit 7	China	Shure	Drum microphone set PG Alta Series 1x PGA52 bass drum microphone 3x PGA56 snare / tom microphones 1x PGA57 snare microphone 2x PGA81 overhead microphones 3x Tom mounts 7x 4.6 m XLR cables Case Warranty hardware 2 years	Drum microphone set PG Alta Series 1x PGA52 bass drum microphone 3x PGA56 snare / tom microphones 1x PGA57 snare microphone 2x PGA81 overhead microphones 3x Tom mounts 7x 4.6 m XLR cables Case Warranty hardware 2 years	-
Microfon dinamic	ND76	China	ElectroVoice	<b>Dynamic large diaphragm vocals microphone</b> (Equivalent EV ND76) Polar pattern: Cardioid Frequency range: 70 - 17,000 Hz Max. SPL: 140 dB 2.4 mV / Pascal Impedance: 350 Ohm Black zinc diecast housing ABS polycarbonate Incl. microphone holder and bag Warranty hardware 2 years	<b>Dynamic large diaphragm vocals microphone</b> Polar pattern: Cardioid Frequency range: 70 - 17,000 Hz Max. SPL: 140 dB 2.4 mV / Pascal Impedance: 350 Ohm Black zinc diecast housing ABS polycarbonate Incl. microphone holder and bag Warranty hardware 2 years	-
Microfon vocal	RE520	China	ElectroVoice	Vocal Microphone (Equivalent EV RE520) Working principle: Condensator Directional characteristic: Supercardioid Frequency range: 40 - 20,000 Hz Max. Sound pressure level: 150 dB Output impedance: 200 ohms Sensitivity: 5.6 mV / Pa (-45 dBV / Pa) @ 1 kHz	Vocal Microphone Working principle: Condensator Directional characteristic: Supercardioid Frequency range: 40 - 20,000 Hz Max. Sound pressure level: 150 dB Output impedance: 200 ohms Sensitivity: 5.6 mV / Pa (-45 dBV / Pa) @ 1 kHz	-

				Requires +48 V phantom power Includes bag Warranty hardware 2 years	Requires +48 V phantom power Includes bag Warranty hardware 2 years	
Microfon vocal	E835-s	Germania	Sennheiser	Microphone (Equivalent XS1) Form Factor - Handheld Sound Field - Mono Capsule - 1 x Dynamic Polar Pattern - Cardioid Orientation - End Address High-Pass Filter - None On-Board Controls - Mic Mute Performance Frequency Range - 55 Hz to 16 kHz Impedance - 300 Ohms Load Impedance - 1 Kiloohms Sensitivity - 1.8 mV/Pa Connectivity Output Connectors (Analog) - 1 x XLR Mounting - Mic Clip/Stand Adapter (Included) Construction Material – Metal Warranty hardware 2 years	Microphone Form Factor - Handheld Sound Field - Mono Capsule - 1 x Dynamic Polar Pattern - Cardioid Orientation - End Address High-Pass Filter - None On-Board Controls - Mic Mute Performance Frequency Range - 40 Hz to 16 kHz Impedance - 350 Ohms Load Impedance - 1 Kiloohms Sensitivity - 1.8 mV/Pa Connectivity Output Connectors (Analog) - 1 x XLR Mounting - Mic Clip/Stand Adapter (Included) Construction Material – Metal Warranty hardware 2 years	-
Microfon vocal	Beta87A	China	Shure	Condenser vocal microphone (Equivalent Beta87A) -Supercardioid polar pattern -Linear transmission range for precise, detailed and true to original song and speech. -Extremely precise supercardioid characteristic over the entire frequency range for the greatest possible feedback resistance with maximum amplification. -Built-in, three-layer wind protection minimizes pop and breathing noises. -Operation with phantom power -Frequency range: 50 Hz - 20 kHz -Output impedance: 100 ohms -Idle sensitivity: -54 dBV / Pa (2 mV) -Maximum sound pressure level: 140.5 dB SPL -Inherent self-noise (equivalent sound pressure): 23.5 dB (A) -Includes microphone clip and storage bag Warranty hardware 2 years	Condenser vocal microphone -Supercardioid polar pattern -Linear transmission range for precise, detailed and true to original song and speech. -Extremely precise supercardioid characteristic over the entire frequency range for the greatest possible feedback resistance with maximum amplification. -Built-in, three-layer wind protection minimizes pop and breathing noises. -Operation with phantom power -Frequency range: 50 Hz - 20 kHz -Output impedance: 100 ohms -Idle sensitivity: -54 dBV / Pa (2 mV) -Maximum sound pressure level: 140.5 dB SPL -Inherent self-noise (equivalent sound pressure): 23.5 dB (A) -Includes microphone clip and storage bag Warranty hardware 2 years	-
Cablu Multicore	M-Studio	China	The sssnake	Studio Multicore Cables 4x Female XLR in the stagebox 4x Balanced 6.3 mm female jack (socket) in stagebox 4x Male XLR on fanout cable 4x Balanced 6.3 mm male jack (plug) in the fanout cable Length: 10 m	Studio Multicore Cables 4x Female XLR in the stagebox 4x Balanced 6.3 mm female jack (socket) in stagebox 4x Male XLR on fanout cable 4x Balanced 6.3 mm male jack (plug) in the fanout cable Length: 10 m	-
Cablu pentru instrument muzical	TMI 9 PP Vintage Black	China	The sssnake	Double sided 6.3mm mono jack Metal connectors Textile coated Colour: Black Length: min 9 m	Double sided 6.3mm mono jack Metal connectors Textile coated Colour: Black Length: min 9 m	-
Saundcard USB	Volt 476, OptiPlex 3000 MFF Intel	China	Universal Audio, DELL	4-Channel audio Interface (Equivalent Universal Audio Volt 476)	4-Channel audio Interface 24 bit / 192 kHz	-

	Core i5-12500T + Dell Pro Wireless Keyboard and Mouse - MK5221W			<p>24 bit / 192 kHz  2 microphone preamps  +48 V phantom power  Switchable air function  2 Mic/Instrument/Line inputs: XLR/6.3 mm jack combo balanced  2 Line inputs: 6.3 mm jack  4 Line outputs: 6.3 mm jack balanced  Stereo headphone output: 6.3 mm jack  MIDI input and output  USB-C connection  Incl. USB cable (type C to A)  Include brand computer, Small Form Factor  Minimum requirements:  Operating System: Windows 11 Pro 64-bit English;  Processor: 6C/12T, up to 4.6 GHz Cache: 18MB, equivalent i5-12500;  Memory: 16 GB DDR4; Hard Drive: SSD 512 GB for System;  Graphics Card: Integrated Graphics;  Network interface: Integrated 10/100/1000 Gigabit Ethernet LAN, Bluetooth;  External I/O Ports: Front: 2 USB2.0 port, 1 USB3.2, 1 USB3.2 Type-C® port, 1 audio jack; Rear: 3+1 USB3.2 ports, 2 USB2.0 ports, 2 DisplayPort 1.4 ports, 1 line-out/in audio port, 3 SATA3.0 slots for 3.5/2.5-inch HDD, and optical drive, 1 PCIe x16 slot, 1 PCIe x4 slot;  Keyboard: USB Wireless Mouse and Keyboard (Eng/Ru);  Optical drive, SD card slot;  Warranty: 2 years.</p>	<p>2 microphone preamps  +48 V phantom power  Switchable air function  2 Mic/Instrument/Line inputs: XLR/6.3 mm jack combo balanced  2 Line inputs: 6.3 mm jack  4 Line outputs: 6.3 mm jack balanced  Stereo headphone output: 6.3 mm jack  MIDI input and output  USB-C connection  Incl. USB cable (type C to A)  Include brand computer, Small Form Factor  Minimum requirements:  Operating System: Windows 11 Pro 64-bit English;  Processor: 6C/12T, up to 4.4 GHz Cache: 18MB, equivalent i5-12500;  Memory: 16 GB DDR4; Hard Drive: SSD 512 GB for System;  Graphics Card: Integrated Graphics;  Network interface: Integrated 10/100/1000 Gigabit Ethernet LAN, Bluetooth;  External I/O Ports  Front:  2 USB 3.2 Gen 1 ports  1 Universal audio jack  Rear:  1 RJ45 Ethernet port 10/100/1000 Mbps  1 Optional port (HDMI) 2.0b/Display port 1.4a (HBR3)/VGA/PS2/serial  1 USB 2.0 port  1 USB 2.0 port with Smart Power On  2 USB 3.2 Gen 1 ports  1 DisplayPort 1.4a (HBR2)  1 HDMI port  1 Power adapter port  Keyboard: USB Wireless Mouse and Keyboard (Eng/Ru);  Optical drive, SD card slot;  Warranty: 2 years.</p>	
Microfon	SM7B	China	Shure	<p>Microphone (Equivalent SM7B)  - Dynamic Speaker and Recording Microphone  - Polar pattern: Cardioid  - Frequency range: 50 – 20,000 Hz  - Sensitivity -59.0 dB (1.12 mV)  - Bass roll-off switch  - Mid-boost switch  - Impedance: 150 ohms  - Shielding against electromagnetic interference  - Swivel mount  - XLR connector  - Includes switch cover plate and windscreen  Microphone Arm ( Equivalent Gator Frameworks Deluxe)</p>	<p>Microphone  - Dynamic Speaker and Recording Microphone  - Polar pattern: Cardioid  - Frequency range: 50 – 20,000 Hz  - Sensitivity -59.0 dB (1.12 mV)  - Bass roll-off switch  - Mid-boost switch  - Impedance: 150 ohms  - Shielding against electromagnetic interference  - Swivel mount  - XLR connector  - Includes switch cover plate and windscreen  Microphone Arm (Roadworx Microphone Arm)  - Table microphone arm with cable guide</p>	-

				<ul style="list-style-type: none"> <li>- Table microphone arm with cable guide</li> <li>- Cables up to 8mm in diameter can be attached to the underside of the arms with a clip system</li> <li>- Aluminium construction</li> <li>- Locking centre joint</li> <li>- 3/8» Rhreaded connection with 5/8» adapter</li> <li>- Table clamp up to 56 mm or table feed-through up to 45 mm (20 mm hole)</li> <li>- Length upper arm: 43 cm</li> <li>- Length lower arm: 43 cm</li> <li>- Colour: Black</li> <li>- Microphone Cable Length: 3 m (equivalent Mogami xlr cable)</li> </ul>	<ul style="list-style-type: none"> <li>- Cables up to 8mm in diameter can be attached to the underside of the arms with a clip system</li> <li>- Aluminium construction</li> <li>- Locking centre joint</li> <li>- 3/8» Rhreaded connection with 5/8» adapter</li> <li>- Table clamp up to 56 mm or table feed-through up to 45 mm (20 mm hole)</li> <li>- Length upper arm: 43 cm</li> <li>- Length lower arm: 43 cm</li> <li>- Colour: Black</li> <li>- Microphone Cable Length: 3 m (Klotz MC5000 XLR Calbe)</li> </ul>	
Microphone Stand	Mic Stand Round Base Boom	China	Roadworx	<p>Microphone Stand (Equivalent Roadworx Mic Stand Round Base Boom)</p> <p>With boom arm and round metal base</p> <p>Length from approx. 92 to 150 cm</p> <p>Boom arm length: 70 cm</p> <p>Threads: 3/8" with 5/8" adapter</p> <p>Base diameter 290 mm</p> <p>Weight: 3.7 kg</p>	<p>Microphone Stand</p> <p>With boom arm and round metal base</p> <p>Length from approx. 92 to 150 cm</p> <p>Boom arm length: 70 cm</p> <p>Threads: 3/8" with 5/8" adapter</p> <p>Base diameter 290 mm</p> <p>Weight: 3.7 kg</p>	-
Level Amplifier	Cloudlifter CL-1 Mic Activator	China	Cloud Microphones	<p>1-Channel Level Amplifier (Equivalent cloudlifter)</p> <p>+25 dB for dynamic or passive ribbon microphones</p> <p>To be used in conjunction with a microphone amplifier with standard phantom power on mixers/preamplifiers/audio interfaces with mic input</p> <p>Requires phantom power</p> <p>XLR input and output</p> <p>Metal casing</p> <p>included band for fixing to microphone stand</p> <p>Warranty hardware 2 years.</p>	<p>1-Channel Level Amplifier</p> <p>+25 dB for dynamic or passive ribbon microphones</p> <p>To be used in conjunction with a microphone amplifier with standard phantom power on mixers/preamplifiers/audio interfaces with mic input</p> <p>Requires phantom power</p> <p>XLR input and output</p> <p>Metal casing</p> <p>included band for fixing to microphone stand</p> <p>Warranty hardware 2 years.</p>	-
Microfon	C417 PP	Ungaria	AKG	<p>General Specifications (Equivalent AKG C417 PP)</p> <p>Type Pre-polarized condenser microphone</p> <p>Polar Pattern Omnidirectional</p> <p>Audio frequency bandwidth 20 - 20000 Hz</p> <p>Equivalent noise level 34 dB-A</p> <p>Sensitivity 7 mV/Pa</p> <p>Signal to Noise 60 dB-A</p> <p>Electrical impedance 200 Ohms</p> <p>Recommended load impedance 1000 Ohms</p> <p>Cable length 1.5 m (5 ft.)</p> <p>Type XLR</p> <p>Gender Female</p> <p>Contacts 3-pin</p> <p>Current 2 mA</p> <p>Warranty hardware 2 years.</p>	<p>General Specifications</p> <p>Type Pre-polarized condenser microphone</p> <p>Polar Pattern Omnidirectional</p> <p>Audio frequency bandwidth 20 - 20000 Hz</p> <p>Equivalent noise level 34 dB-A</p> <p>Sensitivity 7 mV/Pa</p> <p>Signal to Noise 60 dB-A</p> <p>Electrical impedance 200 Ohms</p> <p>Recommended load impedance 1000 Ohms</p> <p>Cable length 1.5 m (5 ft.)</p> <p>Type XLR</p> <p>Gender Female</p> <p>Contacts 3-pin</p> <p>Current 2 mA</p> <p>Warranty hardware 2 years.</p>	-
Microfon	C414 XLII	Ungaria	AKG	<p>Condenser Microphone (equivalent AKG C414 XLII)</p> <p>Microphone</p> <p>Frequency Range - 20 Hz to 20 kHz</p> <p>Primary Applications - Live Sound, Studio Recording</p> <p>Form Factor - Large Diaphragm Mic / Stand/Boom Mount</p> <p>Intended Sound Sources - Vocals, Instrument</p>	<p>Condenser Microphone</p> <p>Frequency Range - 20 Hz to 20 kHz</p> <p>Primary Applications - Live Sound, Studio Recording</p> <p>Form Factor - Large Diaphragm Mic / Stand/Boom Mount</p> <p>Intended Sound Sources - Vocals, Instrument</p> <p>Sound Field - Mono</p>	-

				<p>Sound Field - Mono  Operating Principle - Pressure Gradient  Capsule - Condenser  Diaphragm - 1" / 25.4 mm  Polar Pattern - Cardioid, Figure-8, Hypercardioid, Omnidirectional, Subcardioid/Wide  Pattern Selection - Switched  Orientation - Side Address  Circuitry - Solid-State  Pad - -6 dB, -12 dB, -18 dB  High-Pass Filter - 40 Hz, 12 dB/Octave, 80 Hz, 12 dB/Octave, 160 Hz, 6 dB/Octave  Indicators - 13 x Single LED  On-Board Controls - High-Pass Filter, Pad, Polar Pattern  Windscreen - Foam (Included)  Output Connectors (Analog) - 1 x XLR 3-Pin Male (on Mic)  Mounting - Shockmount (Included)  Included Case - Hard Case  Included Filters - Pop Filter  Construction Material – Metal  Warranty hardware 2 years</p>	<p>Operating Principle - Pressure Gradient  Capsule - Condenser  Diaphragm - 1" / 25.4 mm  Polar Pattern - Cardioid, Figure-8, Hypercardioid, Omnidirectional, Subcardioid/Wide  Pattern Selection - Switched  Orientation - Side Address  Circuitry - Solid-State  Pad - -6 dB, -12 dB, -18 dB  High-Pass Filter - 40 Hz, 12 dB/Octave, 80 Hz, 12 dB/Octave, 160 Hz, 6 dB/Octave  Indicators - 13 x Single LED  On-Board Controls - High-Pass Filter, Pad, Polar Pattern  Windscreen - Foam (Included)  Output Connectors (Analog) - 1 x XLR 3-Pin Male (on Mic)  Mounting - Shockmount (Included)  Included Case - Hard Case  Included Filters - Pop Filter  Construction Material – Metal  Warranty hardware 2 years</p>	
Casti Monitor	DT-770 M	Germania	Beyerdynamic	<p>Monitor Headphones (equivalent DT-770 M)  <b>TECHNICAL SPECIFICATIONS</b>  Transducer type - Dynamic  Operating principle - Closed  Nominal frequency response - 5 - 30,000 Hz  Nominal impedance - 80-250 Ω per cartridge  Nominal SPL - 105 dB SPL  Nominal T.H.D. - &lt; 0.2%  Power handling capacity - 100 mW  Sound coupling to ear - Circumaural  Ambient noise isolation - approx. 35 dB(A)  Nominal headband pressure - approx. 6.5 N  Length and type of cable - 3 m / straight cable  Cable with in-line volume control  Connection - Gold plated mini stereo jack plug (3.5 mm) and 1/4" adapter (6.35 mm)  Warranty hardware 2 years</p>	<p>Monitor Headphones  <b>TECHNICAL SPECIFICATIONS</b>  Transducer type - Dynamic  Operating principle - Closed  Nominal frequency response - 5 - 30,000 Hz  Nominal impedance - 80-250 Ω per cartridge  Nominal SPL - 105 dB SPL  Nominal T.H.D. - &lt; 0.2%  Power handling capacity - 100 mW  Sound coupling to ear - Circumaural  Ambient noise isolation - approx. 35 dB(A)  Nominal headband pressure - approx. 6.5 N  Length and type of cable - 3 m / straight cable  Cable with in-line volume control  Connection - Gold plated mini stereo jack plug (3.5 mm) and 1/4" adapter (6.35 mm)  Warranty hardware 2 years</p>	-
Teleprompter	Off Camera iPad + Wireless Bluetooth Remote For Teleprompter Apple/ Android + Galaxy S23	China, Vietnam	PrompterPeople, Teleprompterpad, Samsung	<p>Teleprompter for fixing the tablet or phone  Articulating Arm:  Load Capacity Up to 2.72 kg  Construction Durable aluminum construction  Length, Fully Extended 28 cm  Weight 0.2 kg  Arm Length 21.1 cm (joint-to-joint length)  Mount CompatibilityTop: 1/4"-20 male screw  Bottom: cold shoe  1/4"-20 female thread (with spacer piece attached)  1/4"-20 male screw (with spacer removed)  TAB GRABBER universal tablet cradle for ultralight teleprompters</p>	<p>Teleprompter for fixing the tablet or phone  Articulating Arm:  Load Capacity Up to 2.72 kg  Construction Durable aluminum construction  Length, Fully Extended 28 cm  Weight 0.2 kg  Arm Length 21.1 cm (joint-to-joint length)  Mount CompatibilityTop: 1/4"-20 male screw  Bottom: cold shoe  1/4"-20 female thread (with spacer piece attached)  1/4"-20 male screw (with spacer removed)  TAB GRABBER universal tablet cradle for ultralight teleprompters</p>	-

				<p>Compatible Display 23 cm to 30 cm (9.25 to 11.75")          Include Remote control          Wireles remote control (teleprompter pad remote)          Wireless remote (application with IOS/Android included)  <b>WIRELESS BLUETOOTH REMOTE FOR TELEPROMPTER APPLE/ANDROID</b>          Work distance 10 meter          Include Battery          Include phone (equivalent S23)          Size 6.1 inches          Dynamic AMOLED 2X, 120Hz, HDR10+, 1200 nits (HBM), 1750 nits (peak)          Resolution 1080 x 2340 pixels, 19.5:9 ratio (~425 ppi density)          Protection Corning Gorilla Glass Victus 2          Always-on display          Chipset Qualcomm SM8550-AC Snapdragon 8 Gen 2 (4 nm)          CPU Octa-core, GPU Adreno 740          Internal min 256GB 8GB RAM  <b>MAIN CAMERA</b> 50 MP, f/1.8, 24mm (wide), 1/1.56", 1.0µm, Dual Pixel PDAF, OIS          10 MP, f/2.4, 70mm (telephoto), 1/3.94", 1.0µm, PDAF, OIS, 3x optical zoom  <b>12 MP</b>, f/2.2, 13mm, 120° (ultrawide), 1/2.55" 1.4µm, Super. Video          8K@24/30fps, 4K@30/60fps, 1080p@30/60/240fps, 1080p@960fps, HDR10+, stereo sound rec., gyro-EIS.          Wi-Fi 802.11 a/b/g/n/ac/6e, tri-band, Wi-Fi Direct          Bluetooth 5.3, A2DP, LE          USB Type-C 3.2, OTG  <b>BATTERY</b> 3900 mAh          Colors Black          Warranty hardware 2 years</p>	<p>Compatible Display 23 cm to 30 cm (9.25 to 11.75")          Include Remote control          Wireles remote control (teleprompter pad remote)          Wireless remote (application with IOS/Android included)  <b>WIRELESS BLUETOOTH REMOTE FOR TELEPROMPTER APPLE/ANDROID</b>          Work distance 10 meter          Include Battery          Include phone          Size 6.1 inches          Dynamic AMOLED 2X, 120Hz, HDR10+, 1200 nits (HBM), 1750 nits (peak)          Resolution 1080 x 2340 pixels, 19.5:9 ratio (~425 ppi density)          Protection Corning Gorilla Glass Victus 2          Always-on display          Chipset Qualcomm SM8550-AC Snapdragon 8 Gen 2 (4 nm)          CPU Octa-core, GPU Adreno 740          Internal min 256GB 8GB RAM  <b>MAIN CAMERA</b> 50 MP, f/1.8, 24mm (wide), 1/1.56", 1.0µm, Dual Pixel PDAF, OIS          10 MP, f/2.4, 70mm (telephoto), 1/3.94", 1.0µm, PDAF, OIS, 3x optical zoom  <b>12 MP</b>, f/2.2, 13mm, 120° (ultrawide), 1/2.55" 1.4µm, Super. Video          8K@24/30fps, 4K@30/60fps, 1080p@30/60/240fps, 1080p@960fps, HDR10+, stereo sound rec., gyro-EIS.          Wi-Fi 802.11 a/b/g/n/ac/6e, tri-band, Wi-Fi Direct          Bluetooth 5.3, A2DP, LE          USB Type-C 3.2, OTG  <b>BATTERY</b> 3900 mAh          Colors Black          Warranty hardware 2 years</p>	
Microfon radio	Ew135P G4 E band	Germania	Sennheiser	<p>System Microfon (Equivalent EW 135P G4-E)          Wireless Technology Analog UHF          Number of RF Channel Frequencies 1680          Included Transmitters 1 x Bodypack with Microphone          Diversity Antenna Diversity          RF Frequency Band 566 to 608 MHz          RF Bandwidth 42 MHz          Frequency Step Size 25 kHz          Max Operating Range 330' / 100.6 m (Line of Sight)          Max Transmitters per Band 12          Deviation 48 kHz (Peak)          Modulation Wideband FM          Receiver Type Camera-Mount          Mounting Options Shoe-Mount (with Included Hardware)          Antenna 1 x Flexible Whip, Fixed</p>	<p>System Microfon          Wireless Technology Analog UHF          Number of RF Channel Frequencies 1680          Included Transmitters 1 x Bodypack with Microphone          Diversity Antenna Diversity          RF Frequency Band 566 to 608 MHz          RF Bandwidth 42 MHz          Frequency Step Size 25 kHz          Max Operating Range 330' / 100.6 m (Line of Sight)          Max Transmitters per Band 12          Deviation 48 kHz (Peak)          Modulation Wideband FM          Receiver Type Camera-Mount          Mounting Options Shoe-Mount (with Included Hardware)          Antenna 1 x Flexible Whip, Fixed</p>	-

				<p>Number of Audio Channels 1  Audio I/O 1 x 3.5 mm TRS Female Unbalanced Output (Lockable)  Gain Range 42 dB (6 dB Steps)  Audio Output Level +12 dBu  Squelch 5 to 25 dB<math>\mu</math>V  Adjacent Channel Isolation &gt;65 dB  Battery Type 2 x AA (Included)  Approx. Battery Life 8 Hours (Alkaline)  Display &amp; Indicators 1 x Backlit LCD (Battery Status, Output Level, RF Level)  Transmitter Type Handheld  RF Output Power 30 mW  Audio I/O None  Audio Input Level 3 V RMS (Max)  Gain Range 48 dB (6 dB Steps)  Frequency Response 80 Hz to 18 kHz (Mic)  80 Hz to 18 kHz (Line)  Sync Method IR  Antenna 1 x Internal  Battery Type 2 x AA (Included)  Approx. Battery Life 8 Hours (Alkaline)  Display &amp; Indicators 1 x Backlit LCD (Audio Level, Battery Status, Signal Strength)  Microphone  Microphone Type Handheld Capsule  Sound Field Mono  Capsule Dynamic  Polar Pattern Cardioid  Maximum SPL 154 dB SPL Peak  Sensitivity 2.1 mV/Pa  Warranty hardware 2 years</p>	<p>Number of Audio Channels 1  Audio I/O 1 x 3.5 mm TRS Female Unbalanced Output (Lockable)  Gain Range 42 dB (6 dB Steps)  Audio Output Level +12 dBu  Squelch 5 to 25 dB<math>\mu</math>V  Adjacent Channel Isolation &gt;65 dB  Battery Type 2 x AA (Included)  Approx. Battery Life 8 Hours (Alkaline)  Display &amp; Indicators 1 x Backlit LCD (Battery Status, Output Level, RF Level)  Transmitter Type Handheld  RF Output Power 30 mW  Audio I/O None  Audio Input Level 3 V RMS (Max)  Gain Range 48 dB (6 dB Steps)  Frequency Response 80 Hz to 18 kHz (Mic)  80 Hz to 18 kHz (Line)  Sync Method IR  Antenna 1 x Internal  Battery Type 2 x AA (Included)  Approx. Battery Life 8 Hours (Alkaline)  Display &amp; Indicators 1 x Backlit LCD (Audio Level, Battery Status, Signal Strength)  Microphone  Microphone Type Handheld Capsule  Sound Field Mono  Capsule Dynamic  Polar Pattern Cardioid  Maximum SPL 154 dB SPL Peak  Sensitivity 2.1 mV/Pa  Warranty hardware 2 years</p>	
Microfon pentru instrument	MD 421-II	Germania	Sennheiser	<p>Microphone (Equivalent Sennheiser MD 421-II)  Operating Principal Pressure Gradient  Capsule Dynamic  Polar Pattern Cardioid  Frequency Range 30 Hz to 17 kHz  Impedance 200 Ohms  Sensitivity in free field, no load (1kHz)  2 mV/Pa +- 3 dB  Connectivity  Output Connectors (Analog) 1 x XLR 3-Pin  Warranty hardware 2 years</p>	<p>Microphone  Operating Principal Pressure Gradient  Capsule Dynamic  Polar Pattern Cardioid  Frequency Range 30 Hz to 17 kHz  Impedance 200 Ohms  Sensitivity in free field, no load (1kHz)  2 mV/Pa +- 3 dB  Connectivity  Output Connectors (Analog) 1 x XLR 3-Pin  Warranty hardware 2 years</p>	-
Microfon	MV7B	China	Shure	<p>Dynamic Podcast microphone (Equivalent MV7B)  Control of microphone gain, headphone level, monitor mixing,mute over touch panel interface  Individual adjustments via the ShurePlus motif desktop app possible (e.g., amplification, compression and EQ presets)  Internal shockmount  Directional characteristics: unidirectional (cardioid)  A / D converter: 16/24 bit, 44.1 / 48 kHz  Frequency range: 50 - 16,000 Hz</p>	<p>Dynamic Podcast microphone  Control of microphone gain, headphone level, monitor mixing,mute over touch panel interface  Individual adjustments via the ShurePlus motif desktop app possible (e.g., amplification, compression and EQ presets)  Internal shockmount  Directional characteristics: unidirectional (cardioid)  A / D converter: 16/24 bit, 44.1 / 48 kHz  Frequency range: 50 - 16,000 Hz</p>	-

				Adjustable gain: 0 to +36 DB Sensitivity: XLR -55 DBV / PA (1.78 mV) at 1 kHz USB -47 DBFS / PA at 1 kHz (with minimal reinforcement Flat Mode 1 Pa = 94 DB SPL) USB Maximum SPL 132 DB SPL DSP modes (presets): near / far, dark / natural / bright Power supply via USB or LIGHTNING connection MFI certified XLR output impedance: 314 ohms at 1 kHz 5/8" Thread XLR output Micro USB output 3.5 mm Jack headphone output Warranty hardware 2 years	Adjustable gain: 0 to +36 DB Sensitivity: XLR -55 DBV / PA (1.78 mV) at 1 kHz USB -47 DBFS / PA at 1 kHz (with minimal reinforcement Flat Mode 1 Pa = 94 DB SPL) USB Maximum SPL 132 DB SPL DSP modes (presets): near / far, dark / natural / bright Power supply via USB or LIGHTNING connection MFI certified XLR output impedance: 314 ohms at 1 kHz 5/8" Thread XLR output Micro USB output 3.5 mm Jack headphone output Warranty hardware 2 years	
Double Ear Intercom Headset	HMD685	China	SuperLux	Double Ear Intercom Headset (equivalent HMD685) Professional intercom headsets with flexible anti-vibration gooseneck boom microphones. The headset is lightweight, provides extra soft ear cushions and headband paddings for outstanding wearing comfort even during extra soft ear cushions Headset is provided with a dynamic vocal unidirectional patterned microphone, featuring excellent acoustic performance and a reliable noise suppression. HEADPHONE Transducer principle : dynamic, closed Ear coupling : Circumaural Frequency response : 20~20,000 Hz Impedance Double-ear: 200 Ω Sensitivity : 96 dB SPL at 1 kHz, 1 mW Max. Input Power : 100 mW Caliper pressure : approx. 4.5 N Connector : 1.5-meter (4.92') straight cord, 4-pin XLR female plug MICROPHONE Transducer principle : dynamic, cardioid Frequency response : 50~15,000 Hz Polar Pattern : cardioid Sensitivity : -64 dBV/Pa (0.6 mV/Pa) at 1 kHz Impedance : 250 Ω	Double Ear Intercom Headset Professional intercom headsets with flexible anti-vibration gooseneck boom microphones. The headset is lightweight, provides extra soft ear cushions and headband paddings for outstanding wearing comfort even during extra soft ear cushions Headset is provided with a dynamic vocal unidirectional patterned microphone, featuring excellent acoustic performance and a reliable noise suppression. HEADPHONE Transducer principle : dynamic, closed Ear coupling : Circumaural Frequency response : 20~20,000 Hz Impedance Double-ear: 200 Ω Sensitivity : 96 dB SPL at 1 kHz, 1 mW Max. Input Power : 100 mW Caliper pressure : approx. 4.5 N Connector : 1.5-meter (4.92') straight cord, 4-pin XLR female plug MICROPHONE Transducer principle : dynamic, cardioid Frequency response : 50~15,000 Hz Polar Pattern : cardioid Sensitivity : -64 dBV/Pa (0.6 mV/Pa) at 1 kHz Impedance : 250 Ω	-
Lavalier Microphone system	Sennheiser ew-D ME2 Y1-3 + Sennheiser ew-D ASA X-Y + Sennheiser Half Wave Dipole rod Antenna	Germania	Sennheiser	System Wireless Technology - Digital UHF Number of RF Channel Frequencies - 2240 Included Receivers - 5 x Receivers Included Transmitters - 5 x Bodypack Included Splitters – 1 x Active Antenna Splitter Diversity - Intelligent Switching Diversity RF Channel Scanning - Auto-Scan Max Operating Range - 100 m (Line of Sight) Max Transmitters per Band - 90 Bluetooth - 5.1 Sample Rate/Resolution - 24-Bit Receiver 5 pcs (equivalent EW-D EM Y1-3)	System Wireless Technology - Digital UHF Number of RF Channel Frequencies - 2240 Included Receivers - 5 x Receivers Included Transmitters - 5 x Bodypack Included Splitters – 1 x Active Antenna Splitter Diversity - Intelligent Switching Diversity RF Channel Scanning - Auto-Scan Max Operating Range - 100 m (Line of Sight) Max Transmitters per Band - 90 Bluetooth - 5.1 Sample Rate/Resolution - 24-Bit Receiver 5 pcs (equivalent EW-D EM Y1-3)	-

			<p>Frequency range U1/5: 1785.2-1799.8 MHz  Receiver Type - Tabletop / Rackmount  Mounting Options - Rackmount, Tabletop  Rackmount Size - 1 RU (1/2 Rack)  Antenna - 2 x 1/4 Wave Rod, BNC (Rear-Mount)  Number of Audio Channels - 1  Audio I/O - XLR 3-Pin Male Balanced  Output (Lockable), 1/4" TRS Female Unbalanced  Output  Gain Range - -3 to +42 dB (3 dB Steps)  Audio Output Level-XLR Output:+18dBu (Balanced),  1/4"Output:+12 dB (Unbalanced)  Frequency Response - 20 Hz to 20 kHz ±3 dB  Power Requirements - AC/DC Power Adapter  AC/DC Power Adapter - 11 to 13 VDC at 300 mA  (Included)  AC Input Power - 100 to 240 VAC, 50 / 60 Hz  Display &amp; Indicators - Backlit OLED (AF Level,  Frequency, Mute, RF Level, Transmitter)  Transmitter 5 pcs (EW-D SK)  Transmitter Type - Bodypack  RF Output Power - 10 mW (ERP)  Audio I/O - 1 x 3.5 mm TRS Female Input  (Lockable)  Muting - Mute Switch  Audio Input Level - 2 to 4.35 V RMS  Sync Method - Bluetooth  Antenna - 1 x Flexible Whip, Fixed (Beltpack)  Power Requirements - Battery  Microphone 5 pcs (equivalent ME-2)  Microphone Type Lavalier  Sound Field Mono  Capsule Electret Condenser  Polar Pattern Omnidirectional  Frequency Range 50 Hz to 18 kHz  Equivalent Noise Level 32 dB  Maximum SPL 130 dB SPL  Sensitivity 17 mV/Pa at 1 kHz  Output Connectors 1 x 1/8" / 3.5 mm TRS Male  (Lockable)  Cable Length 5.2' / 1.6 m  Operating Voltage 7.5 V  Active Antenna Splitter 1 pcs (equivalent EW-D ASA  X-Y)  Active Antenna Splitter (Dual 1:4) with DC Voltage  Distribution  For the UHF-range from 1350-1805 MHz  Incl. 1x power supply NT 12-35 CS and 8x BNC  connection cable  Half-wave dipole rod antenna 2 pcs  Frequency range - Y: 1785 - 1805 MHz  Connection – BNC</p>	<p>Frequency range U1/5: 1785.2-1799.8 MHz  Receiver Type - Tabletop / Rackmount  Mounting Options - Rackmount, Tabletop  Rackmount Size - 1 RU (1/2 Rack)  Antenna - 2 x 1/4 Wave Rod, BNC (Rear-Mount)  Number of Audio Channels - 1  Audio I/O - XLR 3-Pin Male Balanced  Output (Lockable), 1/4" TRS Female Unbalanced  Output  Gain Range - -3 to +42 dB (3 dB Steps)  Audio Output Level-XLR Output:+18dBu (Balanced),  1/4"Output:+12 dB (Unbalanced)  Frequency Response - 20 Hz to 20 kHz ±3 dB  Power Requirements - AC/DC Power Adapter  AC/DC Power Adapter - 11 to 13 VDC at 300 mA  (Included)  AC Input Power - 100 to 240 VAC, 50 / 60 Hz  Display &amp; Indicators - Backlit OLED (AF Level,  Frequency, Mute, RF Level, Transmitter)  Transmitter 5 pcs (EW-D SK)  Transmitter Type - Bodypack  RF Output Power - 10 mW (ERP)  Audio I/O - 1 x 3.5 mm TRS Female Input  (Lockable)  Muting - Mute Switch  Audio Input Level - 2 to 4.35 V RMS  Sync Method - Bluetooth  Antenna - 1 x Flexible Whip, Fixed (Beltpack)  Power Requirements - Battery  Microphone 5 pcs (equivalent ME-2)  Microphone Type Lavalier  Sound Field Mono  Capsule Electret Condenser  Polar Pattern Omnidirectional  Frequency Range 50 Hz to 18 kHz  Equivalent Noise Level 32 dB  Maximum SPL 130 dB SPL  Sensitivity 17 mV/Pa at 1 kHz  Output Connectors 1 x 1/8" / 3.5 mm TRS Male  (Lockable)  Cable Length 5.2' / 1.6 m  Operating Voltage 7.5 V  Active Antenna Splitter 1 pcs (equivalent EW-D ASA  X-Y)  Active Antenna Splitter (Dual 1:4) with DC Voltage  Distribution  For the UHF-range from 1350-1805 MHz  Incl. 1x power supply NT 12-35 CS and 8x BNC  connection cable  Half-wave dipole rod antenna 2 pcs  Frequency range - Y: 1785 - 1805 MHz  Connection – BNC</p>	
--	--	--	--	--	--

Handheld Microphone System	Sennheiser ew-D 835-S set Y1-3 + Sennheiser MDD 835-1 BK + Sennheiser ew-D ASA X-Y + Sennheiser Half Wave Dipole rod Antenna + Sennheiser EW-D Color Coding Set	Germania	Sennheiser  System Frequency range Y1-3: 1785.2 - 1799.8 MHz Wireless Technology – Digital UHF Number of RF Channel Frequencies – 2240 Included Transmitters – 3 x Handheld Diversity - Intelligent Switching Diversity RF Channel Scanning – Auto-Scan Max Operating Range – 100 m Max Transmitters per Band – 90 Bluetooth - 5.1 Sample Rate/Resolution – 24-Bit Receiver 3 pcs (equivalent EW-D EM Y1-3) Frequency range Y1-3: 1785.2 - 1799.8 MHz Receiver Type - Tabletop / Rackmount Mounting Options - Rackmount, Tabletop Rackmount Size - 1 RU (1/2 Rack) Antenna - 2 x 1/4 Wave Rod, BNC (Rear-Mount) Number of Audio Channels - 1 Audio I/O-XLR 3-Pin Male Balanced Output (Lockable), 1/4" TRS Female Unbalanced Gain Range - -3 to +42 dB (3 dB Steps) Audio Output Level- XLR Output: +18 dBu (Balanced), 1/4" Output: +12 dB (Unbalanced) Frequency Response - 20 Hz to 20 kHz ±3 dB Power Requirements - AC/DC Power Adapter AC/DC Power Adapter - 11 to 13 VDC at 300 mA (Included) AC Input Power - 100 to 240 VAC, 50 / 60 Hz Display & Indicators - 1 x Backlit OLED (AF Level, Frequency, Mute, RF Level. Transmitter 3 pcs (equivalent EW-D SKM-S) Transmitter Type – Handheld RF Output Power - 10 mW (ERP) Muting - Mute Switch Audio Input Level - 2 to 4.35 V RMS Auto-Level Control - No Antenna - 1 x Internal (Handheld) Power Requirements - Battery Battery Type - 2 x AA (Included) Display & Indicators - 1 x LED (Mute); 1 x LED (Sync) Microphone 6 pcs (equivalent MMD 835 capsule) Microphone Type - Handheld Capsule Sound Field - Mono Capsule - Dynamic Polar Pattern - Cardioid Equivalent Noise Level - 32 dB Maximum SPL - 154 dB SPL Sensitivity - 2.1 mV/Pa Active Antenna Splitter 1 pcs (equivalent EW-D ASA X-Y) Active Antenna Splitter (Dual 1:4) with DC Voltage Distribution	System Frequency range Y1-3: 1785.2 - 1799.8 MHz Wireless Technology – Digital UHF Number of RF Channel Frequencies – 2240 Included Transmitters – 3 x Handheld Diversity - Intelligent Switching Diversity RF Channel Scanning – Auto-Scan Max Operating Range – 100 m Max Transmitters per Band – 90 Bluetooth - 5.1 Sample Rate/Resolution – 24-Bit Receiver 3 pcs (equivalent EW-D EM Y1-3) Frequency range Y1-3: 1785.2 - 1799.8 MHz Receiver Type - Tabletop / Rackmount Mounting Options - Rackmount, Tabletop Rackmount Size - 1 RU (1/2 Rack) Antenna - 2 x 1/4 Wave Rod, BNC (Rear-Mount) Number of Audio Channels - 1 Audio I/O-XLR 3-Pin Male Balanced Output (Lockable), 1/4" TRS Female Unbalanced Gain Range - -3 to +42 dB (3 dB Steps) Audio Output Level- XLR Output: +18 dBu (Balanced), 1/4" Output: +12 dB (Unbalanced) Frequency Response - 20 Hz to 20 kHz ±3 dB Power Requirements - AC/DC Power Adapter AC/DC Power Adapter - 11 to 13 VDC at 300 mA (Included) AC Input Power - 100 to 240 VAC, 50 / 60 Hz Display & Indicators - 1 x Backlit OLED (AF Level, Frequency, Mute, RF Level. Transmitter 3 pcs (equivalent EW-D SKM-S) Transmitter Type – Handheld RF Output Power - 10 mW (ERP) Muting - Mute Switch Audio Input Level - 2 to 4.35 V RMS Auto-Level Control - No Antenna - 1 x Internal (Handheld) Power Requirements - Battery Battery Type - 2 x AA (Included) Display & Indicators - 1 x LED (Mute); 1 x LED (Sync) Microphone 6 pcs (equivalent MMD 835 capsule) Microphone Type - Handheld Capsule Sound Field - Mono Capsule - Dynamic Polar Pattern - Cardioid Equivalent Noise Level - 32 dB Maximum SPL - 154 dB SPL Sensitivity - 2.1 mV/Pa Active Antenna Splitter 1 pcs (equivalent EW-D ASA X-Y) Active Antenna Splitter (Dual 1:4) with DC Voltage Distribution	-
-------------------------------	---	----------	--	--	---

				For the UHF-range from 1350-1805 MHz Incl. 1x power supply NT 12-35 CS and 8x BNC connection cable Half-wave dipole rod antenna 2 pcs Frequency range - Y: 1785 - 1805 MHz Connection – BNC Include EW-D Color Coding Set	For the UHF-range from 1350-1805 MHz Incl. 1x power supply NT 12-35 CS and 8x BNC connection cable Half-wave dipole rod antenna 2 pcs Frequency range - Y: 1785 - 1805 MHz Connection – BNC Include EW-D Color Coding Set	
--	--	--	--	---	---	--

Semnata: Semnat electronic Numele, Prenumele: Carabut Vladislav În calitate de: Director

Ofertantul: SC „Muzic-Prod” S.R.L. Adresa: Moldova, Chisinau, Durlesti, Str-la II Vovinteni 15