

Anexa 2. Congelator

Parametri solicitati	Parametri oferiti TSX5030LV, Plasma Freezer
Destinație: pentru stocarea și păstrarea produselor sanguine congelate. Tip: vertical, cu două uși; Volumul camerei interne: - de la 1300 lit până la 1400 lit, inclusiv; Temeperatura: - de la minus 25°C până la minus 30°C; - reglabilă; - programabilă; - precizie $\pm 1^{\circ}\text{C}$. Monitorizarea temperaturii: - înregistrare grafică/integrare date termice cu SIA serviciul de sânge; - sistem electronic de control. Panoul de informatii: - va permite vizualizarea parametrilor de temperatură în timp zilnic/săptămânal; - asigurat cu alarmă în caz de depășire a parametrilor programați. Suprafața camerei interne: - din inox sau material rezistent la acțiunea substanțelor biocide folosite în scop de prelucrare sanitară. Suprafețele exterioare din inox sau material rezistent la acțiunea substanțelor biocide folosite în scop de prelucrare sanitară. Componente obligatorii prezente: - materialul sertarelor oțel inoxidabil; - suprafața perforată pentru circulația aerului; - sertare în număr de 12 - 14 unități, reglabile; - asigurate cu sistem telescopic. Sistemul de răcire: Aer forțat; Sistemul de decongelare automat. Agentul frigorific: Ecologic, aprobat de CE Parametrii rețelei electrice: 220/380 V, 50 Hz. - Declarație de conformitate CE/SM și/sau Certificat de conformitate CE/SM – pentru dispozitive medicale sau echipamente electrice. Delarație de la producător prin care se confirmă că dispozitivul medical este destinat pentru stocarea și păstrarea produselor sanguine congelate.	Destinație: pentru stocarea și păstrarea produselor sanguine congelate. Tip: vertical, cu două uși; Volumul camerei interne: 1447 litri Temeperatura: - de la minus 15°C pînă la plus minus 35°C; setpoint minus 30C - reglabilă; - programabilă; - precizie $\pm 1^{\circ}\text{C}$. Monitorizarea temperaturii: - înregistrare grafică , nu exista posibilitatea de integrare a datelor termice cu SIA Serviciul de Sânge; - sistem electronic de control. Panoul de informatii: - va permite vizualizarea parametrilor de temperatură în timp zilnic/săptămânal; - asigurat cu alarmă în caz de depășire a parametrilor programați. Materialul camerei interne: - din oțel inoxidabil; Suprafețele exterioare din material rezistent la acțiunea substanțelor biocide folosite în scop de prelucrare sanitară; - compatibil cu materiale biologice. Componente obligatorii prezente: - materialul sertarelor oțel inoxidabil; - suprafața perforată pentru circulația aerului; - sertare în număr de 14 unități, reglabile; - asigurate cu sistem telescopic. Sistemul de răcire: Aer forțat; Sistemul de decongelare automat. Agentul frigorific: Ecologic, aprobat de CE, tip R290 Parametrii rețelei electrice: 220/380 V, 50 Hz Declarație de conformitate CE sau Certificat de conformitate CE. Prospect tehnic de la producător prin care se confirmă că dispozitivul medical este destinat pentru stocarea și păstrarea produselor sanguine congelate.

-Confirmarea privind prezentarea la livrare a copiilor manualului de deservire, servis manual, diagrama electronica, pașapoartelor tehnice, inclusiv descrierea părților tehnice și componente a dispozitivului, autorizat de producător pentru fiecare dispozitiv. -Confirmarea privind livrarea și instalarea dispozitivelor medicale, în termen de 10 zile lucrătoare din data de notificare emisă de beneficiar corespunzător locațiilor de instalare Chișinău, Bălți și Cahul. -Confirmarea privind instruirea gratuită a personalului implicat în operarea dispozitivului medical pe parcursul a 10 zile din momentul punerii în funcțiune a dispozitivului. -Confirmarea privind asigurarea funcționalității, mentenanței și reparației dispozitivelor medicale pe toată perioada de garanție -Confirmarea privind anul producerii dispozitivului 2021-2022 -Confirmarea a unei perioade de garanție nu mai mică de 36 luni din data finalizării procesului de instruire.	Produsul este certificate conform următoarelor standarde internationale: UL, cUL, CE, FDA, MDD 93/42/EEC (Class IIa), AABB SCoPE -Confirmam prezentarea la livrare a copiilor manualului de deservire, servis manual, diagrama electronica, pașapoartelor tehnice, inclusiv descrierea părților tehnice și componente a dispozitivului, autorizat de producător pentru fiecare dispozitiv. -Confirmam livrarea și instalarea dispozitivelor medicale, în termen de 10 zile lucrătoare din data de notificare emisă de beneficiar corespunzător locațiilor de instalare Chișinău, Bălți și Cahul. -Confirmam instruirea gratuită a personalului implicat în operarea dispozitivului medical asigurat de operatorul economic câștigător, pe parcursul a 10 zile din momentul punerii în funcțiune a dispozitivului. -Confirmam asigurarea funcționalității, mentenanței și reparației dispozitivelor medicale pe toată perioada de garanție -Confirmam anul producerii dispozitivului 2021-2022 -Confirmam ca perioada de garanție oferita este de 36 luni din data finalizării procesului de instruire.
--	---

Thermo Scientific TSX Series High-Performance Refrigerators and Freezers

A better environment
inside and out



Thermo Scientific™
TSX 1447 liter
Refrigerator



Thermo Scientific™
TSX 650 liter
Freezer



Thermo Scientific™
TSX 650 liter
Pharmacy
Refrigerator



Thermo Scientific™
TSX 650 liter
Manual Defrost
Freezer

Lab and clinical-grade storage that adapts to you and your environment



Temperature variation can have an impact on the viability and efficacy of vaccines, medication, reagents and other temperature-sensitive materials. These variations can shorten product shelf life, degrade enzymes and reduce vaccine effectiveness. Therefore, it is important to choose a high-performance refrigerator or freezer that has been designed for the demanding standards of the laboratory and clinical environment.

The sustainable, compliant choice

Thermo Scientific™ TSX Series high-performance refrigerators and freezers are designed with features that support sample protection, sustainability objectives and the EU F-gas regulations. Our V-drive technology is designed to provide temperature uniformity that continually adapts to the lab or clinical environment, offering significant energy savings without compromising protection.

Whisper quiet operation

Compared to conventional refrigerant, high-performance models[†], the TSX Series offers a whisper quiet operation, so you can bring the refrigerator or freezer out of the hallway and back into your lab without disrupting your audio environment.

Energy efficient products

While conventional refrigerant, high-performance refrigerators and freezers can run at very high kWh/day in energy usage, the TSX Series by comparison has been designed to reduce energy usage without compromising performance.

Application-specific models

Our laboratory refrigerators feature your choice of glass or solid door with adjustable shelves. Freezers come in a choice of auto defrost –30°C or manual defrost –20°C setpoint. For blood banking applications, our plasma freezers are FDA Class I and our blood bank refrigerators are FDA Class II. Our pharmacy refrigerators feature convenient, adjustable basket drawers. And for enzyme storage, our –20°C freezers feature enzyme bins for convenient storage.



Biologics



Whole blood
and plasma



Diagnostics kits
and reagents



Enzymes



Industrial testing



Molecular
biology



Vaccines and
pharma



Clinical
applications



Columns

The drive for sample integrity and energy savings

The performance and energy savings of the new TSX Series are driven by our unique **V-drive technology**.

- While conventional, high-performance refrigerators and freezers use single speed compressors that continually cycle on and off, the TSX Series V-drive runs at variable speeds to adjust cooling performance to the conditions inside and outside of the refrigerator or freezer.
- When combined with the automated tuning control, this variable speed drive optimizes the compressors running speed to the current conditions.
- When there are frequent door openings, or samples are added to the refrigerator or freezer, the control system detects the activity and increases the drive speed to bring temperatures back to the set point quickly. This innovative technology is one of the reasons the TSX Series delivers outstanding door opening recovery (DOR) speed, and more peace of mind for busy laboratories.
- When conditions are stable, such as when the unit is running overnight or on weekends, the drive runs at a low speed, reducing energy consumption while maintaining a stable temperature for your samples.


V-drive

Low energy → **Low operating cost**

Adaptive control → **Sample security**

Adaptive control

Adapting to your refrigerator or freezer usage patterns, the TSX V-drive increases compressor speed to quickly restore temperature after door openings.



Variable speed compressors (V-Drive) change speed. As shown in the above graphic, the TSX V-drive, unlike standard compressors that cycle on and off, adjusts to factors such as start-up and door openings, when a higher compressor speed is needed. During normal running time when the door is closed, the V-drive runs at a lower speed to maintain your setpoint.

Easy-to-access controls with setpoint security

Setpoint security

Key-operated triple position switch for main power and alarm; locks in temperature and alarm setpoints to minimize setpoint error and prevent tampering

Graphic thermometer

Easy to view, shows normal, high or low temperature condition; steady green for normal, flashing top bar for overtemperature, flashing bulb for undertemperature

Power failure

Illuminated when main power is interrupted

Service mode

Illuminated when controller is in service programming mode

Touchpad data entry

Increases or decreases setpoint values in programming modes

Interior light switch

Enables interior lighting system (on glass door cabinets)



Automatic defrost system

Defrost sensor manages automatic defrost cycle (except manual defrost models)

Door ajar

Illuminated when door is left open

Battery backup

Continuous charge provide full alarm function in case of power failure

Low battery alarm

Illuminated when the alarm system battery backup charge is low

Audible alarm

Sounds in the event of warm, cold or power loss conditions. Mute will silence audible alarm with 6 minute ring back interval; display remains flashing

A sound environment for critical samples

You know that the constant noise created by compressors can compromise communications and create a less than ideal working environment. The new TSX Series is **up to 10X quieter than our previous generation of refrigerators and freezers**.^{*} Our V-drive technology, combined with superior insulation, limits the sound output of the TSX Series to just **52 dB**, approximately the sound generated by a conventional refrigerator.^{**}

Decibel scale of common sounds. Examples of noise levels in decibels

Noise source	Decibel level
Freeway traffic 15M, vacuum cleaner	70
Conversation in restaurant, office, background music	60
TSX Series	52
Library	40
Quiet rural area	30
Rustling leaves	20
Breathing	10

^{*} Thermo Scientific TSX2304GA compared to Thermo Scientific high-performance 2304A model (non TSX).

^{**} Data on file. October, 2016.



up to
10X
quieter

Designed for ergonomic usage

In addition to the significant reduction in sound, the TSX Series features an ergonomically designed door handle featuring soft touch grip and the microprocessor controller is angled to help prevent neck strain.



TSX Series High-Performance BioMedical Glass Door Refrigerators



Our high-performance glass door refrigerators combine advanced temperature control with high-quality cabinet construction and alarm systems. Positive, forced-air circulation is designed to maintain temperature uniformity to protect important medical and pharmaceutical-products as well as laboratory media, reagents and more.

- Heat-free defrost for maximum temperature uniformity
- GMP Clean Room Class A / ISO 6 (ISO EN 14644-1) compatible with appropriate pre-install preparation
- Four 2" casters for easy mobility; the front two are lockable
- Bright, LED interior lighting
- Self-closing door with 90° stop to assist with inventory loads
- See pages 14–21 for options and accessories



Thermo Scientific™
TSX 650 liter
refrigerator

TSX Series high-performance glass door lab refrigerators

Model no.	Temp. range (setpoint)	Capacity cu. ft. (liters)	Electrical (plug)	Doors	Shelves	Defrost	Certification	Interior dimensions D x W x H in. (cm)	Exterior dimensions D x W x H in. (cm)	Shipping weight lbs. (kg)
TSX1205GY	3–7°C (5°C)	11.5 (326)	115V, 60Hz (NEMA 5-15)	1 glass	4	auto	CE, cUL	21.8 x 20.0 x 52.4 (55.4 x 50.8 x 133.1)	30.5 x 24.0 x 73.0 (77.5 x 61.9 x 185.4)	339 (154)
TSX1205GZ			208-230V, 60Hz (NEMA 6-15)							339 (154)
TSX1205GV			208-230V, 50Hz (CEE 7/7)							339 (154)
TSX2305GY	3–7°C (5°C)	23 (650)	115V, 60Hz (NEMA 5-15)	1 glass	4	auto	CE, cUL	28.5 x 24.0 x 58.0 (72.3 x 61.0 x 147.3)	37.8 x 28.0 x 78.5 (96.0 x 71.1 x 199.4)	450 (204)
TSX2305GZ			208-230V, 50/60Hz (NEMA 6-15)							429 (195)
TSX2305GV			208-230V, 50/60Hz (CEE 7/7)							429 (195)
TSX3005GY	3–7°C (5°C)	29.2 (827)	115V, 60Hz (NEMA 5-15)	1 glass	4	auto	CE, cUL	28.5 x 30.0 x 58.0 (72.3 x 76.2 x 147.3)	37.3 x 34.0 x 78.5 (94.7 x 86.4 x 199.4)	458 (208)
TSX3005GZ			208-230V, 60Hz (NEMA 6-15)							458 (208)
TSX3005GV			208-230V, 50Hz (CEE 7/7)							458 (208)
TSX4505GY	3–7°C (5°C)	45.8 (1297)	115V, 60Hz (NEMA 5-15)	Double Sliding Glass	8	auto	CE, cUL	26.0 x 52.5 x 58.0 (66 x 133.4 x 147.3)	36.6 x 56.5 x 78.5 (93.1 x 143.5 x 199.4)	611 (277)
TSX4505GZ			208-230V, 60Hz (NEMA 6-15)							611 (277)
TSX4505GV			208-230V, 50Hz (CEE 7/7)							611 (277)
TSX5005GY	3–7°C (5°C)	51.1 (1447)	115V, 60Hz (NEMA 5-15)	2 Glass	8	auto	CE, cUL	28.5 x 52.5 x 58.0 (72.4 x 133.4 x 147.3)	37.8 x 56.5 x 78.5 (96.0 x 143.5 x 199.4)	669 (303)
TSX5005GZ			208-230V, 60Hz (NEMA 6-15)							669 (303)
TSX5005GV			208-230V, 50Hz (CEE 7/7)							669 (303)

TSX Series High-Performance BioMedical Solid Door Lab Refrigerators



Our high-performance solid door refrigerators combine advanced temperature control with high-quality cabinet construction and alarm systems. Positive, forced-air circulation is designed to maintain temperature uniformity to protect important medical and pharmaceutical-products as well as laboratory media, reagents and more.

- Heat-free defrost for maximum temperature uniformity
- GMP Clean Room Class A / ISO 6 (ISO EN 14644-1) compatible with appropriate pre-install preparation
- Four 2" casters for easy mobility; the front two are lockable
- Bright, LED interior lighting
- Self-closing door with 90° stop to assist with inventory loads
- See pages 14–21 for options and accessories



Thermo Scientific™
TSX 1447 liter
refrigerator

TSX Series high-performance solid door lab refrigerators

Model no.	Temp. range (setpoint)	Capacity cu. ft. (liters)	Electrical (plug)	Doors	Shelves	Defrost	Certification	Interior dimensions D x W x H in. (cm)	Exterior dimensions D x W x H in. (cm)	Shipping weight lbs. (kg)
TSX1205SY	3–7°C (5°C)	11.5 (326)	115V, 60Hz (NEMA 5-15)	1 solid	4	auto	CE, cUL	21.8 x 20.0 x 52.4 (55.4 x 50.8 x 133.1)	31.1 x 24.0 x 73.0 (79.0 x 61.9 x 185.4)	340 (154)
TSX1205SZ			208-230V, 60Hz (NEMA 6-15)							340 (154)
TSX1205SV			208-230V, 50Hz (CEE 7/7)							340 (154)
TSX2305SY	3–7°C (5°C)	23 (650)	115V, 60Hz (NEMA 5-15)	1 solid	4	auto	CE, cUL	28.5 x 24.0 x 58.0 (72.3 x 61.0 x 147.3)	37.9 x 28.0 x 78.5 (96.2 x 71.1 x 199.4)	426 (193)
TSX2305SZ			208-230V, 50/60Hz (NEMA 6-15)							405 (184)
TSX2305SV			208-230V, 50/60Hz (CEE 7/7)							405 (184)
TSX3005SY	3–7°C (5°C)	29.2 (827)	115V, 60Hz (NEMA 5-15)	1 solid	4	auto	CE, cUL	28.5 x 30.0 x 58.0 (72.3 x 76.2 x 147.3)	37.9 x 34.0 x 78.5 (96.2 x 86.4 x 199.4)	459 (208)
TSX3005SZ			208-230V, 60Hz (NEMA 6-15)							459 (208)
TSX3005SV			208-230V, 50Hz (CEE 7/7)							459 (208)
TSX5005SY	3–7°C (5°C)	51.1 (1447)	115V, 60Hz (NEMA 5-15)	2 solid	8	auto	CE, cUL	28.5 x 52.5 x 58.0 (72.4 x 133.4 x 147.3)	37.9 x 56.5 x 78.5 (96.2 x 143.5 x 199.4)	621 (282)
TSX5005SZ			208-230V, 60Hz (NEMA 6-15)							621 (282)
TSX5005SV			208-230V, 50Hz (CEE 7/7)							621 (282)

TSX Series High Performance Chromatography Refrigerators



Vaccines and medications

Clinical applications

Diagnostics kits and reagents

Columns



Our TSX high-performance chromatography refrigerators are designed for a variety of applications requiring close temperature control, full access to chromatography instrumentation, and easy set-up of instrumentation and apparatus within the chamber. The TSX Chromatography series features industry-leading safety features to ensure maximum protection.

- Heat-free defrost for maximum temperature uniformity
- Two 2" (5 cm) side wall access ports with insulated hinged covers
- GMP Clean Room Class A / ISO 6 (ISO EN 14644-1) compatible with appropriate pre-install preparation
- Four 2" casters for easy mobility; the front two are lockable
- Bright, LED interior lighting
- Self-closing door with 90° stop to assist with inventory loads
- Safety switch protected internal electrical outlet on all models (Duplex outlet on Y and Z models, single outlet on V models)
- See pages 14–21 for options and accessories



Thermo Scientific™
TSX 827 liter
chromatography refrigerator

TSX Series high-performance chromatography refrigerators

Model no.	Temp. range (setpoint)	Capacity cu. ft. (liters)	Electrical (plug)	Doors	Shelves	Defrost	Certification	Interior dimensions D x W x H in. (cm)	Exterior dimensions D x W x H in. (cm)	Shipping weight lbs. (kg)
TSX2305CY	3–7°C (5°C)	23 (650)	115V, 60Hz (NEMA 5-15)	1 glass	0 Full 2 Half	auto	CE, cUL	28.5 x 24.0 x 58.0 (72.3 x 61.0 x 147.3)	37.8 x 28.0 x 78.5 (96.0 x 71.1 x 199.4)	439 (199)
TSX2305CZ			208-230V, 50/60Hz (NEMA 6-15)							418 (190)
TSX2305CV			208-230V, 50/60Hz (CEE 7/7)							418 (190)
TSX3005CY	3–7°C (5°C)	29.2 (827)	115V, 60Hz (NEMA 5-15)	1 glass	0 Full 2 Half	auto	CE, cUL	28.5 x 30.0 x 58.0 (72.3 x 76.2 x 147.3)	37.3 x 34.0 x 78.5 (94.7 x 86.4 x 199.4)	442 (201)
TSX3005CZ			208-230V, 60Hz (NEMA 6-15)							442 (201)
TSX3005CV			208-230V, 50Hz (CEE 7/7)							442 (201)
TSX4505CY	3–7°C (5°C)	45.8 (1297)	115V, 60Hz (NEMA 5-15)	Double Sliding Glass	4 Full 2 Half	auto	CE, cUL	26.0 x 52.5 x 58.0 (66.0 x 133.4 x 147.3)	36.6 x 56.5 x 78.5 (93.1 x 143.5 x 199.4)	600 (272)
TSX4505CZ			208-230V, 60Hz (NEMA 6-15)							600 (272)
TSX4505CV			208-230V, 50Hz (CEE 7/7)							600 (272)
TSX5005CY	3–7°C (5°C)	51.1 (1447)	115V, 60Hz (NEMA 5-15)	2 glass	4 Full 2 Half	auto	CE, cUL	28.5 x 52.5 x 58.0 (72.4 x 133.4 x 147.3)	37.8 x 56.5 x 78.5 (96.0 x 143.5 x 199.4)	658 (298)
TSX5005CZ			208-230V, 60Hz (NEMA 6-15)							658 (298)
TSX5005CV			208-230V, 50Hz (CEE 7/7)							658 (298)

TSX Series High-Performance Blood Bank Refrigerators



Whole blood
and plasma



Our high-performance blood bank refrigerators are designed to meet strict requirements established by the AABB for the storage of whole blood and blood components.

- Factory pre-set to 4°C to meet blood storage guidelines
- Heat-free defrost for maximum temperature uniformity
- Convenient, stainless steel, fully extendable and adjustable drawers
- Standard, built-in chart recorder
- GMP Clean Room Class A / ISO 6 (ISO EN 14644-1) compatible with appropriate pre-install preparation
- Four 2" casters for easy mobility; the front two are lockable
- Bright, LED interior lighting
- Self-closing door with 90° stop to assist with inventory loads
- FDA listed Class II Medical Device, 510K exempt
- See pages 14–21 for options and accessories



Thermo Scientific™
TSX 650 liter
blood bank refrigerator

TSX Series high-performance blood bank refrigerators

Model no.	Temp. range (setpoint)	Capacity cu. ft. / liters (blood bags*)	Electrical (plug)	Doors	Drawers	Defrost	Certification	Interior dimensions D x W x H in. (cm)	Exterior dimensions D x W x H in. (cm)	Shipping weight lbs. (kg)
TSX1204BY			115V, 60Hz (NEMA 5-15)							404 (183)
TSX1204BZ	3–7°C (4°C)	11.5 / 326 (192)	208-230V, 60Hz (NEMA 6-15)	1 glass	6	auto	CE, cUL	21.8 x 20.0 x 52.4 (55.4 x 50.8 x 133.1)	30.5 x 24.0 x 73.0 (77.5 x 61.9 x 185.4)	404 (183)
TSX1204BV			208-230V, 50Hz (CEE 7/7)							404 (183)
TSX2304BY			115V, 60Hz (NEMA 5-15)							550 (249)
TSX2304BZ	3–7°C (4°C)	23 / 650 (385)	208-230V, 60Hz (NEMA 6-15)	1 glass	7	auto	CE, cUL	28.5 x 24.0 x 58.0 (72.3 x 61.0 x 147.3)	37.8 x 28.0 x 78.5 (96.0 x 71.1 x 199.4)	529 (240)
TSX2304BV			208-230V, 50/60Hz (CEE)							529 (240)
TSX3004BY			115V, 60Hz (NEMA 5-15)							554 (251)
TSX3004BZ	3–7°C (4°C)	29.2 / 827 (426)	208-230V, 60Hz (NEMA 6-15)	1 glass	6	auto	CE, cUL	28.5 x 30.0 x 58.0 (72.3 x 76.2 x 147.3)	37.3 x 34.0 x 78.5 (94.7 x 86.4 x 199.4)	554 (251)
TSX3004BV			208-230V, 50Hz (CEE 7/7)							554 (251)
TSX5004BY			115V, 60Hz (NEMA 5-15)							865 (392)
TSX5004BZ	3–7°C (4°C)	51.1 / 1447 (770)	208-230V, 60Hz (NEMA 6-15)	2 glass	14	auto	CE, cUL	28.5 x 52.5 x 58.0 (72.4 x 133.4 x 147.3)	37.8 x 56.5 x 78.5 (96.0 x 143.5 x 199.4)	865 (392)
TSX5004BV			208-230V, 50Hz (CEE 7/7)							865 (392)

*450 mL whole blood bags

TSX Series High-Performance Pharmacy Refrigerators



Our high-performance pharmacy refrigerators feature adjustable basket drawers and glass doors for the easy identification and access of vaccines, pharmaceuticals, chemotherapeutics and other material requiring 2 to 8°C storage.

- Heat-free defrost for maximum temperature uniformity
- Convenient, fully extendable and adjustable basket drawers
- GMP Clean Room Class A / ISO 6 (ISO EN 14644-1) compatible with appropriate pre-install preparation
- Four 2" casters for easy mobility; the front two are lockable
- Bright, LED interior lighting
- Self-closing door with 90° stop to assist with inventory loads
- See pages 14–21 for options and accessories



Thermo Scientific™
TSX 650 liter
pharmacy refrigerator

TSX Series high-performance pharmacy refrigerators

Model no.	Temp. range (setpoint)	Capacity cu. ft. (liters)	Electrical (plug)	Doors	Basket Drawers	Defrost	Certification	Interior dimensions D x W x H in. (cm)	Exterior dimensions D x W x H in. (cm)	Shipping weight lbs. (kg)
TSX1205PY	3–7°C (5°C)	11.5 (326)	115V, 60Hz (NEMA 5-15)	1 glass	5	auto	CE, cUL	21.8 x 20.0 x 52.4 (55.4 x 50.8 x 133.1)	30.5 x 24.0 x 73.0 (77.5 x 61.9 x 185.4)	388 (176)
TSX1205PZ			208-230V, 60Hz (NEMA 6-15)							388 (176)
TSX1205PV			208-230V, 50Hz (CEE 7/7)							388 (176)
TSX2305PY	3–7°C (5°C)	23 (650)	115V, 60Hz (NEMA 5-15)	1 glass	6	auto	CE, cUL	28.5 x 24.0 x 58.0 (72.3 x 61.0 x 147.3)	37.8 x 28.0 x 78.5 (96.0 x 71.1 x 199.4)	531 (241)
TSX2305PZ			208-230V, 50/60Hz (NEMA 6-15)							510 (231)
TSX2305PV			208-230V, 50Hz (CEE 7/7)							510 (231)
TSX3005PY	3–7°C (5°C)	29.2 (827)	115V, 60Hz (NEMA 5-15)	1 glass	6	auto	CE, cUL	28.5 x 30.0 x 58.0 (72.3 x 76.2 x 147.3)	37.3 x 34.0 x 78.5 (94.7 x 86.4 x 199.4)	541 (245)
TSX3005PZ			208-230V, 60Hz (NEMA 6-15)							541 (245)
TSX3005PV			208-230V, 50Hz (CEE 7/7)							541 (245)
TSX5005PY	3–7°C (5°C)	51.1 (1447)	115V, 60Hz (NEMA 5-15)	2 glass	12	auto	CE, cUL	28.5 x 52.5 x 58.0 (72.4 x 133.4 x 147.3)	37.8 x 56.5 x 78.5 (96.0 x 143.5 x 199.4)	830 (376)
TSX5005PZ			208-230V, 60Hz (NEMA 6-15)							830 (376)
TSX5005PV			208-230V, 50Hz (CEE 7/7)							830 (376)

TSX Series High-Performance Auto Defrost –30°C Freezers



Biologics



Diagnostics kits and reagents



Industrial testing



Molecular biology



Our high-performance laboratory freezers are designed for applications requiring storage of reagents, pharmaceuticals, biological and other commonly used laboratory materials such as primers, siRNA molecules and fetal bovine serum (FBS).

- Forced-air circulation for temperature uniformity and fast temperature recovery
- Non-invasive defrost with time and temperature guided cycle
- GMP Clean Room Class A / ISO 6 (ISO EN 14644-1) compatible with appropriate pre-install preparation
- Four 2" casters for easy mobility; the front two are lockable
- Self-closing door with 90° stop to assist with inventory loads
- See pages 14–21 for options and accessories



Thermo Scientific™
TSX 1447 liter
freezer



Thermo Scientific™
TSX 326 liter
freezer

TSX Series high-performance auto defrost –30°C freezers

Model no.	Temp. range (setpoint)	Capacity cu. ft. (liters)	Electrical (plug)	Doors	Shelves	Defrost	Certification	Interior dimensions D x W x H in. (cm)	Exterior dimensions D x W x H in. (cm)	Shipping weight lbs. (kg)
TSX1230FY			115V, 60Hz (NEMA 5-15)							335 (152)
TSX1230FZ	-35° to -15°C (-30°C)	11.5 (326)	208-230V, 60Hz (NEMA 6-15)	1 solid	4	auto	CE, cUL	21.8 x 20.0 x 52.4 (55.4 x 50.8 x 133.1)	31.1 x 24.0 x 73.0 (79.0 x 61.9 x 185.4)	335 (152)
TSX1230FV										335 (152)
TSX2330FY			115V, 60Hz (NEMA 5-15)							423 (192)
TSX2330FZ	-35° to -15°C (-30°C)	23.3 (659)	208-230V, 60Hz (NEMA 6-15)	1 solid	4	auto	CE, cUL	28.5 x 24.0 x 58.0 (72.3 x 61.0 x 147.3)	37.9 x 28.0 x 78.5 (96.2 x 71.1 x 199.4)	402 (182)
TSX2330FV										402 (182)
TSX3030FY			115V, 60Hz (NEMA 5-15)							439 (199)
TSX3030FZ	-35° to -15°C (-30°C)	29.2 (827)	208-230V, 60Hz (NEMA 6-15)	1 solid	4	auto	CE, cUL	28.5 x 30.0 x 58.0 (72.3 x 76.2 x 147.3)	37.9 x 34.0 x 78.5 (96.2 x 86.4 x 199.4)	439 (199)
TSX3030FV										439 (199)
TSX5030FY			115V, 60Hz (NEMA 5-15)							621 (282)
TSX5030FZ	-35° to -15°C (-30°C)	51.1 (1447)	208-230V, 60Hz (NEMA 6-15)	2 solid	8	auto	CE, cUL	28.5 x 52.5 x 58.0 (72.3 x 133.4 x 147.3)	37.9 x 56.5 x 78.5 (96.2 x 143.5 x 199.4)	621 (282)
TSX5030FV										621 (282)

TSX Series High-Performance Manual Defrost -20°C Freezers



Biologics



Diagnostics kits
and reagents



Enzymes



Industrial testing



Molecular
biology



Our manual defrost, high-performance freezers are designed for applications in which even slight intermittent coil warming during auto defrost cannot be tolerated.

- Cold wall convection cooling with temperature uniformity
- Enzyme freezers feature enzyme bins
- GMP Clean Room Class A / ISO 6 (ISO EN 14644-1) compatible with appropriate pre-install preparation
- Four 2" casters for easy mobility; the front two are lockable
- Self-closing door with 90° stop to assist with inventory loads
- See pages 14–21 for options and accessories



Thermo Scientific™
TSX 659 liter
freezer

TSX Series high-performance manual defrost -20°C freezers

Model no.	Temp. range (setpoint)	Capacity cu. ft. (liters)	Electrical (plug)	Doors	Shelves (bins)	Defrost	Certification	Interior dimensions D x W x H in. (cm)	Exterior dimensions D x W x H in. (cm)	Shipping weight lbs. (kg)
TSX2320FY	-25°C to -15°C (-20°C)	23.3 (659)	115V, 60Hz (NEMA 5-15)	1 solid	4 (0)	Manual	CE, cUL	28.5 x 24.0 x 58.0 (72.3 x 61.0 x 147.3)	38.9 x 28.0 x 78.5 (99.0 x 71.1 x 199.4)	459 (208)
TSX2320FZ			208-230V, 50/60Hz (NEMA 6-15)							438 (199)
TSX2320FV			208-230V, 50/60Hz (CEE 7/7)							438 (199)
TSX3020FY	-25°C to -15°C (-20°C)	29.2 (827)	115V, 60Hz (NEMA 5-15)	1 solid	4 (0)	Manual	CE, cUL	28.5 x 30.0 x 58.0 (72.3 x 76.2 x 147.3)	38.9 x 34.0 x 78.5 (99.0 x 86.4 x 199.4)	483 (219)
TSX3020FZ			208-230V, 60Hz (NEMA 6-15)							483 (219)
TSX3020FV			208-230V, 50/60Hz (CEE 7/7)							483 (219)

TSX Series high-performance manual defrost -20°C enzyme freezers

TSX2320EY	-25°C to -15°C (-20°C)	23.3 (659)	115V, 60Hz (NEMA 5-15)	1 solid	9 (45)	Manual	CE, cUL	28.5 x 24.0 x 58.0 (72.3 x 61.0 x 147.3)	38.9 x 28.0 x 78.5 (99.0 x 71.1 x 199.4)	514 (233)
TSX2320EZ			208-230V, 50/60Hz (NEMA 6-15)							493 (224)
TSX2320EV			208-230V, 50/60Hz (CEE 7/7)							493 (224)
TSX3020EY	-25°C to -15°C (-20°C)	29.2 (827)	115V, 60Hz (NEMA 5-15)	1 solid	9 (54)	Manual	CE, cULL	28.5 x 30.0 x 58 (72.3 x 76.2 x 147.3)	38.9 x 34.0 x 78.5 (99.0 x 86.4 x 199.4)	552 (251)
TSX3020EZ			208-230V, 60Hz (NEMA 6-15)							552 (251)
TSX3020EV			208-230V, 50/60Hz (CEE 7/7)							552 (251)

TSX Series High-Performance –30°C Plasma Freezers



Whole blood
and plasma



Our pre-set, high-performance –30°C plasma freezers with automatic defrost are designed to meet strict requirements established by the AABB for the storage of plasma.

- Forced-air circulation for temperature uniformity and fast temperature recovery
- Convenient, stainless steel, fully extendable and adjustable drawers
- GMP Clean Room Class A / ISO 6 (ISO EN 14644-1) compatible with appropriate pre-install preparation
- Standard, built-in chart recorder
- Four 2" casters for easy mobility; the front two are lockable
- Self-closing door with 90° stop to assist with inventory loads
- FDA listed Class I Medical Device, 510K exempt
- See pages 14–21 for options and accessories



Thermo Scientific™
TSX 659 liter
plasma freezer

TSX Series high-performance –30°C plasma freezer

Model no.	Temp. range (setpoint)	Capacity cu. ft. / liters (plasma boxes*)	Electrical (plug)	Doors	Drawers	Defrost	Certification	Interior dimensions D x W x H in. (cm)	Exterior dimensions D x W x H in. (cm)	Shipping weight lbs. (kg)
TSX1230LY			115V, 60Hz (NEMA 5-15)							412 (187)
TSX1230LZ	–35°C to –15°C (–30°C)	11.5 / 326 (273)	208-230V, 60Hz (NEMA 6-15)	1 solid	7	auto	CE, cUL	21.8 x 20.0 x 52.4 (55.4 x 50.8 x 133.1)	31.1 x 24.0 x 73.0 (79.0 x 61.9 x 185.4)	412 (187)
TSX1230LV			208-230V, 50Hz (CEE 7/7)							412 (187)
TSX2330LY			115V, 60Hz (NEMA 5-15)							526 (239)
TSX2330LZ	–35°C to –15°C (–30°C)	23.3 / 659 (532)	208-230V, 50/60Hz (NEMA 6-15)	1 solid	7	auto	CE, cUL	28.5 x 24.0 x 58.0 (72.3 x 61.0 x 147.3)	37.9 x 28.0 x 78.5 (96.2 x 71.1 x 199.4)	505 (229)
TSX2330LV			208-230V, 50Hz (CEE 7/7)							505 (229)
TSX3030LY			115V, 60Hz (NEMA 5-15)							556 (252)
TSX3030LZ	–35°C to –15°C (–30°C)	29.2 / 827 (665)	208-230V, 60Hz (NEMA 6-15)	1 solid	7	auto	CE, cUL	28.5 x 30.0 x 58.0 (72.3 x 76.2 x 147.3)	37.9 x 34.0 x 78.5 (96.2 x 86.4 x 199.4)	556 (252)
TSX3030LV			208-230V, 50Hz (CEE 7/7)							556 (252)
TSX5030LY			115V, 60Hz (NEMA 5-15)							817 (371)
TSX5030LZ	–35°C to –15°C (–30°C)	51.1 / 1447 (1064)	208-230V, 60Hz (NEMA 6-15)	2 solid	14	auto	CE, cUL	28.5 x 52.5 x 58.0 (72.4 x 133.4 x 147.3)	37.9 x 56.5 x 78.5 (96.2 x 143.5 x 199.4)	817 (371)
TSX5030LV			208-230V, 50Hz (CEE 7/7)							817 (371)

*250 mL plasma boxes

Options and Accessories

Productive use of our TSX Series refrigerators and freezers can be enhanced with options and accessories specifically designed to improve utility and convenience. Many options are factory-installed and must be specified with your refrigerator and freezer order. Customer-installed options may require the services of a factory authorized technician. The ordering chart on pages 16-19 will inform you which options are factory- or customer-installed.

Before ordering...

Serial number tags on all of our TSX Series refrigerators and freezers provide model numbers and voltage information needed for accurate selection of options ordered for field installation. You can also refer to the refrigerator and freezer ordering charts in this brochure for model numbers and voltage information. It is recommended that options be ordered when your refrigerator or freezer is ordered. Factory-installed options eliminate down-time during product installation.

Adjustable alarm delay modules

The adjustable alarm delay is designed to eliminate nuisance alarms due to intermittent or transitory conditions such as lightning or brief power outages. The adjustable delay requires an alarm condition to exist continuously for a pre-determined time (adjustable) before a signal is released to a central alarm/monitoring system or telephone dialer.

- Adjustable delay from 0.5 to 32 minutes
- Red alarm indicator light remains flashing after transient condition is corrected; requires manual reset
- Signals chronic alarm conditions that may indicate impending component failure; allows time for inspection or corrective maintenance
- Inserts variable time interval between detection of alarm condition and transmission of signal
- Includes accurate digital timing circuit adjustable from 0.5, 1, 2, 4, 8, 18 or 32 minutes
- Operates independent of the line power; built-in battery uses customer supplied 9V battery

Remote alarm modules

Free-standing remote alarm modules tie-in to the standard remote alarm terminals on the refrigerators and freezers.

4–20 milliamp (MA) transmitters

4–20 milliamp transmitters offer a point-to-point circuit to transmit signals from refrigerator and freezer sensors to a controller, sending an analog signal from 4 to 20 milliamps.

Temperature chart recorders

Standard on blood bank refrigerators and plasma freezers but optional on other models. Chart recorders are 6" (15.2 cm), seven-day and use pressure-sensitive chart paper. One box of 50 charts is included with order.

Door swing options

All single door TSX refrigerators and freezers are right-hand swing but factory-installed, left hand swing doors are available. Door swing direction cannot be changed on double door TSX refrigerators and freezers.

Surge suppressors

Designed to prevent issues related to voltage surges.

Seismic restraint kits

Provides additional stability for regions prone to earthquakes.

e-lock adapter kits

E-locks provide access control with audit-trail capabilities, as well as temperature monitoring. These kits require no electricity and are available in both factory- and customer-installed options for CompX™, Pyxis®, Omnicell® and McKesson™ locks.

Specialty electrical plugs

For countries where NEMA 5-15, 6-15 and Continental EU plugs are not standard, specialty plug options are available. See page 19 for these country-specific plugs.

Options (Refrigerators)

Options for High-Performance Refrigerators Ordering Guide

For use with refrigerator size →	11.5 cu. ft. (325 L)	23 cu. ft. (650 L)	29.2 cu. ft. (826 L)	45.8 cu. ft. (1297 L)	51.1 cu. ft. (1447 L)
Door options (factory-installed)	Model No.	Model No.	Model No.	Model No.	Model No.
Left hand swing, solid door	6995	6997	6999		
Left hand swing, glass door	6996	6998	7000		
Right hand swing, glass door	7066	7012	7013		
Left and right hand swinging doors, solid					7019
Left and right hand swinging doors, glass					7014
6" 7-day inkless chart recorders, -40°C to +25°C					
Free-standing, customer-installed, 115V, 60Hz models			6383-7A		
Free-standing, customer-installed, 208-230V, 60Hz models			6383-7D		
Free-standing, customer-installed, 230V, 50Hz models (EU)			6383-7V		
Free-standing, customer-installed, 230V, 50Hz models (UK)			6383-7W		
Factory-installed (all voltages)			6183-7		
Replacement chart paper, box of 50			6184		
Surge suppressor (customer-installed)					
115V, 60Hz models			6402-1		
208-230V, 60Hz models			6402-2		
230V, 50Hz models			6402-3		
Remote alarm modules (customer-installed)					
115V, 60Hz models			5612-1A		
208-230V, 60Hz models			5612-2D		
230V, 50Hz models			5612-3V		
Alarm delay modules					
Battery operated			6903		
Digital temperature monitors					
Single input channel, temperature range -100° to +25°C, set point resolution of 1°C, high temperature alarm only, numeric LCD display, red visual alarm, 8 ft. Teflon® lead wire, Velcro® mounting strap, 5"L x 2"D x 4.5"W (mm, 130 x 50 x 110), 120v, 60hz, with a 15amp dual prong plug (fits NEMA 5-15R)			6898		

	For use with refrigerator size →	11.5 cu. ft. (325 L)	23 cu. ft. (650 L)	29.2 cu. ft. (826 L)	45.8 cu. ft. (1297 L)	51.1 cu. ft. (1447 L)
Deluxe electronic remote alarm		Model No.	Model No.	Model No.	Model No.	Model No.
Requires a dedicated, analog phone line				6224TA		
4-20 milliamp transmitters						
Self-powered, factory-installed				7204		
Non-powered, factory-installed				6907-1		
Non-powered, customer-installed				6907-2		
e-Lock adapter kits (does not include locks; single door models only)						
CompX adapter, factory-installed		CXELAF				
CompX adapter, customer-installed		CXELAC				
Pyxis glass door adapter, factory-installed		PXELAGF				
Pyxis glass door adapter, customer-installed		PXELAGC				
Pyxis solid door adapter, factory-installed		PXELASF				
Pyxis solid door adapter, customer-installed		PXELASC				
Omnicell glass door adapter, factory-installed		OMELAGF				
Omnicell glass door adapter, customer-installed		OMELAGC				
Omnicell solid door adapter, factory-installed		OMELASF				
Omnicell solid door adapter, customer-installed		OMELASC				
McKesson glass door adapter, factory-installed		MKELAGF				
McKesson glass door adapter, customer-installed		MKELAGC				
McKesson solid door adapter, factory-installed		MKELASF				
McKesson solid door adapter, customer-installed		MKELASC				
Stainless steel interior (factory-installed)						
Stainless steel interior finish		6199-3D	6115	6709	6711	6116

Options (Freezers)

Options for High-Performance Freezers Ordering Guide

	For use with refrigerator size →	11.5 cu. ft. (326 L)	23.3 cu. ft. (659 L)	29.2 cu. ft. (826 L)	51.1 cu. ft. (1447 L)
Door options (factory-installed)		Model No.	Model No.	Model No.	Model No.
Left hand swing, solid door		6995	6997	6999	
6" 7-day inkless chart recorders, -40°C to +25°C					
Factory-installed (all voltages)			6183-7		
Free-standing, customer-installed, 115V, 60Hz models			6383-7A		
Free-standing, customer-installed, 208-230V, 60Hz models			6383-7D		
Free-standing, customer-installed, 230V, 50Hz models (EU)			6383-7V		
Free-standing, customer-installed, 230V, 50Hz models (UK)			6383-7W		
Replacement chart paper, box of 50			6184		
Surge suppressor (customer-installed)					
115V, 60Hz models			6402-1		
208-230V, 60Hz models			6402-2		
230V, 50Hz models			6402-3		
Remote alarm modules (customer-installed)					
115V, 60Hz models			5612-1A		
208-230V, 60Hz models			5612-2D		
230V, 50Hz models			5612-3V		
Alarm delay modules					
Battery operated			6903		
Digital temperature monitors					
Single input channel, temperature range -100° to +25°C, set point resolution of 1°C, high temperature alarm only, numeric LCD display, red visual alarm, 8 ft. Teflon® lead wire, Velcro® mounting strap, 5"L x 2"D x 4.5"W (mm, 130 x 50 x 110), 120v, 60hz, with a 15amp dual prong plug (fits NEMA 5-15R)			6898		
Deluxe electronic remote alarm					
Requires a dedicated, analog phone line			6224TA		
4-20 milliamp transmitters					
Self-powered, factory-installed			7205TA		
Non-powered, factory-installed			4706		
e-Lock adapter kits (does not include locks; single door models only)					
CompX adapter, factory-installed			CXELAF		
CompX adapter, customer-installed			CXELAC		
Pyxis solid door adapter, factory-installed			PXELASF		
Pyxis solid door adapter, customer-installed			PXELASC		
Omniceil solid door adapter, factory-installed			OMELASF		
Omniceil solid door adapter, customer-installed			OMELASC		
McKesson solid door adapter, factory-installed			MKELASF		
McKesson solid door adapter, customer-installed			MKELASC		
Stainless steel interior (factory-installed)					
Stainless steel interior finish (Not available on -20°C models)		6199-3D	6115	6709	6116

Accessories

Accessories for High-Performance Refrigerators and Freezers Ordering Guide

For use with refrigerator size →	11.5 cu. ft. (326 L)	23.3 cu. ft. (659 L)	29.2 cu ft (826 L)	45.8 cu. ft. (1297 L)	51.1 cu. ft. (1447 L)
Shelves	Model No.	Model No.	Model No.	Model No.	Model No.
Epoxy-coated, full size shelf	7125	6696	6695	6696	
Epoxy-coated, half size shelf		6698	6697	6698	
Stainless steel, full size shelf	6696-3	6696-1			
Drawer dividers for roll-out , stainless steel drawers					
4-place divider, order one divider per drawer	7027 (4)	6206 (4)	6963 (5)		6206 (4)
3" casters (note: all models ship standard with 2")					
Set of four, 3" (76mm) casters		6041-1			
Additional wire basket drawers					
Single drawer, for pharmacy refrigerators	WB12	WB23/50	WB30		WB23/50
Enzyme bins					
Sold as each, labels not included		6736			
Seismic restraint kits					
Basic	TFR210				
For OSHPD	TF-LRF12	TF-LRF23	TF-LRF30	TF-LRF50	TF-LRF50

Specialty Plugs for Refrigerators and Freezers

Specialty plugs (factory-installed) for all Models		Model No.
Specialty Plug	Argentina	430381H01
Specialty Plug	Australia (10 Amp)	326741H01
Specialty Plug	Australia (15 Amp)	430268H01
Specialty Plug	Brazil	430383H01
Specialty Plug	China	316705H01
Specialty Plug	Denmark	430380H01
Specialty Plug	Great Britain	316704H01
Specialty Plug	India	430271H01
Specialty Plug	Israel	430273H01
Specialty Plug	Italy	430272H01
Specialty Plug	Switzerland	430382H01
Specialty Plug	Twist Lock Plug NEMA L5-20P	327197H02
Specialty Plug	Twist lock plug NEMA L6-15P	327197H01

Services

Our TSX Series high-performance refrigerators and freezers are designed to meet UL and CE criteria for safety and performance. All connections must comply with local electrical codes.

- Selection charts for each standard model list voltage, rated amperage, recommended circuit breaker size, and NEMA (National Electrical Manufacturers' Association, USA) electrical plug information
- Most refrigerators and freezers are supplied with line cord plugs, which require corresponding receptacles
- Site preparation requires availability of the proper receptacle; a dedicated circuit is required
- Special voltage selections may be available at extra cost and must be specified when ordering
- For questions regarding site preparation, installation and electrical connection, contact your sales representative

Certificate of Calibration

Control, alarm and temperature recording systems are systematically calibrated at the factory for accurate performance. An optional Certificate of Calibration to an NIST (National Institute of Standards and Technology, formerly National Bureau of Standards) traceable instrument includes a model number and serial number certificate (single point calibration). Multiple point calibration is also available. Calibration certificates must be requested when ordering; for details contact your sales representative.

Validation Testing Program

Validation testing services in advance of shipment may accelerate in-house Installation Qualification (IQ) and Operation Qualification (OQ) programs. Validation services include documentation and performance reports, compressor and subsystem component specifications, microprocessor flow diagrams, software specifications and more. For more details, contact your sales representative.

Model no.	Services description
7455TA	Temperature mapping of 24 hours at setpoint to include: • Mapping data graphed at each location • Thermocouple placement diagram • Test equipment list • Average uniformity and stability at specified cycle • Minimum, average and maximum temperatures at each thermocouple location • Uniformity and stability at each location
7456TA	Temperature mapping of 24 hours (traceable instruments and raw data) at setpoint to include: • Mapping data graphed at each location • Thermocouple placement diagram • Test equipment list- utilizing Kaye Validator® thermal validation equipment • Calibration certificates of test equipment • Thermocouple calibration reports • Average uniformity and stability at specified cycle • Minimum, average and maximum temperatures at each thermocouple location • Uniformity and stability at each location
6916-2	Certificate of calibration

Other Accessories



Wireless Monitoring

Thermo Scientific Smart-Vue™ wireless monitoring solution offers 24/7 continuous, real-time wireless monitoring of critical parameters, early warning alerts, and remote data logging. Likewise, Thermo Scientific Smart-Tracker™ requires only a smart phone to access stored temperature readings. No other equipment or installation is necessary.



Clinical Containers

Made with the highest quality resins, Thermo Scientific Nalgene™ bottles are engineered to work together with a proprietary valve seal and a strong, semi-buttress thread design. Our Nalgene bottles offer a leakproof* guarantee because we manufacture and test both components together as part of our routine quality program.



Gibco Media

Gibco™ media, sera, supplements, cells and cell culture reagents are designed to deliver reproducibility and performance for results you can count on. Regardless of whether you are performing cell culture in a research lab or production facility, need a special or defined formulation, or are growing cell lines, primary cells, or stem cells, Gibco products offer a reliable solution.

Visit **thermofisher.com** for wireless monitoring, consumables, media, reagents and more

* Our guarantee for a leakproof seal is subject to our standard product warranty, as set forth in the Thermo Fisher Scientific Terms and Conditions of Sale. Our products are leakproof at ambient temperature and pressure when used with their corresponding closures. However, to ensure safe usage, customers are advised to test our containers and closures under conditions of their planned applications. Please contact technicalsupport@thermofisher.com if you need additional information about our products.



Also available, Thermo Scientific™ TSX Series high-performance undercounter refrigerators

The only undercounter lab-grade refrigerator with redundant cooling

- Low energy usage
- Low noise
- High storage capacity

Australia +61 39757 4300
Austria +43 1 801 40 0
Belgium +32 53 73 42 41
China +800 810 5118 or
+400 650 5118
France +33 2 2803 2180
Germany national toll free 0800 1 536 376
Germany international +49 6184 90 6000

India toll free 1800 22 8374
India +91 22 6716 2200
Italy +39 02 95059 552
Japan +81 3 5826 1616
Netherlands +31 76 579 55 55
New Zealand +64 9 980 6700
Nordic/Baltic/CIS countries
+358 10 329 2200

Russia +7 812 703 42 15
Spain/Portugal +34 93 223 09 18
Switzerland +41 44 454 12 12
UK/Ireland +44 870 609 9203
USA/Canada +1 866 984 3766

Other Asian countries +852 2885 4613
Countries not listed +49 6184 90 6000

Find out more at thermofisher.com/tsx

ThermoFisher
SCIENTIFIC

[1] Manufacturer

Thermo Fisher Scientific (Asheville) LLC
275 Aiken Road
Asheville, NC 28804
USA

[2] Authorized Representative

Thermo Electron LED GmbH
Robert-Bosch-Str. 1
63505 Langenselbold
Germany

[3] Product Type

TSX™ Series -30°C Freezer, FDA Class I Medical Device

[4] Model Name(s) and [5] Rated Voltage, Rated Frequency

TSX5030LV

[6] The object of the declaration described above is in conformity with the relevant Union harmonization legislation:

[7] EC Directives

2014/30/EU	Electromagnetic Compatibility Directive
2014/35/EU	Low Voltage Directive
2011/65/EU	RoHS Directive
2015/863	RoHS Directive

[8] The object of the declaration described above is in conformity with Directive 2011/65/EU and 2015/863 of the European Parliament and of the Council of 22 July 2019 on the restriction of the use of certain hazardous substances in electrical and electronic equipment.

[9] Standards

EN 61326-1:2013	EN 378-2 :2008 + A1:2009 (applicable clauses)
EN 61010-1:2010	UL 471 Ed. 10 (applicable clauses)
EN 50581:2012	CSA C22.2 No. 120 :2013 (applicable clauses)
EN 60335-2-89:2007 (applicable clauses)	

[10] This declaration is valid from the product manufactured after the date. **May 06, 2019**

Dana Jolley
Global Regulatory Affairs Specialist
Laboratory Products Division
Thermo Fisher Scientific

DE ^[1] Hersteller - ^[2] Bevollmächtigter Vertreter - ^[3] Produkttyp - ^[4] Modellbezeichnung(en) - ^[5] Nennspannung, Nennfrequenz – ^[6] Der oben beschriebene Gegenstand der Erklärung erfüllt die einschlägigen Harmonisierungsrechtsvorschriften der Union:: ^[7] EG-Richtlinien - ^[8] Der oben beschriebene Gegenstand der Erklärung erfüllt die Vorschriften der Richtlinie 2011/65/EU des Europäischen Parlaments und des Rates vom 8. Juni 2011 zur Beschränkung der Verwendung bestimmter gefährlicher Stoffe in Elektro- und Elektronikgeräten: ^[9] Normen - ^[10] Diese Erklärung gilt für die nach diesem Datum hergestellten Produkte. ^[10] Diese Erklärung gilt für das Produkt mit folgender Seriennummer und Herstellungsdatum
FR ^[1] Fabricant - ^[2] Représentant agréé - ^[3] Type de produit - ^[4] Désignation(s) du modèle - ^[5] Tension nominale, Fréquence nominale – ^[6] L'objet de la déclaration décrit ci-dessus est conforme à la législation d'harmonisation de l'Union applicable : ^[7] Directives européennes - ^[8] L'objet de la déclaration décrit ci-dessus est conforme à la directive 2011/65/UE du Parlement européen et du Conseil du 8 juin 2011 relative à la limitation de l'utilisation de certaines substances dangereuses dans les équipements électriques et électroniques . ^[9] Normes - ^[10] La présente déclaration est valable à partir de la date de fabrication du produit. ^[10] La présente déclaration est valable pour le produit portant le numéro de série et la date de fabrication suivants.
IT ^[1] Produttore - ^[2] Rappresentante autorizzato - ^[3] Tipo di prodotto - ^[4] Nomi dei modelli - ^[5] Tensione nominale, Frequenza nominali – ^[6] L'oggetto della dichiarazione di cui sopra è conforme alla pertinente normativa di armonizzazione dell'Unione ^[7] Direttive CE - ^[8] L'oggetto della dichiarazione di cui sopra è conforme alla direttiva 2011/65/UE del Parlamento europeo e del Consiglio dell'8 giugno 2011, sulla restrizione dell'uso di determinate sostanze pericolose nelle apparecchiature elettriche ed elettroniche ^[9] Standard - ^[10] Questa dichiarazione è valida dal prodotto costruito dopo la data. ^[10] Questa dichiarazione è valida per il prodotto con i seguenti numero di serie e data di produzione
ES ^[1] Fabricante - ^[2] Representante autorizado - ^[3] Tipo de producto - ^[4] Modelos - ^[5] Tensión nominal, Frecuencia nominal - ^[6] El objeto de la declaración descrita anteriormente es conforme con la legislación de armonización pertinente de la Unión: ^[7] Directivas CE - ^[8] El objeto de la declaración descrito anteriormente es conforme a la Directiva 2011/65/UE del Parlamento Europeo y del Consejo, de 8 de junio de 2011, sobre restricciones a la utilización de determinadas sustancias peligrosas en aparatos eléctricos y electrónicos ^[9] Normas - ^[10] Esta declaración es válida para el producto fabricado después de la fecha. ^[10] Esta declaración es válida para el producto con el siguiente número de serie y fecha de manufactura.
PT ^[1] Fabricante - ^[2] Representante Autorizado - ^[3] Tipo de Produto - ^[4] Nome(s) do Modelo - ^[5] Tensão Nominal, Frequência Nominal – ^[6] O objeto da declaração acima descrito está em conformidade com a legislação de harmonização da União aplicável: ^[7] Directivas da CE - ^[8] O objecto da declaração acima mencionada está em conformidade com a Directiva 2011/65/UE do Parlamento Europeu e do Conselho, de 8 de Junho de 2011, relativa à restrição do uso de determinadas substâncias perigosas em equipamentos eléctricos e electrónicos. ^[9] Normas - ^[10] Esta Declaração é válida para o produto fabricado após a data. ^[10] Esta Declaração é válida para o produto com o seguinte número de série e data de fabrico
NL ^[1] Producent - ^[2] Gemachtigd vertegenwoordiger - ^[3] Producttype - ^[4] Modelnaam/namen - ^[5] Nominale spanning, nominale frequentie – ^[6] Het hierboven beschreven voorwerp is in overeenstemming met de desbetreffende harmonisatiewetgeving van de Unie: ^[7] EC-richtlijnen - ^[8] Het hierboven beschreven voorwerp is conform Richtlijn 2011/65/EU van het Europees Parlement en de Raad van 8 juni 2011 betreffende beperking van het gebruik van bepaalde gevaarlijke stoffen in elektrische en elektronische apparatuur: ^[9] Normen - ^[10] Deze verklaring is geldig voor de producten die zijn geproduceerd na deze datum. ^[10] Deze verklaring is geldig voor het product met het volgende serienummer en productiedatum.
PL ^[1] Producent - ^[2] Autoryzowany Przedstawiciel - ^[3] Typ produktu - ^[4] Nazwa(y) modelu - ^[5] Napięcie znamionowe , częstotliwość znamionowa - ^[6] Wymieniony powyżej przedmiot niniejszej deklaracji jest zgodny z odpowiednimi wymaganiami unijnego prawodawstwa harmonizacyjnego: ^[7] dyrektywy KE - ^[8] Opisany powyżej przedmiot deklaracji jest zgodny z dyrektywą Parlamentu Europejskiego i Rady 2011/65/UE z dnia 8 czerwca 2011 r. w sprawie ograniczenia stosowania niektórych niebezpiecznych substancji w sprzęcie elektrycznym i elektronicznym: ^[9] Standardy - ^[10] Deklaracja ta jest ważna dla wyrobów wyprodukowanych po dacie. ^[10] Niniejsza deklaracja jest ważna dla produktu z następującym numerem seryjnym oraz datą produkcji.
CS ^[1] Výrobce - ^[2] Autorizovaný zástupce - ^[3] Typ produktu - ^[4] Názvy modelů - ^[5] Jmenovité napětí, jmenovitý kmitočet – ^[6] Výše popsáný předmět prohlášení je ve shodě s příslušnými harmonizačními právními předpisy Unie: ^[7] Směrnice ES - ^[8] Výše popsáný předmět prohlášení je ve shodě se směrnicí Evropského parlamentu a Rady 2011/65/EU ze dne 8. června 2011 o omezení používání některých nebezpečných látek v elektrických a elektronických zařízeních: ^[9] Normy - ^[10] Toto prohlášení o shodě platí od data výroby produktu. ^[10] Toto prohlášení o shodě platí pro produkt s následujícím výrobním číslem a datem výroby.

DE ^[1] Hersteller - ^[2] Bevollmächtigter Vertreter - ^[3] Produkttyp - ^[4] Modellbezeichnung(en) - ^[5] Nennspannung, Nennfrequenz – ^[6] Der oben beschriebene Gegenstand der Erklärung erfüllt die einschlägigen Harmonisierungsrechtsvorschriften der Union:: ^[7] EG-Richtlinien - ^[8] Der oben beschriebene Gegenstand der Erklärung erfüllt die Vorschriften der Richtlinie 2011/65/EU des Europäischen Parlaments und des Rates vom 8. Juni 2011 zur Beschränkung der Verwendung bestimmter gefährlicher Stoffe in Elektro- und Elektronikgeräten: ^[9] Normen - ^[10] Diese Erklärung gilt für die nach diesem Datum hergestellten Produkte. ^[10] Diese Erklärung gilt für das Produkt mit folgender Seriennummer und Herstellungsdatum
FR ^[1] Fabricant - ^[2] Représentant agréé - ^[3] Type de produit - ^[4] Désignation(s) du modèle - ^[5] Tension nominale, Fréquence nominale – ^[6] L'objet de la déclaration décrit ci-dessus est conforme à la législation d'harmonisation de l'Union applicable : ^[7] Directives européennes - ^[8] L'objet de la déclaration décrit ci-dessus est conforme à la directive 2011/65/UE du Parlement européen et du Conseil du 8 juin 2011 relative à la limitation de l'utilisation de certaines substances dangereuses dans les équipements électriques et électroniques . ^[9] Normes - ^[10] La présente déclaration est valable à partir de la date de fabrication du produit. ^[10] La présente déclaration est valable pour le produit portant le numéro de série et la date de fabrication suivants.
IT ^[1] Produttore - ^[2] Rappresentante autorizzato - ^[3] Tipo di prodotto - ^[4] Nomi dei modelli - ^[5] Tensione nominale, Frequenza nominali – ^[6] L'oggetto della dichiarazione di cui sopra è conforme alla pertinente normativa di armonizzazione dell'Unione ^[7] Direttive CE - ^[8] L'oggetto della dichiarazione di cui sopra è conforme alla direttiva 2011/65/UE del Parlamento europeo e del Consiglio dell'8 giugno 2011, sulla restrizione dell'uso di determinate sostanze pericolose nelle apparecchiature elettriche ed elettroniche ^[9] Standard - ^[10] Questa dichiarazione è valida dal prodotto costruito dopo la data. ^[10] Questa dichiarazione è valida per il prodotto con i seguenti numero di serie e data di produzione
ES ^[1] Fabricante - ^[2] Representante autorizado - ^[3] Tipo de producto - ^[4] Modelos - ^[5] Tensión nominal, Frecuencia nominal - ^[6] El objeto de la declaración descrita anteriormente es conforme con la legislación de armonización pertinente de la Unión: ^[7] Directivas CE - ^[8] El objeto de la declaración descrito anteriormente es conforme a la Directiva 2011/65/UE del Parlamento Europeo y del Consejo, de 8 de junio de 2011, sobre restricciones a la utilización de determinadas sustancias peligrosas en aparatos eléctricos y electrónicos ^[9] Normas - ^[10] Esta declaración es válida para el producto fabricado después de la fecha. ^[10] Esta declaración es válida para el producto con el siguiente número de serie y fecha de manufactura.
PT ^[1] Fabricante - ^[2] Representante Autorizado - ^[3] Tipo de Produto - ^[4] Nome(s) do Modelo - ^[5] Tensão Nominal, Frequência Nominal – ^[6] O objeto da declaração acima descrito está em conformidade com a legislação de harmonização da União aplicável: ^[7] Directivas da CE - ^[8] O objecto da declaração acima mencionada está em conformidade com a Directiva 2011/65/UE do Parlamento Europeu e do Conselho, de 8 de Junho de 2011, relativa à restrição do uso de determinadas substâncias perigosas em equipamentos eléctricos e electrónicos. ^[9] Normas - ^[10] Esta Declaração é válida para o produto fabricado após a data. ^[10] Esta Declaração é válida para o produto com o seguinte número de série e data de fabrico
NL ^[1] Producent - ^[2] Gemachtigd vertegenwoordiger - ^[3] Producttype - ^[4] Modelnaam/namen - ^[5] Nominale spanning, nominale frequentie – ^[6] Het hierboven beschreven voorwerp is in overeenstemming met de desbetreffende harmonisatiewetgeving van de Unie: ^[7] EC-richtlijnen - ^[8] Het hierboven beschreven voorwerp is conform Richtlijn 2011/65/EU van het Europees Parlement en de Raad van 8 juni 2011 betreffende beperking van het gebruik van bepaalde gevaarlijke stoffen in elektrische en elektronische apparatuur: ^[9] Normen - ^[10] Deze verklaring is geldig voor de producten die zijn geproduceerd na deze datum. ^[10] Deze verklaring is geldig voor het product met het volgende serienummer en productiedatum.
PL ^[1] Producent - ^[2] Autoryzowany Przedstawiciel - ^[3] Typ produktu - ^[4] Nazwa(y) modelu - ^[5] Napięcie znamionowe , częstotliwość znamionowa - ^[6] Wymieniony powyżej przedmiot niniejszej deklaracji jest zgodny z odpowiednimi wymaganiami unijnego prawodawstwa harmonizacyjnego: ^[7] dyrektywy KE - ^[8] Opisany powyżej przedmiot deklaracji jest zgodny z dyrektywą Parlamentu Europejskiego i Rady 2011/65/UE z dnia 8 czerwca 2011 r. w sprawie ograniczenia stosowania niektórych niebezpiecznych substancji w sprzęcie elektrycznym i elektronicznym: ^[9] Standardy - ^[10] Deklaracja ta jest ważna dla wyrobów wyprodukowanych po dacie. ^[10] Niniejsza deklaracja jest ważna dla produktu z następującym numerem seryjnym oraz datą produkcji.
CS ^[1] Výrobce - ^[2] Autorizovaný zástupce - ^[3] Typ produktu - ^[4] Názvy modelů - ^[5] Jmenovité napětí, jmenovitý kmitočet – ^[6] Výše popsáný předmět prohlášení je ve shodě s příslušnými harmonizačními právními předpisy Unie: ^[7] Směrnice ES - ^[8] Výše popsáný předmět prohlášení je ve shodě se směrnicí Evropského parlamentu a Rady 2011/65/EU ze dne 8. června 2011 o omezení používání některých nebezpečných látek v elektrických a elektronických zařízeních: ^[9] Normy - ^[10] Toto prohlášení o shodě platí od data výroby produktu. ^[10] Toto prohlášení o shodě platí pro produkt s následujícím výrobním číslem a datem výroby.

EL) ^[1] Κατασκευαστής - ^[2] Εξουσιοδοτημένος αντιπρόσωπος - ^[3] Είδος προϊόντος - ^[4] Ονομασία μοντέλου - ^[5] Ονομαστική τάση, Ονομαστική συχνότητα - ^[6] Ο στόχος της δήλωσης που περιγράφεται παραπάνω είναι σύμφωνος με τη σχετική ενωσιακή νομοθεσία εναρμόνισης: ^[7] Οδηγίες ΕΚ - ^[8] Το ανωτέρω περιγραφόμενο αντικείμενο της δήλωσης είναι σύμφωνο με την οδηγία 2011/65/ΕΕ του Ευρωπαϊκού Κοινοβουλίου και του Συμβουλίου, της 8ης Ιουνίου 2011, σχετικά με τον περιορισμό της χρήσης ορισμένων επικίνδυνων ουσιών σε ηλεκτρικό και ηλεκτρονικό εξοπλισμό: ^[9] Πρότυπα - ^[10] Η παρούσα δήλωση ισχύει για το κατασκευασμένο προϊόν μετά την ημερομηνία. ^[10] Η παρούσα δήλωση ισχύει για το προϊόν με τον ακόλουθο σειριακό αριθμό και την ημερομηνία κατασκευής
GA) ^[1] Monaróir - ^[2] Ionadaí údaráithe - ^[3] Cineál Táirge - ^[4] Ainm (neacha) Samhail - ^[5] Rátáil Voltage , Minicíocht Rátáil - ^[6] Tá cuspóir an dearbhaithe a bhfuil tuairisc air thuas i gcomhréir le reachtaíocht ábhartha an Aontais maidir le comhchuibhiú: ^[7] Treoracha CE - ^[8] Tá cuspóir an dearbhaithe a bhfuil tuairisc air thuas i gcomhréir le Treoir 2011/65/AE ó Pharlaimint na hEorpa agus ón gComhairle an 8 Meitheamh 2011 maidir le srian ar shubstaintí guaiseacha áirithe a úsáid i dtrealamh leictreach agus leictreonach ^[9] Caighdeáin - ^[10] Tá an dearbhú bailí ón táirge a mhonaraítear i ndiaidh an dáta sin. ^[10] Tá an dearbhú bailí ar feadh an táirge foirgníochta an sraithuimhir leanas agus dáta monaraithe
HR) ^[1] Proizvodač - ^[2] Ovlašteni zastupnik - ^[3] Vrsta proizvoda - ^[4] Naziv(i) modela - ^[5] Nazivni napon, nazivna frekvencija - ^[6] Predmet navedene izjave u skladu je s mjerodavnim zakonodavstvom Unije o usklađivanju: ^[7] Direktive EZ-a - ^[8] Gore opisan predmet izjave u skladu je s Direktivom 2011/65/EU Europskog parlamenta i Vijeća od 8. lipnja 2011. o ograničavanju uporabe određenih opasnih tvari u električnoj i elektroničkoj opremi: ^[9] Norme - ^[10] Ova izjava vrijedi za proizvod proizveden nakon navedenog datuma. ^[10] Ova izjava vrijedi za proizvod sa sljedećim serijskim brojem i datumom proizvodnje
RO) ^[1] Producător - ^[2] Reprezentant Autorizat - ^[3] Tipul Produsului - ^[4] Nume model(e) - ^[5] Tensiune nominală, Frecvența nominală - ^[6] Obiectul declarației descris mai sus este în conformitate cu legislația relevantă de armonizare a Uniunii: ^[7] Directive CE - ^[8] Obiectul declarației descris mai sus este conform Directivei 2011/65/UE a Parlamentului European și a Consiliului din 8 iunie 2011 privind restricțiile de utilizare a anumitor substanțe periculoase în echipamentele electrice și electronice: ^[9] Standarde - ^[10] Această declarație este valabilă pentru produsele fabricate după data curentă. ^[10] Această declarație este valabilă pentru produsul cu următorul număr de serie și următoarea dată de fabricație
HU) ^[1] Gyártó - ^[2] Meghatalmazott képviselő - ^[3] Terméktípus - ^[4] Modell(ek) neve - ^[5] Névleges feszültség, névleges frekvencia - ^[6] A fent ismertetett nyilatkozat tárgya megfelel a vonatkozó uniós harmonizációs jogszabálynak: ^[7] EC-irányelvek - ^[8] E nyilatkozat fent leírt tárgya összhangban van az egyes veszélyes anyagok elektromos és elektronikus berendezésekben való alkalmazásának korlátozásáról szóló, 2011. június 8-i 2011/65/EU európai parlamenti és tanácsi irányelvvel: ^[9] Szabványok - ^[10] Jelen nyilatkozat a megadott dátum után gyártott termékekre érvényes. ^[10] Jelen nyilatkozat a következő sorozatszámú és gyártási dátumú termékekre érvényes.
BG) ^[1] Производител - ^[2] Оторизиран представител - ^[3] Тип продукт - ^[4] Име на модел - ^[5] Номинално напрежение, Номинална честота - ^[6] Предметът на декларацията, описан по-горе, отговаря на съответното законодателство на Съюза за хармонизация: ^[7] Директиви на ЕО - ^[8] Обектът на декларацията, който е описан по-горе, е в съответствие с Директива 2011/65/ЕС на Европейския парламент и на Съвета от 8 юни 2011 г. относно ограничението на употребата на определени опасни вещества в електрическото и електронното оборудване: ^[9] Стандарти - ^[10] Тази декларация е валидна за продуктите, произведени след датата. ^[10] Тази декларация е валидна за продукта със следния сериен номер и дата на производство.
ZH) ^[1] 制造商 - ^[2] 授权代表 - ^[3] 产品类型 - ^[4] 型号 - ^[5] 额定电压、额定频率 - ^[6] 上述声明对象符合相关欧盟协调法规 ^[7] 欧盟指令 - ^[8] 上述声明对象符合欧洲议会和欧盟理事会2011年6月8日关于在电气和电子设备中限制使用某些有害物质的指令2011/65 / EU ^[9] 标准 - ^[10] 本声明自产品制造之日起生效。 ^[10] 本声明适用于具有下述序列号和制造日期的产品。



Thermo Fisher Scientific (Asheville) LLC

Laboratory Products Division
275 Aiken Road
Asheville, North Carolina 28804 UNITED STATES

UL LLC®(UL) issues this certificate to the Firm named above, after assessing the Firm's quality system and finding it in compliance with:

ISO 13485:2016

EN ISO 13485:2016

The design and development, manufacture, distribution, service and installation, technical support, training, and Asheville depot repair of cold storage products and associated equipment; the manufacture, distribution, service, and Asheville depot repair of laboratory sciences products; the manufacture and distribution of temperature control products; the contract manufacture and distribution of automated microbial detection systems.

Certificate with Addendum(s) totals 2 pages.



Authorized by

Paul Hilgeman

Director & Global Industry Leader, Medical
CMIT – Medical Regulatory



Check Certificate
Status: [here](#)

File Number	A28309	Cycle Start	October 19, 2020
Certificate Number	1798.211021	Effective Date	October 21, 2021
Initial Issue Date	August 13, 2018	Expiry Date	October 18, 2022

This quality system registration is included in UL's Directory of Registered Firms and applies to the provision of goods and/or services as specified in the scope of registration from the address(es) shown above. By issuance of this certificate the firm represents that it will maintain its registration in accordance with the applicable requirements. This certificate is not transferable and remains the property of UL LLC.



UL LLC
333 Pfingsten Road
Northbrook, IL 60062-2096 USA



CERTIFICATE OF REGISTRATION

Thermo Fisher Scientific (Asheville) LLC

Laboratory Products Division

275 Aiken Road

Asheville, North Carolina 28804 UNITED STATES

Addendum 1

1-1

Thermo Fisher Scientific (Asheville) LLC

275 Aiken Road

Asheville, North Carolina 28804 UNITED STATES

Performing: Design, purchasing, manufacturing, contract manufacturing, warehouse, QA, QC, human resources, administration, maintenance, calibration, and receiving.

1-2

Thermo Fisher Scientific (Asheville) LLC

28 Schenck Parkway, Suite 400, Building 2B

Asheville, North Carolina 28803 UNITED STATES

Performing: Customer service, contract review, order entry, human resources, service and Installation.

1-3

Thermo Fisher Scientific (Asheville) LLC

501 Elk Park Dr

Woodfin, North Carolina 28804 UNITED STATES

Performing: Product specific training for external and field staff.

1-4

Thermo Fisher Scientific (Asheville) LLC

220 Merrimon Avenue

Weaverville, North Carolina 28787 UNITED STATES

Performing: Warehouse, shipping, Asheville Depot and RMA process.

1-5

Thermo Fisher Scientific (Asheville) LLC

249 Elk Park Dr Suite 703

Woodfin, North Carolina UNITED STATES

Performing: Product specific training for external and field staff.

File Number A28309

Cycle Start October 19, 2020

Certificate Number 1798.211021

Effective Date October 21, 2021

Initial Issue Date August 13, 2018

Expiry Date October 18, 2022

This quality system registration is included in UL's Directory of Registered Firms and applies to the provision of goods and/or services as specified in the scope of registration from the address(es) shown above. By issuance of this certificate the firm represents that it will maintain its registration in accordance with the applicable requirements. This certificate is not transferable and remains the property of UL LLC.



UL LLC
333 Pfingsten Road
Northbrook, IL 60062-2096 USA