

Detalii specifice și standarde tehnice

LOT: „Termobloc pentru PCR”:

№	Denumire produs	Specificatii tehnice minime	Specificatii tehnice oferite; Model, producator.
1	Termobloc pentru PCR	<p>Thermoblock with a temperature range: ambient to +5°C to 150°C. Heat up speed of 5°C per min.</p> <ul style="list-style-type: none"> - Users' self-compensation function to offset between real temperature and indicated temperature (+10.0;>C); <p>Internal PPS bath ensures best insulation, block made of anodized aluminium;</p> <ul style="list-style-type: none"> - Precise temperature control; Digital timer function - delay time and operation control: timer range of 99h 59min alarm; - Convenient integrated timer for time-sensitive incubations; Block removal tool with screw thread included; Locking mode; overheat and over-current protection and sensor error detection; Includes: dry bath, EU plugs, block lifter; - Storage function for the set values of temperature and timer; Various block types (optional); - Safety mechanism: locking mode, overheat and over-current protection and sensor error detection. <p><u>This item includes: 1 unit + 4 blocks: Block of 96 places 0,2 ml PCR tubes, Block 15 places 15 ml conical tubes, Block 8 places 50 ml conical tubes and Block 96 places 0.5 ml PCR tubes</u></p>	<p>Witeg H-20 with accessories</p> <p>Thermoblock with a temperature range: ambient to +5°C to 150°C. Heat up speed of 5°C per min.</p> <ul style="list-style-type: none"> - Users' self-compensation function to offset between real temperature and indicated temperature (+10.0°C); <p>Internal PPS bath ensures best insulation, block made of anodized aluminium;</p> <ul style="list-style-type: none"> - Precise temperature control; Digital timer function - delay time and operation control: timer range of 99h 59min alarm; - Convenient integrated timer for time-sensitive incubations; Block removal tool with screw thread included; Locking mode; overheat and over-current protection and sensor error detection; Includes: dry bath, EU plugs, block lifter; - Storage function for the set values of temperature and timer; Various block types (optional); - Safety mechanism: locking mode, overheat and over-current protection and sensor error detection. <p>This item includes: 1 unit + 4 blocks: Block of 96 places 0,2 ml PCR tubes, Block 15 places 15 ml conical tubes, Block 8 places 50 ml conical tubes and Block 63 places 0.5 ml PCR tubes</p>

	Mandatory requirements	<ul style="list-style-type: none">- Original manufacturer packing for all items;- Quality Certificates (CE and/or DC) or any other equivalent;- ISO 9001-2015	<ul style="list-style-type: none">- Original manufacturer packing for all items;- Quality Certificates (CE and/or DC);- ISO 9001-2015
--	-------------------------------	---	---

Toate bunurile vor fi testate de beneficiar. Acceptarea bunurilor și semnarea actelor de recepție va avea loc după testarea pozitivă efectuată de beneficiar.

NUMELE FURNIZORULUI: **Lokmera SRL**

Semnătura și ștampila autorizate: **Director, Iasîbaș Nicolai**

Locul: **Chișinău**

Data: 15.05.2023

