

Data: “20.” Octombrie 2020

Procedura de achiziție Nr.: ocds-b3wdp1-MD-1602075084494

Certificat de Garantie

Andix SRL

Beneficiar: Direcția Învățământ, Tineret și Sport a Primăriei mun. Bălți

Noi, *Andix SRL*, (numit în continuare „Furnizor/Prestator”) Informăm că pentru furnizarea de bunuri pentru achiziționarea: Achiziționarea tehnicii de calcul și a camerelor video oferim următoarea garanție:

Cod CPV	Denumirea bunurilor	Modelul articolului	Specificarea tehnică deplină propusă de către ofertant	Period de garantie	Luni/zile
1	2		7		
Lotul Nr.1 <i>LT</i> “D.Cantemir” 30213300-8	Calculator personal		CPU Intel Core i5-9400 2.9-4.1GHz (6C/6T, 9MB, S1151, 14nm, Integrated UHD Graphics 630, 65W) Tray; AC Deepcool LGA115x/1200 "THETA15 PWM" (17.8-36dBA, 2000-2800RPM, 50.25CFM, 100mm, PWM, 95W, 290g.); MB Gigabyte B365M H 1.0 mATX; 8GB DDR4- 2666MHz Apacer PC21300, CL19, 288pin DIMM 1.2V; M.2 NVMe SSD 256GB Apacer AS2280P4 [PCIe 3.0 x4, R/W:1800/1100MB/s, 190/180K IOPS, 3D TLC]; 3.5" HDD 500GB Western Digital WD5000AZLX Caviar® Blue™, 7200rpm, 32MB, SATAIII, FR ; 23.8" AOC "24B2XH", Black (IPS, 1920x1080, 7ms, 250cd, LED20M:1, D-Sub+HDMI, Headphone-Out); Power Supply ATX 600W GAMEMAX VP-600-RGB, 80+ Bronze , Active PFC, 120mm RGB fan, Fan Control; Keyboard & Mouse SVEN KB-S330C, Fullsize layout, Splash proof, Fn key, Black, USB; Case mATX GAMEMAX Silent Hill, w/o PSU, 1x120mm, USB3.0, Sound dampening material, Black; Garanție echipament - 24 luni	da	24 luni
Lotul Nr.2 <i>LT</i> “D.Cantemir”	Unitate multifuncțională cu funcții duplex		MFD Canon i-Sensys MF443dw MFD, A4, 38ppm, DADF, Ethernet, WiFi	da	24luni

30232110-8			<p>Print, Copy and Scan Print speed: Single sided : Up to 38 ppm (A4), Up to 63.1 ppm(A5-Landscape) Double sided : Up to 31.9 ipm (A4) Print speed: Single sided : Up to 38 ppm (A4), Up to 63.1 ppm(A5-Landscape) Double sided : Up to 31.9 ipm (A4) Interface type: USB 2.0 Hi-Speed, 10BASE-T/100BASE-TX/1000Base-T, Wireless 802.11b/g/n, Double sided copying: 2-sided to 2-sided (Automatic) Paper input (Standard): 250-sheet cassette, 100-sheet multi-purpose tray, 50-sheet ADF Garanție echipament -. 24 luni</p>		
<p>Lotul Nr.3 <i>LT</i> <i>"D.Cantemir"</i> 32333200-8</p>	<p>Registrator Video de Retea</p>		<p>DHI-NVR608-32-4KS2 System Main Processor Intel Dual-core Processor Operating System Embedded LINUX Audio and Video IP Camera Input 32 Channel Two-way Talk 1 Channel Input, 1 Channel Output, RCA Display Interface 2 HDMI (up to 3840 x 2160 , Different Source), 1 VGA Resolution 3840 x 2160 , 1920 x 1080 , 1280 x 1024, 1280 x 720 , 1024 x 768 Multi-screen Display 1st Screen: 1/4/8/9/16/25/36 2nd Screen: 1/4/8/9/16 OSD Camera title, Time, Video loss, Camera lock, Motion detection, Recording Recording Compression H.265/H.264/MJPEG Resolution 12MP, 8MP, 6MP, 5MP, 4MP, 3MP, 1080P, 1.3MP, 720P etc. Record Rate 384Mbps Bit Rate 16Kbps ~ 20Mbps Per Channel Record Mode Manual, Schedule (Regular, MD (Motion Detection), Alarm, IVS), Holiday, Stop Record Interval 1 ~ 120 min (default: 60 min), Pre-record: 1 ~ 30 sec, Post-record: 10 ~ 300 sec Video Detection and Alarm Trigger Events Recording, PTZ, Tour, Alarm Out, Video Push, Email, FTP, Snapshot, Buzzer and Screen Tips Video Detection Motion Detection, MD Zones: 396 (22 x 18), Video Loss and Tampering Alarm input 16 Channel, Low Level Effective, Green Terminal Interface Relay Output 8 Channel, NO/NC Programmable, Green Terminal Interface Tracking Trigger Event Zoom, Tracking, Recording, Preset, Snapshot, Alarm, etc. Playback and Backup Playback 128 Mbps in Raid 5 Mode; 64 Mbps in single HDD Mode Search Mode Time /Date, Alarm, MD and Exact Search (accurate to second) Playback Function Play, Pause, Stop, Rewind, Fast play, Slow Play, Next File, Previous File, Next Camera, Previous Camera, Full Screen, Repeat, Shuffle, Backup Selection, Digital Zoom</p>	da	12 luni

			<p>Backup Mode USB Device/Network/eSATA Device</p> <p>Third-party Support Third-party Support Dahua, Arecont Vision, AXIS, Bosch, Brickcom, Canon, CP Plus, Dynacolor, Honeywell, Panasonic, Pelco, Samsung, Sanyo, Sony, Videotec, Vivotek, and more</p> <p>Network Interface 2 RJ-45 Ports (10/100/1000Mbps) Ethernet Port 2 Ethernet Ports Joint Working or 2 Independent 1000Mbps Ethernet Ports PoE N/A Network Function HTTP, HTTPS, TCP/IP, IPv4/IPv6, UPnP, RTSP, UDP, SMTP, NTP, DHCP, DNS, IP Filter, PPPoE, DDNS, FTP, Alarm Server, IP Search (Support Dahua IP camera, DVR, NVS, etc.) Optical Fiber Interface N/A Max. User Access 128 users Smart Phone iPhone, iPad, Android Interoperability ONVIF 2.4, CGI Conformant</p> <p>Storage Internal HDD 8 SATA III Ports, Up to 8 TB capacity for each HDD HDD Mode Single, Raid 0/1/5/10(Enterprise-level HDDs are recommended), Support Global HDD Hot-spare eSATA 1 eSATA Port (Please contact technical engineer to confirm the compatible device) SAS N/A</p> <p>Auxiliary Interface Front Cover N/A USB 4 USB Ports (2 USB 2.0 , 2 USB 3.0) RS232 1 Port, for PC Communication and Keyboard RS485 1 Port, for PTZ Control</p> <p>Electrical Power Supply AC100V ~ 240V, 50 ~ 60 Hz Power Consumption <20W (Without HDD)</p> <p>Environmental Operating Conditions -10°C ~ +55°C (+14°F ~ +131°F), 86 ~ 106kpa Storage Conditions -20°C ~ +70°C (-4°F ~ +158°F), 0 ~ 90% RH</p> <p>Construction Dimensions 2U, 440mm x 451.08mm x 94.85mm (17.3" x 17.8" x 3.7") Net Weight 9kg (19.8 lb) (without HDD) Gross Weight 10.5kg (23.1 lb) Installation Rack-mounted</p> <p>Certifications CE EN55022, EN55024, EN50130-4, EN60950-1 FCC Part 15 Subpart B, ANSI C63.4-2014 UL UL 60950-1 and CAN/CSA C22.2 No.60950-1</p>		
	Camera IP		<p style="text-align: center;">DH-IPC-HDW1420S</p> <ul style="list-style-type: none"> · 1/3" 4Megapixel progressive CMOS · H.264+ & H.264 dual-stream encoding · 20fps@4M(2688×1520) &25/30fps@3M(2304×1296) · DWDR, Day/Night(ICR), 3DNR, AWB, AGC, BLC · Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS · 2.8 mm fixed lens (3.6mm optional) · Max IR LEDs Length 30m · IP67, PoE 	da	12 luni
Lotul Nr.4 <i>LT</i> "D.Cantemir,, 30237240-3	Camera Web		Trust Trino HD Video Webcam, 720p HD Webcam with convenient built-in microphone, 1,43m, USB	da	24 luni

Lotul Nr.5 <i>LT</i> <i>"D.Cantemir"</i> 32420000-3	Switch retea tip PoE:		DH-PFS4226-24GT-360 <ul style="list-style-type: none"> · Layer 2 network management PoE switch · Support IEEE802.3af, IEEE802.3at standard · Support Hi-PoE 60W · Network Redundancy: STP/RSTP/MSTP · Support IPv4/IPv6, and DHCP · Network management based on SNMP · Configuration: Web, Telnet, CLI Command · QoS (IEEE802.1p/1Q), CoS/ToS to Increase Determinism · Enhanced Network Security with IEEE802.1X, SNMP v1/v2c/v3, HTTPS, and SSH/SSL · Large data cache(4M), real-time transmission · MAC auto study and aging, MAC address list capacity is 8K · EMC high protection design 	da	12 luni
Lotul Nr.6 <i>LT</i> <i>"D.Cantemir"</i> 32572000-3	Cable UTP Cat 5e (cutia 305m)		Cable UTP Cat.5E, 305m, CCAG, 24awg 4X2X1/0.50, gray color, APC Electronic	nu	-
Lotul Nr.14 Contabilitatea Centralizată 30213300-8	Calculator		Intel® Core™ i3-8100, S1151, 3.6GHz (4C/4T), 6MB Cache, Intel® UHD Graphics 630, 14nm 65W, tray AC Deepcool LGA115x/1200 "THETA21 PWM" (17.8-33.4dBA, 900-2400RPM, 45.9CFM, 92mm, PWM, 95W, 370g.) MB Gigabyte B365M H 1.0 mATX 8GB DDR4- 2666MHz Apacer PC21300, CL19, 288pin DIMM 1.2V 2.5" SATA SSD 512GB Transcend "SSD230" [R/W:560/520MB/s, 85/85K IOPS, SM2258, 3D NAND TLC] Case ATX 500W Soho 5908BG, 2xUSB2.0, Black-Grey, ATX-500W-12cm 23.8" AOC "24B1XH", Black (IPS, 1920x1080, 7ms, 250cd, LED20M:1, D-Sub+HDMI, Headphone-Out) (23.8" IPS W-LED, 1920x1080 Full-HD, 0.275, 7ms GTG, 250 cd/m ² , DCR 20 Mln:1 (1000:1), 178°/178° @C/R>10, D-Sub + HDMI, HDMI Audio-In, Headphone-Out, External Power Adapter, Fixed Stand (Tilt - 3/+22°), Black Borderless) SVEN 170 Black (USB), 2.0 / 2x2.5W RMS, USB power supply, Volume control on the cable Keyboard & Mouse SVEN KB-S330C, Fullsize layout, Splash proof, Fn key, Black, USB	da	24 luni
Lotul Nr.15 Contabilitatea Centralizată 30232110-8	Multifuncțional (echivalent modelului - Canon i-Sensys MF237W + CRG737)	MF237w	MFD Canon i-Sensys MF237w MFD A4, 23 ppm, Wi-Fi, Network, Fax, ADF 35 sheet Print, Copy, Scan and Fax Single sided: Up to 23 ppm (A4)	da	24 luni

Print quality: Up to 1200 x 1200 dpi
Print Resolution: 600 x 600 dpi
Printer languages UFR II-LT
Advanced Space features: Google Cloud
Print Ready

iOS:
AirPrint, Canon PRINT Business app
Android; Mopria certified, Canon Print
Service Plug-in, Canon PRINT Business
app

Multiple Copy: Up to 999 copies
Reduction/Enlargement: 25-400% in
1% increments

Scanner Type: ADF, Flatbed, Colour
Scan Resolution Optical: Up to 600 x
600 dpi

Enhanced: Up to
9600 x 9600 dpi

Scan speed Single sided mono: 20 ipm
(300x300dpi)

Single sided colour: 15
ipm (300x300dpi)

Colour scanning depth: 24 bit/24 bit
(input/output)

Scan to PC: TIFF/JPEG/PDF/Compact
PDF/Searchable PDF

Fax : 33.6 Kbps (Up to 3 seconds/page)

Fax only, Fax/Tel Auto Switch, Answer
Mode, Manual

Paper input (Standard): 250-sheet
cassette

1-sheet
multi-purpose tray

35 sheet

ADF

Paper output: 100-sheet

Interface type: USB 2.0 Hi-Speed,
10BASE-T/100BASE-TX, Wireless

802.11b/g/n, Wireless Direct

Connection

Recommended Monthly Print Volume:

500 - 2,000 pages per month

Duty cycle: Max. 15,000 pages per
month

Memory 256MB

Control Panel: 6 lines B&W LCD

Touch Screen

Cartridge 737 (2,400 pages)

Printer ships with Starter Cartridge (900
pages) Paper input (Standard): 250-sheet
cassette

1-sheet
multi-purpose tray

35 sheet

ADF

Paper output: 100-sheet

Interface type: USB 2.0 Hi-Speed,
10BASE-T/100BASE-TX, Wireless

802.11b/g/n, Wireless Direct

Connection

Recommended Monthly Print Volume:

500 - 2,000 pages per month

Duty cycle: Max. 15,000 pages per
month

Memory 256MB

			Control Panel: 6 lines B&W LCD Touch Screen Cartridge 737 (2,400 pages) Printer ships with Starter Cartridge (900 pages) + Cartus de rezerva Laser Cartridge for HP CF283X (Canon 737H) black Compatible		
Lotul Nr.18 Școala sportiva nr.1 30232110-8	Imprimantă	MF3010 AM/BM, 1.8 m	MFD Canon i-Sensys MF3010 MFD A4, 18ppm Print, Copy and Scan Print Speed: Up to 18 ppm (A4) Print Quality: Up to 1200 x 600 dpi with Automatic Image Refinement Print Resolution: 600 x 400 dpi First Print Out Time: 7.8 secs Printer Languages: UFR II-LT Memory: 64 MB Control Panel: 1 digit LED Copy Speed: Up to 18 ppm (A4) Copy Resolution: Up to 600 x 600 dpi Reduction / Enlargement: 50-200% in 10% increments Scanner Colour Scan Resolution: Optical: Up to 600 x 600 dpi Enhanced: Up to 9600 x 9600 dpi Colour Scanning Depth: 24 bit/24 bit (input/output) Scanner Type Flatbed Paper Input (Standard): 150-sheet tray Paper Output: 100-sheet Interface: USB 2.0 Hi-speed	da	24 luni

Administrator/reprezentant

Gogol A.V (Administrator)

Familia, numele, prenumele, funcția

semnătura/ștampila