



Certificate of Conformity

No. 424 / 14.03.2023

This is to confirm "HEXOL SYNLINER ULTRATRUCK 10W40 UHPD"
Has been formulated with accordance to the specification: ACEA E9, ACEA E7, ACEA E6,
API Service CJ4/SN, CI4/SM, MB 228.51, 228.31; MAN 3477, 3677, 3271-1; DETROIT
DIESEL DDC 93K218; Volvo VDS-4, VDS-3; Renault RLD-3, RLD-2; IVECO TLS E9; CAT
ECF-1a/ECF-2/ECF-3; MACK EO-OPP; Deutz DQC IV-10LA; MTU Type 3.1; JASO DH-2;
DDC 93K218; Cummins CES20081; Scania Low Ash; DAF/Standard Drain
And manufactured by SC Hexol Lube SRL

Batch Number: 1/14.03.2023

Quantity: 4 x 208 Litre Barrels

Total Litres: 832 Litres

Test Results and Characteristics

Characteristics	Unit	Specification	Measured value	Method
Appearance		bright, clear	bright, clear	Visual
Kinematic viscosity at 40 °C	mm ² /s	80 - 120	106.12	ASTM D 445
Kinematic viscosity at 100 °C	mm ² /s	12.5 - 16.3	15.60	ASTM D 445
Viscosity index		min. 155	156	STAS 55-81
Density at 20 °C	g/cm ³	max. 0,8768	0.8550	STAS 35-81

We declare that the product specified above are accordind with the specifications.

Do not modify or alterate this certificate.

Issued to
CALBOR GRUP SRL
CHISINAU
REPUBLICA MOLDOVA

Quality and Environmental Compliance Manager

Ing. Ilinca Rotaru

