

	<p style="text-align: center;"><b>ALCO QUALITY ASSURANCE LABORATORY TEST REPORT</b></p> <p style="text-align: center;">Accreditation No: AZS ISO/IEC 17025:2020/AZ 01.0571.01.21</p>	
---	--	---

**Company:** ALCO LLC  
3, Vali Mammadov st., Sabail dist.  
AZ1095, Baku, Azerbaijan

**Certificate No.:** 2026001  
**Date of issue:** 10/01/2026

**Test sample**

**Product:** EUROTEC Brake & Clutch Fluid DOT-4  
**Batch number:** BF202601001

**Manufacture date:** 10/01/2026  
**Date of sampling:** 10/01/2026  
**Date of analysis:** 10/01/2026

**Test result**

Parameters	Unit	Test method	Limit	Test result
Appearance	-	Visual	Bright & Clear	Bright & Clear
Kinematic viscosity - at minus 40 °C - at 100 °C	mm <sup>2</sup> /s	ASTM D445	Max. 1800 Min. 1.5	1640 2.2
Dry Boiling Point	°C	ASTM D1120	Min. 230	248
Wet Boiling Point	°C	ASTM D 1120	Min. 128	138
pH	mm <sup>2</sup> /s	ASTM D1287	7.0-11.5	7.5
Stability at high temperature	-	ISO 4925	Max. 5.0	4.5

*ALCO QUALITY ASSURANCE LABORATORY accredited by AzAK for AZS ISO/IEC 17025:2020 at test laboratory.*

**Shelf life:** 5 years from the date of manufacture of the product if proper storage conditions are followed.

This product meets the specification set out in its product data sheet (PDS) and has been manufactured in a facility fully complying with the requirements of Integrated Management System standards.



**ALCO QUALITY ASSURANCE LABORATORY  
TEST REPORT**

Accreditation No: AZS ISO/IEC 17025:2020/AZ 01.0571.01.21



**Notes & Instructions:**

- Tests conducted according to International Standard Test Methods are routinely verified to be in compliance with the latest published versions. Minor changes may be made where they have no material impact on test results and are necessitated by reasons such as safety, environmental standards and method effectiveness.
- This certificate is only valid in its entirety.
- This certificate shall not be reproduced except in full, without the written approval of the laboratory.

**Approved by**

Aytan Aliyeva  
**Head of Laboratory**

