

SP 330 series

SP 330DN
SP 330SN
SP 330SFN

RICOH
imagine. change.



SP 330 series specifications

The SP330 series offers the solution that is right for your needs, whether it's just easy-to-manage and compact printing, or multifunction productivity. Compact footprints make these solutions ideal for smaller spaces and maintenance and management are simple, with intuitive operation.

Features for printers in this series include:

- Crisp 32 pages per minute output
- SP 330DN is ideal for use on desktops or under counters
- SP 330SN provides printing, scanning and copying
- SP 330SFN comes with 4.3 inch touch panel and ARDF

SP 330DN/SP 330SN/SP 330SFN

	SP 330DN	SP 330SN	SP 330SFN
GENERAL			
Warm-up time (sec.)	26	30	30
First output speed: B/W (sec.)		7.5	
Continuous output speed (ppm)		32	
Memory: standard (MB)	128	256	256
Weight (kg)	13	18	18
Dimensions: W x D x H (mm)	370 x 392 x 262	405 x 392 x 407	405 x 392 x 420
Power source		220 - 240 V, 50/60 Hz	
Laser classification		Class 1 Laser Product (IEC60825 - 1:2014)	

COPIER (SP 330SN, SP 330SFN)

Multiple copying	-	Up to 99 copies	Up to 99 copies
Resolution	-	1,200 x 1,200 dpi	1,200 x 1,200 dpi
Enlargement/reduction		25 - 400%	
Zoom	-	From 25% to 400% in 1% steps	From 25% to 400% in 1% steps

PRINTER

Printer language: standard	PCL5e (Mac OS), PCL6 (Windows), PostScript 3		
Print resolution: maximum (dpi)	1,200 x 1,200		
Network interface: standard	Ethernet 10 base-T/100 base-TX, USB2.0 Type B		
Network interface: option	Wireless LAN (IEEE 802.11 a/b/g/n/ac)		
Windows® environments	Windows® 7/8.1/10, Windows® Server 2008/2012/2012R2/2016		
Mac OS environments	Macintosh OS X v10.10 or later		
Other supported environments	Linux environment		

SCANNER (SP 330SN, SP 330SFN)

Scanning: B/W (ipm)	-	13	13
Scanning: full colour (ipm)	-	4.5	4.5
Resolution: maximum (dpi)	-	600	600

FAX (SP 330SFN)

Compatibility	-	-	ITU-T (CCITT) G3
Transmission speed (seconds)	-	-	3
Modem speed: maximum (Kbps)	-	-	33.6

PAPER HANDLING

Recommended paper size	A4, A5, A6, B5, B6		
Paper input: standard (sheets)	300		
Paper input: maximum (sheets)	550		
Paper output: standard (sheets)	125	50	50
Paper weight (g/m²)	52 - 162		

ECOLOGY

Power consumption: max. (kWh)	Less than 1.025		
Power consumption: sleep (W)	0.72	0.87	0.87
TEC (kWh)*	0.41	0.42	0.42

* It is a reference value based on the ENERGY STAR Ver.3.0 test method.

OPTIONS

1x 250-sheet Paper tray, IEEE 802.11 a/b/g/n/ac

CONSUMABLES

Starter toner (prints)	1,000
Toner (regular yield) (prints)	3,500
Toner (high yield) (prints)	7,000
Consumable yield measuring method ISO/IEC 19752	

RICOH
imagine. change.

www.ricoh-europe.com



ISO9001 certified, ISO14001 certified, ISO27001 certified

All brand and/or product names are trademarks of their respective owners.

Specifications and external appearance are subject to change without notice. The colour of the actual product may vary from the colour shown in the brochure. The images in this brochure are not real photographs and slight differences in detail might appear.

Copyright © 2021 Ricoh Europe PLC. All rights reserved. This brochure, its contents and/or layout may not be modified and/or adapted, copied in part or in whole and/or incorporated into other works without the prior written permission of Ricoh Europe PLC.