

U500 Urine Analyzer



Accurate and Efficient

- Up to 500 tests/hour for medium/large volume sample testing
- Professional accuracy equivalent to market leader
- Automatic strip detection and alignment for better efficiency
- Test categories include Routine, STAT and QC

Easy to Operate

- Large touch screen LCD offers simple menu navigation
- Uniquely designed strip platform/waste tray unit for easy one-step cleaning

Convenient

- Automatic calibration and waste disposal reduce hands-on time
- Can read strips with up to 14 parameters, including Microalbumin/Creatinine/Calcium
- Strip selection of up to 4 combinations for analyzer reading
- Stores up to 2,000 records and automatically flags abnormal results
- Capable of printing results on sticker paper for quick and easy record management

Data Management Capability

- Includes RS232C port for easy data transfer to an external computer or LIS
- Record Operator/Patient ID by Manual Entry and Barcode Reader

Unique Lockout Functions

- Strip Lockout
 - Pre-set option to prevent using strips of another brand, with a barcode reader or by manual entry
- User Lockout
 - Option to eliminate unapproved users with up to 10 operators
- QC Lockout
 - Prevents testing without passing QC
 - If QC tests fail, analyzer will switch to STAT mode and list "E" at the end of each test number

Specifications

Feature	Specifications
Analyzer Type	Semi-Automatic
Methodology	Reflectance Photometry
Detection	Photosensitive Diode
Throughput	500 tests/hour (Measuring cycle: 7 seconds/test)
Test Categories	Routine, STAT and QC
Lockout Functions	Strip Lockout: Available Upon Request; User/QC Lockout: Included with option to turn ON/OFF
Memory	Last 2,000 Records
Strip Incubation Time	1 Minute
Wavelength	525 and 635 nm
Default Strips	8, 9, 10, 11 Parameters (108 mm x 5 mm)
Strips Available	1-14 parameters (108 mm x 5 mm); see URS Parameters
Parameter Order	Can select the order of parameters for display and print out
Total Combinations Per Analyzer	4 Combinations
Waste Disposal Capacity	Up to 150 Strips
Analyzer Ports	RS232C Port for Barcode Reader or Data Transfer 25 Pin Parallel Port for External Printer
Data Entry Capabilities	Operator/Patient ID - Manual Entry and Barcode Reader (Up to 25 characters)
Connection Capabilities	Internal Thermal Printer (included) RS232C Barcode Reader (optional) Optional External Printer (not included) RS232C Data Transfer Cable (optional)
Major Readable Barcodes	Code 128, Code 39, Codabar (NW-7), EAN 8, EAN 13, Interleave 25, UPCA, UPCE
Calibration	Automatic
Available Languages on the Screen	English and additional language(s)
Operating Conditions	0-40°C (32-104°F); ≤85% RH
Storage Conditions	-5-50°C (23-122°F); ≤90% RH
Power Source	100-240 VAC, 50-60 Hz
Dimensions (L x W x H)	36.6 cm x 28.3 cm x 19.5cm (14.4" x 11.1" x 7.7")
Display Dimensions (L x W)	11.5 cm x 9.0 cm (4.5" x 3.5")
Weight	4.0 kg (8.8 lbs) without batteries or power supply

Ordering Information

Product Name	Catalog No.	Components		Kit Box Dimensions (L x W x H) & Weight	Carton Dimensions (L x W x H) & Weight	Number of Kits/Carton
U500 Urine Analyzer	U211-101 [†]	1 Urine Analyzer	2 Fuses (2.0A)	51.0 cm x 42.0 cm x 38.5 cm; 7 kg	24.8" x 14.6" x 11.8"; 423.3 oz	1
		1 Strip Platform/Waste Tray	1 Power Cord	20.1" x 16.5" x 15.2"; 246.9 oz		
U500 Urine Analyzer with Barcode Reader	U211-111 [†]	1 Urine Analyzer	2 Fuses (2.0A)	55.0 cm x 55.0 cm x 55.0cm; 9.2 kg	21.7" x 21.7" x 21.7"; 324.5 oz	1
		1 Strip Platform/Waste Tray	1 Power Cord			
Barcode Reader	U221-111 [†]	2 Printer Paper Rolls	1 Serial Splitter Cable (RS232C)			22
		1 Barcode Reader (RS232C)	1 Instruction Manual			
Printer Paper Rolls	U121-101	4 Printer Paper Rolls	Thermal Paper (0.06 m x 20 m): 200 results/roll	23.6 cm x 10.8 cm x 7.8 cm; 0.482 kg	63.0 cm x 37.0 cm x 30.0 cm; 12 kg	50
			Sticker Paper (0.06 m x 9 m): 100 results/roll	9.3" x 4.3" x 3.1"; 17.0 oz	24.8" x 14.6" x 11.8"; 423.3 oz	
				12.0 cm x 12.0 cm x 6.5 cm; 0.360 kg	63.0 cm x 37.0 cm x 30.0 cm; 19.4 kg	
				4.7" x 4.7" x 2.6"; 12.7oz	24.8" x 14.6" x 11.8"; 684.3 oz	
U500 Data Transfer Kit	U221-131 [†]	1 Data Transfer Cable (RS232C)	1 Package Insert	12.0 cm x 12.0 cm x 6.5 cm; 0.40 kg	63.0 cm x 37.0 cm x 30.0 cm; 21.4 kg	8
				4.7" x 4.7" x 2.6"; 14.1oz	24.8" x 14.6" x 11.8"; 684.3 oz; 754.9 oz	
				16.0 cm x 13.0 cm x 3.5 cm; 0.147kg	25.0 cm x 21.0 cm x 15.0 cm; 1.36 kg	
				6.3" x 5.1" x 1.4"; 5.2 oz	9.8" x 8.3" x 5.9"; 48.0 oz	

✓ CE Marked for sale in the European Community



† FDA 510(k) Cleared