## MAIN APPLICATIONS

Ambulance Car

**Emergency Dept.** 

Home-Care

**Patient Transfer** 

Room / Ward

Tracheostomy

Veterinary



ASKIR 36BR is a portable suction unit for the aspiration of body liquids, oral, nasal and tracheal aspiration in adults or children. For professional use and with a powerful aspiration of max 36 l/min, ASKIR 36BR is lightweight for easy transport. Three different options for operation: AC/DC adapter, internal rechargeable battery and 12V make it a versatile suction unit approved for NON-STOP operation without overheating. Provided with visual and acoustic alarm indicating low battery level. Available with Lead-type battery or Li-lon battery. The Li-lon battery model is equipped with a pressure sensor placed in the PCB reduces by 50% the speed of the motor when no vacuum is detected and therefore no aspiration is taking place, and PROXIMITY function to switch ON/OFF without touch.

## **ACCESSORIES INCLUDED OPTIONS**

- Liquid Collection Jar with overflow valve system (different options, see below)
- 8x14mm Silicone Tubes, length 150cm (autoclavable) + Conical Connector ø10-11-12mm (antistatic upon request)
- Antibacterial & Hydrophobic Filter (single-patient)
- Power Cord + 12V Car Adapter + AC/DC Universal Adapter

- Stand on 5 Castors Ø 50mm with Brakes
- REF 27730
- Carrying Bag (for 1000ml jar) SP 0207/02
- Carrying Bag (for 2000ml jar) SP 0207

TECHNICAL FEATURES	ASKIR 36BR LEAD	NEW ASKIR 36 LI-ION (Proximity)
Motor — Power Feeding —	Oiless and maintenance-free piston pump 14V 4A 100-240V~	Oiless and maintenance-free piston pump 14V 4A 100-240V~
_	50-60Hz AC/DC power adapter provided with the unit 12V == 4A Lead rechargeable battery	50-60Hz AC/DC power adapter 14.8V 5.2A Li-Ion rechargeable battery

Autonomy 60 min. - Recharging Time 4 hours

\_ 12V --- 4A Car adapter Electromechanical switch ON/OFF Switch — ISO 10079-1 Classification — — HIGH VACUUM / HIGH FLOW

— IP21

Max Vacuum (adjustable) — -0.80 bar -80 kPa -600 mmHg

Max free air flow rate \_\_\_\_ \_ 36 l/min

Noise Level \_\_\_\_ \_ 65,5 dBA (with jar) / 68,5 dBA (without jar) Duty cycle — Non-stop operation (by mains only)

Weight kg 4.39

- cm 35 x 21 x 18

Years of Warranty -Shipping carton -3 Place of Manufacturing -

Autonomy 70 min. - Recharging Time 6 hours 12V == 4A Car adapter Soft-Touch switch HIGH VACUUM / HIGH FLOW

-0.80 bar -80 kPa -600 mmHg

36 l/min 60 dBA

Non-stop operation (by mains only)

kg 3.00

cm 35 x 21 x 18

2 2 Italy



## LI-ION **AVAILABLE CONFIGURATIONS LEAD**

Italy

RE 410200/03 RE 410205 ASKIR 36BR with 1000 ml autoclavable jar in policarbonate Makrolon 2858 ASKIR 36BR with 2000 ml autoclavable jar in policarbonate Makrolon 2858 RE 410200/09 RE 410205/01 ASKIR 36BR with 1000 ml Flovac® disposable liner and reusable container RE 410201 RE 410205/02 RE 410201/01 RE 410205/03 ASKIR 36BR with 2000 ml Flovac® disposable liner and reusable container

Jars in APEC® autoclavable up to 143°C available upon request

**CE** 0123