

# TOP TRACE NM 50 RFI MONITORING ECG ELECTRODES



Support	FOAM	Gel	SOLID gel
Diameter	50 mm.	Sensor material	Ag/AgCl
Reorder cod.	13628	Manufacturer Ceracarta Spa	Italy

TECHNICAL DATA			
Product profile		Electric features	
Disposable ECG electrode, white FOAM type diam. 50mm. Circular shaped, centered snap with conductive solid gel column. Aggressive medical grade adhesive. It eliminates the mess of liquid gels, while still offering low impedance. It holds the aqueous content in a polymerized hydrogel formulation, being non-irritating, non-sensitizing and non-cytotoxic to the skin.		DC offset Voltage	0,12 mV
<b>Features</b>	It is manufactured out of an aggressive, non-sensitizing, acrylic copolymer coated foam. All electrodes are Latex-free.	AC Impedance 10 Hz	60 (OHMS)
<b>Benefits</b>	This hypoallergic, non-irritating, disposable electrode meets and exceeds all AAMI performance specs.	DC Offset 5 sec after capacitor discharge	6,5 (Mv)
<b>Applications</b>	Specially designed for the difficult adhesions conditions that occur in patient standard monitoring	Recovery Slope 30 second interval	0,0 (mV/sec)
<b>Performance Charact.</b>	The electrode incorporates a proprietry solid gel formulation and is tested according to the voluntary Association of the Advancement of Medical Instrumentation (AAMI), USA	AC Impedance after defib.	46 (OHMS)
<b>Packaging</b>	40 pcs / Aluminium envelopes 800 pcs/ Box 4,800 pcs / Master carton	<b>Compliance to standards:</b> 2017/745 ANSI / AAMI EC12 : 2000 Standard Class I device Product branded CE	