

Client RED-Nord

Oferta ocds-b3wdp1-MD-1681233892167

Data 03 mai 2023

TRIOMAC SRL

 Cod fiscal 1006606001224
 Cod TVA 7400782
 BC "Moldindconbank" SA, fil Centru
 Cod MOLDMD2X309
 Cont IBAN MD49ML000000002251609230

N/o		Produs	Cantitatea	Pret fara TVA	Pret cu TVA	Pret total, fara TVA	Pret total, cu TVA	Valuta
1	Base	PowerEdge R650 Server	2	331950	398340,00	663900,00	796680,00	MDL
	FRONT STORAGE	10x2.5 Front Storage	2					
	BACKPLANE	SAS/SATA/NVMe Capable Backplane	2					
	Trusted Platform Module	Trusted Platform Module 2.0 V3	2					
	Chassis Configuration	2.5" Chassis with up to 10 HDDs (SAS/SATA) including max of 4 Universal Drives, 3 PCIe Slots, 2 CPU	2					
	Processor	Intel® Xeon® Silver 4314 2.4G, 16C/32T, 10.4GT/s, 24M Cache, Turbo, HT (135W) DDR4-2666	2					
	Additional Processor	Intel® Xeon® Silver 4314 2.4G, 16C/32T, 10.4GT/s, 24M Cache, Turbo, HT (135W) DDR4-2666	2					
	Processor Thermal Configuration	Heatsink for 2 CPU configuration (CPU less than or equal to 165W)	2					
	Memory Configuration Type	Performance Optimized	2					
	Memory DIMM Type and Speed	3200MT/s RDIMMs	2					
	Memory Capacity	16GB RDIMM, 3200MT/s, Dual Rank	24					
	RAID Configuration	C7, Unconfigured RAID for HDDs or SSDs (Mixed Drive Types Allowed)	2					
	RAID/Internal Storage Controllers	Front PERC H755 Rear Load	2					
	Hard Drives	1.92TB SSD SAS, RI, up to 24Gbps 512e 2.5in Hot-Plug, AG Drive	8					
	Hard Drives (PCIe SSD/Flex Bay)	1.6TB Enterprise NVMe Mixed Use AG Drive U.2 Gen4 with carrier	4					
	BIOS and Advanced System Configuration Settings	Power Saving BIOS Setting	2					
	Embedded Systems Management (Multi)	iDRAC9, Enterprise 15G	2					
	Advanced System Configurations	UEFI BIOS Boot Mode with GPT Partition	2					
	Fans	4 High Performance Fans for 2 CPU	2					
	Power Supply	Dual, Hot-plug, Power Supply Fault Tolerant Redundant (1+1), 800W, Mixed Mode, NAF	2					
	Power Cords	Rack Power Cord 4M (C13/C14 12A)	4					
	PCIe Riser	Riser Config 0, 2CPU, Half Length, Low Profile, 3 x16 Slots, SW GPU Capable	2					
	Motherboard	PowerEdge R650 Motherboard with Broadcom 5720 Dual Port 1Gb On-Board LOM	2					
	OC P 3.0 Network Adapters	Broadcom 5720 Quad Port 1GbE BASE-T Adapter, OCP NIC 3.0	2					
	Additional Network Cards	Broadcom 57412 Dual Port 10GbE SFP+ Adapter, PCIe Low Profile	2					
	Password	iDRAC, Factory Generated Password	2					
	Group Manager	iDRAC Group Manager, Enabled	2					
	Bezel	LCD Bezel for x8 and x10 Chassis	2					
	Boot Optimized Storage Cards	BOSS-S2 controller card + with 2 M.2 480GB (RAID 1)	2					
	Rack Rails	ReadyRails Sliding Rails Without Cable Management Arm or Strain Relief Bar	2					
	Server Accessories	Optional Serial Card (COM), Low Profile	2					
	SHIPPING	PowerEdge R650 Shipping EMEA1 (English/French/German/Spanish/Russian/Hebrew)	2					
	Shipping Material	R650 Ship 4x3.5, 10x2.5, 8x2.5 NVMe	2					
	Regulatory	PowerEdge R650 CE, CCC, Marking, No BIS Marking	2					
	Shipping/Order information	Enterprise Order - EMEA	2					
	Dell Services: Hardware Support	Parts Only Warranty 12Months, 12 Month(s)	2					
	Dell Services: Extended Service	Basic Next Business Day, 60 Month(s)	2					
	Dell Services: Deployment Services	No Installation Service Selected (Contact Sales rep for more details)	2					
	Anti Theft Device & Asset Tagging	Asset Tag - ProSupport (Website, barcode, Onboard MacAddress)	2					
	Shipping Box Labels - Standard	Order Configuration Shipbox Label (Ship Date, Model, Processor Speed, HDD Size, RAM)	2					

Suma totala, cu TVA	796 680,00	MDL
Total TVA	132780,00	MDL

 Oferta valabila 120 zile
 Termen de livrare: 55 zile

responsabil: Sleptov Serghei

