





EC Certificate

Full Quality Assurance System Directive 98/79/EC on In Vitro Diagnostic Medical Devices (IVDD), Annex IV excluding (4, 6) (List A and B and devices for self-testing)

No. V1 104507 0003 Rev. 01

Manufacturer:

ACON Laboratories, Inc.

5850 Oberlin Drive, #340 San Diego CA 92121 USA

Product Category(ies): In Vitro diagnostics for the detection of human infections and tumor markers, blood glucose measuring self-testing systems, self-testing devices for clinical chemistry, hematology and pregnancy and ovulation

The Certification Body of TÜV SÜD Product Service GmbH declares that the aforementioned manufacturer has implemented a quality assurance system for design, manufacture and final inspection of the respective devices / device families in accordance with IVDD Annex IV. This quality assurance system conforms to the requirements of this Directive and is subject to periodical surveillance. For marketing of List A devices an additional Annex IV (4) certificate is mandatory. See also notes overleaf.

Report no.: SH1974310

Valid from: Valid until: 2019-10-24 2022-09-12

Date,

2019-10-24

1. Pumil

Stefan Preiß Head of Certification/Notified Body

Page 1 of 4 TÜV SÜD Product Service GmbH is Notified Body with identification no. 0123





EC Certificate

Full Quality Assurance System Directive 98/79/EC on In Vitro Diagnostic Medical Devices (IVDD), Annex IV excluding (4, 6) (List A and B and devices for self-testing)

No. V1 104507 0003 Rev. 01

Model(s):

For Detail Models see attachment

Facility(ies):

ACON Laboratories, Inc. 5850 Oberlin Drive, #340, San Diego CA 92121, USA

ACON Laboratories, Inc. 10125 Mesa Rim Road, San Diego CA 92121, USA

AZURE Institute, Inc. 10125 Mesa Rim Road, San Diego CA 92121, USA





EC Certificate

Full Quality Assurance System Directive 98/79/EC on In Vitro Diagnostic Medical Devices (IVDD), Annex IV excluding (4, 6) (List A and B and devices for self-testing)

No. V1 104507 0003 Rev. 01

For the product(s)/product category (ies):

On Call Plus Blood Glucose Monitoring System, On Call Plus Blood Glucose Test Strips, On Call EZ II Blood Glucose Monitoring System, On Call Redi Blood Glucose Monitoring System, On Call Redi II Blood Glucose Test Strips, On Call Advanced Blood Glucose Monitoring System, On Call Advanced Blood Glucose Test Strips, On Call Platinum Blood Glucose Monitoring System, On Call Platinum Blood Glucose Test Strips, On Call Chosen Blood Glucose Monitoring System, On Call Chosen Blood Glucose Test Strips, On Call Vivid Blood Glucose Monitoring System (OGM-101), On Call Vivid Blood Glucose Test Strips (OGS-101), On Call Vivid Pal Blood Glucose Monitoring System (OGM-102), On Call Sharp Blood Glucose Monitoring System (OGM-121), On Call Sharp Blood Glucose Test Strips (OGS-121) On Call Plus II Blood Glucose Monitoring System (OGM-171), On Call Plus II Blood Glucose Test Strips (OGS-171), On Call Extra Blood Glucose Monitoring System (OGM-191), On Call Extra Blood Glucose Test Strips (OGS-191), On Call GK Dual Blood Glucose & Ketone Monitoring System (OGM-161), On Call Blood Ketone Test Strips (OGS-161), D-ONE Blood Glucose Monitoring System, D-ONE Blood Glucose Test Strips, Urinalysis Reagent Strips (Urine), UTI Urinary Tract Infection Test Strips, Toxoplasma IgG EIA Test Kit, Toxoplasma IgM EIA Test Kit, Rubella IgG EIA Test Kit, Rubella IgM EIA Test Kit, CMV IgG EIA Test Kit,

Page 3 of 4 TÜV SÜD Product Service GmbH is Notified Body with identification no. 0123

TÜV SÜD Product Service GmbH • Certification Body • Ridlerstraße 65 • 80339 Munich • Germany





EC Certificate

Full Quality Assurance System Directive 98/79/EC on In Vitro Diagnostic Medical Devices (IVDD), Annex IV excluding (4, 6) (List A and B and devices for self-testing)

No. V1 104507 0003 Rev. 01

CMV IgM EIA Test Kit, Total PSA EIA Test Kit, PT Coagulation Monitoring System (CCM-121), PT Coagulation Test Strips (CCS-121), Cholesterol Monitoring System (CCM-111), CHOL Total Cholesterol Test Devices (CCS-111), TRIG Triglycerides Test Devices (CCS-112), HDL High Density Lipoprotein Test Devices (CCS-113), 3-1 Lipid Panel Test Devices (CCS-114), Cholesterol CTRL Control Devices, Cholesterol Monitoring System (CCM-101), CHOL Total Cholesterol Test Strips (CCS-101), PT/INR Monitoring System (CCM-151), PT/INR Test Strips (CCS-151), Hemoglobin Testing System (CCM-141), Hemoglobin Test Strips (CCS-141), hCG Pregnancy Rapid Test Cassette (Urine), Pregnancy Rapid Test Midstream, On Call Extra Mobile Blood Glucose Monitoring System (OGM-281) On Call Sure Blood Glucose Monitoring System (OGM-211) On Call Sure Sync Blood Glucose Monitoring System (OGM-212) On Call Sure Blood Glucose Test Strips (OGS-211) On Call GU Dual Blood Glucose & Uric Acid Monitoring System (OGM-201) On Call Blood Uric Acid Test Strips (OGS-201) LH Ovulation Rapid Test Cassette (Urine) **Ovulation Rapid Test Midstream Ovulation & Pregnancy Test Combo Pack** On Call Extra Voice Blood Glucose Monitoring System (OGM-291) Early Detection Pregnancy Test **Digital Pregnancy Test**

Page 4 of 4 TÜV SÜD Product Service GmbH is Notified Body with identification no. 0123

Declaration of Conformity

ACON Laboratories, Incorporated 5850 Oberlin Drive #340 San Diego, CA 92121, USA

We, the manufacturer, declare under our sole responsibility that the *in vitro* diagnostic device:

Mission ® Liquid Urine Control (U021-011, U021-021, U021-031)

classified as Others in the directive 98/79/EC,

meets all the provisions of the directive 98/79/EC on *in vitro* diagnostic medical devices which apply to it

The self-declaration is according to Annex III (excluding Section 6) of the Directive.

Authorized Representative: Medical Device Safety Service GmbH Schiffgraben 41 30175 Hannover, Germany

Signed this 11th day of December, 2019 in San Diego, CA, USA

Qiyi Xie, MD, MPH Senior Staff, Regulatory Affairs & Clinical Affairs Acon Laboratories, Inc.







Certificate No. Q5 104507 0001 Rev. 01

Holder of Certificate:

ACON Laboratories, Inc.

5850 Oberlin Drive, #340 San Diego CA 92121 USA

Certification Mark:



Scope of Certificate:

Design and Development, Manufacture and distribution of In Vitro Diagnostic Test Kits and Reagents for the Determination of Infectious Diseases, Clinical Chemistry, Drugs of Abuse, Tumor/Cardiac Marker, Fertility/Pregnancy and Blood Glucose Monitoring System, Lancing Devices and Lancets

The Certification Body of TÜV SÜD Product Service GmbH certifies that the company mentioned above has established and is maintaining a quality management system, which meets the requirements of the listed standard(s). See also notes overleaf.

Report No.:

SH1974310

Valid from: Valid until: 2019-10-24 2022-09-06

Date,

2019-10-24

1. Pumil

Stefan Preiß Head of Certification/Notified Body





Certificate No. Q5 104507 0001 Rev. 01

Applied Standard(s):	EN ISO 13485:2016 Medical devices - Quality management systems - Requirements for regulatory purposes (ISO 13485:2016) DIN EN ISO 13485:2016

Facility(ies): ACON Laboratories, Inc. 5850 Oberlin Drive, #340, San Diego CA 92121, USA

> ACON Laboratories, Inc. 10125 Mesa Rim Road, San Diego CA 92121, USA

ACON Laboratories, Inc. 6865 Flanders Dr., Suite B, San Diego CA 92121, USA

AZURE Institute, Inc. 10125 Mesa Rim Road, San Diego CA 92121, USA



STATEMENT

We, ACON Laboratories, Inc. having a registered office at *5850 Oberlin Drive #340, San Diego, CA 92121* assign SRL Sanmedico having a registered office at *A. Corobceanu street 7A, apt. 9, Chisinău, MD-2012, Moldova,* as authorized representative in correspondence with the conditions of directive 98/79/EC.

We declare that the company mentioned above is authorized to register, notify, renew or modify the registration of medical devices on the territory of the Republic of Moldova.

This authorization will be valid for one year after the date of this statement.

Date: June 1, 2021

Signature:

Qiyi Xie, Md, MPH Sr. Officer, Regulatory & Clinical Affairs ACON Laboratories, Inc. Ph: 858-875-8011 Email: qxie@aconlabs.com

Mission® Urinalysis Reagent Strips and Urine Analyzers



Obtain reliable and cost-effective results with Mission[®] Urinalysis Reagent Strips and Urine Analyzers!

- Accurate
- Reliable
- Convenient



Urinalysis Reagent Strips



Simple and Accurate

- Analytical sensitivity better than or comparable to market leaders
- · High quality color chart ensures accurate visual reading

Flexible

- Compatible for visual and analyzer reading
- · More than 30 different combinations available

Multiple Packaging Options and Long Shelf Life


- Canister Packaging
 Available in 25, 50, 100 and 150 strips per kit
- · 2 year shelf life for unopened canisters which offers cost savings and convenience for high volume testing
- · 3 month shelf life for strips in opened canisters
- Pouch Packaging New!
- Single-strip Pouch
 - Individually packaged strips with 1, 3, 6 and 20 strips and 1 color chart per kit for OTC or low volume testing . Unique packaging maintains 2 year shelf life for all strips in the kit compared to 3 months for remaining strips in an
 - opened canister
- Multi-strip Pouch
 - Canister Refill Kits with 25 strips/pouch uniquely packaged to save cost for low volume testing and extended shelf life by using the canister for refills



Step 1: Immerse strip into urine



Step 2: Remove excess urine



Step 3: Obtain results by analyzer or visual reading

		Type of Strip *				Reading Method		thod	Analyzer-Read	Parameters												
Catalog No.	No. of Parameters	For Visual	For Analyzer Reading (U120/U500)	Strips per Canister *	Pouch Packaging [▲]		Strips: Standard (S)															
NO.	ranameters	For Visual Reading	(U120/U500)	Carnister	rackaging	Visual	U120	U500	or Additional (A)	ASC	GLU	BIL	KET	SG	BLO	рН	PRO	URO	NIT	LEU	ALB	CRE
U031-131	13	13C	NA	100*	~	1	NA	NA	A	*	*	*	*	*	*	*	*	*	*	*	*	*
U031-111	11		I1A	100	~	1	1	1	S	*	*	*	*	*	*	*	*	*	*	*		
		12	10U	100		1	~	1	S		*	*	*	*	*	*	*	*	*	*		
U031-101	10		10A	100	× .	~	1	~	А	*	*	*	*	*	*	*	*	*	*			
			10C	100*		1	~	1	S		*		*	*	*	*	*		*	*	*	*
U031-091	9		90	100	✓	~	1	~	S		*	*	*	*	*	*	*	*	*			
			BU			1	~	1	Α		*	*	*		*	*	*	*	*			
U031-081	8		BN	100	4	~	1	1	S		*		*	*	*	*	*		*	*		
		-	BS			1	1	1	A		*		1	*	*	*	*	*	*	*		
U031-071	7		7N	100	~	1	1	1	A		*		*		*	*	*	_	*	*		
U031-061	6	6N	6NE	100	1	~	~	~	A		*				*	*	*		*	*		
		6U	6UE			1	1	1				*	1	*	*		*	*	*			
		5B	5BE			1	1				*		*		*	*	*					
U031-051	5	5N	5NE	100	×	1	1	~	A		*			_	*		*	_	*	*		
94505/1, "6:601	(3) (3)	5S	5SE	0.5875576	25.0	1	~				*			*	*	*	*					
		5U	5UE			1	~					*	_	-	*		-	*	*	*		
		4S	4SE	100		1	1	~	A		*		0	*		*	*	_				
		4B	4BE			1	~				*				*	*	*					
U031-041	4	4K	4KE			1	1	1			*		*			*	*					
		4G	4GE			1	1				*				*		*			*		
		4N	4NE			1	1	*							*		*		*	*		
		4P	4PE			4	1	1			*		Ú.				*		*	*		
		3P	3PE			1	~	~			*					*	*					
U031-031	3	ЗK	3KE	100	~	1	~	1	А		*		*				*					
		3G	3GE			1	× ×	1			*		*			*						
		ЗN	3NE			1	1	1						-	*				*	*		
		2G	2GE			4	1	~			*						*					
		2K	2KE			1	~	1			*		*									
10000000000000	100	2N	2NE			1	\checkmark	1							*					*		
U031-021	2	2B	2BE	100	1	1	~	1	A		*		*									
		2U	2UE			1	1	1											*	*		
		2S 2SE	-			1	~	1						*		*						
		2C	2CE	100*		4	1	1									_				*	*
		1B	1BE			1	1				_		_		*		-					
		1P	1PE			1	~	1			-			_		*	-				,	
U031-011	1	1G	1GE	100	×	1	~	~	A		*											
		1K	1KE			1	~	1					*									
	1R 1RE			1	~	1	1 1								*							

♦Type of Strip:

Visual Strip Size

1-6 Parameters: 5 mm x 80 mm; 7-11 Parameters: 5 mm x 108 mm; 12-13 Parameters: 5 mm x 121 mm U120/U500 Strip Size

Also available in canisters of 25, 50 and 150 strips Not available in canisters of 150 strips

▲ Single-strip Pouch available in 1,3, 6 and 20 strip kit Canister Refill Kit, with 25 strips per pouch or canister, available in 3-pouch and 1- canister kit, or 4-pouch kit

1-11 Parameters: 5 mm x 108 mm:

"E" means extended strip length for 1-6 Parameters

CE Marked for sale in the European Community Cleared for US 510(k)

F

U120 Urine Analyzer





- Up to 120 tests/hour in Continuous Test Option
- · Capable of reading 1 strip at a time in Single Test Option
- · Test modes include Routine, STAT and QC
- · Automatic calibration for accurate results and easy operation

Reliable

 Can read up to 4 Strip combinations with 8, 9, 10, 11 parameters, additional strips with 1-11 parameters available upon request · Minimal training required

- Convenient Operation Saves and recalls the last 2,000 results automatically
- · Audible beep signals operator to dip strips in urine
- · Can print up to 3 copies per test for convenient reviewing and easy record keeping · Option to print results on sticker paper for quick and simple record management

Easy Data Management

Includes RS232C port for easy data transfer to an external computer or LIS
 Optional Barcode Reader to record patient ID

Unique Lockout Functions new!

- Strip Lockout Prevents using strips of another brand on the U120 Urine Analyzer
 - · Requires barcode reader scan or manual entry of the canister code
- User Lockout
- Eliminates unapproved users from testing
 Up to 10 lab operators can perform testing, but only the lab administrator can change analyzer settings • QC Lockout

 - · Prevents testing without passing QC QC tests can be performed once every 8 hours, day, week or month • Analyzer will alert when to run QC test
 - . If QC tests fail, analyzer will switch to STAT mode and list "E" at the end of each test number

Specifications

Feature	Specifications					
Analyzer Type	Manual					
Methodology	Reflectance Photometry					
Detection	Photosensitive Diode					
Throughput	Single Test Option: 60 tests/hour Continuous Test Option: 120 tests/hour					
Test Modes	Routine, STAT and QC					
Lockout Functions	Strip Lockout: Available Upon Request; Us	er/QC Lockout: Included with option to turn ON/OFF				
Memory	Last 2,000 results	4				
Strip Incubation Time	1 Minute					
Wavelength of Monochromatic LED	525 nm and 635 nm					
Standard Strips	8, 9, 10, 11 Parameters (5 mm x 108 mm	n)				
Additional Strips Available	1-11 Parameters (5 mm x 108 mm); see URS Parameters					
Total Combinations Per Analyzer	4 Combinations					
Analyzer Ports	Standard RS232C Port for Barcode Reader or Data Transfer USB Port for Data Transfer 25 Pin Parallel Port for External Printer					
Capabilities	Internal Thermal Printer (included) Optional External Printer (not included)	RS232C Barcode Reader (optional) USB or RS232C Data Transfer Cable (optional)				
Major Readable Barcodes	Code 128, Code 39, Codabar (NW-7), Inte EAN 8, EAN 13	rleaved 25, UPC-A, UPC-E,				
Calibration	Automatic					
Available Languages on the Screen	English and additional language(s)					
Operating Conditions	0-40°C (32-104°F); ≤85% RH					
Storage Conditions	-5-50°C (23-122°F); ≤90% RH					
Power Source	100-240 VAC, 50-60 Hz					
Dimensions (L x W x H)	27.2 cm x 26.9 cm x 14.6 cm (10.7" x 10	.6" x 5.7")				
Display Dimensions (L x W)	10.8 cm x 5.7 cm (4.2" x 2.2")					
Weight	2.6 kg (5.7 lbs)					

Ordering Information

Product Name	Catalog No.	Components			Kit Box Dimensions (L x W x H) & Weight	Carton Dimensions (L x W x H) & Weight	Number of Kits/Carton			
U120 Urine Analyzer	U111-101√ [†]	1 Urine Analyzer 1 Strip holder		2 Fuses (2.0A) 1 Power Cord	42.0 cm x 41.5 cm x 3	34				
0 120 Office Analyzer	U111-101**	2 Printer Paper Roll	s	1 Quick Start Guide 1 Instruction Manual	16.4" x 16.2" x 12.					
U120 Urine Analyzer	U111-111à	1 Urine Analyzer 1 Strip holder		2 Fuses (2.0A) 44.5cm x 44.5cm x 40.0cm; 5.5 kg						
with Barcode Reader	omini	2 Printer Paper Roll 1 Barcode Reader (T QUICK Start Guide		17.5" x 17.5" x 15.	া				
Barcode Reader	U221-111 ^à	1 Barcode Reader (RS232C)		1 Barcode Reader (RS232C) 1 Serial Splitter Cable (R		U221-111√ [†] 1 Barcode Reader (RS232C) 1 Serial Splitter Cable (RS2	1 Serial Splitter Cable (RS232C)	23.6 cm x 10.8 cm x 7.8 cm; 0.482 kg 9.3" x 4.3" x 3.1"; 17.0 oz	63.0 cm x 37.0 cm x 30.0 cm; 12.0 kg 24.8" x 14.6" x 11.8"; 423.3 oz	22
Printer Paper Rolls	1000	4 Printer Paper Rolls		Paper (0.06 m x 20 m): 200 results/roll	12.0 cm x 12.0 cm x 6.5 cm; 0.36kg 4.7" x 4.7" x 2.6"; 12.7oz	63.0 cm x 37.0 cm x 30.0 cm; 19.4 kg 24.8" x 14.6" x 11.8"; 684.3 oz	50			
Philler Paper Kolla	U121-101			aper (0.06 m x 9 m): 100 results/roll	12.0 cm x 12.0 cm x 6.5 cm; 0.4 kg 4.7" x 4.7" x 2.6"; 14.1 oz	63.0 cm x 37.0 cm x 30.0 cm; 21.4 kg 24.8" x 14.6" x 11.8"; 684.3 oz; 754.9 oz				
U120 Data Transfer Kit	U221-131 ^à	1 Data Transfer Cable	e (RS232C)	1 Package Insert	16.0 cm x 13.0 cm x 3.5 cm; 0.147 kg 6.3" x 5.1" x 1.4"; 5.2 oz	25.0 cm x 21.0 cm x 15.0 cm; 1.36 kg 9.8" x 8.3" x 5.9"; 48.0 oz	8			



U500 Urine Analyzer



- Accurate and Efficient Up to 500 tests/hour for medium/large volume sample testing Professional accuracy equivalent to market leader Automatic strip detection and alignment for better efficiency Test modes include Routine, STAT and QC

Easy to Operate
 Large buch screen LCD offers simple menu navigation
 Uniquely designed strip platform/waste tray unit for easy one-step cleaning

Convenient

- Convenient Automatic calibration and waste disposal reduce hands-on time Can read strips with 8, 9, 10, 11 parameters, additional strips with 1-11 parameters available upon request Strip selection of up to 4 combinations for analyzer reading Stores up to 2,000 records and automatically flags abnormal results Capable of printing results on sticker paper for quick and easy record management

Data Management Capability • Includes RS232C port for easy data transfer to an external computer or LIS • Optional Barcode Reader to record patient ID Unique Lockout Functions ^{Coming Scont}

- Strip Lockout
 Prevents using strips of another brand on the U500 Urine Analyzer
 Requires barcode reader scan or manual entry of the canister code
- User Lockout
- Eliminates unapproved users from testing
 Up to 10 lab operators can perform testing, but only the lab administrator can change analyzer settings QC Lockout
 Prevents testing without passing QC
- - QC tests can be performed once every 8 hours, day, week or month
 Analyzer will alert when to run QC test

 - . If QC tests fail, analyzer will switch to STAT mode and list "E" at the end of each test number

Specifications

Feature	Specifications				
Analyzer Type	Semi-Automatic				
Methodology	Reflectance Photometry				
Detection	Photosensitive Diode				
Throughput	500 tests/hour (Measuring cycle: 7 seco	nds/test)			
Test Modes	Routine, STAT and QC				
Lockout Functions	Strip Lockout: Available Upon Request; Use	er/QC Lockout: Included with option to turn ON/OFF			
Memory	Last 2,000 Records				
Strip Incubation Time	1 Minute				
Wavelength	525 and 635 nm				
Standard Strips	8, 9, 10, 11 Parameters (5 mm x 108 mm)			
Additional Strips Available	1-11 Parameters (5 mm x 108 mm); see UR	S Parameters			
Total Combinations Per Analyzer	4 Combinations				
Waste Disposal Capacity	Up to 150 Strips				
Analyzer Ports	Standard RS232C Port for Barcode Rea 25 Pin Parallel Port for External Printer	der or Data Transfer			
Capabilities	Internal Thermal Printer (included) Optional External Printer (not included)	RS232C Barcode Reader (optional) RS232C Data Transfer Cable (optional)			
Major Readable Barcodes	Code 128, Code 39, Codabar (NW-7), Inter	leaved 25, UPC-A, UPC-E, EAN 8, EAN 13			
Calibration	Automatic				
Available Languages on the Screen	English and additional language(s)				
Operating Conditions	0-40°C (32-104°F); ≤85% RH				
Storage Conditions	-5-50°C (23-122°F); ≤ 90% RH				
Power Source	100-240 VAC, 50-60 Hz				
Dimensions (L x W x H)	36.6 cm x 28.3 cm x 19.5 cm (14.4" x 11.1	1" x 7.7")			
Display Dimensions (L x W)	11.5 cm x 9.0 cm (4.5" x 3.5")				
Weight	4.0 kg (8.8 lbs)				

Ordering Information

Product Name	Catalog No.	Components			Kit Box Dimensions (L x W x H) & Weight	Carton Dimensions (L x W x H) & Weight	Number of Kits/Carton	
		1 Urine Analyzer 1 Strip Platform/Wast	e Trav	2 Fuses (2.0A) 1 Power Cord	51.0 cm x 42.0 cm x 3	3.5 cm; 7 kg	1 22	
U500 Urine Analyzer	U211-101	2 Printer Paper Roll		1 Instruction Manual	20.1" X 16.5" x 15.	2"; 246.9 oz	1	
1 Urine Analyzer 2 Fuses (2.0A)		55.0 cm x 55.0 cm x 5	55.0cm; 9.2 kg					
U500 Urine Analyzer with Barcode Reader	U211-111√	1 Strip Platform/Wast 2 Printer Paper Roll 1 Barcode Reader (I	s	1 Power Cord 1 Serial Splitter Cable (RS232C) 1 Instruction Manual	21.7" x 21.7" x 21.7"; 324.5 oz			
Barcode Reader	U221-111à	1 Barcode Reader (I	RS232C)	1 Serial Splitter Cable (RS232C)	23.6 cm x10.8 cm x 7.8 cm; 0. 482 kg 9.3" x 4.3" x 3.1"; 17.0 oz	63.0 cm x 37.0 cm x 30.0 cm; 12 kg 24.8" x 14.6" x 11.8"; 423.3 oz	22	
Printer Paper Rolls		4 Printer Paper Rolls	Thermal F	Paper (0.06 m x 20 m): 200 results/roll	12.0 cm x 12.0 cm x 6.5 cm; 0.360 kg 4.7" x 4.7" x 2.6"; 12.7oz	63.0 cm x 37.0 cm x 30.0 cm; 19.4 kg 24.8" x 14.6" x 11.8"; 684.3 oz	50	
Finiter raper Kolls	U121-101	4 Finter Paper Rolls	Sticker Paper (0.06 m x 9 m): 100 resu		12.0 cm x 12.0 cm x 6.5 cm; 0.40 kg 4.7" x 4.7" x 2.6"; 14.10z	63.0 cm x 37.0 cm x 30.0 cm; 21.4 kg 24.8" x 14.6" x 11.8"; 684.3 oz; 754.9 oz		
U500 Data Transfer Kit	U221-131√	1 Data Transfer Cable	e (RS232C)	1 Package Insert	16.0 cm x 13.0 cm x 3.5 cm; 0.147kg 6.3" x 5.1" x 1.4"; 5.2 oz	25.0 cm x 21.0 cm x 15.0 cm; 1.36 kg 9.8" x 8.3" x 5.9"; 48.0 oz	8	

We also offer other rapid diagnostic and medical products:

Blood Glucose Monitoring Systems, Immunoassay EIA/ELISA and more.

✓ CE Marked for sale in the European Community



ACON Laboratories, Inc., 10125 Mesa Rim Road, San Diego, CA 92121, U.S.A. • Tel: 1-858-875-8000 • Fax: 1-858-200-0729 • E-mail: info@aconlabs.com Please visit our website for details: www.aconlabs.com

Mission® Urine Controls



Global Diagnostics for Local Markets™

Mission[®] Urine Controls

Reliable

- Use with Mission" and Mission" Expert Urinalysis Reagent Strips and Urine Analyzers for optimum quality control
- Validate urinalysis results and prevent procedure errors
- Control Level 1 provides negative results for LEU, NIT, URO, PRO, pH, BLO, SG, KET, BIL, GLU, ASC, ALB^{treat} and CRE'
- Control Level 2 provides positive results for LEU, NIT, URO, PRO, pH, BLO, SG, KET, BIL, GLU, ALB^{hear} and CRE^{hear} with negative results for ASC

Quick and Convenient Testing

- Ensures accurate results for all parameters
- Obtain quick results in any setting Competitively priced

Two Types of Urine Controls Available

- Liquid Urine Control Ready-to-use without dissolving in distilled water
- 24 months shelf life for unopened controls at 2-8°C
- Two Packaging Options
 - Dropper Tip Bottles-Current packaging now available in separate positive and negative levels!
 Dropper tip bottles provide efficient use of the control solution
 - · Easily drop the control solution onto each reagent pad using the dropper tip bottle
 - Control can be used up to 40 times within 30 days at room temperature
 - Diptube-New packaging available in separate positive and negative levels!
 Diptube packaging allows for quick testing similar to using a urine specimen
 Simply dip the strip into the control solution and read results

 - · Control can be used up to 20 times within 30 days at room temperature
- **Dry Strip Urine Control**
- Portable for use anywhere with no refrigeration required Dissolve the dry strip urine control in distilled water, dip urine strip in the control solution, then compare to color chart
- Each control solution can be used for up to 12 tests at 2-30 °C within 8 hours for all parameters
- 24 months shelf life at 2-30°C for unopened controls



Specifications

Features		Specifications						
Product Name		Liquid Urine Control	Liquid Diptube Urine Control	Dry Strip Urine Control				
Test Parameters			LEU, NIT, URO, PRO, pH, BLO, SG, KET, BIL, GLU, ASC, ALB, CRE (13)					
Solution Detection	ection Level 1 Negative: LEU, NIT, URO, PRO, pH, BLO, SG, KET, BIL, GLU, ASC, ALB, CRE							
Levels	Level 2	Positive: LEU, NIT, URO, PRO, pH, BLO, SG, KET, BIL, GLU, ALB and CRE, Negative ASC						
Compatible Urine S	trips		Mission [®] Urinalysis Reagent Strips, Mission [®] Exper	rips, Mission® Expert Urinalysis Reagent Strips				
Reading Time/Stabi	eading Time/Stability Refer to insert		Refer to insert	Refer to insert				
Storage Temperatur	rage Temperature 2-8°C		2-8°C	2-30°C				
Unopened Control S	Shelf Life	24 months	24 months	24 months				
Opened Control Stability 30 days at 15-30°C or until the expiration date at 2-8°C			30 days at 15-30°C or until the expiration date at 2-8°C	2-30°C: 3 months for Dry Strip; 8 hours for Control Solution for all parameters				
Maximum Tests per	Unit	20 or 40 tests/bottle	20 tests/diptube	12 tests/control solution of 1 dry strip				

Ordering Information

Product Name	Catalog No.	Components	Kit Box Dimensions (LxWxH) & Weight	Carton Dimensions (LxWxH) & Weight	# Kits/Carton
		Level 1: 3 x 10 mL /bottle; Level 2: 3 x 10 mL/bottle	85 mm x 55 mm x 60 mm; 107 g	400 mm x 270 mm x 345 mm; 5.2 kg	198
		Level 1: 3 x 5 mL/bottle; Level 2: 3 x 5 mL/bottle	85 mm x 55 mm x 60 mm; 75 g	400 mm x 270 mm x 345 mm; 4.2 kg	198
	U021-011: Combo	Level 1: 1 x 10 mL/bottle; Level 2: 1 x 10 mL/bottle	55 mm x 28 mm x 60 mm; 41 g	400 mm x 270 mm x 345 mm; 6.6 kg	228
/+		Level 1: 1 x 5 mL/bottle; Level 2: 1 x 5 mL/bottle	55 mm x 28 mm x 60 mm; 31 g	400 mm x 270 mm x 345 mm; 5.5 kg	228
Liquid Urine Control √T		6 x 10 mL/bottle	85 mm x 55 mm x 60 mm; 107 g	400 mm x 270 mm x 345 mm; 5.2 kg	198
	U021-021: Level 1;	6 x 5 mL/bottle	85 mm x 55 mm x 60 mm; 75 g	400 mm x 270 mm x 345 mm; 4.2 kg	198
	U021-031: Level 2	2 x 10 mL/bottle	55 mm x 28 mm x 60 mm; 41 g	400 mm x 270 mm x 345 mm; 6.6 kg	228
		2 x 5 mL/bottle	55 mm x 28 mm x 60 mm; 31 g	400 mm x 270 mm x 345 mm; 5.5 kg	228
		Level 1: 2 x 12 mL/diptube; Level 2: 2 x 12 mL/diptube	130 mm x 55 mm x 55 mm; 101 g	385 mm x 255 mm x 320 mm; 4.7 kg	30
Liquid Diptube	U021-071: Combo	Level 1: 1 x 12 mL/diptube; Level 2: 1 x 12 mL/diptube	130 mm x 55 mm x 55 mm; 62 g	385 mm x 255 mm x 320 mm; 3.5 kg	30
Liquid Diptube Urine Control V1	U021-081: Level 1;	4 x 12 mL/diptube	130 mm x 55 mm x 55 mm; 101 g	385 mm x 255 mm x 320 mm; 4.7 kg	30
	U021-091: Level 2	2 x 12 mL/diptube	130 mm x 55 mm x 55 mm; 62 g	385 mm x 255 mm x 320 mm; 3.5 kg	30
		Level 1: 1 x 25 strips/canister; Level 2: 1 x 25 strips/canister	100 mm x 51 mm x 110 mm; 126 g	280 mm x 280 mm x 260 mm; 3.6 kg	24
Dry Strip Urine Control à	U021-041: Combo	Level 1: 1 x 10 strips/canister; Level 2: 1 x 10 strips/canister	100 mm x 51 mm x 110 mm; 106 g	280 mm x 280 mm x 260 mm; 3.1 kg	24
	U021-051: Level 1;	2 x 25 strips/canister	100 mm x 51 mm x 110 mm; 126 g	280 mm x 280 mm x 260 mm; 3.6 kg	24
	U021-061: Level 2	2 x 10 strips/canister	100 mm x 51 mm x 110 mm; 106 g	280 mm x 280 mm x 260 mm; 3.1 kg	24

✓ CE Marked for sale in the European Community **(**€ † FDA 510(k) Cleared

We also offer other rapid diagnostic and medical products for:

Blood Glucose Monitoring Systems, Clinical Chemistry including Urinalysis, Immunoassay EIA/ELISA and more. Contact us for worldwide distribution and custom manufacturing (OEM) opportunities

