



# PRISTA® UHPD 10W-40

## HEAVY DUTY DIESEL ENGINE OILS

### Description and Application

**Prista® UHPD 10W-40** is top quality synthetic diesel engine oil designated for the lubrication of heavy-duty diesel engines designed according to the latest international diesel exhaust emission standards Euro IV, Euro V and Euro VI and equipped with the relevant diesel particulate filters.

**Prista® UHPD 10W-40** is recommended for use in the latest makes and models of turbocharged diesel engines, operated at severe loads and conditions in heavy-duty trucks and buses whose manufacturer recommend extended oil drain intervals. For the optimum oil drain interval the users should follow the applicable manufacturers' recommendations for the relevant performance levels below.

### Benefits

- the best choice for Euro IV, Euro V and Euro VI heavy duty diesel engines
- engine cleanliness at significantly extended oil drain intervals
- extremely minimized hazardous exhaust emissions
- protection against cylinder bore polishing and cylinder liner wear
- problem-free engine start-ups at very low ambient temperatures

### Specifications

	SAE 10W-40
ACEA	E6/E7/E8/E9/E11
API	CK-4
Daimler Trucks	DTFR 15C110, DTFR 15C100
MB-old specification	228.51/228.31
MAN	M3775
Volvo	VDS-4.5
Renault Trucks	RLD-3
MTU	Type 3.1
Deutz	DQC IV-18LA
Mack	EOS-4.5
Cummins	CES 20086
Caterpillar	ECF-3
JASO	DH-2
Detroit Diesel	DDC 93K222

### Typical Characteristics

Parameter	Test Method	Typical Value
Density at 20°C, g/ml	EN ISO 3675	0.855
Kinematic Viscosity at 100°C, mm <sup>2</sup> /s	EN ISO 3104	14.6
Kinematic Viscosity at 40°C, mm <sup>2</sup> /s	EN ISO 3104	96.3
Viscosity Index	ISO 2909	158
Flash point COC, °C	EN ISO 2592	240
Pour point, °C	ISO 3016	-39
TBN (HClO <sub>4</sub> ), mg KOH/g	ASTM D 2896	10.4
Sulfated Ash, %	EN ISO 3987	1.0

Important note: typical data values do not constitute a specification but are an indication based on current production and can be affected by allowable production tolerances. The right to make modifications is reserved.



## Health, Safety and Handling

Based on current available information, this product is not expected to produce adverse effects on health when used for the intended application.

For more information about product MSDS, terms and conditions for storage and shelf life please visit: [www.prista-oil.com](http://www.prista-oil.com)

# Delo 400 XSP-SD SAE 5W-30

## High performance synthetic heavy-duty diesel engine oil

### Product description

Delo® 400 XSP-SD SAE 5W-30 is a high performance synthetic heavy duty engine oil designed for fuel economy and meets the performance requirements of a wide range of naturally aspirated and turbocharged diesel engines in on-highway, off-highway and construction service.

Delo 400 XSP-SD SAE 5W-30 is based on ISOSYN® technology with low SAPS performance and dispersant, detergent, oxidation, anti-wear, corrosion, viscosity improver and de-foaming additives and meets Euro VI emissions requirements, while offering extended drain intervals.

### Customer benefits

- Designed for improved fuel economy performance while helping maintain robust component wear protection and engine service life
- Formulated for good performance in a wide range of engines, and helps reduce inventories, costs, and the risk of misapplication
- Low viscosity synthetic base oils offer rapid circulation in cold and sub-zero engine start-ups
- Extended drain formulation combines synthetic base stocks and additives to promote wear, oxidation, sludge and thickening control
- Offers reliable Diesel Particulate Filter (DPF) clogging protection and helps reduce cleaning while improving DPF service life



### Product highlights

- **Designed for fuel economy and engine service life**
- **Helps reduce inventories and misapplication**
- **Offers protection in sub-zero engine starts**
- **Extended drain formulation**
- **Promotes DPF protection and service life**

**Selected specification standards include:**

ACEA	API
Caterpillar	Cummins
DAF	Daimler Trucks
Detroit Diesel	Deutz
Ford	JASO
Mack	Mercedes Benz
MTU	Renault Trucks
Scania	Volvo

## Applications

- Delo 400 XSP-SD SAE 5W-30 is a high performance engine oil recommended for four-stroke naturally aspirated and turbocharged diesel engines.
- Delo 400 XSP-SD SAE 5W-30 is recommended for diesel engines meeting Euro I - Euro V and the latest Euro VI emissions requirements where allowed by the OEMs and is suitable for use in engines with global after treatment systems.
- Delo 400 XSP-SD SAE 5W-30 is recommended for use in older engines as well as today's most modern low emission designs. It is formulated for high performance with many fuels including low sulphur and ultra-low sulphur diesel fuels, and many biofuel formulations.

## Approvals, performance and recommendations

### Approvals

- |                  |  |
|------------------|--|
| • Cummins        | CES 20086  |
| • Daimler Truck  | DTFR 15C110<br>(previously MB 228.51)<br><br>DTFR 15C120<br>(previously MB 228.52) |
| • Detroit Diesel | DFS 93K222   |
| • Deutz          | DQC IV-18 LA<br>(approval request submitted)<br>DQC TTCD°                          |
| • Mack           | EOS-4.5  |
| • MAN            | M3677, M3691   |
| • MTU            | Oil Category 3.1   |
| • Renault Trucks | RLD-3  |
| • Scania         | LDF-4  |
| • Volvo          | VDS-4.5  |

### Performance

- |                  |   |
|------------------|---|
| • ACEA           | E6, E7, E9  |
| • API            | CK-4, CJ-4, CI-4 Plus, CI-4, CH-4<br>SN, SM, SL, SJ |
| • JASO           | DH-2  |
| • Caterpillar    | ECF-3   |
| • DAF            | Extended drain (Euro IV to VI)**                    |
| • Ford           | WSS-M2C213-A1                                       |
| • Mack           | EO-O Premium Plus, EO-N,<br>EO-M Plus, EO-M         |
| • MAN            | M3477**, M3271-1**                                  |
| • Mercedes Benz  | MB 228.31   |
| • Renault Trucks | RLD-2, RLD, RXD, RGD                                |
| • Volvo          | VDS-4, VDS-3  |
| • Scania         | Low Ash   |

### Suitable for use

Delo 400 XSP-SD SAE 5W-30 is suitable for use in applications requiring:

- |                  |                   |
|------------------|-------------------|
| • Iveco          | 18-1804 TLS E6*** |
| • Liebherr       | LH-00-ENG LA      |
| • Renault Trucks | RD-2, RD          |
| • Volvo          | VDS-2, VDS        |

° Product approved for DQC IV-18 LA are also approved for use in Deutz TTCD engines

\* Can be used in Euro IV & Euro V MX engines and in Euro VI MX & PX engines for DAF

\*\* these product claims are obsolete by MAN and no approvals can be obtained, applications that require these claims can be fulfilled by MAN M3677 approved products

\*\*\* check equipment/vehicle manual to ensure that the drain interval of oil is aligned with S content in the fuel used in the engine

Typical test data		
Test	Test Methods	Results
Viscosity Grade		5W-30
Shelf Life: 60 months from date of filling indicated on the product label		
Density at 15°C, kg/l	ASTM D4052	0.858
Kinematic viscosity at 40°C, mm <sup>2</sup> /s	ASTM D445	73
Kinematic viscosity at 100°C, mm <sup>2</sup> /s	ASTM D445	12.2
Viscosity Index	ASTM D2270	164
Pour point, °C	ASTM D97	-42
Flash point COC, °C	ASTM D92	231
Total Base Number, mg KOH/g	ASTM D2896	10
Sulphated Ash, %wt	ASTM D874	0.9

The typical test data set out above does not constitute a specification. It is indicative only and can be affected by allowable production tolerances. Chevron may modify this test data. Modified data will supersede all previous data, so please ensure you refer to the latest version of this Product Data Sheet (PDS).

**Disclaimer:** Data provided in this Product Data Sheet (PDS) is based on standard tests under laboratory conditions and is indicative only. This product should not be used for any purpose other than those expressly set out in this PDS. The user has sole responsibility for verifying that this product is suitable for the user's intended application. Neither Chevron nor its subsidiaries (i) make any warranty or representation as to the accuracy or completeness of this PDS; and/or (ii) accept liability for any loss or damage suffered as a result of the use of this product other than in accordance with the terms of this PDS.

When disposing of used product, take care to protect the environment and follow local legislation.

Safety Data Sheets (SDS's) are available for all Chevron products. If you require a SDS or any further information regarding a Chevron product, please contact your local sales office or see [www.texacolubricants.com](http://www.texacolubricants.com).

Always confirm that the product selected is consistent with the original equipment manufacturer's recommendation for the equipment operating conditions and customer's maintenance practices.

A Chevron company product



MAN Truck & Bus SE Postfach 44 02 58 90207 Nürnberg

Abt/Kürzel

E-Mail

Nürnberg

BST-TEAM

bstinfo@man.eu

10.07.2024

Subject: **Prolongation letter TUC 1802/21**

MAN standard: **M 3677**

**M 3691**

Start of approval: 05.07.2021

End of approval: 04.07.2027

Validity:

Dear Sir or Madam,

we are pleased to inform you that the following product has been prolonged under MAN TUC 1802/21 .

**Delo 400 XSP-SD 5W-30**

**SAE 5W-30**

This prolongation is only available for the unchanged formulation and in combination with the original approval letter. The approval will automatically expire at the point of time indicated above. A prolongation has to be applied within the approval period.

Yours faithfully,

MAN Truck & Bus SE

This letter was created electronically without signature.

MAN/DCS2000 BSD\_SF\_PROLONG\_Vers. 2.0

Vorsitzender des Aufsichtsrats: Christian Levin  
Vorstand: Alexander Vlaskamp (Vorsitzender)  
Murat Aksel · Hubert Altschäffl · Friedrich-W. Baumann  
Michael Kobriger · Inka Koljonen · Dr. Frederik Zohm

Sitz der Gesellschaft: München

Registergericht: Amtsgericht München, HRB 247520  
USt-IdNr. DE811125281

MAN Truck & Bus SE  
Postfach 44 02 58 90207 Nürnberg  
Vogelweiherstraße 33 90441 Nürnberg

Telefon +49. 911. 420-0 oder Durchwahl  
Telefax +49. 911. 446522

Commerzbank Aktiengesellschaft, Dachau BLZ 700 400 41 Konto 1450600  
IBAN: DE33 7004 0041 0145 0600 00 BIC: COBADEFFXXX  
Stadtsparkasse München BLZ 701 500 00 Konto 89104400  
IBAN: DE36 7015 0000 0089 1044 00 BIC: SSKMDEMM

Ein Unternehmen der MAN Gruppe - [www.mantruckandbus.com](http://www.mantruckandbus.com)



# PRISTA® SHPD LS 15W-40

Old name: Prista Super SHPD

## ULTRA HIGH-PERFORMANCE DIESEL ENGINE OIL

### Description and Application

**Prista® SHPD LS 15W-40** is a new category engine oil of medium SAPS level intended for moderately extended oil drain intervals. This oil is based on API Group II base oils as per the new motor oil tendencies and complies with the requirements imposed by the heavy-duty diesel engines running on bio-diesel fuel in accordance with EU regulations. This lubricant is designated for the lubrication of the most modern heavy duty and heavy-loaded diesel engines used in international haulage and equipped with the modern aftertreatment systems (EGR or SCR) for hazardous NOx reduction and/or diesel particulate filters (DPF) combined with low-sulfur diesel fuels.

**Prista® SHPD LS 15W-40** multigrade engine oil is recommended for highly rated diesel engines complying with Euro IV, Euro V & Euro VI low emission standards and operated under severe loads and conditions.

### Benefits

- Protection against cylinder bore polishing and wear
- High engine cleanliness with considerably extended drain intervals up to 60 000 km
- Problem-free operation even in case of a heavily sooted oil
- High temperature thickening protection
- Bearing corrosion protection
- Foam control
- Easy engine start-ups even at very low sub-zero temperatures

### Specifications

	SAE 15W-40
ACEA	E6/E7/E9/E11
API	CK-4
Daimler Truck	DTFR 15C100
MB-old specification	228.31
MAN	M 3775
MTU	Type 3.1
Volvo	VDS-4.5
Renault Trucks	RLD-3
Deutz	DQC III-18-LA
Caterpillar	ECF-3
Cummins	CES 20086
Mack	EOS-4.5
Detroit Diesel	93K222
JASO	DH-2

### Typical Characteristics

Parameter	Test Method	Typical Value
Density at 20°C, g/ml	EN ISO 3675	0.882
Kinematic Viscosity at 100°C, mm <sup>2</sup> /s	EN ISO 3104	14.8
Kinematic Viscosity at 40°C, mm <sup>2</sup> /s	EN ISO 3104	109
Viscosity Index	ISO 2909	140
Flash point COC, °C	EN ISO 2592	234
Pour point, °C	ISO 3016	-33
TBN (HClO <sub>4</sub> ), mg KOH/g	ASTM D 2896	9.5
Sulfated Ash, %	EN ISO 3987	1.0

Important note: typical data values do not constitute a specification but are an indication based on current production and can be affected by allowable production tolerances. The right to make modifications is reserved.



## Health, Safety and Handling

Based on current available information, this product is not expected to produce adverse effects on health when used for the intended application. For more information about product MSDS, terms and conditions for storage and shelf life please visit: [www.prista-oil.com](http://www.prista-oil.com)