

Sphygmomanometer LD-60









Professional Sphygmomanometer With Phonendoscope.

Features:

- Metal Aneroid Manometer.
- Stethoscope Attached to the Cuff.
- Nylon Cuff for Upper Arm Circumference 33-46 cm.
- Check Valve Screen Filter from Clogging Up with Dust.
- Metal Needle Air Valve.
- The cuff has size marks and a metal fixing ring for convenient use.

Features	
Model	LD-60
Stethoscope included	YES
Stethoscope Attached to the Cuff	YES
Manometer material	Metal
Manometer dial diameter	45 mm
Adaptable for left or right hand	No
Valve type	Metal Needle Air Valve
Measuring Range (pressure)	0-300 mmHg
BLOWER WITH NON-RETURN VALVE	
Check valve filter	YES
CUFF	
Cuff model	LD Cuff N2LR
Cuff size	33-46 cm
With a Metal fixing Ring	YES
Number of tubes	2
Cuff material	Nylon
Cuff case material	TPU
MEASUREMENT	
Measuring Range (pressure)	0-300 mmHg
Measuring Accuracy (cuff pressure)	+/- 3 mmHg
Operating Conditions (temperature)	10 °C to 40 °C
Operating Conditions (relative humidity)	85% and below
OTHER	
Weight	390 g
Dimensions	115 x 185 x 75 mm
Aperoid Gauge Mylon D-Ring Cuff Rulh with Valve S	tethoscope Attached to the Cuff Carrying

Aneroid Gauge, Nylon D-Ring Cuff, Bulb with Valve, Stethoscope Attached to the Cuff, Carrying Case, Operating Instructions, Warranty Card.