



ELEC TECHNOLOGIES GROUP LIMITED

Add: NO. 11, Lianfeng Rd., Dali, Qingxi, Dongguan, Guangdong, China 523648

www.electechnologies.com

Tel: 86-769-87731088/87738088

Model #	UPS650PE	
Capacity	650VA/390W	
Front panel		
Rear panel		
AVR	3 steps of AVR, CPU controlled	
INPUT		
Input voltage range	<u>110V</u> : 85~150Vac±5Vac	
	<u>220V</u> : 145~290Vac±5Vac	
Input frequency range	50Hz / 60Hz (Auto sensing)	
OUTPUT		
Output voltage range	<u>110V</u> : 102~132Vac	
	<u>220V</u> : 200~255Vac	
Output frequency (DC mode)	50±0.5Hz / 60±0.5Hz	
Wave form	PWM (DC Mode)	
Transfer time	Typical 2~6ms, Max.10ms.	
BATTERY		
QTY & capacity of battery	1 pc*12V7Ah	
Charging period	4~6 hours recover to 90% capacity	
PROTECTION & FUNCTION		

PROTECTION	1. Battery low voltage protection 2. Overload protection 3. Short circuit protection
FUNCTION	1. Auto re-starts when AC recovers 2. Silence setup 3. Automatic charging (offline charging)
MANAGEMENT	
RJ45/11 & USB	Optional
PHYSICAL	
Unit dimension (mm)	314*97*143
Gross weight (1pc, kg)	4,9
Net weight (1pc, kg)	4,6

