


CUBE 30 TOUCH

SED-RATE SYSTEM

**30 ESR RESULTS IN 25 MIN WITH MODIFIED
WESTERGREN METHOD**




DIESSE



FEATURES

- BATCH / CONTINUOUS WORKING MODE
- TOUCH SCREEN INTERFACE
- REDUCED SIZE
- NO SAMPLE CONSUMPTION
- NO WASTE FLUIDS
- SAFETY

Analyze different and non-dedicated tubes



Environmentally friendly

No production of waste materials, without extra-cost for liquid waste disposal.

Test performed on edta/cbc samples

The test is performed on blood samples collected in the same top lavender tubes used for full blood count.

USER FRIENDLY

- Up to 30 samples simultaneously
- Internal bar-code reader
- Ease of use
- Reduction of turn-around time Standardization
- Internal mixing of samples by complete inversion of the tubes
- 10.1 inches colour touch screen
- Innovative graphic interface
- Fast Turn-Around Time (TAT)
- 30 results in less than 25 minutes



TECHNICAL CHARACTERISTICS

POWER SUPPLY
110 to 230 VAC (50 – 60Hz)

MIXING OF SAMPLES
in compliance with CLSI and ICSH requirements

ABSORBED ELECTRICAL POWER
max 100 W

DIMENSIONS
450 x 390 x 297 mm (w x h x d)

DISPLAY
10,1" wide vertical type

WEIGHT
14 Kg

NOISE LEVEL
< 80 Db

WORKING TEMPERATURE
+ 15° to + 35°C

BAR-CODE READER
Automatic internal

RELATIVE HUMIDITY
from 20% to 80% without condensation



INSTRUMENTS AND ACCESSORIES

CUBE 30 TOUCH	1	Ref. 10395
TEST DEVICE NEXT 500	500 tests	Ref. 10293
TEST DEVICE NEXT 1K	1000 tests	Ref. 10294
TEST DEVICE NEXT 5K	5000 tests	Ref. 10296
TEST DEVICE NEXT 10K	10.000 tests	Ref. 10297
ESR CONTROL CUBE	4 x 9 ml	Ref. 10435
ESR CONTROL CUBE	2 x 9 ml	Ref. 10436
EXTERNAL BAR-CODE READER	1	Ref. P20550510
THERMAL PAPER	1	Ref. 10403

DIESSE
DIESSE

www.diesse.it