

1200VA UPS with AVR, advanced UPS-PC-1202AP

ULTIMATE DEFENCE

- Provides backup power prevents data loss
- Protects your sensitive and valuable equipment
- Compact and reliable ideal for home and small office use



Features

- Uninterruptable 1200 VA power supply for PC's
- Automatic output voltage regulation (AVR)
- USB interface
- LED status indication
- Short circuit protection
- Surge, spike and lightning protection
- Audible and visual alarms
- Overcharge and overdischarge protection
- Fax/Modem/Telephone protection socket
- Including Practical UPS Management software

Packaging

Q'ty in crtn, pcs	2
Crtn volume, CUM	0.0465
Crtn weight, kgs	22.54
Individual package size LxWxH:	390x185x295 mm
Carton size LxWxH:	400x375x310 mm
Country of origin	CN
Barcode	8716309047814
Customs code	8504408490

Package contents

UPS
Power cord
USB cable
Software CD
Spare fuse

Specifications

UPS type: line interactive
Input: AC 162 295 V, 50 Hz / 60 Hz $\pm$ 10 %
Output: AC 188 254 V, 50 Hz / 60 Hz $\pm$ 0.5 % (on battery)
Waveform: sine wave (AC mains), simulated sine wave (battery)

Temperature compensation: -20mV/1 °C (per cell)
Switching time: no more than 5 ms
Backup time: 2...20 mins (depends on the load)
Battery: sealed lead-acid 12V/7Ah x 2pcs
Charge time: up to 12 hours
Sockets: 1x input (C14), 4x output (C13 / Shuko optional); 2x telephone RJ11 connectors; 1x USB-BF connector

System requirements

Software is compatible with Windows 7, Windows 2008 server, Windows 8/10

In order to work correctly, the connected load should be at least 5% of the maximum capacity of the UPS. For example, a 700 W UPS needs at least a connected load of 35 W to work.

Certificates

