

# PRODUCT APPROVED SHEET

## 产品承认书

客户名称 (CUSTOMER) : \_\_\_\_\_  
 产品名称 (PRODUCT) : UPS  
 产品型号 (PART NO) : U-650VA  
 版次 (VERSION NO) : 1.0  
 日期 (DATE) : 2019.04.02

批准 (印章)  
 Approval (stamp): \_\_\_\_\_



会签(sign)		
销售(Sales Department)	品质(Quality Dept)	总经办(General Deparment)
<i>Junon Zeng</i>	<i>曾行</i>	<i>伍梓</i>

## AMENDMENT RECORDS

Revision	Description	Date	Prepare	Approval
A	New Release	2019-04-02		

### CONFIDENTIALITY

TOP CONFIDENTIAL     
  CONFIDENTIAL     
  INTERNAL ONLY

### DISTRIBUTION

MFG 产     
  QA     
  R&D     
  FNC  
 PMC     
  PME     
  PUR     
  HR&A  
 SALES     
  -OTHER



DOC No.	
Rev	A
Page	3 / 5

1. Product Brief Image



## 2.Specifications

No.	Item	Specifications
1	Built-in Battery Capacity	12V/7.5Ah
2	Type	Line-interactive
3	Input Voltage Range	160 - 280 V (AVR)
4	Input Frequency Range	65/45Hz
5	Output Wave Form	PWM
6	Output Voltage Range(AC port)	220 ± 10 %
7	Protection against short circuit, electromagnetic and radio interference	Yes
8	Output Frequency Range	60/50Hz
9	Capacity, W	400W
10	Power Socket Type Schuko	4 Surge Protector + 4 Battery backup
11	Conection to PC via USB	Thru USB interface it will be possible to check the status of the UPS by software for Windows (software included). In case of voltage loss, the source can finish the system correctly, then it can be disconnected, using the software. The software allows to set the PC disconnect time.
12	Additional ports	Min. 2x ports data line protection (RJ45)
13	Cable lenth	min. 1,5 m.
14	Timp de comutare tipic	≤ 10 ms
15	Backup Time	On half load – 8 minutes
16	Over Temperature Protection (IC control)	Product would cut off the output and go into stop work mode when the inside enclosure temperature is over below settings: Temperature of IC: 150°C * Stop Work Mode: Output is cut off.
17	Operation Condition	Charge Temperature: 0°C~45°C Discharge Temperature: 0°C~60°C



DOC No.	
Rev	A
Page	5 / 5

18	Standard Storage Condition	Temperature: 25°C±5°C Humidity: 65±20% RH
19	Unit Dimensions	280*245*130mm
20	Net Weight	5.6KG
21	Noise Level	Less Than 40dB

