




## **FY0508** Heparin Cap

Material: PC Sterilization: EO Individal Hard Blister Packing, 100pcs/Box, 5000pcs/ctn



Material: ABS Sterilization : EO Color: Red, White, Blue, etc. Individal Hard Blister Packing, 100pcs/Box

# **FY0620** Medical Connector



#### FY062001 **Needle Free Connector**

Features:

- Transparent housing material: Polycarbonate or Copolyester.
   Metal-free & MRI-compatible.
- 3. Latex-free. 4. Multiple insertion at least 100 times/day.
- 5. Priming Volume: 0.09ml.
- 6. Perfect flowing rate: 350 ml/min under one meter water pressure

## FY062002

### **Y-port Valves**

Material: Polycarbonate or Copolyester Size: ID 4.01mm, 3.6mm

FY062003 **Tube End Valves** 

Material: Polycarbonate or Copolyester Size: ID 2.0mm, 2.5mm, 2.8mm, 3.7mm, 4.1mm





# FY0511 **Micro-flow Regulator**

Flow range: 5ml/h-250ml/h Materials: Regulator: ABS Tube: PVC Other accessories: PC & ABS Extension Tube Length: 45cm is common, others are also available. Sterilization: EO Packing Details: Poly-bag per pcs, 200pcs/inner box, 20boxes/carton





# FY062004 **Positive Pressure Needle Free Connector**

#### Features:

1.Patent design of positive pressure avoids back flow of blood during removal of syringe. This will help to prevent blood clot at the catheter tip inside the blood vessel. 2. The housing is impregnated with PC Ag+ which helps to lower

infection.

Protruding design of the stalk at the injection port follows infection control protocol.
 High quality spring ensures multiple insertion at the injection site without leaking.

5. Two sealing rings at the upper and lower end of the stalk keeps the connector out air, fluid and outside substance.
6. The straight flow of fluid path creates less turbulence and complies with proper transfusion protocol.
7. The holding capacity of remaining fluid is less than 0.06ml.

# FY050701 **Three Way Stopcock**

Parts: Body(PC), Plas(PE), Screw Cap(ABS) Individal Hard Blister Packing, 50pcs/Box, 1000pcs/ctn Sterilization: EO

