

### Matricea de conformitate

#### **1. Baterii 12v/5 Ah pentru UPS Eaton9SX 5000, APC SMART UPS 2200VA, UPS Eaton 9155 (5kVA)**

<b>Descrierea cerinta:</b>	<b>Parametrii solicitati</b>	<b>Parametrii Furnizati Datasheet (CSB_HR1227W.pdf)</b>
		Model: <b>Acumulator CSB-Hitachi 12V/5Ah (HR1227W 12V/5Ah)</b>
Tensiunea	12V (6 celule in bloc)	12V (6 cells per unit)
Capacitatea nominala	Min. 27W @15 min, descarcare pina la tensiunea de 1.67V pe celula	27W @15min-rate to 1.67V per cell @25°C (77°F)
Greutatea	Min. 1.97 Kg	Approx. 1.97 Kg
Curentul maximal de descarcare	Min. 130A (5sec)	100/130A (5sec)
Curentul de scurt circuit	Min. 424A	424A
Curenul maxim de incarcare	2.7A	2.7A
Tipul conectorului	F2	F1/F2 -Faston Tab187/250
Dimensiuni acumulator	Lungimea 90.0mm; Latimea 70.0mm Inaltimea (W) - 106.1mm	Lungime (L) 90.0±1.0 mm Latime (W)70.0±1.0 mm Inaltime (H) 106.1±1.5 mm
<b>Cantitatea</b>	<b>1716 buc.</b>	

#### **2. Baterii 12v/7 Ah pentru UPS Eaton 9155 (10kVA UPS)**

<b>Descrierea cerinta:</b>	<b>Parametrii solicitati</b>	<b>Parametrii Furnizati Datasheet (GP 1272 F2.pdf)</b>
		Model: <b>Acumulator CSB-Hitachi 12V/7Ah (CSB-Hitachi GP1272)</b>
Tensiunea nominala	12V (6 celule in bloc)	12V (6 cells per unit)
Capacitatea nominala	Min. 8Ah @20 Ore, descarcare pina la	7.2Ah @20hr-rate to 1.75V per cell @25°C

Greutatea	Min. 2.4 Kg	Approx. 2.40 Kg
Curentul maximal de descarcare	Min. 130A (5sec)	100/130A (5sec)
Curentul de scurt circuit	Min. 275A	276A
Curenul maxim de incarcare	2.2A	2.16A
Tipul conectorului	F2	F1/F2 terminal -Faston Tab 187/250
Dimensiuni acumulator	Lungimea 150.9mm; Latimea 64.8mm Inaltimea (W) - 98.6mm	Lungime (L) 150.9±2.0 mm Latime(W) 64.8±1.0 mm Inaltime (H) 98.6±1.0 mm
<b>Cantitatea</b>	<b>96 buc.</b>	

### 3. Baterii 12v/9 Ah. Pentru UPS Eaton 9130

Descrierea cerinta:	Parametrii solicitati	Parametrii Furnizati Datasheet (HR 1234.pdf)
		Model: <b>Acumulator CSB-Hitachi 12V/9Ah (CSB-Hitachi HR1234W)</b>
Tensiunea nominala	12V (6 celule in bloc)	12V (6 cells per unit)
Capacitatea nominala	Min. 34W @15min, descarcare pina la tensiunea de 1.67V pe celula	34W @15min-rate to 1.67V per cell @25°C
Greutatea	Min. 2.5 Kg	Approx. 2.50 Kg
Curentul maximal de	Min. 130A (5sec)	130A (5sec)
Curentul de scurt circuit	Min. 349A	349A
Curenul maxim de incarcare	3.4A	3.4A
Tipul conectorului	F2	F2 -Faston Tab250
Dimensiuni acumulator	Lungimea 150.9mm; Latimea 64.8mm Inaltimea (W) - 98.6mm	Lungime (L) 150.9±2.0 mm Latime (W) 64.8±1.0 mm Inaltime (H) 98.6±1.0 mm
<b>Cantitatea</b>	<b>858 buc.</b>	