

ANNEX II + III: TECHNICAL SPECIFICATIONS + TECHNICAL OFFER

Contract title: Supply of <...>

p 1 /...

Publication reference: <insert reference>

Columns 1-2 should be completed by the contracting authority

Columns 3-4 should be completed by the tenderer

Column 5 is reserved for the evaluation committee

Annex III - the contractor's technical offer

The tenderers are requested to complete the template on the next pages:

- Column 2 is completed by the contracting authority shows the required specifications (not to be modified by the tenderer),
- Column 3 is to be filled in by the tenderer and must detail what is offered (for example the words 'compliant' or 'yes' are not sufficient)
- Column 4 allows the tenderer to make comments on its proposed supply and to make eventual references to the documentation

The eventual documentation supplied should clearly indicate (highlight, mark) the models offered and the options included, if any, so that the evaluators can see the exact configuration. Offers that do not permit to identify precisely the models and the specifications may be rejected by the evaluation committee.

The offer must be clear enough to allow the evaluators to make an easy comparison between the requested specifications and the offered specifications.

| 1. Item number | 2. Specifications required | 3. Specifications offered | 4. Notes, remarks, ref to documentation | 5. Evaluation committee's notes |
|-------------------|---|---|--|------------------------------------|
| 1 | <p>TECHNICAL SPECIFICATIONS - TRUCK:</p> <p>Vehicle category: N3GS, in accordance with the regulations on the registration of vehicles and trailers;</p> <p>New and unused vehicle chassis must be manufactured in 2025 or later;</p> <p>The chassis manufacturer must have an official national representative in the Republic of Moldova, capable of ensuring maintenance and warranty for both the vehicle offered and the entire assembly (chassis + superstructure). The warranty period is at least 3 years, and the post-warranty period is at least 7 years;</p> <p>Overall dimensions (L x W x H) of the vehicle:</p> <ul style="list-style-type: none"> - Maximum length: 12,000 mm; - Maximum width: 2,550 mm; - Maximum height (measured from | <p>N3GS, Renault Trucks, Official Dealer in Republic of Moldova.</p> <p>Overall dimensions (L x W x H) of the vehicle:</p> <ul style="list-style-type: none"> 3 Length: 10,200 mm; 4 Width: 2,550 mm; 5 Height (measured from ground level): 3,800 mm, when loading a metal container manufactured according to DIN 30722 standards (which define the hook height and the distances to the anchoring elements on the transport platform subframe), with internal dimensions between | | |

| 1. Item number | 2. Specifications required | 3. Specifications offered | 4. Notes, remarks, ref to documentation | 5. Evaluation committee's notes |
|-------------------|--|--|--|------------------------------------|
| | <p>ground level): maximum 3,800 mm, when loading a metal container manufactured according to DIN 30722 standards (which define the hook height and the distances to the anchoring elements on the transport platform subframe), with internal dimensions between 4,250 and 7,000 mm;</p> <p>Loading capacity of the vehicle, equipped with the hydraulic loading/unloading system with hook: minimum 15,000 kg;</p> <p>Rated motor power: minimum 350 HP (generated exclusively by the internal combustion engine);</p> <p>Estimated engine life cycle: minimum 1,000,000 km;</p> <p>Maximum speed: minimum 100 km/h;</p> <p>Maximum gradient: minimum 30%;</p> <p>When fully equipped, with all supplies and crew on board (fully operational),</p> | <p>4,250 and 7,000 mm;</p> <p>Loading capacity of the vehicle, equipped with the hydraulic loading/unloading system with hook: 16,000 kg;</p> <p>Rated motor power: 490 HP (360kW) (generated exclusively by the internal combustion engine);</p> <p>Estimated engine life cycle: minimum 1,000,000 km;</p> <p>Maximum speed: 110 km/h;</p> <p>Maximum gradient: minimum 30%;</p> <p>When fully equipped, with all supplies and crew on board (fully operational), the vehicle maintain its stability to safely travel on terrain with slopes of at least 25 degrees.</p> <p>The angles of attack, departure angles and ground clearance of the fully operational vehicle must</p> | | |

| 1. Item number | 2. Specifications required | 3. Specifications offered | 4. Notes, remarks, ref to documentation | 5. Evaluation committee's notes |
|-------------------|---|---|--|------------------------------------|
| | <p>the vehicle must maintain its stability to safely travel on terrain with slopes of at least 25 degrees.</p> <p>The angles of attack, departure angles and ground clearance of the fully operational vehicle must allow movement on unpaved roads and rough terrain:</p> <p>Ground clearance: minimum 300 mm;</p> <p>Angle of approach: minimum 25 °;</p> <p>Departure angle: minimum 25 °.</p> <p>The vehicle, equipped with a hydraulic hook loading/unloading system, has an adjustable rear underrun protection device (RUPD);</p> <p>The special vehicle will be delivered and will operate without a tachograph.</p> <p>Engine and auxiliary systems:</p> <p>3.2.1.1. Emission standard: according to EU regulations in force on the date of delivery;</p> | <p>allow movement on unpaved roads and rough terrain:</p> <p>Ground clearance: 331/327 mm;</p> <p>Angle of approach: 25 °;</p> <p>Departure angle: 25 °.</p> <p>The vehicle, equipped with a hydraulic hook loading/unloading system, has an adjustable rear underrun protection device (RUPD);</p> <p>The special vehicle will be delivered and will operate without a tachograph.</p> <p>Engine and auxiliary systems:</p> <p>Emission standard: according to EU regulations in force on the date of delivery;</p> <p>Fuel type: diesel;</p> <p>Fuel tank with a minimum capacity of 315 liters, AdBlue tank with a minimum capacity of 48 liters,</p> | | |

| 1. Item number | 2. Specifications required | 3. Specifications offered | 4. Notes, remarks, ref to documentation | 5. Evaluation committee's notes |
|-------------------|---|--|--|------------------------------------|
| | <p>3.2.1.2. Fuel type: diesel;</p> <p>3.2.1.3. Fuel tank with a minimum capacity of 300 liters, AdBlue tank with a minimum capacity of 25 liters, positioned so as not to affect the ability to travel on rough terrain and protected laterally and below by a metal shield, against damage when traveling on paved or unpaved roads;</p> <p>3.2.1.4. Electric engine preheating system for use during periods of standstill, powered by an external source;</p> <p>3.2.1.5. Oil sump designed for slopes exceeding 30°, protected at the bottom by a metal shield, against damage when driving on paved or unpaved roads;</p> <p>3.2.1.6. Towbars for the maximum load of the fire truck, located at the front and rear of the chassis;</p> <p>3.2.1.7. Equipped with a traction control system (ASR or equivalent).</p> | <p>positioned so as not to affect the ability to travel on rough terrain and protected laterally and below by a metal shield, against damage when traveling on paved or unpaved roads;</p> <p>Electric engine preheating system for use during periods of standstill, powered by an external source;</p> <p>Oil sump designed for slopes exceeding 30°, protected at the bottom by a metal shield, against damage when driving on paved or unpaved roads;</p> <p>1.1. Towbars for the maximum load of the fire truck, located at the front and rear of the chassis; Equipped with a traction control system (ASR or equivalent).</p> <p>Transmission</p> <p>6x6 transmission with differential lock for front, rear and interaxle axle;</p> | | |

| 1. Item number | 2. Specifications required | 3. Specifications offered | 4. Notes, remarks, ref to documentation | 5. Evaluation committee's notes |
|----------------------|--|--|---|--|
| | <p>3.2.2. Transmission:</p> <p>3.2.2.1. 6x6 transmission with differential lock for front, rear and interaxle axle;</p> <p>3.2.2.2. Automatic or automated manual transmission, dedicated to vehicles, with sufficient gear ratios to ensure movement in all driving conditions;</p> <p>3.2.2.3. Front axle suspension with stabilizer bar or pneumatic system, designed to operate both on paved roads and on unpaved or rough terrain;</p> <p>3.2.2.4. Rear axle suspension with stabilizer bar or pneumatic system, designed to operate both on paved roads and on unpaved or rough terrain.</p> <p>3.2.3. Wheel and tire system:</p> <p>3.2.3.1. Tires must be manufactured at least in the year of purchase;</p> <p>3.2.3.2. Mud and snow (M+S) tires mounted on steel rims (including</p> | <p>Automatic or automated manual transmission, dedicated to vehicles, with sufficient gear ratios to ensure movement in all driving conditions;</p> <p>Front axle suspension with stabilizer bar or pneumatic system, designed to operate both on paved roads and on unpaved or rough terrain;</p> <p>Rear axle suspension with stabilizer bar or pneumatic system, designed to operate both on paved roads and on unpaved or rough terrain.</p> <p>Wheel and tire system:</p> <p>Tires will be manufactured at least in the year of purchase;</p> <p>Mud and snow (M+S) tires mounted on steel rims (including spare tire). Tires must have a tread</p> | | |

| 1. Item number | 2. Specifications required | 3. Specifications offered | 4. Notes, remarks, ref to documentation | 5. Evaluation committee's notes |
|-------------------|---|---|--|------------------------------------|
| | <p>spare tire). Tires must have a tread suitable for both paved and unpaved roads;</p> <p>3.2.3.3. The rear axle may have dual wheels;</p> <p>3.2.3.4. Spare wheel of the same type and size as those fitted to the vehicle. The vehicle must be equipped with a mechanism for lowering and raising the spare wheel from the mounting position without affecting the ground clearance, regardless of its location on the vehicle.</p> <p>3.2.4. Steering system: Power steering.</p> <p>3.2.5. Braking system, at least the following requirements:</p> <p>3.2.5.1. Electrically assisted;</p> <p>3.2.5.2. Anti-lock braking system (ABS or equivalent);</p> <p>3.2.5.3. Throttle slip regulation (ASR or equivalent);</p> <p>3.2.6. Electronic stability</p> | <p>suitable for both paved and unpaved roads;</p> <p>The rear axle have dual wheels;</p> <p>Spare wheel of the same type and size as those fitted to the vehicle. The vehicle must be equipped with a mechanism for lowering and raising the spare wheel from the mounting position without affecting the ground clearance, regardless of its location on the vehicle.</p> <p>Steering system: Power steering.</p> <p>Braking system, at least the following requirements:</p> <p>Electrically assisted;</p> <p>Anti-lock braking system (ABS or equivalent);</p> <p>Throttle slip regulation (ASR or equivalent);</p> <p>Electronic stability program (ESP or equivalent);</p> | | |

| 1. Item number | 2. Specifications required | 3. Specifications offered | 4. Notes, remarks, ref to documentation | 5. Evaluation committee's notes |
|-------------------|--|--|--|------------------------------------|
| | <p>program (ESP or equivalent);</p> <p>3.2.7. Auxiliary braking system (retarder or equivalent);</p> <p>3.2.8. Hill start assist system;</p> <p>3.2.9. Hill descent control system;</p> <p>3.2.9.1. Coupling for the trailer's pneumatic braking system;</p> <p>3.2.9.2. The vehicle must not be equipped with a speed limiter;</p> <p>3.2.9.3. The braking system must have an external connection, electrical or pneumatic, which allows a minimum pressure to be permanently maintained in the system when stationary.</p> <p>3.2.9.4. Electrical system:</p> <p>3.2.9.5. Equipped with sockets for connecting to external devices;</p> <p>3.2.9.6. System voltage: 24 V;</p> <p>3.2.9.7. Two maintenance-free batteries;</p> | <p>Anti-lock braking system (ABS)</p> <p>Retarder and service brake linking</p> <p>Differential engagement management (if equipped) at speeds <10 km/h (4x2)</p> <p>Hill Start Aid</p> <p>Braking performance warning</p> <p>Emergency brake assist (EBA)</p> <p>Emergency brake lights (EBL)</p> <p>Stop lights emergency lighting</p> <p>Hill start assist system;</p> <p>Hill descent control system;</p> <p>Coupling for the trailer's pneumatic braking system;</p> <p>The vehicle is not equipped with a speed limiter;</p> | | |

| 1. Item number | 2. Specifications required | 3. Specifications offered | 4. Notes, remarks, ref to documentation | 5. Evaluation committee's notes |
|-------------------|--|---|--|------------------------------------|
| | <p>3.2.9.8. Main switch for disconnecting all vehicle consumers;</p> <p>3.2.9.9. All electrical system cables must be hidden and protected from impact during movement and must be halogen-free;</p> <p>3.2.9.10. The vehicle must be equipped with an external connector to allow stationary charging (when parked) of batteries and other equipment that requires charging. The battery charging system must include an electronic charger with automatic adapter for long-term maintenance and storage;</p> <p>3.2.9.11. The external 230 V AC connector must be a male connector, mounted on the driver's side of the vehicle. Two female connectors must also be provided, each with an attached cable of at least 10 meters;</p> <p>3.2.9.12. The 230 V AC circuit must be equipped with earthing, ensuring a leakage current of maximum 30 mA, or protected by an</p> | <p>The braking have an external connection, electrical or pneumatic, which allows a minimum pressure to be permanently maintained in the system when stationary.</p> <p>Electrical system: Equipped with sockets for connecting to external devices;</p> <p>System voltage: 24 V;</p> <p>Two maintenance-free batteries;</p> <p>Main switch for disconnecting all vehicle consumers; electronic from key remote.</p> <p>All electrical system cables are hidden and protected from impact during movement and must be halogen-free;</p> <p>The vehicle is equipped with an external connector to allow stationary charging (when parked) of batteries and other equipment that requires charging. The battery</p> | | |

| 1. Item number | 2. Specifications required | 3. Specifications offered | 4. Notes, remarks, ref to documentation | 5. Evaluation committee's notes |
|-------------------|--|--|--|------------------------------------|
| | <p>isolating transformer. If the protection is earthing only, a warning label near the socket must have the following message: „ATENȚIE! A SE CONECTA DOAR LA O PRIZĂ AUTORIZATĂ”.</p> <p>3.2.9.13. Starting the engine will not be possible while connected to an external 230 V AC power source, unless the outlet has an automatic disconnect that deactivates when the engine is started.</p> <p>3.2.10. Lighting system:</p> <p>3.2.10.1. Signal lights (mounted on the chassis) with front and rear fog lights;</p> <p>3.2.10.2. All vehicle headlights and lamps must be LED only, protected by a stainless steel protective grille to prevent accidental damage.</p> <p>3.2.11. Cabin:</p> <p>3.2.11.1. The steering wheel</p> | <p>charging system must include an electronic charger with automatic adapter for long-term maintenance and storage; Automatic Self Ejecting Socket similar to Ambulance.</p> <p>The external 230 V AC connector is a male connector, mounted on the driver's side of the vehicle. Two female connectors must also be provided, each with an attached cable of at least 10 meters;</p> <p>The 230 V AC circuit protection is earthing only, warning label near the socket must have the following message: „ATENȚIE! A SE CONECTA DOAR LA O PRIZĂ AUTORIZATĂ”.</p> <p>Starting the engine will not be possible while connected to an external 230 V AC power source, due to the outlet has an automatic</p> | | |

| 1. Item number | 2. Specifications required | 3. Specifications offered | 4. Notes, remarks, ref to documentation | 5. Evaluation committee's notes |
|-------------------|---|---|--|------------------------------------|
| | <p>will be on the left side. The cabin will be a single-piece, metal type, closed, advanced, with suspension and anti-corrosion protection;</p> <p>3.2.11.2. The cab must be manufactured and tested in accordance with the ECE R29-3 standard;</p> <p>3.2.11.3. Manual folding of the cab must be possible using a hydraulic system;</p> <p>3.2.11.4. Equipped with 2 doors and 1+2 seats, and all seats must be equipped with seat belts in accordance with legal requirements;</p> <p>3.2.11.5. The driver's seat must have air suspension and be adjustable in at least two directions;</p> <p>3.2.11.6. Sunshades mounted on the inside and outside of the windshield;</p> <p>3.2.11.7. Heated rear-view mirrors with electric or manual adjustment;</p> <p>3.2.11.8. Front and right exterior mirrors for blind spots, with</p> | <p>disconnect that deactivates when the engine is started.</p> <p>Lighting system:</p> <p>Signal lights (mounted on the chassis) with front and rear fog lights;</p> <p>All vehicle headlights and lamps are LED only, protected by a stainless steel protective grille to prevent accidental damage.</p> <p>Cabin:</p> <p>The steering wheel will be on the left side. The cabin will be a single-piece, metal type, closed, advanced, with suspension and anti-corrosion protection;</p> <p>The cab must be manufactured and tested in accordance with the ECE R29-3 standard.</p> <p>Manual folding of the cab is possible using a hydraulic system;</p> <p>Equipped with 2 doors and 1+2 seats, and all seats must be</p> | | |

| 1. Item number | 2. Specifications required | 3. Specifications offered | 4. Notes, remarks, ref to documentation | 5. Evaluation committee's notes |
|----------------------|---|--|---|--|
| | <p>electric or manual adjustment;</p> <p>3.2.11.9. All side windows are electrically or manually operated;</p> <p>3.2.11.10. The cabin must be equipped with an air conditioning system (with automatic heating and air conditioning)</p> <p>3.2.11.11. The cab must be equipped with an additional autonomous cabin heating system, which uses diesel directly from the vehicle tank. This function must be able to be used both during travel to and from intervention missions and when stationary at the intervention site;</p> <p>3.2.11.12. The color of the cab will be red, shade RAL 3000. Car wrap (stickers or foil) is not allowed;</p> <p>3.2.11.13. AM/FM vehicle radio with multifunction display and USB connections, integrated into the vehicle dashboard, with a minimum of four speakers;</p> <p>3.2.11.14. Satellite navigation</p> | <p>equipped with seat belts in accordance with legal requirements;</p> <p>The driver's seat must have air suspension and be adjustable in at least two directions;</p> <p>Sunshades mounted on the inside and outside of the windshield;</p> <p>Heated rear-view mirrors with electric or manual adjustment;</p> <p>Front and right exterior mirrors for blind spots, with electric or manual adjustment;</p> <p>All side windows are electrically or manually operated;</p> <p>The cabin is equipped with an air conditioning system (with automatic heating and air conditioning)</p> <p>The cab is equipped with an additional autonomous cabin heating system, which uses diesel</p> | | |

| 1. Item number | 2. Specifications required | 3. Specifications offered | 4. Notes, remarks, ref to documentation | 5. Evaluation committee's notes |
|-------------------|---|--|--|------------------------------------|
| | <p>system based on GPS or Galileo with Android Auto/Apple CarPlay, with updated maps of the Republic of Moldova and Europe. With the possibility of updating maps by the vehicle owner;</p> <p>3.2.11.15. An HD rear view camera (1920x1080) that activates automatically when reversing, with integrated rear parking sensors;</p> <p>3.2.11.16. A traffic recording device that records on an SD or microSD card (the card will be delivered with the vehicle, compatible with the recording device, with a minimum capacity of 128 GB, at least Class 10+ with a minimum transfer rate of 10 MB/s), with a minimum video recording resolution of 1920 x 1080@30 fps Full HD. It will allow video recording (including vehicle speed data and GPS position), so that the route and the road traveled can be monitored (regardless of whether the acoustic and light signals are active). During periods of standstill with the engine</p> | <p>directly from the vehicle tank. This function must be able to be used both during travel to and from intervention missions and when stationary at the intervention site;</p> <p>The color of the cab will be red, shade RAL 3000. No car wrap (stickers or foil) on the cabin;</p> <p>AM/FM vehicle radio with multifunction display and USB connections, integrated into the vehicle dashboard, with four speakers;</p> <p>Satellite navigation system based on GPS or Galileo with Android Auto/Apple CarPlay, with updated maps of the Republic of Moldova and Europe. With the possibility of updating maps by the vehicle owner; SYGIC NAVIGATION.</p> <p>An HD rear view camera (1920x1080) that activates automatically when reversing part of truck system. Rear parking</p> | | |

| 1. Item number | 2. Specifications required | 3. Specifications offered | 4. Notes, remarks, ref to documentation | 5. Evaluation committee's notes |
|-------------------|--|---|--|------------------------------------|
| | <p>off, the recording function will be automatically deactivated, and it will be automatically activated when the engine is started. The necessary accessories for downloading the data will also be provided. Depending on the technical solution adopted for the camera device (integrated or not in the interior elements of the cabin), a mounting system will be provided to allow its use.</p> <p>3.2.12. Additional equipment:</p> <ul style="list-style-type: none"> • Acoustic and optical warning system: • A light bar, with a minimum length of 1200 mm and no wider than the cab, mounted on the roof at the upper front of the cab, with blue LED strobe modules, protected by a stainless steel grille for impact resistance, with the following specifications: • Four blue side modules and two white modules, positioned symmetrically on either side of the central acoustic module. • Each optical module must contain | <p>sensors with separate display installed on board.</p> <p>A traffic recording device that records on an SD or microSD card (the card will be delivered with the vehicle, compatible with the recording device, with a minimum capacity of 128 GB, at least Class 10+ with a minimum transfer rate of 10 MB/s), with a minimum video recording resolution of 1920 x 1080@30 fps Full HD. It will allow video recording (including vehicle speed data and GPS position), so that the route and the road traveled can be monitored (regardless of whether the acoustic and light signals are active). During periods of standstill with the engine off, the recording function will be automatically deactivated, and it will be automatically activated when the engine is started. The necessary accessories for downloading the data will also be</p> | | |

| 1. Item number | 2. Specifications required | 3. Specifications offered | 4. Notes, remarks, ref to documentation | 5. Evaluation committee's notes |
|----------------------|---|---|---|--|
| | <p>a minimum of 24 LEDs, with a minimum power of 50 lumens per LED and a flash frequency of at least 50 flashes per minute;</p> <ul style="list-style-type: none"> • The length of each optical module must be at least one third of the total length of the light bar (with the maximum dimensions allowed after mounting the diffuser); • Polycarbonate lenses and caps for maximum visual effect and anti-fog; • Corrosion and water resistant protected bar; • The acoustic module must include one or more speakers; • Acoustic signal generator with at least three tone options; • Maximum power of at least 150W; • External audio input with switchable function for transmitting voice messages via microphone; • Optical signaling system of LED | <p>provided.A mounting system will be provided to allow its use.</p> <p>Additional equipment:</p> <ul style="list-style-type: none"> • Acoustic and optical warning system: • A light bar, with a minimum length of 1200 mm and no wider than the cab, mounted on the roof at the upper front of the cab, with blue LED strobe modules, protected by a stainless-steel grille for impact resistance, with the following specifications: • Four blue side modules and two white modules, positioned symmetrically on either side of the central acoustic module. • Each optical module must contain a minimum of 24 LEDs, with a minimum power of 50 lumens per LED and a flash frequency of at least 50 flashes per minute; | | |

| 1. Item number | 2. Specifications required | 3. Specifications offered | 4. Notes, remarks, ref to documentation | 5. Evaluation committee's notes |
|----------------------|--|---|---|--|
| | <p>"flash" type with eight blue lamps, each with at least 8 LEDs, protected by a stainless steel grid, located as follows:</p> <ul style="list-style-type: none"> • 2 lamps in the front of the cabin, at the radiator level; • 2 lamps at the upper rear of the vehicle, integrated into the superstructure; • 2 lamps on each upper side, integrated into the superstructure. • A sequence of blue "flashing" LED lamps/modules with a flashing frequency of at least 50 flashes per minute, integrated into the sides of the container (covering at least 50% of the container length symmetrically), emitting at least 50 lumens per LED and at least 8 LEDs/module; • Control box for the acoustic-optical warning system, mounted on the dashboard. • An audible warning device that produces a sound activated by the | <p>The length of each optical module will be at least one third of the total length of the light bar (with the maximum dimensions allowed after mounting the diffuser);</p> <p>Polycarbonate lenses and caps for maximum visual effect and anti-fog;</p> <p>Corrosion and water resistant protected bar;</p> <p>The acoustic module will include one or more speakers;</p> <p>Acoustic signal generator with three tone options;</p> <p>Maximum power 150W;</p> <p>External audio input with switchable function for transmitting voice messages via microphone;</p> <p>Optical signaling system of LED "flash" type with eight blue lamps,</p> | | |

| 1. Item number | 2. Specifications required | 3. Specifications offered | 4. Notes, remarks, ref to documentation | 5. Evaluation committee's notes |
|-------------------|--|---|--|------------------------------------|
| | <p>reverse gear for the vehicle to move backwards.</p> <p>3.3. Hydraulic loading/unloading system with hook and manipulator.</p> <p>3.3.1. The hydraulic hook loading/unloading system is mounted on the vehicle chassis;</p> <p>3.3.2. The hydraulic hook loading/unloading system will be manufactured in accordance with the DIN 30722 standard (which defines the hook height and the distances from the subframe anchoring elements on the transport platform);</p> <p>3.3.3. It will allow the loading/unloading of containers manufactured according to the DIN 30722 standard, with the following dimensions:</p> <ul style="list-style-type: none"> - Maximum internal length L max = 7,000 mm; - Bed height varying between 500 – 800 mm; | <p>each with at least 8 LEDs, protected by a stainless steel grid, located as follows:</p> <p>2 lamps in the front of the cabin, at the radiator level;</p> <p>2 lamps at the upper rear of the vehicle, integrated into the superstructure;</p> <p>A sequence of blue "flashing" LED lamps/modules with a flashing frequency of at least 50 flashes per minute, integrated into the sides of the container (covering at least 50% of the container length symmetrically), emitting at least 50 lumens per LED and at least 8 LEDs/module;</p> <p>Control box for the acoustic-optical warning system, mounted on the dashboard.</p> <p>An audible warning device that produces a sound</p> | | |

| 1. Item number | 2. Specifications required | 3. Specifications offered | 4. Notes, remarks, ref to documentation | 5. Evaluation committee's notes |
|-------------------|---|---|--|------------------------------------|
| | <p>- Maximum external width =2,550 mm.</p> <p>3.3.4. The system must have the capacity to handle the metal bed with a total weight of: at least 16,000 kg (the container's own weight plus its load);</p> <p>3.3.5. It must allow for the secure attachment of the metal platform/container manufactured in accordance with DIN 30722 standard during transport, even on unpaved roads;</p> <p>3.3.6. The hydraulic hook loading/unloading system must be controlled from the vehicle's driver's seat.</p> <p>3.3.7. The manipulator is mounted on the chassis;</p> <p>3.3.8. Minimum telescopic arm length: 10 m;</p> <p>3.3.9. The manipulator must be able to lift at least 4,450 kg at a distance of 2.5 m and at least 1,300kg at a distance of 10 m;</p> | <p>activated by the reverse gear for the vehicle to move backwards.</p> <p>Hydraulic loading/unloading system with hook and manipulator.</p> <p>The hydraulic hook loading/unloading system is mounted on the vehicle chassis;</p> <p>The hydraulic hook loading/unloading system will be manufactured in accordance with the DIN 30722 standard (which defines the hook height and the distances from the subframe anchoring elements on the transport platform);</p> <p>It will allow the loading/unloading of containers manufactured according to the DIN 30722 standard, with the following dimensions:</p> <p>- Maximum internal length L max = 6,800 mm;</p> | | |

| 1. Item number | 2. Specifications required | 3. Specifications offered | 4. Notes, remarks, ref to documentation | 5. Evaluation committee's notes |
|-------------------|--|---|--|------------------------------------|
| | <p>3.3.10. The manipulator must have a minimum lifting capacity of 128 kNm;</p> <p>3.3.11. Base: cast and stress relieved to eliminate potential stress concentrators in welded construction;</p> <p>3.3.12. The rotation system lubrication will be carried out in a tank of gear oil, completely separate from the hydraulic system;</p> <p>3.3.13. The manipulator must be able to rotate at a minimum angle of 415°;</p> <p>3.3.14. The manipulator must be able to rotate without moving the container at 360°;</p> <p>3.3.15. The column must include an internal channel for guiding the hydraulic hoses, ensuring their protection;</p> <p>3.3.16. The arms will consist of two hydraulically articulated segments, one of which is telescopic</p> | <p>- Bed height varying between 500 – 800 mm;</p> <p>Maximum external width 2550 mm.</p> <p>The system has the capacity to handle the metal bed with a total weight of: max. 16,000 kg (the container's own weight plus its load);</p> <p>It allows for secure attachment of the metal platform/container manufactured in accordance with DIN 30722 standard during transport, even on unpaved roads;</p> <p>The hydraulic hook loading/unloading system is controlled from the vehicle's driver's seat and remote controll.</p> <p>The manipulator is mounted on the chassis;</p> <p>Telescopic arm length: 10,7 m;</p> <p>The manipulator is able to lift at least 4,500 kg at a distance of 3.2</p> | | |

| 1. Item number | 2. Specifications required | 3. Specifications offered | 4. Notes, remarks, ref to documentation | 5. Evaluation committee's notes |
|----------------------|--|---|---|--|
| | <p>with a minimum of three hydraulic sections;</p> <p>3.3.17. Minimum operating radius of 10 meters, using a specially designed arm for medium distances;</p> <p>3.3.18. Additional skids on the left and right sides of the arm to ensure high accuracy;</p> <p>3.3.19. Additional articulation between the column and the main boom of the crane, as well as between the main boom and the telescopic boom, ensuring constant torque and speed in any working position of the crane;</p> <p>3.3.20. Stabilizing beam with hydraulic extension on both sides for optimal opening;</p> <p>3.3.21. Hydraulic telescopic system for ground adjustment;</p> <p>3.3.22. Ball joint legs for optimal adaptability and stability in various terrain conditions;</p> <p>3.3.23. The manipulator</p> | <p>m and 1,260kg at a distance of 10,7 m;</p> <p>The manipulator has a lifting capacity of 141,6 kNm;</p> <p>The manipulator is able to rotate without moving the container at 360 °;</p> <p>The column include an internal channel for guiding the hydraulic hoses, ensuring their protection;</p> <p>The arms consist of two hydraulically articulated segments, one of which is telescopic with three hydraulic sections</p> <p>Operating radius of 10,7 meters, using a specially designed arm for medium distances;</p> <p>Additional skids on the left and right sides of the arm to ensure high accuracy;</p> <p>Additional articulation between the column and the main boom of the</p> | | |

| 1. Item number | 2. Specifications required | 3. Specifications offered | 4. Notes, remarks, ref to documentation | 5. Evaluation committee's notes |
|-------------------|--|--|--|------------------------------------|
| | <p>must be equipped with a main distributor capable of performing 2-3 simultaneous movements;</p> <p>3.3.24. The manipulator will be operated manually from the base, only in case of emergency;</p> <p>3.3.25. The manipulator will be equipped with a remote control system, allowing efficient and safe operation from a considerable distance;</p> <p>3.3.26. Safety features: the electronic system must include an overload detection function, with the ability to block controls that could increase the operating torque beyond specified limits, thus ensuring the protection of both the manipulator and the operator;</p> <p>3.3.27. The manipulator must be equipped with a mushroom-type emergency stop button, located in an accessible and visible place, for immediate stopping of operations in critical situations;</p> <p>3.3.28. The crane rotation system will be equipped with safety</p> | <p>crane, as well as between the main boom and the telescopic boom, ensuring constant torque and speed in any working position of the crane; Double Link.</p> <p>Stabilizing beam with hydraulic extension on both sides for optimal opening;</p> <p>Hydraulic telescopic system for ground adjustment;</p> <p>Ball joint legs for optimal adaptability and stability in various terrain conditions;</p> <p>The manipulator is equipped with a main distributor capable of performing 2-3 simultaneous movements;</p> <p>The manipulator will be operated manually from the base, only in case of emergency;</p> <p>The manipulator is equipped with a remote control system, allowing</p> | | |

| 1. Item number | 2. Specifications required | 3. Specifications offered | 4. Notes, remarks, ref to documentation | 5. Evaluation committee's notes |
|----------------------|---|---|---|--|
| | <p>valves to ensure protection during rotation operations;</p> <p>3.3.29. The main boom cylinder and secondary cylinders (double-acting) will be equipped with safety valves to protect against overloads and unforeseen situations;</p> <p>3.2.1. Telescopic cylinders must be equipped with safety valves to ensure safe and efficient extension and retraction operations;</p> <p>3.2.2. The manipulator will be equipped with safety valves in the hydraulic caliper system to prevent overloads and ensure safe and efficient operation of the equipment under various conditions;</p> <p>3.2.3. Electronic systems: a visual and acoustic warning system for the operator will be installed, with warning lights mounted on the outriggers/stabilizers, to ensure the</p> | <p>efficient and safe operation from a considerable distance</p> <p>Safety features: the electronic system include an overload detection function, with the ability to block controls that could increase the operating torque beyond specified limits, thus ensuring the protection of both the manipulator and the operator;</p> <p>The manipulator is equipped with a mushroom-type emergency stop button, located in an accessible and visible place, for immediate stopping of operations in critical situations;</p> <p>The crane rotation system will be equipped with safety valves to ensure protection during rotation operations;</p> <p>The main boom cylinder and secondary cylinders (double-acting) will be equipped with safety valves to</p> | | |

| 1. Item number | 2. Specifications required | 3. Specifications offered | 4. Notes, remarks, ref to documentation | 5. Evaluation committee's notes |
|-------------------|---|---|--|------------------------------------|
| | <p>safe and efficient operation of the manipulator;</p> <p>3.2.4. Electronic systems: a capacity limitation system will be implemented, with continuous adjustment depending on the extension and position of the stirrups. The system will ensure the maximum possible load lift in stable conditions for any position of the stirrup legs;</p> <p>3.2.5. Electronic systems: a collision prevention system will be installed to avoid bridges or overpasses during transport, ensuring the safety of the manipulator and preventing material damage;</p> <p>3.2.6. Electronic systems: a warning system will be implemented to signal if the outrigger/stabilizer system is not properly secured, preventing potential accidents or damage;</p> <p>3.2.7. An integrated electronic system for maintenance alerts, diagnostics and error code generation will be installed, ensuring</p> | <p>protect against overloads and unforeseen situations;</p> <p>Telescopic cylinders must be equipped with safety valves to ensure safe and efficient extension and retraction operations;</p> <p>The manipulator is equipped with safety valves in the hydraulic caliper system to prevent overloads and ensure safe and efficient operation of the equipment under various conditions;</p> <p>Electronic systems: a visual and acoustic warning system for the operator is installed, with warning lights mounted on the outriggers/stabilizers, to ensure the safe and efficient operation of the manipulator;</p> <p>Electronic systems: a capacity limitation system is implemented, with continuous adjustment depending on the extension and position of the stirrups. The system</p> | | |

| 1. Item number | 2. Specifications required | 3. Specifications offered | 4. Notes, remarks, ref to documentation | 5. Evaluation committee's notes |
|----------------------|--|--|---|--|
| | <p>optimal functionality and reliability of the manipulator;</p> <p>3.2.8. An automatic system will be implemented to divert hydraulic oil directly to the tank if the lever is not operated for 3 seconds, ensuring the safety and protection of the equipment;</p> <p>3.2.9. An automatic system will be implemented to turn off the crane's electronic system if the lever is not operated for 30 minutes, ensuring energy savings and operational safety;</p> <p>3.2.10. The manipulator will be equipped with an LED spotlight mounted on the telescopic arm, which provides additional lighting for operation in low light or dark conditions, ensuring safety and efficiency during nighttime activities;</p> <p>3.2.11. Hydraulic system: The manipulator will be equipped with a factory-installed high-pressure hydraulic pump, together with a fully equipped hydraulic oil tank with return filter and wear indicator.</p> | <p>ensure the maximum possible load lift in stable conditions for any position of the stirrup legs;</p> <p>Electronic systems: a collision prevention system is installed to avoid bridges or overpasses during transport, ensuring the safety of the manipulator and preventing material damage;</p> <p>Electronic systems: a warning system is implemented to signal if the outrigger/stabilizer system is not properly secured, preventing potential accidents or damage</p> <p>An integrated electronic system for maintenance alerts, diagnostics and error code generation will be installed, ensuring optimal functionality and reliability of the manipulator;</p> <p>An automatic system will be implemented to divert hydraulic oil directly to the tank if the lever is not operated for 3 seconds,</p> | | |

| 1. Item number | 2. Specifications required | 3. Specifications offered | 4. Notes, remarks, ref to documentation | 5. Evaluation committee's notes |
|-------------------|--|---|--|------------------------------------|
| | <p>3.4. Flat rack container</p> <p>The container will be equipped with a support and loading/unloading system, manufactured according to the DIN 30722 standard (which defines the hook height and the distances from the subframe anchoring elements on the transport platform).</p> <p>The platform has the following characteristics (Annex no. 2):</p> <p>3.4.1. Inner length: maximum 7,000 mm;</p> <p>3.4.2. External width: maximum 2,550 mm;</p> <p>3.4.3. Maximum height (with supports and tarpaulin installed): maximum 2,400 mm;</p> <p>3.4.4. Equipped with locking and securing systems while the</p> | <p>ensuring the safety and protection of the equipment;</p> <p>An automatic system will be implemented to turn off the crane's electronic system if the lever is not operated for 30 minutes, ensuring energy savings and operational safety;</p> <p>The manipulator will be equipped with an LED spotlight mounted on the telescopic arm, which provides additional lighting for operation in low light or dark conditions, ensuring safety and efficiency during nighttime activities;</p> <p>Hydraulic system: The manipulator will be equipped with a factory-installed high-pressure hydraulic pump, together with a fully equipped hydraulic oil tank with return filter and wear indicator.</p> <p>Flat rack container</p> | | |

| 1. Item number | 2. Specifications required | 3. Specifications offered | 4. Notes, remarks, ref to documentation | 5. Evaluation committee's notes |
|-------------------|---|---|--|------------------------------------|
| | <p>vehicle is moving Metal flooring with anti-slip strips, impact-resistant, equipped with slots or anchoring systems;</p> <p>3.4.5. The opening system of the equipment compartments will be provided with side rollers (left and right), and the rear compartment will be equipped with a rigid door, with a vertical opening upwards.</p> <p>3.5. The communications equipment will include:</p> <p>a) A fuse panel for all equipment, including warning devices;</p> <p>b) 12V DC bipolar sockets for communications equipment, including electrical conductors, capable of carrying a current of 20 A and supplied with paired connectors;</p> <p>c) Bipolar sockets must be installed in accessible and properly insulated places;</p> <p>d) An antenna installed on the cabin with the antenna cable placed inside, with a TNC connector.</p> <p>3.6. The vehicle will be marked</p> | <p>The container will be equipped with a support and loading/unloading system, manufactured according to the DIN 30722 standard (which defines the hook height and the distances from the subframe anchoring elements on the transport platform).</p> <p>The platform has the following characteristics (Annex no. 2):</p> <p>Inner length 6,600 mm;</p> <p>External width: 2,550 mm;</p> <p>Maximum height (with supports and tarpaulin installed):2,400 mm.</p> <p>Equipped with locking and securing systems while the vehicle is moving Metal flooring with anti-slip strips, impact-resistant, equipped with slots or anchoring systems;</p> <p>The opening system of the equipment compartments will be</p> | | |

| 1. Item number | 2. Specifications required | 3. Specifications offered | 4. Notes, remarks, ref to documentation | 5. Evaluation committee's notes |
|-------------------|---|---|--|------------------------------------|
| | <p>on the sides and front with the inscriptions "DRCS nr.2", as well as with the logos of the "General Inspectorate for Emergency Situations". In addition, the vehicle will be marked on the sides with the logo "112".</p> <p>3.7. The color of the superstructure will be red, shade RAL 3000. Car wrap (stickers or foil) is not allowed. The vehicle will be equipped with reflective plates and strips.</p> <p>3.8. The inscriptions and markings will meet the requirements set out in Government Decision No. 500/2018. The exact text of the inscriptions (name and identification number of the firefighters, type of special vehicle, etc.) will be provided by the beneficiary (GIES) before signing the contract.</p> <p>3.9. The vehicle must be equipped with small lamps with flexible rubber arms, mounted behind the chassis.</p> <p>3.10. The vehicle, including all</p> | <p>provided with side rollers (left and right), and the rear compartment will be equipped with a rigid door, with a vertical opening upwards.</p> <p>The communications equipment will include:</p> <ul style="list-style-type: none"> a) A fuse panel for all equipment, including warning devices; b) 12V DC bipolar sockets for communications equipment, including electrical conductors, capable of carrying a current of 20 A and supplied with paired connectors; c) Bipolar sockets must be installed in accessible and properly insulated places; d) An antenna installed on the cabin with the antenna cable placed inside, with a TNC connector. <p>The vehicle will be marked on the sides and front with the inscriptions "DRCS nr.2", as well as with the</p> | | |

| 1. Item number | 2. Specifications required | 3. Specifications offered | 4. Notes, remarks, ref to documentation | 5. Evaluation committee's notes |
|----------------------|--|---|---|--|
| | <p>its components and equipment, must be new, unused, and not refurbished.</p> | <p>logos of the "General Inspectorate for Emergency Situations". In addition, the vehicle will be marked on the sides with the logo "112".</p> <p>The color of the superstructure will be red, shade RAL 3000. Car wrap (stickers or foil) is not allowed. The vehicle will be equipped with reflective plates and strips.</p> <p>The inscriptions and markings will meet the requirements set out in Government Decision No. 500/2018. The exact text of the inscriptions (name and identification number of the firefighters, type of special vehicle, etc.) will be provided by the beneficiary (GIES) before signing the contract.</p> <p>The vehicle must be equipped with small lamps with flexible rubber arms, mounted behind the chassis.</p> <p>The vehicle, including all its components and equipment, must</p> | | |

| 1. Item number | 2. Specifications required | 3. Specifications offered | 4. Notes, remarks, ref to documentation | 5. Evaluation committee's notes |
|----------------------|--|---|---|--|
| | | be new, unused, and not refurbished. | | |
| | <p>CONTAINER TECHNICAL SPECIFICATIONS</p> <p>1.1. The transportable container will be built in accordance with DIN 30722, which defines the</p> | <p>The transportable container will be built in accordance with DIN 30722, which defines the hook height and the distances to the anchoring elements of the subframe on the transport</p> | | |

| 1. Item number | 2. Specifications required | 3. Specifications offered | 4. Notes, remarks, ref to documentation | 5. Evaluation committee's notes |
|----------------------|---|--|---|--|
| | <p>hook height and the distances to the anchoring elements of the subframe on the transport platform. It will be loaded on vehicles equipped with a hook system that allows its loading/unloading and will meet the following dimensional specifications:</p> <p>1.1.1. Inner length L. = 7000 mm;</p> <p>1.1.2. Maximum external width l = 2550 mm (preferably 2500 mm);</p> <p>1.1.3. External height h = 2400 mm;</p> <p>1.2. The total mass of the container assembly (including the lifting/loading hook assembly) loaded with all materials/equipment listed in the product inventory must not exceed 15,000 kg;</p> <p>1.3. The material transport compartment: must allow the storage and transport of at least 1000 meters of hose, with a diameter of up to 300 mm, with couplings, and allow the deployment of hose pipes and must</p> | <p>platform. It will be loaded on vehicles equipped with a hook system that allows its loading/unloading and will meet the following dimensional specifications:</p> <p>Inner length L. = 6600 mm;</p> <p>Maximum external width l = 2550 mm</p> <p>External height h = 2400 mm;</p> <p>The total mass of the container assembly (including the lifting/loading hook assembly) loaded with all materials/equipment listed in the product inventory is not exceeding 15,000 kg;</p> <p>The material transport compartment: allow the storage and transport of at least 1000 meters of hose, with a diameter of up to 300 mm, with couplings, and allow the deployment of hose</p> | | |

| 1. Item number | 2. Specifications required | 3. Specifications offered | 4. Notes, remarks, ref to documentation | 5. Evaluation committee's notes |
|-------------------|--|---|--|------------------------------------|
| | <p>be organized with spaces designed for the following categories of technical equipment:</p> <p>1.3.1. Telescopic lighting mast, according to annex no. 3;</p> <p>1.3.2. Hose and accessory compartment, according to Annex No. 4;</p> <p>1.4. The container will be equipped with an autonomous electrical system, powered by one or two batteries, with the option of recharging from an external power source (external 220 V generator). The lighting system will include:</p> <p>LED interior lighting, ensuring adequate illumination for identifying all equipment inside.</p> <p>1.1. External lighting required for unloading materials, with LEDs that will illuminate the area around the container within a radius of 5 meters. This system will be designed to</p> | <p>pipes and must be organized with spaces designed for the following categories of technical equipment:</p> <p>Telescopic lighting mast, according to annex no. 3;</p> <p>Hose and accessory compartment, according to Annex No. 4;</p> <p>The container will be equipped with an autonomous electrical system, powered by one or two batteries, with the option of recharging from an external power source (external 220 V generator). The lighting system will include:</p> <p>LED interior lighting, ensuring adequate illumination for identifying all equipment inside.</p> <p>External lighting required for unloading materials, with LEDs that will illuminate the area around the container within a radius of 5 meters. This system will be</p> | | |

| 1. Item number | 2. Specifications required | 3. Specifications offered | 4. Notes, remarks, ref to documentation | 5. Evaluation committee's notes |
|-------------------|--|--|--|------------------------------------|
| | <p>fit within the overall dimensions of the container.</p> <p>1.2. External marking lighting with orange LED lamps positioned in the upper corners of the container, visible from the side and rear. Additional orange LED lamps of the same type are installed on the lower side, vertically aligned with the upper lamps.</p> <p>1.3. The hose compartment container must be equipped with at least the following:</p> <p>1.3.1. A rear door equipped with ladder access.</p> <p>1.3.2. Floor clad with seawater-resistant anodized checkered tiles and stainless steel walls.</p> <p>1.3.3. Fully enclosed, foldable aluminum top covers that also function as safety railings.</p> <p>1.3.4. Equipment and tool cabinets, equipped with access panels and roller doors with locks.</p> | <p>designed to fit within the overall dimensions of the container.</p> <p>External marking lighting with orange LED lamps positioned in the upper corners of the container, visible from the side and rear. Additional orange LED lamps of the same type are installed on the lower side, vertically aligned with the upper lamps.</p> <p>The hose compartment container is equipped with at least the following:</p> <p>A rear door equipped with ladder access.</p> <p>Floor clad with seawater-resistant anodized checkered tiles and stainless steel walls.</p> <p>Fully enclosed, foldable aluminum top covers that also function as safety railings.</p> | | |

| 1. Item number | 2. Specifications required | 3. Specifications offered | 4. Notes, remarks, ref to documentation | 5. Evaluation committee's notes |
|-------------------|--|---|--|------------------------------------|
| | <p>1.3.5. Hose compartments equipped with fastening belts to prevent hoses from moving during container handling.</p> | <p>Equipment and tool cabinets, equipped with access panels and roller doors with locks.</p> <p>Hose compartments equipped with fastening belts to prevent hoses from moving during container handling.</p> | | |
| | <p>1 TELESCOPIC LIGHTING MAST</p> <p>Minimum technical requirements:</p> <ul style="list-style-type: none"> - Integrated as a fixed component of the container; - Fully electropneumatic drive; - Electrically controlled (12/24V, DC or 220V, AC) via a wired remote control with a cable | <p>TELESCOPIC LIGHTING MAST</p> <p>Minimum technical requirements:</p> <p>Integrated as a fixed component of the container;</p> <p>Fully electropneumatic drive;</p> | | |

| 1. Item number | 2. Specifications required | 3. Specifications offered | 4. Notes, remarks, ref to documentation | 5. Evaluation committee's notes |
|-------------------|---|---|--|------------------------------------|
| | <p>length of at least 5 meters;</p> <ul style="list-style-type: none"> - The power supply must be provided from both the vehicle's electrical system and the generator; - Telescopic mast cylinders made of anodized aluminum; - Lamp rotation in vertical plane: 315°; - Lamp rotation in horizontal plane: 360°; - Equipped with four (4) LED lamps/projectors, each with a minimum output of 12,000 lumens, which emit cool white light and provide protection against accidental impacts; - Minimum height from the ground (when the container is on the vehicle chassis): 5,000 mm; - Automatic return to transport position. | <ul style="list-style-type: none"> - Electrically controlled (12/24V, DC or 220V, AC) via a wired remote control with a cable length of at least 5 meters; - The power supply must be provided from both the vehicle's electrical system and the generator; - Telescopic mast cylinders made of anodized aluminum; - Lamp rotation in vertical plane: 315°; - Lamp rotation in horizontal plane: 360°; - Equipped with four (4) LED lamps/projectors, each with a minimum output of 12,000 lumens, which emit cool white light and provide protection against accidental impacts; - Minimum height from the ground (when the container is on | | |

| 1. Item number | 2. Specifications required | 3. Specifications offered | 4. Notes, remarks, ref to documentation | 5. Evaluation committee's notes |
|-------------------|--|---|--|------------------------------------|
| | | the vehicle chassis): 5,000 mm; - Automatic return to transport position. | | |
| | <p align="center">2 TECHNICAL SPECIFICATIONS</p> <p align="center">"High capacity pump"</p> <p>1. DESTINATION</p> <p>1.1. The high-capacity pump is a self-priming, trailer-mounted diesel engine pump designed to evacuate dirty water and liquids with solid content, for flood response operations, industrial accidents, or other emergency situations requiring rapid evacuation of liquids.</p> <p>1.2. The entire contents of the High Capacity Pump will be subject to a verification program developed by the specialists of the General Inspectorate for Emergency Situations together with those of the supplier, before initial delivery. The</p> | <p align="center">TECHNICAL SPECIFICATIONS</p> <p align="center">"High capacity pump"</p> <p>DESTINATION</p> <p>The high-capacity pump is a self-priming, trailer-mounted diesel engine pump designed to evacuate dirty water and liquids with solid content, for flood response operations, industrial accidents, or other emergency situations requiring rapid evacuation of liquids.</p> <p>The entire contents of the High Capacity Pump will be subject to a verification program developed by the specialists of the General Inspectorate for Emergency Situations together with those of the supplier, before initial</p> | | |

| 1. Item number | 2. Specifications required | 3. Specifications offered | 4. Notes, remarks, ref to documentation | 5. Evaluation committee's notes |
|----------------------|---|--|---|--|
| | <p>purpose of this process is to determine whether it meets the technical and tactical performance requirements stipulated in the current technical specifications.</p> <p>2. APPROVAL AND CERTIFICATION</p> <p>The high-capacity pump must be manufactured in accordance with the applicable European directives and regulations and must bear the CE conformity marking. It must be accompanied by a Declaration of Conformity and a Quality Certificate, issued by the manufacturer and supplier under their own responsibility.</p> <p>3. GENERAL REQUIREMENTS</p> <p>3.1. The equipment will be delivered fully assembled,</p> | <p>delivery. The purpose of this process is to determine whether it meets the technical and tactical performance requirements stipulated in the current technical specifications.</p> <p>APPROVAL AND CERTIFICATION</p> <p>The high-capacity pump is manufactured in accordance with the applicable European directives and regulations and must bear the CE conformity marking. It must be accompanied by a Declaration of Conformity and a Quality Certificate, issued by the manufacturer and supplier under their own responsibility.</p> <p>GENERAL REQUIREMENTS</p> <p>The equipment will be delivered fully assembled, functional and ready to use;</p> | | |

| 1. Item number | 2. Specifications required | 3. Specifications offered | 4. Notes, remarks, ref to documentation | 5. Evaluation committee's notes |
|-------------------|--|---|--|------------------------------------|
| | <p>functional and ready to use;</p> <p>3.2. All components must bear the CE marking and comply with the relevant European standards;</p> <p>3.3. The pump must be self-priming and be able to prime automatically in the event of loss of suction;</p> <p>3.4. The supplier will provide:</p> <ul style="list-style-type: none"> - Minimum 24-month warranty; - Training for the beneficiary on operation and maintenance; - Two monitoring visits to the production unit; - Complete technical documentation in Romanian (manuals, diagrams, spare parts <p>list);</p> <p>3.5. The equipment and accessories installed and/or supplied with the vehicle</p> | <p>All components must bear the CE marking and comply with the relevant European standards;</p> <p>The pump is self-priming and is able to prime automatically in the event of loss of suction;</p> <p>The supplier will provide:</p> <ul style="list-style-type: none"> 2. Minimum 24-month warranty; 3. Training for the beneficiary on operation and maintenance; 4. Two monitoring visits to the production unit; 5. Complete technical documentation in Romanian (manuals, diagrams, spare parts <p>list);</p> <p>The equipment and accessories installed and/or supplied with the</p> | | |

| 1. Item number | 2. Specifications required | 3. Specifications offered | 4. Notes, remarks, ref to documentation | 5. Evaluation committee's notes |
|-------------------|---|--|--|------------------------------------|
| | <p>must comply with the standards listed in point 5.</p> <p>4. TECHNICAL CHARACTERISTICS OF THE PUMP AND TRAILER</p> <p>4.1. Minimum technical characteristics of the pump</p> <p>4.1.1. Minimum flow rate: 1100 m³/h;</p> <p>4.1.2. Minimum height: 40 m;</p> <p>4.1.3. Maximum size of solid particles: 50 mm;</p> <p>4.1.4. Minimum liquids supported: dirty water, suspensions, sludge;</p> <p>4.1.5. Sealing: mechanical;</p> <p>4.1.6. Pumped liquid temperature: 0°C – 40°C;</p> <p>4.1.7. Ambient operating</p> | <p>vehicle must comply with the standards listed in point 5.</p> <p>6. TECHNICAL CHARACTERISTICS OF THE PUMP AND TRAILER</p> <p>Minimum technical characteristics of the pump</p> <p>Flow rate: 1100 m³/h;</p> <p>Height: 40 m;</p> <p>Maximum size of solid particles: 50 mm;</p> <p>Minimum liquids supported: dirty water, suspensions, sludge;</p> <p>Sealing: mechanical;</p> <p>Pumped liquid temperature: 0°C – 40°C;</p> | | |

| 1. Item number | 2. Specifications required | 3. Specifications offered | 4. Notes, remarks, ref to documentation | 5. Evaluation committee's notes |
|-------------------|---|--|--|------------------------------------|
| | <p>temperature: -15°C to +40°C;</p> <p>4.1.8. Engine type: Diesel.</p> <p>4.1.9. The engine must be started exclusively from the battery;</p> <p>4.1.10.2.Outlet: Standardized large diameter Storz couplings (8" = 204 mm)</p> <p>4.2. The pump must be mounted on a heavy 4-wheel trailer;</p> <p>4.3. The trailer must include:</p> <p>4.3.1. Electrical connection system compatible with signal lights (7 and 13 pin plug)</p> <p>4.3.2. Interchangeable tow hooks for compatibility with both trucks (standard bolt- on coupling) and cars (ball coupling type B or C)</p> <p>4.3.3. Protective structure in the form of a metal casing or waterproof and UV-</p> | <p>Ambient operating temperature: -15°C to +40°C</p> <p>Engine type: Diesel.</p> <p>The engine must be started exclusively from the battery;</p> <p>Outlet: Standardized large diameter Storz couplings (8" = 204 mm)</p> <p>The pump must be mounted on a heavy 4-wheel trailer; The trailer must include:</p> <p>Electrical connection system compatible with signal lights (7 and 13 pin plug)</p> <p>Interchangeable tow hooks for compatibility with both trucks (standard bolt- on coupling) and cars (ball coupling type B or C)</p> <p>Protective structure in the form of a metal casing or waterproof and UV- resistant tarpaulin;</p> | | |

| 1. Item number | 2. Specifications required | 3. Specifications offered | 4. Notes, remarks, ref to documentation | 5. Evaluation committee's notes |
|-------------------|---|---|--|------------------------------------|
| | <p>resistant tarpaulin;</p> <p>4.3.4. The casing must be equipped with a lifting hook with the help of the manipulator in case of need;</p> <p>4.3.5. Dedicated spaces for mounting a filter and four suction hoses with a diameter of 300 mm, each with a minimum length of 4 meters;</p> <p>4.3.6. Command and control panel;</p> <p>4.3.7. Battery box with cables;</p> <p>4.3.8. IP 68 LED lights mounted on the housing for illuminating the work area at night;</p> <p>4.3.9. Fuel tank with a minimum capacity of 300 liters;</p> <p>4.3.10. Maximum permitted speed on public roads, according to legal regulations (80 km/h)</p> <p>4.4 The pump in the set must be equipped with a filter and four suction hoses with a</p> | <p>The casing must be equipped with a lifting hook with the help of the manipulator in case of need;</p> <p>Dedicated spaces for mounting a filter and four suction hoses with a diameter of 300 mm, each with a minimum length of 4 meters;</p> <p>Command and control panel;</p> <p>Battery box with cables;</p> <p>IP 68 LED lights mounted on the housing for illuminating the work area at night;</p> <p>Fuel tank with a minimum capacity of 300 liters;</p> <p>Maximum permitted speed on public roads, according to legal regulations (80 km/h)</p> | | |

| 1. Item number | 2. Specifications required | 3. Specifications offered | 4. Notes, remarks, ref to documentation | 5. Evaluation committee's notes |
|----------------------|---|--|---|--|
| | diameter of 300 mm, each with a minimum length of 4 meters mounted on the trailer.. | The pump in the set must be equipped with a filter and four suction hoses with a diameter of 300 mm, each with a minimum length of 4 meters mounted on the trailer.. | | |
| | | | | |