

IEC60598_2_3M ATTACHMENT			
Clause	Requirement + Test	Result - Remark	Verdict
ATTACHMENT TO TEST REPORT B5-3/117/B/24 IEC 60598-2-3 EUROPEAN GROUP DIFFERENCES AND NATIONAL DIFFERENCES Luminaires Part 2: Particular requirements Section 3: Luminaires for road and street lighting			
Differences according to		EN 60598-2-3:2003 + A1:2011 used in conjunction with EN IEC 60598-1:2021 + A11:2022	
TRF template used		IECEE OD-2020-F2:2020, Ed. 1.1	
Attachment Form No.		EU_GD_IEC60598_2_3M	
Attachment Originator		UL(Demko)	
Master Attachment		2022-05-24	
Copyright © 2022 IEC System for Conformity Testing and Certification of Electrical Equipment (IECEE), Geneva, Switzerland. All rights reserved.			
	CENELEC COMMON MODIFICATIONS (EN)		P
3.5 (3)	MARKING		N/A
3.5 (3.2.12)	Note 4 deleted		N/A
3.6 (4)	CONSTRUCTION		N/A
4.7 (4.11.6)	Electro-mechanical contact systems: electric strength test at 1 500 V		N/A
3.10 (5)	EXTERNAL AND INTERNAL WIRING		P
3.10 (5.2.2)	Cables equal to EN 50525 (all parts)		P
	Paragraph 2 deleted		P
	Replace table 5.1 – Supply cord		N/A
3.12 (12)	ENDURANCE TESTS AND THERMAL TESTS		N/A
3.12 (12.4.2c)	Thermal test (normal operation) see footnote c to table 12.2 relating to unsleeved fixed wiring		N/A
ZB	ANNEX ZB, SPECIAL NATIONAL CONDITIONS (EN)		N/A
(3.3)	DK: power supply cords of class I luminaires with label		N/A
(5.2.1)	CY, DK, FI, UK: type of plug		N/A

IEC60598_2_3M ATTACHMENT			
Clause	Requirement + Test	Result - Remark	Verdict
(5.2.18)	DK: socket-outlets		N/A
ZC	ANNEX ZC, NATIONAL DEVIATIONS (EN)		N/A
(4 & 5)	FR: Shuttered socket-outlets 10/16A		N/A
	FR: Safety requirements for high buildings <i>(Decree of 30 December 2011 on safety regulations for the construction of high-rise buildings and their protection against fire and panic risks; Section VIII; Article GH 48, Lighting)</i> Glow-wire test for outer parts of luminaires:		N/A
	- 850°C for luminaires in stairways and horizontal travel paths		N/A
	- 650°C for indoor luminaires		N/A
	UK: Requirements according to United Kingdom Building Regulation		N/A