

SPECIFICAȚII TEHNICE

Anexa nr. 22 la Documentația standard elaborată prin
Ordinul ministrului finanțelor nr.115 din 15.09.2021

Autoritatea Contractanta: Cadastrul Bunurilor Imobile
Numărul procedurii de achiziție nr. MTender ID ocds-b3wdp1-MD-1747117578006
Denumirea procedurii de achiziție: Achiziț ionarea echipamentului ș i accesoriilor TI

Data: 12.06.2025
Lot: (1,2,3,4,6)
Page 1 of 2

Nr.d /o	Denumirea bunurilor	Denumirea modelului bunului	Țara de origine	Produ- cătorul	Specificarea tehnică deplină solicitată de către autoritatea contractantă	Specificarea tehnică deplină propusă de către ofertant	Standard e de referință
	1	2	3	4	5	6	7
1	Lotul nr.1 Monitor 27"	ThinkVision T27-40	CHINA	LENOVO	Echipament nou. Nu se acceptă renovat Data producerii: minim anul 2024 Diagonală ecran: minim 27 inch Tip rezoluție: Full HD Rezoluț ie optima: minim 1920 x 1080 Luminozitate: minim 300 cd/m² Conectivitate: 1 x VGA; 1 x HDMI; 1 x DisplayPort Porturi audio: 1 x Audio out; 1 x Audio in Port USB integrat: opț ional Difuzoare incorporate: opț ional Accesorii: 1 x Cablu HDMI; 1 x Cablu alimentare; 1 x cablu DisplayPort Garanție: minim 24 luni, cu întreținere la Centrul de deservire autorizat în Republica Moldova. Soluț ionarea cazurilor de garanț ie în termen de până la 30 de zile lucrătoare.	Lenovo ThinkVision T27-40 Echipament nou. Data producerii: 2024 Diagonală ecran: 27 inch Tip rezoluție: Full HD Rezoluț ie optima: 1920 x 1080 Luminozitate: 300 cd/m² Conectivitate: 1x VGA; 1 x HDMI; 1 x DisplayPort Porturi audio: 1x Audio out; 1 x Audio (USB sound card, "Virtus Plus") Port USB integrat: 3x USB-A (USB 5Gbps), 1x USB-C® (USB 5Gbps, PD 15W), 1x USB-B (USB 5Gbps, USB upstream) Difuzoare incorporate: opț ional Cabluri: 1 x HDMI; 1x alimentare; 1x cablu DisplayPort; Garanție: 24 luni, cu întreținere la Centrul de deservire autorizat în Republica Moldova. Soluț ionarea cazurilor de garanț ie în termen de până la 30 de zile lucrătoare.	ISO

Accent Tenno SRL

IDNO: 1002600037469

TVA: 0244960

BC "MOLDOVA-AGROINDBANK" S.A. suc. 'MAIB PARK'

BIC AGRNMD2X522

IBAN LEI: MD52AG000000022515264935



2	Lotul nr.2 UPS	GMB EG- UPS-033	CHINA	Gembird	Echipament nou. Nu se acceptă renovat Data producerii: minim anul 2024 Puterea maximală de ieș ire: 825 VA Tensiunea nominală la intrare: 220V / 230V / 240V AVR (Automatic Voltage Regulation): DA Prize de ieș ire: IEC 320 C13 Numărul prizelor de ieș ire: 3 Baterie: 12V 9Ah Timp mediu de funcț ionare: minim 10 min Conectare Interfața: USB Interfața: RJ-45 Protecț ie scurtcircuit (SCP): DA Protecț ie suprasarcină (OPP): DA Garanție: minim 24 luni, cu întreținere la Centrul de deservire autorizat în Republica Moldova. Soluț ionarea cazurilor de garanț ie în termen de până la 30 de zile lucrătoare.	Echipament nou. Data producerii: anul 2024 Puterea maximală de ieș ire: 1200 VA Tensiunea nominală la intrare: 220V / 230V / 240V AVR (Automatic Voltage Regulation): DA Prize de ieș ire: IEC 320 C13 Numărul prizelor de ieș ire: 3 Baterie: Utilizează 2 baterii de 12V / 7Ah (total 24V / 7Ah), Timp mediu de funcț ionare: 10 min. Conectare Interfața: USB Interfața: RJ-45 Protecț ie scurtcircuit (SCP): DA Protecț ie suprasarcină (OPP): DA Garanție: 24 luni, cu întreținere la Centrul de deservire autorizat în Republica Moldova. Soluț ionarea cazurilor de garanț ie în termen de până la 30 de zile lucrătoare.	
3	Lotul nr.3 Căș ti cu microfon	Poly Blackwire 3215	CHINA	Poly	Echipament nou. Nu se acceptă renovat Data producerii: minim anul 2024 Tip de conexiune: cu fir Frecventa de raspuns (Hz): 20 – 20000 Conectare: USB Microfon: Da Lungime cablu: minim 1,30 m Utilizare: birou, Call Center Reducerea zgomotului pe fundal (ANC - Active Noise Cancelling): DA Compatibilitate: Windows 7, 8, 10 ,11 Garanț ie: minim 12 luni	Poly Blackwire 3215 Monaural USB-A Headset (Bulk), Microphone noise-canceling, SoundGuard, DSP, Receive output from 20 Hz–20 kHz, Microphone 100 Hz–10 kHz, Call answer/ignore/end/hold, redial, mute, volume +/-, OEM, CABLE LENGTH 1610mm mpatibilitate: Windows 7, 8, 10 ,11 Garanț ie: 12 luni	
4	Lotul nr.4	Logitech S150	China	Logitech	Echipament nou. Nu se acceptă renovat Data producerii: minim anul 2024 Tip de conexiune: cu fir Conectare: USB Microfon: Da Putere RMS: minim 1.2W Compatibilitate: Windows 7, 8, 10 ,11 Garanț ie: minim 12 luni	Echipament nou; ta producerii: anul 2024 Logitech S150 Speakers 2.0 (RMS 1.2W, 2x0.6W), Digital USB Speaker, Black Compatibilitate: Windows 7, 8, 10 ,11 Garanț ie: 12 luni	

Accent Tenno SRL

IDNO: 1002600037469

TVA: 0244960

BC" MOLDOVA-AGROINDBANK" S.A. suc. 'MAIB PARK'

BIC AGRNMD2X522

IBAN LEI: MD52AG000000022515264935



6	Lotul nr.6 Mikrotik cAP ac (RBcAPGi- 5acD2nD)	RBcAPGi- 5acD2nD	Mikrotik MikroTik	Latvia	CPU nominal frequency: 716 MHz CPU core count: 4 Size of RAM: 128 MB Storage Size: 16MB 10/100/1000 Ethernet ports: 2 First wireless module: 802.11a/n/ac Second wireless module: 802.11b/g/n PoE in 802.3 af/at PoE Input Voltage: 11 V - 57 V PoE out up to 57V PCB temperature monitor Tested ambient temperature: -40 to +50C MTBF: Approximately 100'000 hours at 25C Antenna gain: 2 CPU: QCA9556 Max Power consumption: 24W Number of chains: 3 Storage type: FLASH Storage size: 16 MB Wireless 2.4 GHz Max data rate: 300 Mbit/s Wireless 2.4 GHz number of chains: 2 Antenna gain dBi for 2.4 GHz: 2 Wireless 2.4 GHz generation: Wi-Fi 4 Wireless 5 GHz Max data rate: 867 Mbit/s Wireless 5 GHz number of chains 2 Antenna gain dBi for 5GHz: 2.5 Wireless 5 GHz generation: Wi-Fi 5 Certification: CE, FCC, IC, EAC, ROHS Warranty: 1 an Embended wireless characteristics: Wireless band – 5Ghz and 2.4Ghz simultaneously AP / Station / Bridge modes supported 802.1X for wireless authentication to radius server Wireless scanner for detection of the free wifi channels The possibility to make virtual access points and bridge them with 802.1Q VLAN Wireless signal level and mac based access control Wireless Sniffer, wireless snooper	CPU nominal frequency: 716 MHz CPU core count: 4 Size of RAM: 128 MB Storage Size: 16MB 10/100/1000 Ethernet ports: 2 First wireless module: 802.11a/n/ac Second wireless module: 802.11b/g/n PoE in 802.3 af/at PoE Input Voltage: 11 V - 57 V PoE out up to 57V PCB temperature monitor Tested ambient temperature: -40 to +50C MTBF: Approximately 100'000 hours at 25C Antenna gain: 2 CPU: QCA9556 Max Power consumption: 24W Number of chains: 3 Storage type: FLASH Storage size: 16 MB Wireless 2.4 GHz Max data rate: 300 Mbit/s Wireless 2.4 GHz number of chains: 2 Antenna gain dBi for 2.4 GHz: 2 Wireless 2.4 GHz generation: Wi-Fi 4 Wireless 5 GHz Max data rate: 867 Mbit/s Wireless 5 GHz number of chains 2 Antenna gain dBi for 5GHz: 2.5 Wireless 5 GHz generation: Wi-Fi 5 Certification: CE, FCC, IC, EAC, ROHS Warranty: 1 an Embended wireless characteristics: Wireless band – 5Ghz and 2.4Ghz simultaneously AP / Station / Bridge modes supported 802.1X for wireless authentication to radius server Wireless scanner for detection of the free wifi channels The possibility to make virtual access points and bridge them with 802.1Q VLAN Wireless signal level and mac based access control Wireless Sniffer, wireless snooper	ISO
---	--	---------------------	----------------------	--------	--	--	-----

Accent Tenno SRL

IDNO: 1002600037469

TVA: 0244960

BC "MOLDOVA-AGROINDBANK" S.A. suc. 'MAIB PARK'

BIC AGRNMD2X522

IBAN LEI: MD52AG000000022515264935



				Router capabilities: MPLS Routing protocols – OSPF, BGP, RIP IGMP Proxy VPN – IPSec, OVPN, PPTP, L2TP (as server and as client) SNMP, NetFlow 802.1Q VLAN support DHCP Server, relay and client User groups support with radius authentication DNS Caching with the possibility to make static registrations in DNS. The protocol to view neighbor devices which support the same protocol. CDP support FTP and SMB Server NTP Server and Client Management – SSH, Telnet, WEB, API for making personal application for management Bridging interfaces, subinterfaces Bandwidth test server and client IP Scanner – to scan all network devices from specified range of IP addresses Packet sniffer CapsMAN support The possibility to make scripts for backup or internet failover with e-mail notification. The possibility to schedule the scripts. Logging local or remote with the possibility to specify processes which we want to log (DHCP, VPN, Firewall...) VRF Garant ie: minim 12 luni	Router capabilities: MPLS Routing protocols – OSPF, BGP, RIP IGMP Proxy VPN – IPSec, OVPN, PPTP, L2TP (as server and as client) SNMP, NetFlow 802.1Q VLAN support DHCP Server, relay and client User groups support with radius authentication DNS Caching with the possibility to make static registrations in DNS. The protocol to view neighbor devices which support the same protocol. CDP support FTP and SMB Server NTP Server and Client Management – SSH, Telnet, WEB, API for making personal application for management Bridging interfaces, subinterfaces Bandwidth test server and client IP Scanner – to scan all network devices from specified range of IP addresses Packet sniffer CapsMAN support The possibility to make scripts for backup or internet failover with e-mail notification. The possibility to schedule the scripts. Logging local or remote with the possibility to specify processes which we want to log (DHCP, VPN, Firewall...) VRF Garant ie: 12 luni	
--	--	--	--	--	--	--

Nume: Oleg Savcenko

În calitate de: Director

Ofertantul: „Accent Tehno” SRL

Adresa: or. Chişinău, str. Bulgară, 33/1